

SEPP 65 Apartment Design Guide																
No.	Required / Permitted		Comment	Comply												
Part 3 - Siting the Development																
3A	Site Analysis															
3A-1	Site analysis illustrates that design decisions have been based on opportunities and constraints of the site conditions and their relationship to the surrounding context.			Yes												
3B	Orientation															
3B-1	Building types and layouts respond to the streetscape and site while optimising solar access within the development.			Yes												
3B-2	Overshadowing of neighbouring properties is minimised during mid-winter.			N/A												
3C	Public Domain Interface															
3C-1	Transition between private and public domain is achieved without compromising safety and security.			Yes												
3C-2	Amenity of the public domain is retained and enhanced.			Yes												
3D	Communal and Public Open Space															
3D-1	An adequate area of communal open space is provided to enhance residential amenity and to provide opportunities for landscaping.			N/A												
	Design Criteria	Communal open space has a minimum area equal to 25% of the site. Required: 25% x 1,194.7m² = 299m² Developments achieve a minimum of 50% direct sunlight to the principal usable part of the communal open space for a minimum of 2 hours between 9 am and 3 pm on 21 June (mid-winter).	No changes are proposed to the approved communal open space area of the development.	N/A												
3D-2	Communal open space is designed to allow for a range of activities, respond to site conditions and be attractive and inviting.			N/A												
3D-3	Communal open space is designed to maximise safety.			N/A												
3D-4	Public open space, where provided, is responsive to the existing pattern and uses of the neighbourhood.			N/A												
3E	Deep Soil Zones															
3E-1	Deep soil zones provide areas on the site that allow for and support healthy plant and tree growth. They improve residential amenity and promote management of water and air quality.			N/A												
	Design Criteria	Deep soil zones are to meet the following minimum requirements: <table><tr><th>Site area</th><th>Minimum dimensions</th><th>Deep soil zone (% of site area)</th></tr><tr><td>less than 650m²</td><td>-</td><td rowspan="4">7%</td></tr><tr><td>650m² - 1,500m²</td><td>3m</td></tr><tr><td>greater than 1,500m²</td><td>6m</td></tr><tr><td>greater than 1,500m² with significant existing tree cover</td><td>6m</td></tr></table> Required: 7% x 1,194.7m² = 83.6m² Design guidance On some sites it may be possible to provide larger deep soil zones, depending on the site area and context: <ul style="list-style-type: none">• 10% of the site as deep soil on sites with an area of 650m² - 1,500m²• 15% of the site as deep soil on sites greater than 1,500m²	Site area	Minimum dimensions	Deep soil zone (% of site area)	less than 650m²	-	7%	650m² - 1,500m²	3m	greater than 1,500m²	6m	greater than 1,500m² with significant existing tree cover	6m	No changes are proposed to the extent of deep soil zone areas of the development.	N/A
Site area	Minimum dimensions	Deep soil zone (% of site area)														
less than 650m²	-	7%														
650m² - 1,500m²	3m															
greater than 1,500m²	6m															
greater than 1,500m² with significant existing tree cover	6m															

SEPP 65 Apartment Design Guide																
No.	Required / Permitted		Comment	Comply												
	Design guidance	<p>Achieving the design criteria may not be possible on some sites including where:</p> <ul style="list-style-type: none">the location and building typology have limited or no space for deep soil at ground level (e.g. central business district, constrained sites, high density areas, or in centres).there is 100% site coverage or non-residential uses at ground floor level. <p>Where a proposal does not achieve deep soil requirements, acceptable stormwater management should be achieved and alternative forms of planting provided such as on structure.</p>														
3F	Visual Privacy															
3F-1	Adequate building separation distances are shared equitably between neighbouring sites, to achieve reasonable levels of external and internal visual privacy.			Yes												
	Design Criteria	<p>Separation between windows and balconies is provided to ensure visual privacy is achieved. Minimum required separation distances from buildings to the side and rear boundaries are as follows:</p> <table><tr><th>Building height</th><th>Habitable rooms and balconies</th><th>Non-habitable rooms</th></tr><tr><td>up to 12m (4 storeys)</td><td>6m</td><td>3m</td></tr><tr><td>up to 25m (5-8 storeys)</td><td>9m</td><td>4.5m</td></tr><tr><td>over 25m (9+ storeys)</td><td>12m</td><td>6m</td></tr></table> <p>Note: Separation distances between buildings on the same site should combine required building separations depending on the type of room.</p> <p>Gallery access circulation should be treated as habitable space when measuring privacy separation distances between neighbouring properties.</p>	Building height	Habitable rooms and balconies	Non-habitable rooms	up to 12m (4 storeys)	6m	3m	up to 25m (5-8 storeys)	9m	4.5m	over 25m (9+ storeys)	12m	6m	No changes are proposed to the approved extent of building separation of the development.	N/A
Building height	Habitable rooms and balconies	Non-habitable rooms														
up to 12m (4 storeys)	6m	3m														
up to 25m (5-8 storeys)	9m	4.5m														
over 25m (9+ storeys)	12m	6m														
		Apartment buildings should have an increased separation distance of 3m (in addition to the requirements set out in design criteria 1) when adjacent to a different zone that permits lower density residential development to provide for a transition in scale and increased landscaping.	Not Applicable.	N/A												
3F-2	Site and building design elements increase privacy without compromising access to light and air and balance outlook and views from habitable rooms and private open space.			N/A												
3G	Pedestrian Access and Entries															
3G-1	Building entries and pedestrian access connects to and addresses the public domain.			N/A												

SEPP 65 Apartment Design Guide																												
No.	Required / Permitted		Comment	Comply																								
3G-2	Access, entries and pathways are accessible and easy to identify.			Yes																								
3G-3	Large sites provide pedestrian links for access to streets and connection to destinations.			N/A																								
3H	Vehicle Access																											
3H-1	Vehicle access points are designed and located to achieve safety, minimise conflicts between pedestrians and vehicles and create high quality streetscapes.			N/A																								
3J	Bicycle and Car Parking																											
3J-1	Car parking is provided based on proximity to public transport in metropolitan Sydney and centres in regional areas.			Yes																								
	Design Criteria	<p>For development in the following locations:</p> <ul style="list-style-type: none">on sites that are within 800 metres of a railway station or light rail stop in the Sydney Metropolitan Area; oron land zoned, and sites within 400 metres of land zoned, B3 Commercial Core, B4 Mixed Use or equivalent in a nominated regional centre. <p>The minimum car parking requirement for residents and visitors is set out in the Guide to Traffic Generating Developments, or the car parking requirement prescribed by the relevant council, whichever is less.</p> <table><tr><th colspan="2">Control</th></tr><tr><td>1 bedroom</td><td>0.6 spaces</td></tr><tr><td>2 bedroom</td><td>0.9 space</td></tr><tr><td>3 bedroom</td><td>1.4 spaces</td></tr><tr><td>4+ bedroom</td><td>1.4 spaces</td></tr><tr><td>Visitor / dwelling</td><td>0.2 spaces</td></tr></table>	Control		1 bedroom	0.6 spaces	2 bedroom	0.9 space	3 bedroom	1.4 spaces	4+ bedroom	1.4 spaces	Visitor / dwelling	0.2 spaces	<p>The subject site is within 800 metres of Lidcombe Station.</p> <table><tr><th colspan="2">Required</th></tr><tr><td>1 bedroom - 0.6 x 24 = 14.4</td><td></td></tr><tr><td>2 bedroom - 0.9 x 39 = 35.1</td><td></td></tr><tr><td>3 bedroom - 1.4 x 9 = 12.6</td><td></td></tr><tr><td>Visitor - 0.2 x 72 = 14.4</td><td></td></tr><tr><td>Total 76.5 sp</td><td></td></tr></table> <p>99 car parking spaces have been provided, made up of 78 resident spaces, 15 visitor spaces and 6 commercial spaces.</p>	Required		1 bedroom - 0.6 x 24 = 14.4		2 bedroom - 0.9 x 39 = 35.1		3 bedroom - 1.4 x 9 = 12.6		Visitor - 0.2 x 72 = 14.4		Total 76.5 sp		Yes
Control																												
1 bedroom	0.6 spaces																											
2 bedroom	0.9 space																											
3 bedroom	1.4 spaces																											
4+ bedroom	1.4 spaces																											
Visitor / dwelling	0.2 spaces																											
Required																												
1 bedroom - 0.6 x 24 = 14.4																												
2 bedroom - 0.9 x 39 = 35.1																												
3 bedroom - 1.4 x 9 = 12.6																												
Visitor - 0.2 x 72 = 14.4																												
Total 76.5 sp																												
3J-2	Parking and facilities are provided for other modes of transport.			Yes																								
3J-3	Car park design and access is safe and secure			Yes																								
3J-4	Visual and environmental impacts of underground car parking are minimised.			N/A																								
3J-5	Visual and environmental impacts of on-grade car parking are minimised.			N/A																								
3J-6	Visual and environmental impacts of above ground enclosed car parking are minimised.			N/A																								
Part 4 - Designing the Building																												
4A	Solar and Daylight Access																											
4A-1	To optimise the number of apartments receiving sunlight to habitable rooms, primary windows and private open space.			N/A																								
	Design Criteria	<p>Living rooms and private open spaces of at least 70% of apartments in a building receive a minimum of 2 hours direct sunlight between 9 am and 3 pm at mid-winter in the Sydney Metropolitan Area and in the Newcastle and Wollongong local government areas.</p> <p>Required: 70% x 72 units = 50.4 units</p> <p>A maximum of 15% of apartments in a building receive no direct sunlight between 9 am and 3 pm at mid-winter.</p> <p>Maximum:15% x 72 units = 10.8 units</p>	<p>No changes are proposed which would affect the approved extent of solar access achieved to living rooms and private open space areas of the development.</p>	N/A																								

SEPP 65 Apartment Design Guide					
No.	Required / Permitted		Comment	Comply	
4A-2	Daylight access is maximised where sunlight is limited.			N/A	
4A-3	Design incorporates shading and glare control, particularly for warmer months.			N/A	
4B	Natural Ventilation				
4B-1	All habitable rooms are naturally ventilated.			N/A	
4B-2	The layout and design of single aspect apartments maximises natural ventilation.			N/A	
4B-3	The number of apartments with natural cross ventilation is maximised to create a comfortable indoor environment for residents.			N/A	
	Design Criteria	At least 60% of apartments are naturally cross ventilated in the first nine storeys of the building. Apartments at ten storeys or greater are deemed to be cross ventilated only if any enclosure of the balconies at these levels allows adequate natural ventilation and cannot be fully enclosed.	No changes are proposed which would affect the approved extent of natural ventilation achieved to apartments of the development.	N/A	
		Required: 60% x 72 units = 43.2 units			
		Overall depth of a cross-over or cross-through apartment does not exceed 18m, measured glass line to glass line.	No changes are proposed to the approved depth of cross-over or cross-through apartments of the development.		N/A
4C	Ceiling Heights				
4C-1	Ceiling height achieves sufficient natural ventilation and daylight access.			N/A	
4C-1	Design Criteria	Measured from finished floor level to finished ceiling level, minimum ceiling heights are:	No changes are proposed to the approved floor to ceiling heights of the development.	N/A	
		Minimum ceiling height for apartment and mixed use buildings			
		Habitable rooms			2.7m
		Non-habitable			2.4m
		For 2 storey apartments			2.7m for main living area floor 2.4m for second floor, where its area does not exceed 50% of the apartment area
		Attic spaces			1.8m at edge of room with a 30 degree minimum ceiling slope
		If located in mixed used areas			3.3m for ground and first floor to promote future flexibility of use
		These minimums do not preclude higher ceilings if desired.			
4C-2	Ceiling height increases the sense of space in apartments and provides for well-proportioned rooms.			N/A	
4C-3	Ceiling heights contribute to the flexibility of building use over the life of the building.			N/A	
4D	Apartment Size and Layout				
4D-1	The layout of rooms within an apartment is functional, well organised and provides a high standard of amenity.			N/A	

SEPP 65 Apartment Design Guide					
No.	Required / Permitted		Comment	Comply	
	Design Criteria	Apartments are required to have the following minimum internal areas:	No changes are proposed to the approved apartment sizes of the development.	N/A	
		Apartment type			Minimum internal area
		Studio			35m ²
	1 bedroom	50m ²			
	2 bedroom	70m ²			
	3 bedroom	90m ²			
		The minimum internal areas include only one bathroom. Additional bathrooms increase the minimum internal area by 5m ² each. A fourth bedroom and further additional bedrooms increase the minimum internal area by 12m ² each.			
		Every habitable room must have a window in an external wall with a total minimum glass area of not less than 10% of the floor area of the room. Daylight and air may not be borrowed from other rooms.	No changes are proposed to the approved window arrangement of the development.	N/A	
4D-2	Environmental performance of the apartment is maximised.			N/A	
	Design Criteria	Habitable room depths are limited to a maximum of 2.5 x the ceiling height.	No changes are proposed to the approved habitable room depths of development.	N/A	
		In open plan layouts (where the living, dining and kitchen are combined) the maximum habitable room depth is 8m from a window.	No changes are proposed to the approved open plan layout depths of the development.	N/A	
4D-3	Apartment layouts are designed to accommodate a variety of household activities and needs.			N/A	
	Design Criteria	Master bedrooms have a minimum area of 10m ² and other bedrooms 9m ² (excluding wardrobe space).	No changes are proposed to the approved bedrooms of the development.	N/A	
		Bedrooms have a minimum dimension of 3m (excluding wardrobe space).			
		Living rooms or combined living/dining rooms have a minimum width of: • 3.6m for studio and 1 bedroom apartments • 4m for 2 and 3 bedroom apartments.	No changes are proposed to the combined living / dining rooms of the development.	N/A	
		The width of cross-over or cross-through apartments are at least 4m internally to avoid deep narrow apartment layouts.	No changes are proposed to the cross-over or cross-through apartments of the development.	N/A	

SEPP 65 Apartment Design Guide						
No.	Required / Permitted			Comment	Comply	
4E	Private Open Space and Balconies					
4E-1	Apartments provide appropriately sized private open space and balconies to enhance residential amenity.				N/A	
	Design Criteria	All apartments are required to have primary balconies as follows:		No changes are proposed to the approved primary balconies of the development.	N/A	
		Dwelling type	Minimum area			Minimum depth
		Studio apartments	4m ²			-
		1 bedroom apartments	8m ²			2m
		2 bedroom apartments	10m ²			2m
3+ bedroom apartments		12m ²	2.4m			
The minimum balcony depth to be counted as contributing to the balcony area is 1m.		Not Applicable.	N/A			
For apartments at ground level or on a podium or similar structure, a private open space is provided instead of a balcony. It must have a minimum area of 15m ² and a minimum depth of 3m.						
4E-2	Primary private open space and balconies are appropriately located to enhance liveability for residents.				N/A	
4E-3	Private open space and balcony design is integrated into and contributes to the overall architectural form and detail of the building.				N/A	
4E-4	Private open space and balcony design maximises safety.				N/A	
4F	Common Circulation and Spaces					
4F-1	Common circulation spaces achieve good amenity and properly service the number of apartments.				N/A	
	Design Criteria	The maximum number of apartments off a circulation core on a single level is eight.		No changes are proposed to the maximum number of apartments off a circulation core of the development.	N/A	
		For buildings of 10 storeys and over, the maximum number of apartments sharing a single lift is 40.		Not Applicable.	N/A	
4F-2	Common circulation spaces promote safety and provide for social interaction between residents.				N/A	
4G	Storage					
4G-1	Adequate, well designed storage is provided in each apartment.				Yes	
	Design Criteria	In addition to storage in kitchens, bathrooms and bedrooms, the following storage is provided:		Storage areas have been provided within the units and within the basement of the development.	Yes	
		Dwelling type	Storage size volume			
		Studio apartments	4m ³			
		1 bedroom apartments	6m ³			
		2 bedroom apartments	8m ³			
3+ bedroom apartments		10m ³				
At least 50% of the required storage is to be located within the apartment.						
4G-2	Additional storage is conveniently located, accessible and nominated for individual apartments.				N/A	
4H	Acoustic Privacy					
4H-1	Noise transfer is minimised through the siting of buildings and building layout.				N/A	
4H-2	Noise impacts are mitigated within apartments through layout and acoustic treatments.				N/A	
4J	Noise and Pollution					
4J-1	In noisy or hostile environments the impacts of external noise and pollution are minimised through the careful siting and layout of buildings.				N/A	

SEPP 65 Apartment Design Guide			
No.	Required / Permitted	Comment	Comply
4J-2	Appropriate noise shielding or attenuation techniques for the building design, construction and choice of materials are used to mitigate noise transmission.		N/A
4K	Apartment Mix		
4K-1	A range of apartment types and sizes is provided to cater for different household types now and into the future.		N/A
4K-2	The apartment mix is distributed to suitable locations within the building.		N/A
4L	Ground Floor Apartments		
4L-1	Street frontage activity is maximised where ground floor apartments are located.		N/A
4L-2	Design of ground floor apartments delivers amenity and safety for residents.		N/A
4M	Façades		
4M-1	Building facades provide visual interest along the street while respecting the character of the local area.		N/A
4M-2	Building functions are expressed by the façade.		N/A
4N	Roof Design		
4N-1	Roof treatments are integrated into the building design and positively respond to the street.		N/A
4N-2	Opportunities to use roof space for residential accommodation and open space are maximised.		N/A
4N-3	Roof design incorporates sustainability features.		N/A
4O	Landscape Design		
4O-1	Landscape design is viable and sustainable.		N/A
4O-2	Landscape design contributes to the streetscape and amenity.		N/A
4P	Planting on Structures		
4P-1	Appropriate soil profiles are provided.		N/A
4P-2	Plant growth is optimised with appropriate selection and maintenance.		N/A
4P-3	Planting on structures contributes to the quality and amenity of communal and public open spaces.		N/A
4Q	Universal Design		
4Q-1	Universal design features are included in apartment design to promote flexible housing for all community members.		N/A
4Q-2	A variety of apartments with adaptable designs are provided.		N/A
4Q-3	Apartment layouts are flexible and accommodate a range of lifestyle needs.		N/A
4R	Adaptive Reuse		
4R-1	New additions to existing buildings are contemporary and complementary and enhance an area's identity and sense of place.		N/A
4R-2	Adapted buildings provide residential amenity while not precluding future adaptive reuse.		N/A
4S	Mixed Use		
4S-1	Mixed use developments are provided in appropriate locations and provide active street frontages that encourage pedestrian movement.		N/A
4S-2	Residential levels of the building are integrated within the development, and safety and amenity is maximised for residents.		N/A
4T	Awnings and Signage		
4T-1	Awnings are well located and complement and integrate with the building design.		N/A
4T-2	Signage responds to the context and desired streetscape character.		N/A
4U	Energy Efficiency		
4U-1	Development incorporates passive environmental design.		N/A
4U-2	Development incorporates passive solar design to optimise heat storage in winter and reduce heat transfer in summer.		N/A
4U-3	Adequate natural ventilation minimises the need for mechanical ventilation.		N/A
4V	Water Management and Conservation		
4V-1	Potable water use is minimised.		N/A
4V-2	Urban stormwater is treated on site before being discharged to receiving waters.		N/A
4V-3	Flood management systems are integrated into site design.		N/A
4W	Waste Management		
4W-1	Waste storage facilities are designed to minimise impacts on the streetscape, building entry and amenity of residents.		N/A
4W-2	Domestic waste is minimised by providing safe and convenient source separation and recycling.		N/A
4X	Building Maintenance		
4X-1	Building design detail provides protection from weathering.		N/A

SEPP 65 Apartment Design Guide			
No.	Required / Permitted	Comment	Comply
4X-2	<i>Systems and access enable ease of maintenance.</i>		N/A
4X-3	<i>Material selection reduces ongoing maintenance costs.</i>		N/A