

- 2. LEVELS GIVEN ARE FINAL FINISHED LEVELS AND ALLOWANCES SHALL BE MADE FOR THICKNESS OF PAVEMENT, LANDSCAPING, ETC., INCLUDING ALLOWANCES FOR COMPACTION AND SETTLEMENT FINISHED SURFACES SHALL BE FREE OF LOCAL IRREGULARITIES AND EVENLY GRADED BETWEEN LEVEL POINTS GIVEN ENSURE THAT FINISHED SURFACES ARE FREE DRAINING TOWARDS STORMWATER PITS.
- 3. REFER TO THE SURVEY DRAWINGS AND OTHER CONSULTANTS DRAWINGS FOR THE LOCATION OF EXISTING SERVICES THE BUILDER IS TO ALLOW FOR ALL ADJUSTMENT AND RELOCATION OF SERVICES AFFECTED BY THE WORKS ANY ADJUSTMENT OR RELOCATION OF SERVICES SHALL BE CARRIED OUT TO THE APPROVAL OF THE SUPERINTENDENT
- 4. ADDITIONAL SUBSOIL DRAINAGE SHALL BE PROVIDED WHERE DIRECTED BY THE SUPERINTENDENT.
- 5. DURING THE COURSE OF CONSTRUCTION AND THE EXTENT OF THE MAINTENANCE PERIOD THE BUILDER IS TO PROVIDE AND MAINTAIN A SUITABLE SEDIMENT AND EROSION CONTROL SYSTEM IN ACCORDANCE WITH THE SPECIFICATIONS AND THE REQUIREMENTS OF THE LOCAL COUNCIL THIS SHALL INCLUDE BUT NOT BE LIMITED TO:
- (A) ERECTION OF SEDIMENT FENCING (B) PROVISION OF STRAW BALES TO PROTECT ALL PITS (C) REVEGETATION OF ALL DISTURBED AREAS AS SOON AS RELEVANT WORKS ARE COMPLETED



SCALE 1200

٠		,				•		
	٠		•		•		•	
٠		٠						
	٠		٠		,		•	
٠		٠				1		•
	٠		٠		٠		1	
٠		•		•		•		1



HATCHED AREAS SHOWN THUS ON PLAN DENOTES EXTENT OF AREA TO BE REWORKED TO RELOCATE EXISTING SPORTS COURT. NOTE: CHANGE IN LEVELS APPROXIMATE ONLY. CONFIRM ALL EXISTING LEVELS WITH SURVEY DRAWINGS.

## EXTERNAL WORKS PLAN

100 MIN. THICK SLAB ON GROUND - TYPICAL U.N.O. SL102 MESH TOP - TYPICAL THROUGHOUT U.N.O.

## REFER TO DRAWING C.00 FOR CONSTRUCTION NOTES



