

20-22 Mindarie Street & 30 Pinaroo Place, Lane Cove Residential Development

OPERATIONAL WASTE MANAGEMENT PLAN

14/12/2020 Report No. SO477 Revision F

Client

BCL2 Limited

Suite 3A, O'Sullivan Road, Leumeah NSW 2560 T 0418 352 727 • E pau-lahi.haangana@bluechp.com.au

Architect

Stanton Dahl Architects 18-20 Oxford Street, Epping www.stantondahl.com.au T 02 8876 5300 • E design@stantondahl.com.au

ELEPHANTS FOOT RECYCLING SOLUTIONS • ABN 70 001 378 294 44-46 Gibson Ave Padstow NSW 2211 www.elephantsfoot.com.au

T +612 9780 3500 • F +612 9707 2588 E info@elephantsfoot.com.au



SCOPE

This waste management plan (WMP) only applies to the **operational** phase of the proposed development; therefore the requirements outlined in this WMP must be implemented during the operational phase of the site and may be subject to review upon further expansion for, and/or changes to the development.

The waste management of the **construction** and **demolition** phases of the development are not addressed in this report. It is EFRS's understanding that a construction and demolition WMP will be completed by a separate party appointed by the developer, and submitted separately to this report. Typically, the head contractor of the site will be responsible for removing all construction-related waste offsite in a manner that meets all authority requirements.

Revision	Date	Prepared by	Reviewed by	Description	Signed
А	17/02/2020	J Parker	A Armstrong	Draft	Stellin
В	28/04/2020	J Parker	A Armstrong	Final	Stellin
С	18/05/2020	J Parker	A Armstrong	Amendment	Stellin
D	4/11/2020	J Parker	A Armstrong	Amendment	Stellin
E	13/11/2020	J Parker	A Armstrong	Amendment	Stellin
F	14/12/2020	J Parker	A Armstrong	Amendment	Stellin

REVISION REFERENCE

The information contained in this document produced by Elephants Foot Recycling Solutions (EFRS) is solely for the use of the client identified on the cover sheet for the purpose for which it has been prepared for. EFRS undertakes no duty, nor accepts any responsibility for any third party who may rely upon this document. Reproduction, publication or distribution of this document without written permission from EFRS is strictly prohibited.



TABLE OF CONTENTS

GLOSSARY OF TERMS	i
LIST OF TABLES	iii
INTRODUCTION	
DEVELOPMENT SUMMARY	
SITE LOCATION	2
LANE COVE COUNCIL	
COUNCIL OBJECTIVES	
COUNCIL REQUIREMENTS	
STAKEHOLDER ROLES AND RESPONSIBILITIES	
EDUCATION	
LIMITATIONS	5
RESIDENTIAL WASTE MANAGEMENT	
ESTIMATED WASTE VOLUMES AND PROVISIONS	
HOUSEHOLD WASTE	6
COMMON AREAS	
SOURCE SEPERATION	7
GENERAL WASTE (GARBAGE)	7
RECYCLING	7
GREEN WASTE	7
BULKY GOODS	7
ELECTRONIC WASTE	
CHEMICAL WASTE	
ORGANIC WASTE AND COMPOSTING	
MOVEMENT AND TRANSPORTATION OF BINS	
COLLECTION OF WASTE	
COLLECTION AREA	
INSTALLATION EQUIPMENT AND DESIGN	
EQUIPMENT SUMMARY	
WASTE ROOM AREAS	
GARBAGE ROOMS	
CONSTRUCTION REQUIREMENTS	
SIGNAGE	
VENTILATION	
USEFUL CONTACTS	
APPENDICES	
APPENDIX A ARCHITECTURAL DRAWING EXCERPTS	
APPENDIX A.1 SITE PLAN	



APPENDIX A.2	WASTE ROOMS/COLLECTION AREA	14
APPENDIX B	PRIMARY WASTE MANAGEMENT PROVISIONS	15
APPENDIX B.1	LANE COVE BIN SPECIFICATIONS	15
APPENDIX B.2	SIGNAGE FOR WASTE & RECYCLING BINS	16
APPENDIX B.3	TYPICAL SRV	17
APPENDIX B.4	TYPICAL MOTORISED BIN TUG	
APPENDIX B.5	TYPICAL SEATED BIN MOVER	19
APPENDIX C	INSTALLATION EQUIPMENT	20
APPENDIX C.1	TYPICAL SINGLE WASTE CHUTE SPECIFICATIONS .	20
APPENDIX C.2	TYPICAL LINEAR TRACK SYSTEM	21
APPENDIX D	SECONDARY WASTE MANAGEMENT PROVISIONS	22
APPENDIX D.1	TYPICAL WORM FARM SPECIFICATIONS	22
APPENDIX D.2	TYPICAL APARTMENT STYLE COMPOST BINS	23
APPENDIX D.3	ELECTRIC ORGANIC COMPOST BIN	24

GLOSSARY OF TERMS

TERM	DESCRIPTION
Baler	A device that compresses waste into a mould to form bales which may be self-supporting or retained in shape by strapping
Chute	A ventilated, vertical pipe passing from floor to floor of a building with openings as required to connect with hoppers and normally terminating at its lower end at the roof of the central waste room(s)
Chute Discharge	The point at which refuse exits from the refuse chute
Chute Discharge Room	A secure, enclosed area or room housing the discharge and associated equipment for the refuse chute
Collection Area/Point	The identified position or area where garbage or recyclables are actually loaded onto the collection vehicle
Compactor	A machine for compressing waste into disposable or reusable containers
Composter	A container/machine used for composting specific food scraps
Crate	A plastic box used for the collection of recyclable materials
Garbage	All domestic waste (Except recyclables and green waste)
Green Waste	All vegetated organic material such as small branches, leaves and grass clippings, tree and shrub pruning, plants and flowers
Hopper	A fitting into which waste is placed and from which it passes into a chute or directly into a waste container. It consists of a fixed frame and hood unit (the frame) and a hinged or pivoted combined door and receiving unit
L	Litre(s)
Liquid Waste	Non-hazardous liquid waste generated by commercial premises that is supposed to be connected to sewer or collected for treatment and disposal by a liquid waste contractor (including grease trap waste)
LRV	Large rigid vehicle described by AS 2890.2-2002 Parking facilities – Off- street commercial vehicle facilities as heavy rigid vehicle (HRV)
Mobile Garbage Bin(s) (MGB)	A waste container generally constructed of plastic with wheels with a capacity in litres of 120, 240, 360, 660, 1000 or 1100
MRV	Medium rigid vehicle
Putrescible Waste	Component of the waste stream liable to become putrid. Usually breaks down in a landfill to create landfill gases and leachate. Typically applies to food, animal and organic products.
Recycling	Glass bottles and jars – PET, HDPE and PVC plastics; aluminium aerosol and steel cans; milk and juice cartons; soft drink, milk and shampoo containers; paper, cardboard, junk mail, newspapers and magazines

- *Refuse* Material generated and discarded from residential and commercial buildings including general waste, recyclables, green waste and bulky items
- *SRV* Small rigid vehicle as in AS 2890.2-2002 Parking facilities Off-street commercial vehicle facilities, generally incorporating a body width of 2.33

LIST OF TABLES

Table 1: Stakeholder Roles and Responsibilities	4
Table 2: Calculated Waste Generation – Residential	
Table 3: Equipment Summary	
Table 4: Waste Room Areas	



INTRODUCTION

EFRS has been tasked to prepare the following waste management plan for BCL2 Limited for the operational management of waste generated by the residential development located at 20-22 Mindarie Street and 30 Pinaroo Place, Lane Cove North.

Waste management strategies and auditing are a requirement for new developments to provide support for the building design, and promote strong sustainability outcomes for the building. It is EFRS's belief that a successful waste management strategy contains three key objectives:

- *i.* **Promote responsible source separation** to reduce the amount of waste that goes to landfill, by implementing convenient and efficient waste management systems
- *ii.* **Ensure adequate waste provisions and robust procedures** that will cater for potential changes during the operational phase of the development
- *iii.* **Compliance** with all relevant council codes, policies, and guidelines.

To achieve these objectives, this WMP identifies the different waste streams likely to be generated during the operational phase of the development. Associated information includes: how the waste will be handled and disposed of, details of bin sizes/quantities and waste rooms, descriptions of the proposed waste management equipment used and information on waste collection points and frequencies.

It is essential that this waste management plan is integral to the overall management of the building and clearly communicated to all relevant stakeholders.

DEVELOPMENT SUMMARY

The proposed development falls under the LGA of Lane Cove Council, and consists of:


- 1 building of 6 levels
 - o 30 residential units in total

All figures and calculations are based on area schedules as advised by our client and shown on architectural drawings.



SITE LOCATION

The site is located at 20-22 Mindarie Street and 30 Pinaroo Place, Lane Cove, as shown below. The site has frontages to Mindarie Street and Pinaroo Place, with vehicle access via Pinaroo Place.



Source: Google Maps





LANE COVE COUNCIL

The garbage and recycling will be guided by the services and acceptance criteria of the Lane Cove Council. All waste facilities and equipment are to be designed and constructed to be in compliance with the Lane Cove Council's *Lane Cove Development Control Plan* (2010), Australian Standards and statutory requirements.

COUNCIL OBJECTIVES

- Ensure appropriate waste storage and collection facilities.
- Maximise source separation and recovery of recyclables.
- Ensure waste management systems are as intuitive for occupants as possible and are readily accessible.
- Ensure appropriate resourcing of waste management systems, including servicing.
- Minimise risk to health and safety associated with handling and disposal of waste and recycled material, and ensure optimum hygiene.
- Minimise adverse environmental impacts associated with waste management.
- Discourage illegal dumping by providing on site storage, and removal services.

COUNCIL REQUIREMENTS

Access – Ensure waste systems are easy to use and collection vehicles are able to access buildings to safely remove waste and recycling;

Safety - Ensure safe practises for storage, handling and collection of waste and recycling;

Pollution Prevention – Prevent stormwater pollution that may occur as a result of poor waste storage and management practises;

Noise Minimisation – Provide acoustic insulation to the waste service facilities or residential units adjacent to or above chutes, waste storage facilities, chute discharge, waste compaction equipment and waste collection vehicle access points;

Ecologically Sustainable Development (ESD) – Promote the principles of ESD through resource recovery and recycling leading to a reduction in the consumption of finite natural resources;

Hygiene – Ensure health and amenity for residents, visitors and workers in the Lane Cove Council



STAKEHOLDER ROLES AND RESPONSIBILITIES

The following table demonstrates the primary roles and responsibilities of the respective stakeholders:

Roles	Responsibilities
Strata/Management	 Ensuring that all waste service providers submit monthly reports on all equipment movements and waste quantities/weights; Organising internal waste audits/visual assessments on a regular basis; and Manage any non-compliances/complaints reported through waste audits.
Building Manager/Waste Caretaker	 Ensuring effective signage, communication and education is provided to occupants, tenants and cleaners; Providing staff/contractors with equipment manuals, training, health and safety procedures, risk assessments, and PPE to control hazards associated with all waste management activities; Ensuring site safety for residents, children, visitors, staff and contractors; Abiding by all relevant OH&S legislation, regulations, and guidelines; Assessing any manual handling risks and prepare a manual handling control plan for waste and bin transfers; Preventing storm water pollution by taking necessary precautions (securing bin rooms, preventing overfilling of bins) General maintenance and cleaning of chute doors on each level; Cleaning and transporting of bins as required; Organising, maintaining and cleaning the general and recycled waste holding area; Organising both garbage and recycled waste pick-ups as required; Organising bulky goods collection when required; and Investigating and ensuring prompt clean-up of illegally dumped waste materials.
Residents/Tenants	 Dispose of all garbage and recycling in the allocated waste chutes and/or MGBs provided; Ensure adequate separation of garbage and recycling; and Compliance with the provisions of Council and the WMP.
Council/Private Waste Contractor	 Provide a reliable and appropriate waste collection service; Provide feedback to building managers/residents in regards to contamination of recyclables; and Work with building managers to customise waste systems where possible.
Gardening/Landscaping Contractor	Removal of all garden organic waste generated during gardening maintenance activities for recycling at an offsite location.
Building Contractors	Removing all construction related waste offsite in a manner that meets all authority requirements.

Table 1: Stakeholder Roles and Responsibilities



EDUCATION

Educational material encouraging correct separation of garbage and recycling items must be provided to each resident by building management to ensure correct use of the waste chute. This should include the correct disposal process for bulky goods (old furniture, large discarded items, etc.), and other appropriate materials (electronic, chemical waste, etc.). It is recommended that information is provided in multiple languages to support correct practises and minimise the possibility of chute blockages as well as contamination in the collective waste bins.

It is also recommended that the owners' corporation website contain information for residents to refer to regarding use of the chute. Information should include:

- Directions on using the chute doors;
- Recycling and garbage descriptions (council provides comprehensive information);
- How to dispose of bulky goods and any other items that are not garbage or recycling;
- Residents' obligations to whs and building management; and
- How to prevent damage or blockages to the chute (example below).

To prevent damage or blockage to rubbish chute DO NOT dispose of any newspapers, umbrellas, bedding, cigarettes, cartons, coat hangers, brooms, mops, large plastic wrappings from furniture, white goods, any sharp objects, hot liquid or ashes, oil, unwrapped vacuum dust, syringes, paint and solvents, car parts, bike parts, chemicals, corrosive and flammable items, soil, timber, bricks or other building materials, furniture, etc. down the chute.

LIMITATIONS

The purpose of this report is to document a Waste Management Plan (WMP) as part of a development application and is supplied by Elephants Foot Recycling Solutions (EFRS) with the following limitations:

- Drawings, estimates and information contained in this waste management plan have been prepared by analysing the information, plans and documents supplied by the client, and third parties including Council and government information. The assumptions based on the information contained in the WMP is outside the control of EFRS;
- the figures presented in the report are an estimate only the actual amount of waste generated will be dependent on the occupancy rate of the building/s and waste generation intensity as well as the building managements approach to educating residents and tenants regarding waste management operations and responsibilities;
- the building manager will make adjustments as required based on actual waste volumes (if waste is greater than estimated) and increase the number of bins and collections accordingly;
- the report will not be used to determine or forecast operational costs or prepare any feasibility study or to document any safety or operational procedures;
- the report has been prepared with all due care however no assurance or representation is made that the WMP reflects the actual outcome and EFRS will not be liable to you for plans or outcomes that are not suitable for your purpose, whether as a result of incorrect or unsuitable information or otherwise;
- EFRS offer no warranty or representation of accuracy or reliability of the WMP unless specifically stated;
- any manual handling equipment recommended should be provided at the recommendation of the appropriate equipment provider who will assess the correct equipment for supply;
- Design of waste management chute equipment and systems must be approved by the supplier.



RESIDENTIAL WASTE MANAGEMENT

The *Lane Cove Development Control Plan* (2010) has been referenced to calculate the total number of bins required for the residential units.

Lane Cove Council's waste and recycling generation rates for residential developments is as follows:

Garbage:	1x 240L MGBs per three units collected weekly
Recycling Co-mingled:	1x 240L MGBs per ten units collected weekly
Recycling Paper:	1x 240L MGBs per ten units collected weekly

Calculations are based on generic figures; waste generation rates may differ according to the residents' waste management practice.

ESTIMATED WASTE VOLUMES AND PROVISIONS

The following table shows the estimated volume (L) of garbage and recycling generated by the development.

# Units	Garbage Generation Rate (L/unit/week)	Generated Garbage (L/week)	Comingled Recycling Generation Rate (L/unit/week)	Generated Comingled Recycling (L/week)	Paper/Cardboard Recycling Generation Rate (L/unit/week)	Generated Paper/ Cardboard Recycling (L/week)
30	80	2400	24	720	24	720
Ostariana	Bin Size (L)	240	Bin Size (L)	240	Bin Size (L)	240
Collections &	Bins per Day	2	Bins per Day	1	Bins per Day	1
	Collections per Week	1	Collections per Week	1	Collections per Week	1
	Total Garbage Bins	10	Total Comingled Bins	3	Total Paper/Cardboard Bins	3

Table 2: Calculated Waste Generation – Residential

HOUSEHOLD WASTE

A single garbage chute will be installed with access provided on all residential levels. The chute is to be used for the disposal of garbage only.

Garbage discharges into 240L bins placed on a linear track system. The discharge is located in the chute discharge room on basement level 1.

Recycling bins will be situated in the waste compartment on each residential level for collection of recyclable items. The caretaker/cleaner will be responsible for monitoring the capacity of recycling bins and exchanging, emptying or storing them in the basement level waste room as and when required.

Full garbage and recycling bins will be collected directly from the basement waste room by Council's waste contractor.

COMMON AREAS

The lobbies, amenities and circulation areas will be supplied with suitably branded waste and recycling bins where considered appropriate. These areas generate minimal waste, however garbage and recycling receptacles should be provided and located in convenient locations.

Washroom facilities should be supplied with collection bins for paper towels (if used). Sanitary bins for female restroom facilities must also be arranged with an appropriate contractor.



SOURCE SEPERATION

Waste avoidance, recovery and reuse of discarded materials and responsible management of hazardous waste are all crucial elements of sustainable development. Effective waste management practices in residential developments significantly improve environmental, social, and economic outcomes on both a local and regional scale, and should be integrated into the waste management processes.

GENERAL WASTE (GARBAGE)

Residents will be supplied with a collection area in each unit to deposit garbage and collect recyclable material suitable for one day's storage. This is typically located generally in the kitchen, under bench or similar alternate area. Residents should wrap or bag their garbage; bagged garbage should not exceed 3kg in weight or 35cm x 35cm x 35cm in dimension.

RECYCLING

Recycling must not be bagged. It is recommended that residents use a crate or dedicated bin for collecting recyclables within the allocated residential space provided to ensure correct separation.

Cardboard furniture boxes or large cardboard containers should not be included in the garbage chute – a cardboard collection bin will be made available to residents to deposit flattened cardboard and will be managed by the waste caretaker. Residents should be advised of the location of these bins by building management.

GREEN WASTE

Green waste is not typically generated from multi-unit dwellings other than from surrounding building landscaped areas and is removed by the designated maintenance contractor. In the event that green waste is produced i.e trimming of indoor or balcony plants then this may be disposed of via coordination with the building caretaker or cleaner. Very small quantities may be disposed of via the general waste stream.

BULKY GOODS

A room or caged area will be made available for the storage of discarded residential bulky items (e.g. whitegoods, furniture, etc.). This room should be located within close proximity of the waste room and must have a minimum doorway width of 1700mm to allow for easy movement of large waste items in and out of the room.

Lane Cove council requires that any development with 10 or more dwellings must have a bulky goods room. Lane cove council requires that the bins are designed to the following minimum sizes:

- 1-10 units 10m²
- 11-20 units 20m²
- >21 units 30m²

These areas are crucial to prevent residents from illegally dumping bulky waste on the footpath outside Councils scheduled collection times. Regular illegal dumping can attract other dumped waste, generate litter, detract significantly from the quality and appearance of the development and reduce amenity of the street.

Residents will be required to liaise with building management regarding the transportation and disposal of bulky goods. Ideally, bulky waste should be collected on a regular schedule so that the storage area does not become overfull and so that residents know when to place items in

OPERATIONAL WASTE MANAGEMENT PLAN



there for collection. Councils may arrange for more frequent collections of bulky waste for MUDs, however collection frequencies vary among different local government areas.

Donations to charitable organisations should be encouraged. Clean, sound furniture and household goods etc. are highly sought after to provide for the disadvantaged. Donations can be arranged with the assistance of the building manager/waste caretaker.

ELECTRONIC WASTE

Electrical waste (e.g. fluorescent tubing, batteries, laptops etc.) can potentially contaminate soil and surrounding water bodies if not disposed correctly. These items must not be placed in standard garbage and recycling bins. Disposal or recycling of electronic waste will be organised with the assistance of the building caretaker. These items must not be placed in garbage or recycling bins due to safety and environmental factors. Residents and/or the building manager may choose to contact Council to find out about new/existing strategies for the disposal/collection of electronic waste.

CHEMICAL WASTE

Chemical wastes (e.g. cleaning chemicals, paints, oils solvents) pose detrimental effects to human health and the environment and should be disposed of to a suitable licensed disposal facility. No liquid wastes or wash down waters should be disposed of via the storm water drainage system. Household Chemical CleanOut events are held at various locations throughout NSW on specified dates throughout the year. Locations and dates are subject to change; hence it is recommended that the building caretaker confirm these details with their local Council.

ORGANIC WASTE AND COMPOSTING

Recycling organic waste, such as food scraps and garden materials, dramatically reduces the quantity of waste being diverted to land fill and thus reduces residents' ecological footprint. Compost material can also be returned to the soil as a rich fertilizer and improve plant growth and the overall health of surrounding vegetation. It is recommended that a space for composting and worm farming is made available for all residents in a communal facility or in small private courtyards (*see APPENDIX D.1*). Composting facilities are to be sited on an unpaved area with soil depth of at least 300mm. Residents may also choose to purchase and install apartment style compost bin where practical and self-manage these systems (*see APPENDIX D.3*).



MOVEMENT AND TRANSPORTATION OF BINS

The building manager/waste caretaker is responsible for any transportation of bins that occurs on this site.

Transfer of waste and all bin movements require minimal manual handling; the operator must assess manual handling risks and provide any relevant documentation to building management.

If required, the developer should contact a bin-tug, trailer or tractor consultant to provide equipment recommendations. Examples of motorised bin moving equipment can be found in APPENDIX B.4 and APPENDIX B.5.

Bins may have to be fitted with hitches to enable the simultaneous transportation of multiple bins to the collection area. Council must be informed of any hitch attachments required to be installed on bins.

COLLECTION OF WASTE

All waste generated by the development will be collected by Council's waste contractor using an SRV. It is intended for garbage, comingled recycling and paper/cardboard recycling all to be collected on a weekly basis.

Prior to collections, the building manager/caretaker will be responsible for ensuring that all bins are neatly arranged within the basement level waste room for ease of servicing.

On collection days, Council's waste contractor collection vehicle will access the site from Pinaroo Place and drive into the basement, pulling-up adjacent to the waste room. Collection staff will then access the waste room and service the bins.

Once servicing is complete, the vehicle will leave the site in a forward-facing direction. The building manager/waste caretaker will then be responsible for ensuing bins are once again neatly arranged within the waste room, ready to resume operational use.

COLLECTION AREA

It is Elephant Foot's understanding that the collection areas have been reviewed by a traffic consultant to confirm the swept paths, load requirements and clearances for waste collections. Council have stated that a clearance height of at least 2.6m will be required for the collection vehicle.



INSTALLATION EQUIPMENT AND DESIGN EQUIPMENT SUMMARY

Table 3: Equipment Summary						
Component	Part	Qty	Notes			
Chutes	Galvanised Steel / LLDPE Polyethylene Plastic 510mm or 610mm (for 20+ levels)	1	510/610mm diameter (See APPENDIX C.1 for Typical Chute Section)			
Equipment A	Garbage 3-bin 240L MGB Linear Track System	1	(See APPENDIX C.2 for Typical Linear System)			
Equipment B	Suitable Bin Moving Equipment	N/A	Optional (See APPENDIX B.4 & APPENDIX B.5 for Typical Bin Movers)			

WASTE ROOM AREAS

All waste discharge points should be caged off to ensure the safety of any personnel accessing the waste room. Access to waste discharge rooms should be provided to the building manager/waste caretaker **only**. Under no circumstances should access be provided to any residents, or waste collection staff.

Chute discharge requires a minimum of 3000mm distance from floor to ceiling and needs to be free of service pipes and other overhead obstacles within the immediate space around the chute discharge.

The areas allocated for residential waste rooms, commercial/retail bin store, bulky goods and collection areas are detailed in Table 4 below. The areas provided are estimates only. Final areas will depend upon room and bin layouts.

Level	Waste Room Type	Equipment	Estimated Area (m ²)
B1	Chute Discharge Room	10 x 240L MGBs (Garbage) 3 x 240L MGBs (Comingled Recycling) 3 x 240L MGBs (Paper/Cardboard Recycling) 1 x 3-Bin 240L Linear Track System	40
	Bulky Goods Waste Storage Room	N/A	26

Table 4: Waste Room Areas



GARBAGE ROOMS

CONSTRUCTION REQUIREMENTS

The garbage room will be required to contain the following facilities to minimise odours, deter vermin, protect surrounding areas, and make it a user-friendly and safe area:

- waste room floor to be sealed with a two pack epoxy;
- waste room walls and floor surface is flat and even;
- all corners coved and sealed 100mm up, this is to eliminate build-up of dirt;
- a hot and cold water facility with mixing facility and hose cock must be provided for washing the bins;
- any waste water discharge from bin washing must be drained to sewer in accordance with the relevant water board. (Sydney Water);
- tap height of 1.6m;
- storm water access preventatives (grate);
- all walls painted with light colour and washable paint;
- equipment electric outlets to be installed 1700mm above floor levels;
- the room must be mechanically ventilated;
- light switch installed at height of 1.6m;
- waste rooms must be well lit (sensor lighting recommended);
- optional automatic odour and pest control system installed to eliminate all pest types and assist with odour reduction – this process generally takes place at building handover – building management make the decision to install;
- if 660L or 1100L bins are utilised, 2 x 820mm (minimum) door leafs must be used;
- all personnel doors are hinged, lockable and self-closing;
- waste collection area must hold all bins bin movements should be with ease of access;
- conform to the Building Code of Australia, Australian Standards and local laws; and
- childproofing and public/operator safety shall be assessed and ensured

SIGNAGE

The building manager/caretaker is responsible for waste room signage including safety signage (see APPENDIX B.2). Appropriate signage must be prominently displayed on doors, walls and above all bins, clearly stating what type of waste or recyclables is to be placed in the bin underneath.

All chute doors on all residential levels will be labelled with signs directing chute operations and use of chute door.

VENTILATION

Waste and recycling rooms must have their own exhaust ventilation system either;

- Mechanically exhausting at a rate of 5L/m² floor area, with a minimum rate of 100L/s minimum; or
- Naturally permanent, unobstructed, and opening direct to the external air, not less than one-twentieth (1/20) of the floor area

Mechanical exhaust systems shall comply with AS1668 and not cause any inconvenience, noise or odour problem.



USEFUL CONTACTS

Elephants Foot Recycling Solutions does not warrant or make representation for goods or services provided by suppliers.

LANE COVE COUNCIL CUSTOMER SERVICE

Phone: (02) 9911 3555

Email: lccouncil@lanecove.nsw.gov.au

SULO MGB (MGB, Public Place Bins, Tugs and Bin Hitches) Phone: 1300 364 388

CLOSED LOOP (Organic Dehydrator) Phone: 02 9339 9801

ELECTRODRIVE (Bin Mover) Phone: 1800 333 002

Email: sales@electrodrive.com.au

RUD (Public Place Bins, Recycling Bins) Phone: 07 3712 8000

Email: Info@rud.com.au

CAPITAL CITY WASTE SERVICES (Private Waste Services Provider) Phone: 02 9359 9999

REMONDIS (Private Waste Services Provider) Phone: 13 73 73

SITA ENVIRONMENTAL (Private Waste Services Provider) Phone: 13 13 35

NATIONAL ASSOCIATION OF CHARITABLE RECYCLING ORGANISATIONS INC. (NACRO)

Phone: 03 9429 9884

Email: information@nacro.org.au

PURIFYING SOLUTIONS (Odour Control) Phone: 1300 636 877

Email: sales@purifyingsolutions.com.au

MOVEXX (Bin Movers) Phone: 1300 763 444

AUSCOL (Recyling Oils & Animal Fats) Phone: 1800 629 476


KOMPACT EQUIPMENT (Equipment & Servicing Provider) Phone: 1300 566 722 Email: info@kompactequipment.com.au

ELEPHANTS FOOT RECYCLING SOLUTIONS (Chutes, Compactors & eDiverter Systems) 44 – 46 Gibson Avenue Padstow NSW 2211 Phone: 1300 434 374 Email: wmp@elephantsfoot.com.au

APPENDICES


APPENDIX A ARCHITECTURAL DRAWING EXCERPTS

APPENDIX A.1 SITE PLAN




Source: Stanton Dahl Architects, Drawing No. DA02, Rev.01, 01/12/20 – Site & External Works Plan





APPENDIX A.2 WASTE ROOMS/COLLECTION AREA



Source: Stanton Dahl Architects, Drawing No. DA06, Rev.01, 01/12/20 – Floor Plans - Basement L1





APPENDIX B PRIMARY WASTE MANAGEMENT PROVISIONS APPENDIX B.1 LANE COVE BIN SPECIFICATIONS

Bin type	Height	Depth	• Width
• 80 Litre Bin	• 870mm	• 530mm	• 450mm
120 Litre Bin	• 940mm	• 560mm	• 485mm
• 240 Litre Bin	• 1080mm	• 735mm	• 580mm

These dimensions are only a guide and differ slightly according to manufacturer, if bins have flat or dome lids and are used with different lifting devices.

Source: Lane Cove Development Control Plan (2010)



APPENDIX B.2 SIGNAGE FOR WASTE & RECYCLING BINS

Waste Signs

Signs for garbage, recycling and organics bins should comply with the standard signs promoted by the EPA (Environmental Protection Authority).

Examples of waste wall posters (EPA supplied)



Examples of bin lid stickers (EPA supplied)



Problem Waste Signs

The EPA has also produced a range of images and signs that can be used for problem wastes, such as fluoro globes and tubes, household and car batteries, e-waste and smoke detectors. To access these resources, contact the NSW EPA. Some examples are shown below.



Safety Signs

The use of safety signs for waste resource recovery rooms must comply with *AS1319 Safety signs for occupational environments*. Safety signs must be used to regulate and control safety related to behaviour, warn of hazards and provide emergency information, including fire protection information. Suitable signs should be decided for each development as required.



Source: New South Wales Environmental Protection Authority Better Practice Guide for Resource Recovery (2019)



APPENDIX B.3 TYPICAL SRV



REARLIFT TRUCK 4X2 MID RANGE 10m⁵ & 12m³ BODY



Specifications:


- Overall Length 6440mm (6.14 METRES)
- Overall Width 2200mm (2.20 METRES) * NOTE: DOES NOT INCLUDE MIRRORS*
- Maximum Height 2830mm (2.83 METRES)
- Turning Circle 15000mm (15.00 METRES) Kerb to Kerb
- Tare Weight 6200 kg/s
- * GVM 10400 kg/s
- 120 litre & 240 litre & 660 litre & 1100 litre Plastic SULO bins

SYDNEY/CITY AREA ONLY

Source: Capital City Waste Services



APPENDIX B.4 TYPICAL MOTORISED BIN TUG



Typical applications:

- Move trolleys, waste bin trailers and 660/1100L bins up and down a ramp incline.
- Quiet, smooth operation with zero emissions and simple to use, no driver's licence required
- Suitable for:
 - High rise building & apartment basements
 - Large factories & warehouse with sloped ground
 - Caravan parks & other large outdoor areas

Features:

- 1 tonne tow capacity of inclines up to 8 degrees
- 500kg tow capacity if inclines up to 14 degrees
- CE Compliant
- 4.5 km/h max speed
- 2 x 80amp batteries includes charger
- Powerful transaxle
- Hitch to suit 660L bins


Safety Features:

- Intuitive paddle lever control
- Stops and repels the unit if activated when reversing.
- Site assessment recommended to assess ramp incline steepness (See Useful Contacts)



APPENDIX B.5 TYPICAL SEATED BIN MOVER






		UNIT M.	BULL 2	BULL 4
Manufacturer	DEC			
Model	BULL			
Platform loading cap.	Nominal capacity	kg		
Pull capacity	Pull nominal capacity	kg	2000	4000
Power type	Electric - endotermic		electric	electric
Controltype	Standing / seated thiller / steer		seated / steer	seated / stee
Tyres	Pn=pneum. Se=superelastic		Pn	Pn
Wheels	N. front/rear - x drive	n.	1/2X	1/2X
Platform dimensions	L x B (lengh x width)	mm		
Platform hight	h6 = unload clearence	mm		
Overal dimensions	L = lenght B = width h1 = foot leve h3 = Seat height h4 = Steer height	mm mm mm mm	1500 900 1820 310 1250	1600 930 1960 340 1330
Turning radius	R1 = front min. external R2 = rear min. external R3 = front min. internal	mm mm mm	1400 1000 400	1500 1000 400
Aisle width	A = 180° turn	mm	2200	2300
Tow hook height	s = center from ground	mm	220-350-490	240-380-520



APPENDIX CINSTALLATION EQUIPMENTAPPENDIX C.1TYPICAL SINGLE WASTE CHUTE SPECIFICATIONS



Waste chutes are supplied per the following specifications:


- either 510mm or 610mm (for 20+ levels) galvanised steel or recycled LLDPE polyethylene plastic;
- galvanised steel chute hoppers are wrapped with 50mm poly-wool R1.3 noise insulation foil to assist in noise reduction (or equivalent);
- penetrations on each building level at vertically perpendicular points with minimum penetration dimensions of either 600x600/700x700mm (square) or 650/750mm diameter (round) are required to accommodate the chute installation;
- a wash down system and vent should also be included as part of the chute system;
- council and supplier require that all chutes are installed without offsets to achieve best
 practise operationally for the building; and
- two hour fire-rated (AS1530.4-2005) stainless steel refuse chute doors at each service level. All doors are to be fitted with a self-closing mechanism to meet BSA fire standards.

<u>NOTE</u>: Chute doors are installed after walls rendered, painted or when required. Information stickers will be placed on each chute door at each residential level.



OPERATIONAL WASTE MANAGEMENT PLAN

APPENDIX C.2 TYPICAL LINEAR TRACK SYSTEM




LAYOUT PLAN scale 1:20



APPENDIX D SECONDARY WASTE MANAGEMENT PROVISIONS APPENDIX D.1 TYPICAL WORM FARM SPECIFICATIONS

Worm farms



Space requirements for a typical worm farm for an average household:

Height – 300mm per level

Width – 600mm

Length – 900mm

There are many worm farm arrangements. The above dimensions are indicative only.

lower bin collects

SOURCE: Department of Environment and Climate Change NSW 2008, Better Practice Guide for Waste Management in Multi-Unit Dwellings



APPENDIX D.2 TYPICAL APARTMENT STYLE COMPOST BINS



Apartment Style Compost bin – available from hardware stores

Suitable for:

- Vegetables
- Coffee grounds and filters
- Tea and tea bags
- Crushed eggshells (but not eggs)
- Nutshells
- Houseplants
- Leaves
- Cardboard rolls, cereal
- Boxes, brown paper bags
- Clean paper
- Shredded newspaper
- Fireplace ashes
- Wood chips, sawdust,
- Toothpicks, burnt matches
- Cotton and wool rags
- Dryer and vacuum cleaner lint
- Hair and fur
- Hay and straw

780mm

400mm

APPENDIX D.3 ELECTRIC ORGANIC COMPOST BIN



Product Specifications

Decomposition Method	Fermentation by microorganisms
Decomposition Capacity	2 metric tonnes per year* (4 kg per day*)
Rating	220-240 V 50⁄60 Hz - 1.1 A
Decomposition Time	24 hrs
Operating Temperature	0C and 40C.**
Deodorisation Method	Nano-Filter system
Maximum Power	210 W
Power Usage	Average 1 kwh per day
Weight	21 kgs
External Dimensions	w 400 mm d 400 mm h 780 mm

* Food Waste Handling Capacity - based on an optimal operating environment.

** Ambient temperature range of area where unit may be installed.

SOURCE: Closed Loop Domestic Composter – See Useful Contacts http://www.closedloop.com.au/domestic-composter