BASIX™Certificate

Building Sustainability Index www.planningportal.nsw.gov.au/development-and-assessment/basix

Multi Dwelling

Certificate number: 1793147M

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.planningportal.nsw.gov.au/definitions

Secretary

Date of issue: Monday, 28 April 2025

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



Project summary		
Project name	BEGA VALLEY RAWLINSON DT	
Street address	112 RAWLINSON STREET BEGA	2550
Local Government Area	BEGA VALLEY	
Plan type and plan number	Deposited Plan DP1187097	
Lot no.	2	·
Section no.	-	
No. of residential flat buildings	3	
Residential flat buildings: no. of dwellings	43	
Multi-dwelling housing: no. of dwellings	21	
No. of single dwelling houses	0	
Project score		
Water	✓ 40	Target 40
Thermal Performance	✓ Pass	Target Pass
Energy	₩ 81	Target 62
Materials	· -100	Target n/a

Certificate Prepared by

Name / Company Name: Mantle Sustainable

ABN (if applicable):

Version: 4.03 / EUCALYPTUS_03_01_0

Description of project

Project address	
Project name	BEGA VALLEY RAWLINSON DT
Street address	112 RAWLINSON STREET BEGA 2550
Local Government Area	BEGA VALLEY
Plan type and plan number	Deposited Plan DP1187097
Lot no.	2
Section no.	-
Project type	
No. of residential flat buildings	3
Residential flat buildings: no. of dwellings	43
Multi-dwelling housing: no. of dwellings	21
No. of single dwelling houses	0
Site details	
Site area (m²)	9585
Roof area (m²)	3303
Non-residential floor area (m²)	0
Residential car spaces	54
Non-residential car spaces	0

Common area landscape						
Common area lawn (m²)	187					
Common area garden (m²)	113					
Area of indigenous or low water use species (m²)	80					
Assessor details and thermal loads						
Assessor number	DMN/23/2131					
Certificate number	HLXUJG4O9V					
Climate zone	18					
Project score						
Water	✓ 40	Target 40				
Thermal Performance	✓ Pass	Target Pass				
Energy	✓ 81	Target 62				
Materials	✓ -100	Target n/a				

Version: 4.03 / EUCALYPTUS_03_01_0

page 2/52

Description of project

The tables below describe the dwellings and common areas within the project

Residential flat buildings - AP, 31 dwellings, 3 storeys above ground

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
101	1	27.5	5.1	0	0
105	1	45.5	6.1	0	0
109	1	50.2	6.3	0	0
113	1	26.6	5.2	0	0
203	1	29.2	5.1	0	0
207	1	49	6.1	0	0
211	1	49	6	0	0
301	2	69.5	5.7	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
102	1	27.6	5.1	0	0
106	1	49.8	6.1	0	0
110	2	60.7	5.5	0	0
114	1	46	6.2	0	0
204	2	71	5	0	0
208	1	49	6.1	0	0
212	1	28.4	5.2	0	0
302	2	69.5	5.7	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
103	1	27.7	5.1	0	0
107	1	49.1	6.1	0	0
111	1	38.1	6	0	0
201	1	29.2	5.1	0	0
205	1	49	6.1	0	0
209	1	50.2	6.3	0	0
213	1	28.4	5.2	0	0
303	1	69.7	5.5	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
104	2	68.4	5	0	0
108	1	49.2	6.1	0	0
112	1	26.5	5.2	0	0
202	1	29.2	5.1	0	0
206	1	49.8	6.1	0	0
210	2	70.4	5.5	0	0
214	1	49.7	6.2	0	0

Residential flat buildings - BH1, 6 dwellings, 1 storey above ground

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
B1.1	1	18.5	4.3	0	0
B1.5	1	18.5	4.3	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
B1.2	1	18.5	4.3	0	0
B6	1	18.5	4.3	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
B1.3A	1	21.4	6.1	0	0

Certificate No.: 1793147M

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
B1.4A	1	29.2	6.2	0	0

Residential flat buildings - BH2, 6 dwellings, 1 storey above ground

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
B2.1	1	23.3	6.2	0	0
B2.5	1	18.5	4.4	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
B2.2A	1	31.5	6.3	0	0
B2.6	1	18.5	4.4	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
B2.3	1	18.5	4.4	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
B2.4	1	18.5	4.4	0	0

Multi-dwelling houses

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
10A	4+	151.6	4.72	35.57	30
12B	1	40.4	3.99	0	0
2B	1	51	5.56	0	0
5A	4+	159.7	3.65	53	30
7B	1	39.7	4.32	0	0
9B	1	47.6	6.37	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
11A	2	101.3	2.74	52.64	30
1A	3	145.8	3.46	43.21	30
3A	4+	158.3	5.6	45.93	30
6A	3	127	2.5	42.65	30
8A	2	108.8	2.72	50	30

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
11B	1	39.7	4.32	0	0
1B	1	55.8	5.89	0	0
4A	3	156.7	2.83	46	30
6B	1	39.6	3.84	0	0
8B	1	39.7	4.32	0	0

Certificate No.: 1793147M

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
12A	3	112.8	2.6	45	30
2A	2	136.8	3.04	46.75	30
4B	1	52.5	5	0	0
7A	2	101.2	2.75	50	30
9A	2	122.3	6.86	34.5	30

Description of project

The tables below describe the dwellings and common areas within the project

Common areas of unit building - AP

Common area	Floor area (m²)
Hallway/lobby type (No. 1)	90.94

Common areas of unit building - BH1

Common area	Floor area (m²)
Community room (No. 1)	28.85

Common areas of unit building - BH2

Common area	Floor area (m²)
Community room (No. 2)	26.28

Version: 4.03 / EUCALYPTUS_03_01_0

Schedule of BASIX commitments

- 1. Commitments for Residential flat buildings AP
 - (a) Buildings
 - (i) Materials
 - (b) Dwellings
 - (i) Water
 - (ii) Energy
 - (iii) Thermal Performance
 - (c) Common areas and central systems/facilities
 - (i) Water
 - (ii) Energy
- 2. Commitments for Residential flat buildings BH1
 - (a) Buildings
 - (i) Materials
 - (b) Dwellings
 - (i) Water
 - (ii) Energy
 - (iii) Thermal Performance
 - (c) Common areas and central systems/facilities
 - (i) Water
 - (ii) Energy
- 3. Commitments for Residential flat buildings BH2
 - (a) Buildings
 - (i) Materials
 - (b) Dwellings

BASIX

(i) Water

- (ii) Energy
- (iii) Thermal Performance
- (c) Common areas and central systems/facilities
 - (i) Water
 - (ii) Energy
- 4. Commitments for multi-dwelling housing
 - (a) Dwellings
 - (i) Water
 - (ii) Energy
 - (iii) Thermal Performance and Materials
- 5. Commitments for single dwelling houses
 - (a) Dwellings
 - (i) Water
 - (ii) Energy
 - (iii) Thermal Performance and Materials
- 6. Commitments for common areas and central systems/facilities for the development (non-building specific)
 - (b) Common areas and central systems/facilities
 - (i) Water
 - (ii) Energy

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carriedout. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

1. Commitments for Residential flat buildings - AP

(a) Buildings

(i) Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Floor types", "External wall types", "Internal wall types", "Ceiling and roof types", "Frames" and "Glazing" tables below.			>
(b) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all specifications included in the tables below.		>	
(c) The applicant must construct the floors, walls, roof, ceiling and roof, windows, glazed doors and skylights of the development in accordance with the specifications listed in the tables below. In the case of glazing, a 5% variance from the area values listed in the "Frames" and "Glazing" tables is permitted.	>	>	~
(d) The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the below tables.			V

Floor types						
Floor type	Area (m2)	Insulation	Low emissions option			
suspended floor above garage, frame: suspended concrete slab	778.8	polyurethane	30% cement substitute			
floors above habitable rooms, frame: suspended concrete slab	936.2	polyurethane	30% cement substitute			

	External wall types										
External wall type	Construction type	Area (m2)	Low emissions option	Insulation							
External wall type 1	framed (metal clad),frame:timber - H2 treated softwood	700	none	fibreglass batts or roll							
External wall type 2	reverse brick veneer,frame:timber - H2 treated softwood	2600	none	fibreglass batts or roll							

Version: 4.03 / EUCALYPTUS_03_01_0

BASIX

Certificate No.: 1793147M

External wall types										
External wall type	Construction type	Area (m2)	Low emissions option	Insulation						
	framed (fibre cement sheet or boards),frame:timber - H2 treated softwood	500	none	fibreglass batts or roll						

Internal wall types										
Internal wall type	Construction type	Area (m2)	Insulation							
Internal wall type 1	plasterboard, frame:timber - untreated softwood	30	-							

Reinforcement concrete frames/columns									
Building has reinforced concrete frame/columns?	Volume (m³)	Low emissions option							
-	-	-							

Ceiling and roof types										
Ceiling and roof type	Area (m²)	Roof Insulation	Ceiling Insulation							
framed - metal roof, frame: timber - H2 treated softwood	953.65	foil/sarking	fibreglass batts or roll							
concrete - plasterboard internal, frame: timber - H2 treated softwood	2034.35	-	fibreglass batts or roll							

	Glazing types		Frame types					
Single glazing (m²)	Double glazing (m²)	Triple glazing (m²)	Aluminium frames (m²)	Timber frames (m²)	uPVC frames (m²)	Steel frames (m²)	Composite frames (m²)	
20	0	0	20	0	0	0	0	

(b) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	>	~	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		•	V
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		•	~
(e) The applicant must install:			
(aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and		-	~
(bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		-	~
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	V	~	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		•	
(g) The pool or spa must be located as specified in the table.	V	•	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	~	~	~

	Fixtures			Appliances		Individual pool			Individual spa					
Dwelling no.	All shower- heads	All toilet flushing systems	taps	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish- washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
	4 star (> 6 but <= 7.5 L/min)	5 star	5 star	5 star	-	-	-	-	-	-	-	-	-	-

Version: 4.03 / EUCALYPTUS_03_01_0

Department of Planning, Housing and Infrastructure

Certificate No.: 1793147M

	Alternative water source											
Dwelling no.	Alternative water supply systems	Size	Configuration	Landscape connection	Toilet connection (s)	Laundry connection	Pool top- up	Spa top-up				
All dwellings	No alternative water supply	-	-	-	-	-	-	-				

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system.	>	>	>
(c) The applicant must install, in each bathroom, kitchen and laundry of the dwelling, the ventilation system specified for that room in the table below. Each such ventilation system must have the operation control specified for it in the table.		>	>
(d) The applicant must install the cooling and heating system/s specified for the dwelling under the "Living areas" and "Bedroom areas" headings of the "Cooling" and "Heating" columns in the table below, in/for at least 1 living/bedroom area of the dwelling. If no cooling or heating system is specified in the table for "Living areas" or "Bedroom areas", then no systems may be installed in any such areas. If the term "zoned" is specified beside an air conditioning system, then the system must provide for day/night zoning between living areas and bedrooms.		*	•
(e) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Artificial lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that the "primary type of artificial lighting" for each such room in the dwelling is fluorescent lighting or light emitting diode (LED) lighting. If the term "dedicated" is specified for a particular room or area, then the light fittings in that room or area must only be capable of being used for fluorescent lighting or light emitting diode (LED) lighting.		~	*
(f) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Natural lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that each such room or area is fitted with a window and/or skylight.	>	~	~
(g) This commitment applies if the applicant installs a water heating system for the dwelling's pool or spa. The applicant must:			
(aa) install the system specified for the pool in the "Individual Pool" column of the table below (or alternatively must not install any system for the pool). If specified, the applicant must install a timer, to control the pool's pump; and		-	
(bb) install the system specified for the spa in the "Individual Spa" column of the table below (or alternatively must not install any system for the spa). If specified, the applicant must install a timer to control the spa's pump.		-	
(h) The applicant must install in the dwelling:			
(aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below;		_	

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and		>	>
(cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		>	
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		>	

	Hot water	Bathroom ventilation system Kitchen ventilation system			Laundry ventilation system		
Dwelling no.	Hot water system	Each bathroom Operation control Each kitchen Operation control		Each laundry	Operation control		
All dwellings	electric instantaneous	central ducted	-	central ducted	-	central ducted	-

	Cooling		Hea	ting	Natural lighting		
Dwelling no.	living areas	bedroom areas	living areas		No. of bathrooms or toilets	Main kitchen	
All dwellings	-	-	-	-	0	yes	

	Individual pool			Individual spa Appliances other efficiency mea			measures	measures		
Dwelling no.	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	electric cooktop & electric oven	4 star	8.0 star	no	no

(iii) Thermal Performance	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	>		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		>	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		~	~
(g) Where there is an in-slab heating or cooling system, the applicant must:	~	~	~
(aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or			
(bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.			
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	V	~	V
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	V		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		~	

		Thermal loads	
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)
101	5.5	19.4	24.900
103	4.6	19	23.600
104	7.9	12.2	20.100
105	15.6	22.1	37.700

Department of Planning, Housing and Infrastructure

		Thermal loads					
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)				
106	48.5	8.8	57.300				
107	44.5	12.2	56.700				
108	38.2	17.2	55.400				
109	44.2	8.6	52.800				
110	38.7	14	52.700				
111	9.8	25.3	35.100				
112	5.9	22.2	28.100				
113	3.1	18.3	21.400				
114	3	10.2	13.200				
201	4.4	15.7	20.100				
202	1.3	15.08	16.380				
203	1.2	11.7	12.900				
204	4.1	7.5	11.600				
205	6	10.7	16.700				
206	38.4	5.1	43.500				
207	37.4	6.4	43.800				
209	33.7	4.2	37.900				
210	25.9	11.4	37.300				
211	7.3	16	23.300				
212	4.9	20.4	25.300				
213	3	18.8	21.800				
214	1.7	13.3	15.000				
301	15.4	14.5	29.900				
302	18.5	11.1	29.600				
303	51.7	6.3	58.000				
All other dwellings	28.8	7.2	36.000				

(c) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		>	•
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	>	•	>
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	>	~	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		~	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		~	>
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		~	~

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	4 star (> 6 but <= 7.5 L/min)	5 star	5 star	4 star

Central systems	Size	Configuration	Connection (to allow for)
Central water tank - rainwater or stormwater (No. 1)	60000	To collect run-off from at least: - 1140 square metres of roof area of buildings in the development - 0 square metres of impervious area in the development - 0 square metres of garden/lawn area in the development - 0 square metres of planter box area in the development (excluding, in each case, any area which drains to, or supplies, any other alternative water supply system).	- irrigation of 100 square metres of common landscaped area on the site - car washing in 1 car washing bays on the site

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		>	V

Version: 4.03 / EUCALYPTUS_03_01_0

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		>	<
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	>	V	<

	Common area ve	Common area ventilation system Common area lighting			
Common area	Ventilation system type	Ventilation efficiency measure	Primary type of artificial lighting	Lighting efficiency measure	Lighting control system/ BMS
Hallway/lobby type (No. 1)	no mechanical ventilation	-	compact fluorescent	manual on / manual off	no

2. Commitments for Residential flat buildings - BH1

(a) Buildings

(i) Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Floor types", "External wall types", "Internal wall types", "Ceiling and roof types", "Frames" and "Glazing" tables below.			>
(b) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all specifications included in the tables below.		>	
(c) The applicant must construct the floors, walls, roof, ceiling and roof, windows, glazed doors and skylights of the development in accordance with the specifications listed in the tables below. In the case of glazing, a 5% variance from the area values listed in the "Frames" and "Glazing" tables is permitted.	~	>	~
(d) The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the below tables.			~

Floor types									
Floor type	Area (m2)	Insulation	Low emissions option						
concrete slab on ground, frame:	182.95	-	30% cement substitute						

	External wall types										
External wall type	Construction type	Area (m2)	Low emissions option	Insulation							
External wall type 1	framed (metal clad),frame:timber - H2 treated softwood	700	none	fibreglass batts or roll							
External wall type 2	reverse brick veneer,frame:timber - H2 treated softwood	2600	none	fibreglass batts or roll							
External wall type 3	framed (fibre cement sheet or boards),frame:timber - H2 treated softwood	500	none	fibreglass batts or roll							

Internal wall types									
Internal wall type	Construction type	Area (m2)	Insulation						
1	plasterboard, frame:timber - untreated softwood	30	-						

Version: 4.03 / EUCALYPTUS_03_01_0

BASIX

Certificate No.: 1793147M

Reinforcement concrete frames/columns									
Building has reinforced concrete frame/columns?	Volume (m³)	Low emissions option							
-	-	-							

Ceiling and roof types									
Ceiling and roof type	Area (m²)	Roof Insulation	Ceiling Insulation						
framed - metal roof, frame: timber - H2 treated softwood	154	foil/sarking	fibreglass batts or roll						

	Glazing types		Frame types					
Single glazing (m²)	Double glazing (m²)	Triple glazing (m²)	Aluminium frames (m²)	Timber frames (m²)	uPVC frames (m²)	Steel frames (m²)	Composite frames (m²)	
40	0	0	40	0	0	0	0	

(b) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	>	~	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		>	>
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		>	>
(e) The applicant must install:			
(aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and		-	~
(bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		-	~
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	V	~	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		>	
(g) The pool or spa must be located as specified in the table.	>	~	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	>	~	~

	Fixtures			Appliances		Individual pool			Individual spa					
Dwelling no.	All shower- heads	All toilet flushing systems	taps	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish- washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
	4 star (> 6 but <= 7.5 L/min)	5 star	5 star	5 star	-	-	-	-	-	-	-	-	-	-

Version: 4.03 / EUCALYPTUS_03_01_0

Department of Planning, Housing and Infrastructure

		Alternative water source										
Dwelling no.	Alternative water supply systems	Size	Configuration	Landscape connection	Toilet connection (s)	Laundry connection	Pool top- up	Spa top-up				
All dwellings	No alternative water supply	-	-	-	-	-	-	-				

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system.	>	>	>
(c) The applicant must install, in each bathroom, kitchen and laundry of the dwelling, the ventilation system specified for that room in the table below. Each such ventilation system must have the operation control specified for it in the table.		>	>
(d) The applicant must install the cooling and heating system/s specified for the dwelling under the "Living areas" and "Bedroom areas" headings of the "Cooling" and "Heating" columns in the table below, in/for at least 1 living/bedroom area of the dwelling. If no cooling or heating system is specified in the table for "Living areas" or "Bedroom areas", then no systems may be installed in any such areas. If the term "zoned" is specified beside an air conditioning system, then the system must provide for day/night zoning between living areas and bedrooms.		*	•
(e) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Artificial lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that the "primary type of artificial lighting" for each such room in the dwelling is fluorescent lighting or light emitting diode (LED) lighting. If the term "dedicated" is specified for a particular room or area, then the light fittings in that room or area must only be capable of being used for fluorescent lighting or light emitting diode (LED) lighting.		~	*
(f) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Natural lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that each such room or area is fitted with a window and/or skylight.	>	~	~
(g) This commitment applies if the applicant installs a water heating system for the dwelling's pool or spa. The applicant must:			
(aa) install the system specified for the pool in the "Individual Pool" column of the table below (or alternatively must not install any system for the pool). If specified, the applicant must install a timer, to control the pool's pump; and		-	
(bb) install the system specified for the spa in the "Individual Spa" column of the table below (or alternatively must not install any system for the spa). If specified, the applicant must install a timer to control the spa's pump.		-	
(h) The applicant must install in the dwelling:			
(aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below;		_	

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and		~	< -
(cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		~	
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		>	

	Hot water	Bathroom ven	tilation system	Kitchen venti	lation system	Laundry ventilation system		
Dwelling no.	Hot water system	Each bathroom	Operation control	Each kitchen	Operation control	Each laundry	Operation control	
All dwellings	electric instantaneous	individual fan, ducted to façade or roof		individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	

	Cooling		Hea	ting	Natural lighting		
Dwelling no.	living areas	bedroom areas	living areas		No. of bathrooms or toilets	Main kitchen	
All dwellings	-	-	-	-	0	yes	

	Individual pool			Individual spa Appliances other efficiency measurements			measures			
Dwelling no.	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	electric cooktop & electric oven	4 star	8.0 star	no	no

(iii) Thermal Performance	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	>		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		>	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		~	~
(g) Where there is an in-slab heating or cooling system, the applicant must:	~	~	~
(aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or			
(bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.			
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	V	~	V
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	V		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		~	

		Thermal loads	
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)
B1.1	13.9	20.7	34.600
B1.2	10.7	18.3	29.000
B1.3A	20.5	27.4	47.900
B1.4A	41.7	17.3	59.000

Department of Planning, Housing and Infrastructure

BASIX

Certificate No.: 1793147M

	Thermal loads				
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)		
B1.5	30.4	21.3	51.700		
All other dwellings	29.8	22.5	52.300		

(c) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		~	~
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	>	~	>
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	>	>	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		~	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		~	V
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		~	V

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	4 star (> 6 but <= 7.5 L/min)	5 star	5 star	4 star

Central systems	Size	Configuration	Connection (to allow for)
Central water tank - rainwater or stormwater (No. 2)	10000	To collect run-off from at least: - 288 square metres of roof area of buildings in the development - 0 square metres of impervious area in the development - 0 square metres of garden/lawn area in the development - 0 square metres of planter box area in the development (excluding, in each case, any area which drains to, or supplies, any other alternative water supply system).	- irrigation of 100 square metres of common landscaped area on the site - car washing in 1 car washing bays on the site

Version: 4.03 / EUCALYPTUS_03_01_0

Central systems	Size	Configuration	Connection (to allow for)
Central water tank - rainwater or stormwater (No. 3)	10000	To collect run-off from at least: - 295 square metres of roof area of buildings in the development - 0 square metres of impervious area in the development - 0 square metres of garden/lawn area in the development - 0 square metres of planter box area in the development (excluding, in each case, any area which drains to, or supplies, any other alternative water supply system).	- irrigation of 100 square metres of common landscaped area on the site - car washing in 1 car washing bays on the site

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		>	>
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		>	>
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	•	>	•

	Common area ve	entilation system		Common area lighting			
Common area	Ventilation system type	Ventilation efficiency measure	Primary type of artificial lighting	Lighting efficiency measure	Lighting control system/ BMS		
Community room (No. 1)	air conditioning system	time clock or BMS controlled	compact fluorescent	manual on / manual off	no		

Department of Planning, Housing and Infrastructure

page 25/52

3. Commitments for Residential flat buildings - BH2

(a) Buildings

(i) Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Floor types", "External wall types", "Internal wall types", "Ceiling and roof types", "Frames" and "Glazing" tables below.			>
(b) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all specifications included in the tables below.		>	
(c) The applicant must construct the floors, walls, roof, ceiling and roof, windows, glazed doors and skylights of the development in accordance with the specifications listed in the tables below. In the case of glazing, a 5% variance from the area values listed in the "Frames" and "Glazing" tables is permitted.	~	>	~
(d) The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the below tables.			~

Floor types									
Floor type	Area (m2)	Insulation	Low emissions option						
concrete slab on ground, frame:	182.95	-	30% cement substitute						

	External wall types											
External wall type	Construction type	Area (m2)	Low emissions option	Insulation								
External wall type 1	framed (metal clad),frame:timber - H2 treated softwood	700	none	fibreglass batts or roll								
External wall type 2	reverse brick veneer,frame:timber - H2 treated softwood	2600	none	fibreglass batts or roll								
External wall type 3	framed (fibre cement sheet or boards),frame:timber - H2 treated softwood	500	none	fibreglass batts or roll								

Internal wall types									
Internal wall type	Construction type	Area (m2)	Insulation						
1	plasterboard, frame:timber - untreated softwood	30	-						

Version: 4.03 / EUCALYPTUS_03_01_0

Reinforcement concrete frames/columns									
Building has reinforced concrete frame/columns?	Volume (m³)	Low emissions option							
-	-	-							

Ceiling and roof types									
Ceiling and roof type	Area (m²)	Roof Insulation	Ceiling Insulation						
framed - metal roof, frame: timber - H2 treated softwood	159	foil/sarking	fibreglass batts or roll						

	Glazing types		Frame types					
Single glazing (m²)	Double glazing (m²)	Triple glazing (m²)	Aluminium frames (m²)	Timber frames (m²)	uPVC frames (m²)	Steel frames (m²)	Composite frames (m²)	
40	0	0	40	0	0	0	0	

(b) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	>	>	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		~	~
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		>	~
(e) The applicant must install:			
(aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and		~	~
(bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		~	~
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	V	~	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		~	
(g) The pool or spa must be located as specified in the table.	V	~	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	~	~	>

	Fixtures			Appliances Individual pool			Individual spa							
Dwelling no.	All shower- heads	All toilet flushing systems	taps	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish- washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
	4 star (> 6 but <= 7.5 L/min)	5 star	5 star	5 star	-	-	-	-	-	-	-	-	-	-

Department of Planning, Housing and Infrastructure

Certificate No.: 1793147M

	Alternative water source										
Dwelling no.	Alternative water supply systems	Size	Configuration	Landscape connection	Toilet connection (s)	Laundry connection	Pool top- up	Spa top-up			
All dwellings	No alternative water supply	-	-	-	-	-	-	-			

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system.	~	~	>
(c) The applicant must install, in each bathroom, kitchen and laundry of the dwelling, the ventilation system specified for that room in the table below. Each such ventilation system must have the operation control specified for it in the table.		>	>
(d) The applicant must install the cooling and heating system/s specified for the dwelling under the "Living areas" and "Bedroom areas" headings of the "Cooling" and "Heating" columns in the table below, in/for at least 1 living/bedroom area of the dwelling. If no cooling or heating system is specified in the table for "Living areas" or "Bedroom areas", then no systems may be installed in any such areas. If the term "zoned" is specified beside an air conditioning system, then the system must provide for day/night zoning between living areas and bedrooms.		•	•
(e) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Artificial lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that the "primary type of artificial lighting" for each such room in the dwelling is fluorescent lighting or light emitting diode (LED) lighting. If the term "dedicated" is specified for a particular room or area, then the light fittings in that room or area must only be capable of being used for fluorescent lighting or light emitting diode (LED) lighting.		•	*
(f) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Natural lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that each such room or area is fitted with a window and/or skylight.	~	~	~
(g) This commitment applies if the applicant installs a water heating system for the dwelling's pool or spa. The applicant must:			
(aa) install the system specified for the pool in the "Individual Pool" column of the table below (or alternatively must not install any system for the pool). If specified, the applicant must install a timer, to control the pool's pump; and		_	
(bb) install the system specified for the spa in the "Individual Spa" column of the table below (or alternatively must not install any system for the spa). If specified, the applicant must install a timer to control the spa's pump.		-	
(h) The applicant must install in the dwelling:			
(aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below;		_	

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and		~	<
(cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		~	
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		¥	

	Hot water	Hot water Bathroom ventilation system Kitchen ventilation system			Laundry ventilation system		
Dwelling no.	Hot water system	Each bathroom	Operation control	Each kitchen	Operation control	Each laundry	Operation control
All dwellings	electric instantaneous	individual fan, ducted to façade or roof		individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off

	Cooling		Hea	ting	Natural lighting		
Dwelling no.	living areas	bedroom areas	living areas		No. of bathrooms or toilets	Main kitchen	
All dwellings	-	-	-	-	0	yes	

	Individual pool			Individual spa Appliances other efficiency measures			measures			
Dwelling no.	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	electric cooktop & electric oven	4 star	8.0 star	no	no

(iii) Thermal Performance	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	>		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		>	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		~	~
(g) Where there is an in-slab heating or cooling system, the applicant must:	~	~	~
(aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or			
(bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.			
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	V	~	V
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	V		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		~	

	Thermal loads				
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)		
B2.1	3.8	19.3	23.100		
B2.2A	9.5	16	25.500		
B2.3	21	35.3	56.300		
B2.4	38.2	19.6	57.800		

Department of Planning, Housing and Infrastructure

	Thermal loads				
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)		
B2.5	38.6	19.8	58.400		
All other dwellings	37.7	22.7	60.400		

(c) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		~	~
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	>	~	>
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	>	>	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		~	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		~	V
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		~	V

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	4 star (> 6 but <= 7.5 L/min)	5 star	5 star	4 star

Central systems	Size	Configuration	Connection (to allow for)
Central water tank - rainwater or stormwater (No. 4)	10000	To collect run-off from at least: - 300 square metres of roof area of buildings in the development - 0 square metres of impervious area in the development - 0 square metres of garden/lawn area in the development - 0 square metres of planter box area in the development (excluding, in each case, any area which drains to, or supplies, any other alternative water supply system).	- irrigation of 0 square metres of common landscaped area on the site - car washing in 1 car washing bays on the site

Version: 4.03 / EUCALYPTUS_03_01_0

Central systems	Size	Configuration	Connection (to allow for)
Central water tank - rainwater or stormwater (No. 5)	10000	To collect run-off from at least: - 300 square metres of roof area of buildings in the development - 0 square metres of impervious area in the development - 0 square metres of garden/lawn area in the development - 0 square metres of planter box area in the development (excluding, in each case, any area which drains to, or supplies, any other alternative water supply system).	- irrigation of 0 square metres of common landscaped area on the site - car washing in 1 car washing bays on the site

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		>	>
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		>	>
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	•	>	•

	Common area ve	entilation system		Common area lighting			
Common area	Ventilation system type	Ventilation efficiency measure	Primary type of artificial lighting	Lighting efficiency measure	Lighting control system/ BMS		
Community room (No. 2)	air conditioning system	none i.e., continuous	compact fluorescent	manual on / manual off	no		

Department of Planning, Housing and Infrastructure

4. Commitments for multi-dwelling housing

(a) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	~	>	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		~	>
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		~	V
(e) The applicant must install:			
(aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and			V
(bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		-	~
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	V	~	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		~	
(g) The pool or spa must be located as specified in the table.	V	~	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	~	~	~

	Fixtures				Appliances		Individual pool				Individual spa			
Dwelling no.	All shower- heads	All toilet flushing systems	taps	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish- washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
	4 star (> 6 but <= 7.5 L/min)	5 star	5 star	5 star	-	-	-	-	-	-	-	-	-	-

Version: 4.03 / EUCALYPTUS_03_01_0

BASIX

Certificate No.: 1793147M

	Alternative water source								
Dwelling no.	Alternative water supply systems	Size	Configuration	Landscape connection	Toilet connection (s)	Laundry connection	Pool top- up	Spa top-up	
All dwellings	No alternative water supply	-	-	-	-	-	-	-	

olans	Show on CC/CDC plans & specs	Certifier check
•	~	>
	~	~
	~	•
	~	*
1	~	~
	-	
	_	
	_	, ,

Department of Planning, Housing and Infrastructure

BASIX

page 36/52

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below;		~	
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and		~	~
(cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		~	
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		~	
(j) The applicant must install the photovoltaic system specified for the dwelling under the "Photovoltaic system" heading of the "Alternative energy" column of the table below, and connect the system to that dwelling's electrical system.	V	~	¥

	Hot water	Bathroom ven	tilation system	Kitchen venti	lation system	Laundry ventilation system		
Dwelling no.	Hot water system	Each bathroom	Operation control	Each kitchen	Operation control	Each laundry	Operation control	
All dwellings	electric instantaneous	individual fan, ducted to façade or roof		individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	

	Coo	ling	Hea	ting	Natural lighting		
Dwelling no.	living areas	bedroom areas	living areas	bedroom areas	No. of bathrooms or toilets	Main kitchen	
All dwellings	-	-	-	-	0	yes	

	Individual pool			Individual spa		Appliances other efficiency measures				
Dwelling no.	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	electric cooktop & electric oven	4 star	8.0 star	no	no

	Alternative energy							
Dwelling no.	Photovoltaic system (min rated electrical output in peak kW)	Photovoltaic collector installation	Orientation inputs					
All dwellings	-	-	-					

(iii) Thermal Performance and Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	~		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		>	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		~	~
(g) Where there is an in-slab heating or cooling system, the applicant must:	V	~	V
(aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or			
(bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.			
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	V	~	V
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	~		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		~	

Department of Planning, Housing and Infrastructure

Certificate No.: 1793147M

		Thermal loads								
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)							
10A	42.9	14.5	57.400							
11A	37.2	6.5	43.700							
11B	24.6	23.8	48.400							
12A	27.7	18	45.700							
12B	18.6	29.4	48.000							
1A	26.2	14.3	40.500							
1B	21.6	29.2	50.800							
2A	33	19.2	52.200							
2B	21.6	21.4	43.000							
BA	47.1	7.10	54.200							
1A	24.3	12.2	36.500							
4B	28.2	29.2	57.400							
5A	44.1	6.5	50.600							
6A	14.6	6.7	21.300							
6B	26.8	28.2	55.000							
7A	19.9	7.4	27.300							
7B	26	21.1	47.100							
3A	15.1	4.7	19.800							
ВВ	24.5	20.3	44.800							
9A	17.5	6.3	23.800							
All other dwellings	28.5	27.5	56.000							

		Construction of floors and walls									
Dwelling no.	Concrete slab on ground (m²)	Suspended floor with open subfloor (m²)	Suspended floor with enclosed subfloor (m²)	Suspended floor above garage (m²)	Primarily rammed earth or mudbrick walls						
10A	75.8	-	37.9	37.9	no						
11A	50.65	-	25.32	25.32	no						
11B	-	-	18.95	18.95	no						
12A	56.4	-	28.2	28.2	no						
12B	-	-	20.2	20.2	no						
1A	72.9	-	36.45	36.45	no						

	Construction of floors and walls									
Dwelling no.	Concrete slab on ground (m²)	Suspended floor with open subfloor (m²)	Suspended floor with enclosed subfloor (m²)	Suspended floor above garage (m²)	Primarily rammed earth or mudbrick walls					
1B	-	<u> </u> -	27.9	27.9	no					
2A	68.4	-	34.2	34.2	no					
2B	-	-	25.5	25.5	no					
3A	79.15	-	39.57	39.57	no					
4A	78.35	-	39.17	39.17	no					
4B	-	-	26.25	26.25	no					
5A	79.85	-	39.92	39.92	no					
6A	63.5	-	31.75	31.75	no					
6B	-	-	19.8	19.8	no					
7A	50.6	-	25.3	25.3	no					
8A	54.4	-	27.2	27.2	no					
9A	61.15		30.57	30.57	no					
9B	-	-	23.8	23.8	no					
All other dwellings	-	-	19.85	19.85	no					

	Floor types									
		Concrete slab on ground				Suspended floor above enclosed subfloor			floor above op	en subfloor
Dwelling no.	Area (m²)	Insulation	Low emissions option	Dematerialisation	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation
10A	75.8	-	30% cement substitute	waffle pod slab	plywood, frame: timber - H2 treated softwood	37.9	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
11A	50.65	-	30% cement substitute	waffle pod slab	treated softwood, frame: timber - H2 treated softwood	25.32	fibreglass batts or roll	-	-	-
11B	-	-	-	conventional slab	plywood, frame: timber - H2 treated softwood	18.95	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll

Certificate No.: 1793147M

	Floor types									
		Concre	te slab on groun	d	Suspended flo	oor above end	losed subfloor	Suspended floor above open subfloor		
Dwelling no.	Area (m²)	Insulation	Low emissions option	Dematerialisation	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation
12A	56.4	-	30% cement substitute	waffle pod slab	plywood, frame: timber - H2 treated softwood	28.2	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
12B	-	-	-	conventional slab	plywood, frame: timber - H2 treated softwood	20.2	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
1A	72.9	-	30% cement substitute	waffle pod slab	plywood, frame: timber - H2 treated softwood	36.45	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
1B	-	-	-	conventional slab	plywood, frame: timber - H2 treated softwood	27.9	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
2A	68.4	-	30% cement substitute	waffle pod slab	plywood, frame: timber - H2 treated softwood	34.2	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
2B	-	-	-	conventional slab	plywood, frame: timber - H2 treated softwood	25.5	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
3A	79.15	-	30% cement substitute	waffle pod slab	plywood, frame: timber - H2 treated softwood	39.57	fibreglass batts or roll	plywood, frame: timber - untreated softwood	-	fibreglass batts or roll
4A	78.35	-	-	conventional slab	plywood, frame: timber - H2 treated softwood	39.17	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
4B	-	-	-	conventional slab	plywood, frame: timber	26.25	fibreglass batts or roll	plywood, frame: timber	-	fibreglass batts or roll

	Floor types									
		Concre	te slab on groun	d	Suspended flo	oor above end	losed subfloor	Suspended floor above open subfloor		
Dwelling no.	Area (m²)	Insulation	Low emissions option	Dematerialisation	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation
					- H2 treated softwood	ĺ		- H2 treated softwood		
5A	79.85	-	30% cement substitute	waffle pod slab	plywood, frame: timber - H2 treated softwood	39.92	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
6A	63.5	-	30% cement substitute	waffle pod slab	plywood, frame: timber - H2 treated softwood	31.75	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
6B	-	-	-	conventional slab	plywood, frame: timber - H2 treated softwood	19.8	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
7A	50.6	-	30% cement substitute	waffle pod slab	plywood, frame: timber - H2 treated softwood	25.3	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
8A	54.4	-	30% cement substitute	waffle pod slab	plywood, frame: timber - H2 treated softwood	27.2	fibreglass batts or roll	plywood, frame: timber - untreated softwood	-	fibreglass batts or roll
9A	61.15	-	30% cement substitute	waffle pod slab	plywood, frame: timber - H2 treated softwood	30.57	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
9B	-	-	-	conventional slab	plywood, frame: timber - H2 treated softwood	23.8	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll
All other dwellings	-	-	-	conventional slab	plywood, frame: timber - H2 treated softwood	19.85	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	-	fibreglass batts or roll

	Floor types										
		oor above ha ns or mezzar		Suspende	ed floor abov	e garage			Garage flo	oor	
Dwelling no.	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation	Low emissions option	Dematerialisation
10A	plywood, frame: timber - H2 treated softwood	46.72	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	37.9	fibreglass batts or roll	concrete slab on ground	42	-	30% cement substitute	waffle pod slab
11A	plywood, frame: timber - H2 treated softwood	27.74	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	25.32	fibreglass batts or roll	concrete slab on ground	25	-	30% cement substitute	waffle pod slab
11B	plywood, frame: timber - H2 treated softwood	29.32	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	18.95	fibreglass batts or roll	concrete slab on ground	25	-	30% cement substitute	waffle pod slab
12A	plywood, frame: timber - H2 treated softwood	27.6	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	28.2	fibreglass batts or roll	concrete slab on ground	25	-	30% cement substitute	waffle pod slab
12B	plywood, frame: timber - H2 treated softwood	28.99	-	plywood, frame: timber - H2 treated softwood	20.2	fibreglass batts or roll	concrete slab on ground	25	-	30% cement substitute	waffle pod slab
1A	particle board, frame: timber - H2 treated softwood	23.46	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	36.45	fibreglass batts or roll	concrete slab on ground	20	-	30% cement substitute	waffle pod slab
1B	plywood, frame: timber - H2 treated softwood	25.89	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	27.9	fibreglass batts or roll	concrete slab on ground	20	-	30% cement substitute	waffle pod slab
2A	plywood, frame: timber - H2 treated softwood	23.04	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	34.2	fibreglass batts or roll	concrete slab on ground	20	-	30% cement substitute	waffle pod slab
2B	plywood, frame: timber	25.56	fibreglass batts or roll	plywood, frame: timber	25.5	fibreglass batts or roll	concrete slab on ground	20	-	30% cement substitute	waffle pod slab

	Floor types										
		oor above ha ms or mezzar		Suspende	ed floor abov	e garage			Garage flo	oor	
Dwelling no.	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation	Low emissions option	Dematerialisation
	- H2 treated softwood			- H2 treated softwood							
3A	plywood, frame: timber - H2 treated softwood	47.6	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	39.57	fibreglass batts or roll	concrete slab on ground	42	-	30% cement substitute	waffle pod slab
4A	plywood, frame: timber - H2 treated softwood	22.83	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	39.17	fibreglass batts or roll	concrete slab on ground	20	-	30% cement substitute	waffle pod slab
4B	plywood, frame: timber - H2 treated softwood	47	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	26.25	fibreglass batts or roll	concrete slab on ground	42	fibreglass batts or roll	30% cement substitute	conventional slab
5A	plywood, frame: timber - H2 treated softwood	45.65	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	39.92	fibreglass batts or roll	concrete slab on ground	42	-	30% cement substitute	waffle pod slab
6A	plywood, frame: timber - H2 treated softwood	22.5	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	31.75	fibreglass batts or roll	concrete slab on ground	20	-	30% cement substitute	waffle pod slab
6B	plywood, frame: timber - H2 treated softwood	45.84	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	19.8	fibreglass batts or roll	concrete slab on ground	42	fibreglass batts or roll	30% cement substitute	waffle pod slab
7A	plywood, frame: timber - H2 treated softwood	22.75	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	25.3	fibreglass batts or roll	concrete slab on ground	20	-	30% cement substitute	waffle pod slab
8A	plywood, frame: timber - H2 treated softwood	22.72	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	27.2	fibreglass batts or roll	concrete slab on ground	20	-	30% cement substitute	waffle pod slab

BASIX

Certificate No.: 1793147M

	Floor types											
		First floor above habitable rooms or mezzanine			Suspended floor above garage			Garage floor				
Dwelling no.	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation	Low emissions option	Dematerialisation	
9A	plywood, frame: timber - H2 treated softwood	26.86	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	30.57	fibreglass batts or roll	concrete slab on ground	20	-	30% cement substitute	waffle pod slab	
9B	plywood, frame: timber - H2 treated softwood	31.37	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	23.8	fibreglass batts or roll	concrete slab on ground	25	-	30% cement substitute	waffle pod slab	
All other dwellings	plywood, frame: timber - H2 treated softwood	24.32	fibreglass batts or roll	plywood, frame: timber - H2 treated softwood	19.85	fibreglass batts or roll	concrete slab on ground	20	-	30% cement substitute	waffle pod slab	

	External walls							
		External v	wall type 1			External v	vall type 2	
Dwelling no.	Wall type	Area (m²)	Insulation	Low emissions option	Wall type	Area (m²)	Insulation	Low emissions option
All dwellings	reverse brick veneer, frame : timber - H2 treated softwood	110	fibreglass batts or roll	none	cavity brick, frame : timber - H2 treated softwood	32	fibreglass batts or roll	none

	External walls							
		External v	vall type 3			External v	vall type 4	
Dwelling no.	Wall type	Area (m²)	Insulation	Low emissions option	Wall type	Area (m²)	Insulation	Low emissions option
All dwellings	-	-	-	-	-	-	-	-

	Internal walls									
	Internal	walls shared with	n garage		Internal wall type	1	Internal wall type 2			
Dwelling no.	Wall type	Area (m²)	Insulation	Wall type	Area (m²)	Insulation	Wall type	Area (m²)	Insulation	
All dwellings	-	-	-	plasterboard, frame: timber - untreated softwood	50	fibreglass batts or roll	-	-	-	

	Ceiling and roof	f							
	Flat	ceiling / pitched	roof	Raked ceil	ling / pitched or s	killion roof	F	lat ceiling / flat ro	of
Dwelling no.	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation
All dwellings	-	-	Ceiling:,Roof:	-	-	Ceiling:,Roof:	-	-	Ceiling:,Roof:

		Glazing type				Frame types		
Dwelling no.	Single glazing (m²)	Double glazing (m²)	Triple glazing (m²)	Aluminium frames (m²)	Timber frames (m²)	uPVC frames (m²)	Steel frames (m²)	Composite frames (m²)
All dwellings	10	0	0	10	0	0	0	0

5. Commitments for single dwelling houses

(a) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	>	>	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		>	>
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		→	>
(e) The applicant must install:			
(aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and		~	V
(bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		✓	~
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	V	~	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		~	
(g) The pool or spa must be located as specified in the table.	V	~	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	~	~	~

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system.	>	>	.
(c) The applicant must install, in each bathroom, kitchen and laundry of the dwelling, the ventilation system specified for that room in the table below. Each such ventilation system must have the operation control specified for it in the table.		V	<

Version: 4.03 / EUCALYPTUS_03_01_0

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(d) The applicant must install the cooling and heating system/s specified for the dwelling under the "Living areas" and "Bedroom areas" headings of the "Cooling" and "Heating" columns in the table below, in/for at least 1 living/bedroom area of the dwelling. If no cooling or heating system is specified in the table for "Living areas" or "Bedroom areas", then no systems may be installed in any such areas. If the term "zoned" is specified beside an air conditioning system, then the system must provide for day/night zoning between living areas and bedrooms.		~	~
(e) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Artificial lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that the "primary type of artificial lighting" for each such room in the dwelling is fluorescent lighting or light emitting diode (LED) lighting. If the term "dedicated" is specified for a particular room or area, then the light fittings in that room or area must only be capable of being used for fluorescent lighting or light emitting diode (LED) lighting.		*	>
(f) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Natural lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that each such room or area is fitted with a window and/or skylight.	~	~	~
(g) This commitment applies if the applicant installs a water heating system for the dwelling's pool or spa. The applicant must:			
(aa) install the system specified for the pool in the "Individual Pool" column of the table below (or alternatively must not install any system for the pool). If specified, the applicant must install a timer, to control the pool's pump; and		~	
(bb) install the system specified for the spa in the "Individual Spa" column of the table below (or alternatively must not install any system for the spa). If specified, the applicant must install a timer to control the spa's pump.		→	
(h) The applicant must install in the dwelling:			
(aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below;		-	
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and		→	~
(cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		→	
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		~	
(j) The applicant must install the photovoltaic system specified for the dwelling under the "Photovoltaic system" heading of the "Alternative energy" column of the table below, and connect the system to that dwelling's electrical system.	~	~	~
(iii) Thermal Performance and Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			

(iii) Thermal Performance and Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	~		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		>	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		>	~
(g) Where there is an in-slab heating or cooling system, the applicant must:	<	~	~
(aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or			
(bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.			
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	~	~	V
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	V		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		~	

6. Commitments for common areas and central systems/facilities for the development (non-building specific)

(b) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		~	>
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	>	•	>
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	~	~	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		~	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		~	<
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		~	~

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	4 star (> 6 but <= 7.5 L/min)	5 star	5 star	4 star

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		>	>
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		>	>
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	>	~	>

Version: 4.03 / EUCALYPTUS_03_01_0

Department of Planning, Housing and Infrastructure

Central energy systems	Туре	Specification
Alternative energy supply	Photovoltaic system	Rated electrical output (min): 150 peak kW
Other	-	-

Notes

- 1. In these commitments, "applicant" means the person carrying out the development.
- 2. The applicant must identify each dwelling, building and common area listed in this certificate, on the plans accompanying any development application, and on the plans and specifications accompanying the application for a construction certificate / complying development certificate, for the proposed development, using the same identifying letter or reference as is given to that dwelling, building or common area in this certificate.
- 3. This note applies if the proposed development involves the erection of a building for both residential and non-residential purposes (or the change of use of a building for both residential and non-residential purposes). Commitments in this certificate which are specified to apply to a "common area" of a building or the development, apply only to that part of the building or development to be used for residential purposes.
- 4. If this certificate lists a central system as a commitment for a dwelling or building, and that system will also service any other dwelling or building within the development, then that system need only be installed once (even if it is separately listed as a commitment for that other dwelling or building).
- 5. If a star or other rating is specified in a commitment, this is a minimum rating.
- 6. All alternative water systems to be installed under these commitments (if any), must be installed in accordance with the requirements of all applicable regulatory authorities. NOTE: NSW Health does not recommend that stormwater, recycled water or private dam water be used to irrigate edible plants which are consumed raw, or that rainwater be used for human consumption in areas with potable water supply.

Legend

BASIX

- 1. Commitments identified with a "V" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).
- 2. Commitments identified with a "V" in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.
- 3. Commitments identified with a "V" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled. (Note: a certifying authority must not issue an occupation certificate (either interim or final) for a building listed in this certificate, or for any part of such a building, unless it is satisfied that each of the commitments whose fulfilment it is required to monitor in relation to the building or part, has been fulfilled).

Version: 4.03 / EUCALYPTUS 03 01 0

Department of Planning, Housing and Infrastructure

Certificate No.: 1793147M