Step 1: About the building

Frame type (dominant)

Suspended floor type (typical)

Fill out blue cells	Fil	l ou	t b	lue	cell	s
---------------------	-----	------	-----	-----	------	---

Reinforced concrete

Reinforced concrete

Step 1: About the building	Fill out I	Diue celis			
Building location and site data	Value		Unit	Note	Comment
Building address	2 Colo Street, Mittagong NSV	V 2575 (Lot 21 DP 1029384)			
Postcode	2575			Required	Postcode of building
Town/city	ALPINE + 20 other localities			Town/city/suburb/region automated from postcode (may not give exact town name)	Town/city/suburb/region of the building site.
Distance to nearest major city/town			km	Enter for rural/regional locations only	Declare the shortest route by road to your site from the centre of your nearest major city (>100,000 people). The route must be traversable by a semitraller truck.
Project stage	Development Application			Required	Stage of development
New build or major renovation?	Major renovation			Required	
Brownfield or greenfield site?	Brownfield			Required	
-	•		•		
Floor area by NCC building classification	, ,	Net (NLA/NSA/UFA)	Unit	Note	
Please enter all floor areas relevant to your building. Leave all building classifications. Please also enter the correspor Area) where it is commonly used for that building classifications.	iding net area (Net Lettable A				
Class 1a: Detached residential buildings			m²	Required for Class 1a: Detached residential houses, townhouses	Gross Floor Area (GFA), as defined by the AIQS Australian Cost Management Manual
Class 1b: Boarding houses and hostels	10,331		m²	Required for Class 1b: Boarding house, guest house, hostel	Net area (Net Lettable Area, Net Sellable Area, Usable Floor Area), as defined by the PCA's Method of Measurement
Class 2: Multi-unit residential buildings			m²	Required for Class 2: Multi-unit residential, including apartment buildings	
Class 3: Other residential buildings			m²	Required for Class 3: Other residential buildings	
Class 4: Residential inside non-residential			m²	Required for Class 4: Residential building inside a non-residential building, e.g., caretaker resi	dence
Class 5: Office buildings			m²	Required for Class 5: Office building	
Class 6: Retail buildings			m²	Required for Class 6: Retail building, e.g., shop, restaurant, café	
Class 7a: Carparks			m²	Required for Class 7a: Carparks	
Class 7b: Warehouse-type buildings			m²	Required for Class 7b: Warehouses, wholesalers and storage facilities	
Class 8: Industrial buildings			m²	Required for Class 8: Industrial buildings, e.g., factories and workshops	
Class 9a: Healthcare buildings			m²	Required for Class 9a: Healthcare, e.g., hospitals, clinics, day surgeries	
Class 9b: Civic buildings			m²	Required for Class 9b: Civic buildings, e.g., theatres, civic centres, train stations	
Class 9c: Aged care and personal care buildings			m²	Required for Class 9c: Aged care and personal care	
Class 10a: Non-habitable buildings			m²	Required for Class 10a: Non-habitable buildings including sheds, carports and private garage	S S
Class 10b: Miscellaneous structures			m²	Required for Class 10b: Miscellaneous structures, including fences, masts, antennas, retainin	
Class 10c: Bushfire shelters			m²	Required for Class 10c: Bushfire shelters not attached to a Class 1a building	
Total	10,331	0	m²	Required: Sum of m² inputs must be more than 0.	
	!				
Project information	Value		Unit	Note	
Total cost of project		47,000,000	AUD excl. GST	Required	Include labour, materials, transport, plant, equipment and professional fees. Exclude GST, land, finance, escalation and other costs.
Building design life		50	years	Required	If uncertain, enter 50 years
Estimated envelope life			years	Optional	
Estimated replacement cycle for mechanical services			years	Optional	
Estimated replacement cycle for vertical transportation			years	Optional	
	•		•		•
Dimensions of the building and the site	Value		Unit	Note	
Site area		66,626	m²	Required	Total area of site to external boundary.
Shared services or infrastructure	No			Required	Indicate if there are shared services that the building utilises, or shared foundations, basement or podium
Building footprint area		2,340	m²	Required	Total floor area of the ground floor measured to the outside edge of the floorplate.
Typical floor area (if different to building footprint area)			m²	Only needed if different to row above	
Typical floor perimeter		308	m	Required	
Area of external carpark (not included in GFA)		1,480	m ²	Required. Enter 0 if not applicable.	
Area of external hardstand (not included in GFA)			m ²	Required. Enter 0 if not applicable.	
Area of other hard landscaping (not included in GFA)		598	m ²	Required. Enter 0 if not applicable.	Include all other impervious areas. For example, patios, paths and driveways (not already included in carparks and hardstands above).
Number of floors/storeys above ground, including ground floor		5	no.	Required	
Number of floors/storeys below ground		0	no.	Required. Enter 0 if not applicable.	
Number of floors/storeys of car parking		1	no.	Required. Enter 0 if not applicable.	
Total height above ground		23	m	Required	Measured from the average finished grade to the highest point of the building, excluding protrusions (lighting rods, masts, chimneys, etc.)
Structural material choices	Value		Unit	Note	
Foundation type	Piles			Required	
	Deleterated assessed				

Required

Only needed for multi-storey buildings

Describe low carbon materials specified in your building (e.g. green concrete, low carbon bricks)	-Lower Carbon Concrete Or Ashcrete Envisia concrete by Bowat: lower carbon concrete with excellent performance benefits and plastic placement and finishing properties similar to conventional concretes. Allowing less cement to be used in the concrete manufacturing process without impacting on performance (50% cement replacement). Ashcrete: substitutes for traditional concrete. Ashcrete mitigate both the high rate of carbon dioxide production during cement production and the disposal of fly ash, a residue of coal-based energy production. It is more environmentally friendly when compared to cement concreteBrick: We would look at locally manufactured Brick (Bowral brick). While the brick has not been specified yet, we are investigating low carbon bricks made from recycled construction and demolition waste from the site.	Required	
Describe recycled content specified in your building (e.g. recycled steel)	-Concrete: The quality of the existing concrete is very low and it is largely lightly or in places unreinforced. Concrete can be crushed and reused in new pawments / Low carbon Bricks etc. on the site and within the buildingCast fron Columns: The columns from M1 are all to be salvaged, retained and will be re-used as part of the landscape on the siteTimber: The major material to be dismantled is timber: It forms floor framing, flooring, columns, roof trusses, roof beams and other elements. Much of the timber is damaged but much of it is capable of future use, even if not structurally. It is proposed to dismantle the timber elements and milled for new purposes and retained on site for re-use. The aim is to re-use as much timber as possible on the site as part of the works. Timber can be used for linings, cladding, joinery and new furnitureSteel elements: Steel falls into several forms: structural steel that is exposed and steel that forms part of the concrete structures. Much of the steel is very deteriorated and will be recycled. Some elements, where they are sound will be assessed for potential re-use on site.	Required	

Step 2: Quantity of materials

Complete all blue cells that are applicable to the building. Leave items that aren't applicable blank.

Fill out blue cells

Material category	Sub-category 1	Sub-category 2	Sub-category 3	Value	Unit of measure Comment	AIQS ACMM Code	ICMS3 (Level 3 Codes Construction
Structure							
The structural parts of the building that a	re below ground (substructure)	and above ground (sup	erstructure).				
This includes fill below the substructure, t excludes external areas such as hardst		suspended floors, wall s	tructure, roof structure, sta	irs, lift shafts and balconie			
Coverage of structural material spend	-	-	-	8	Required. Coverage of <u>spend</u> for structural elements entered below. Minimum requirement = 80%. Exclude head contractor preliminaries and margins.		
Concrete in-situ	≤10 MPa	-			m³ Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
oncrete in-situ	>10 MPa to ≤20 MPa	-			m³ Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete in-situ	>20 MPa to ≤32 MPa	-	-		m³ Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete in-situ	>32 MPa to ≤40 MPa	-			m³ Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
oncrete in-situ	>40 MPa to ≤50 MPa	-	-	4,662.0	m³ Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
oncrete in-situ	>50 MPa to ≤60 MPa	-	-		m³ Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
oncrete in-situ	>60 MPa to ≤80 MPa	-	-		m³ Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
oncrete in-situ	>80 MPa to ≤100 MPa	-			m³ Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
oncrete in-situ	>100 MPa	-	-		m³ Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete pre-cast panel	-	-	-		Please enter reinforcing steel in relevant line items below. If not known at DA stage, please m your best estimate. If not known at CC stage, please ask your supplier.	ake 01_SB or 02-11	02 or 03
Concrete block	Hollow core	-	-	153.0	m ² Enter as <u>cubic metres</u> , calculated as (area in m ²) * (thickness in mm / 1000). Please include all block fill concrete and all reinforcing steel in relevant line items above/below	01_SB	02 or 03
oncrete block/brick	Solid		-		m³ Enter as <u>cubic metres</u> , calculated as (area in m²) * (thickness in mm / 1000)	01_SB	02 or 03
Concrete block/brick	Solid AAC	-	-		m³ Solid Aerated Autoclaved Concrete (AAC) block. Enter as cubic metres, calculated as (area in m²) * (thickness in mm / 1000).	01_SB	02 or 03
Nortar					<u> </u>	01 SB	02 or 03
teinforcing steel	Bar & mesh			528,120	Include all reinforcing steel bar/mesh in the building's structure in this row. Usually the calculated as kg/m³ per concrete element and then summed. Example: 10 m³ of 40 MPa con		02 or 03
einforcing steel	Fibre & strand				@ 100 kg/m³ + 5 m³ of 50 MPa concrete @ 150 kg/m³ = 1,750 kg reinforcing steel.	v. 01 SB or 02-11	02 or 03
•	Hot rolled structural	•	•		Include all steel fibre reinforcing and steel strand in the building's structure in this ro	01_SB 01 02-11	02 or 03
tructural steel tructural steel	Cold formed structural	•	•		Examples include universal beams, universal columns and welded beams Examples include C purlins, Z purlins and all light gauge steel framing	01_SB 01_SB	02 or 03
tructural steel	Other welded structural	•	•		Examples include C punins, 2 punins and air light gauge steer training	01_SB 01_SB	02 or 03
tructural steel	Plate	•	•		Include any allowance for connections here	01_SB 01_SB	02 or 03
tructural steel	Sheet	•	•		include any allowance for connections here	01_SB 01_SB	02 or 03
tainless steel	Sileet	•	•		Delmosily for an aircorred timbor structure connections	02_11	02 or 03
einforced concrete piles	Concrete	-	-	1,904	Primarily for engineered timber structure connections Please enter reinforcing steel in the line below. If not known at DA stage, please make your b estimate. If not known at CC stage, please ask your supplier.	_	02 or 03
teinforced concrete piles	Steel reinforcing			418,880	If not known at DA stage, please ask your supplied. If not known at DA stage, please make your best estimate. If not known at CC stage, please is your supplier.	sk 01_SB	02 or 03
iteel piles					Where concrete and reinforcing steel are also used, enter these in the rows above.	01 SB	02 or 03
mber poles/piles					m ³ Where concrete and reinforcing steel are also used, enter these in the rows above.	01_SB	02 or 03
imber polesiplies	Sawn softwood			140.0	m ³	02_11	02 or 03
imber (solid)	Sawn hardwood			110.	 m ³	02_11	02 or 03
mber (engineered)	CLT				m³	02_11	02 or 03
imber (engineered)	Glulam				m³	02_11	02 or 03
imber (engineered)	LVL				m³	02_11	02 or 03
imber (engineered)	OSB				n³ Enter as <u>cubic metres</u> , calculated as (area of wall in m²) * (thickness in mm / 1000)	02_11	02 or 03
rick	Heat cured				m ³ Enter as cubic metres, calculated as (area of wall in m ²) * (thickness in mm / 1000)	02_11	02 or 03
ructural Insulated Panel (SIP)	Steel outer				m ²	01_SB	02 or 03
ructural Insulated Panel (SIP)	Aluminium outer				 n²	01_SB	02 or 03
ructural Insulated Panel (SIP)	Engineered timber outer				 m²	01_SB	02 or 03
I	.g				Include purchased material only. Exclude site-won material.	01_SB	01
and & gravel		-	-	320	Include purchased material only. Exclude site-won material and sand/gravel in concrete.	01_SB	01
aterproofing membrane	Bituminous			1,117	m ²	01_SB	01 or 02 or 03
aterproofing membrane	Polyethylene			2,066	 n²	01_SB	01 or 02 or 03
ther structural (Describe and add unit >>)	. 2., 501,10110			2,000	Please enter a description for any structural material that does not fit a predefined classification	_	0 , 0 , 0 2 0 , 0 0
ther structural (Describe and add unit >>)					Please enter a description for any structural material that does not fit a predefined classification. Please enter a description for any structural material that does not fit a predefined classification.		
(Doconido una ada unitera)					Please enter a description for any structural material that does not fit a predefined classification. Please enter a description for any structural material that does not fit a predefined classification.		

Envelope
The skin of the building that separates the internal building from the external environment.
This includes the roof cladding, wall cladding, windows, doors and internal/external shading. It also includes insulation and the internal wall lining of envelope walls.

Coverage of envelope material spend	-	-	-	89	%	Required. Coverage of <u>spend</u> for the envelope items you have entered below. Minimum requirement = 80%. Exclude head contractor preliminaries and margins.		
						Enter as m² of roof area. Exclude allowances for overlap in the roofing sheets. This row includes	J	
Roof cladding	Profiled steel	-	-		m²	all metal-coated and pre-painted steel sheets where steel is the base metal. Examples include: galvanised steel, zinc-alluminium (zincallume) coated steel and zinc-alluminium-magnesium (ZAM) coated steel, whether painted or unpainted.	05_RF	03 or 04
Roof cladding	Profiled aluminium		-		m²	Enter as m² of roof area. Exclude allowances for overlap in the roofing sheets. This row also includes pre-painted aluminium sheets.	05_RF	03 or 04
Roof cladding	Profiled zinc		-		m²	Enter as m ² of roof area. Exclude allowances for overlap in the roofing sheets. This row also includes pre-painted zinc sheets.	05_RF	03 or 04
Roof cladding	Membrane			1,952	m²	Enter as m² of roof area. Exclude allowances for overlap in the membrane sheets.	05_RF	03 or 04
Roof cladding	Tiles (traditional clay)				m²	Enter as m² of roof area. Exclude allowances for overlap between the tiles.	05_RF	03 or 04
Roof cladding	Tiles (concrete)				m²	Enter as m² of roof area. Exclude allowances for overlap between the tiles.	05_RF	03 or 04
Roof cladding	Other (Please describe >>)				m²	Please enter a description for any roofing that does not fit a predefined classification	05_RF	03 or 04
Wall cladding	Bricks (heat cured)	-	-	1,823	m²	Enter as m² of wall area. Heat-cured bricks use a kiln or furnace to raise the brick temperature above ambient temperature during curing process.	06_EW	03 or 04
Wall cladding	Bricks (air dried)				m²	Enter as m² of wall area. Air-dried bricks are cured using ambient temperature.	06_EW	03 or 04
Wall cladding	Bricks (under fired)				m²	Enter as m² of wall area.	06_EW	03 or 04
Wall cladding	Bricks (concrete)				m²	Enter as m² of wall area	06_EW	03 or 04
Wall cladding	Mortar and render				kg		06_EW	03 or 04
Wall cladding	Profiled steel	-	-		m²	Enter as m³ of wall area. Exclude allowances for overlap in the cladding sheets, offcuts, etc. This row includes all metal-coated and pre-painted steel sheets where steel is the base metal. Examples nickude: galwansed steel, zinc-aluminium (zincalume) coated steel and zinc-aluminium-	06_EW	03 or 04
Wall cladding	Profiled aluminium				m²	magnesium (ZAM) coated steel, whether painted or unpainted. Enter as m² of wall area. Exclude allowances for overlap in the cladding sheets, offcuts, etc. This	06 EW	03 or 04
-		-	-			row also includes pre-painted aluminium sheets. Enter as m² of wall area. Exclude allowances for overlap in the cladding sheets, offcuts, etc. This	_	
Wall cladding	Profiled zinc	-	-		m²	row also includes pre-painted zinc sheets.	06_EW	03 or 04
Wall cladding	GRC cladding	-	-		m²	Enter as m² of wall area. GRC = Glass Reinforced Concrete.	06_EW	03 or 04
Wall cladding	Timber weatherboards	-	-		m²	Enter as m² of wall area. Exclude allowances for overlap between weatherboards, offcuts, etc.	06_EW	03 or 04
Wall cladding	Fibre cement board	-	-		m²	Enter as m² of wall area. Exclude allowances for offcuts, etc.	06_EW	03 or 04
Wall cladding	Terracotta	-	-		m²	Enter as m² of wall area. Exclude allowances for offcuts, etc.	06_EW	03 or 04
Wall cladding	Brick tiles / veneers	-	-		m²	Enter as m² of wall area. Exclude allowances for offcuts, etc.	06_EW	03 or 04
Wall cladding	Plasterboard	-	-		m²	Enter as m² of wall area. Exclude allowances for offcuts, etc. Include both external wall linings and internal wall linings for envelope walls.	12_WF or 06_EW	03 or 04
Wall cladding	Plywood	-	-		m²	Enter as m² of wall area. Exclude allowances for offcuts, etc. Include both external wall linings and internal wall linings for envelope walls.	12_WF or 06_EW	03 or 04
Wall cladding	Other (Please describe >>)				m²	Please enter a description for any wall cladding that does not fit a predefined classification	06_EW or 12_WF	03 or 04
Windows & doors	Aluminium frame	Single glazed	-		m²	Include all single glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Aluminium frame	Double glazed	-	1,654	m²	Include all double glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Aluminium frame	Triple glazed	-		m²	Include all triple glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Timber frame	Single glazed	-		m²	Include all single glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Timber frame	Double glazed			m²	Include all double glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Timber frame	Triple glazed	-		m²	Include all triple glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	uPVC frame	Single glazed			m²	Include all single glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	uPVC frame	Double glazed			m²	Include all double glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	uPVC frame	Triple glazed	-		m²	Include all triple glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Frameless	Single glazed			m²	Include all single glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Frameless	Double glazed			m²	Include all double glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Frameless	Triple glazed			m²	Include all triple glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Other (Please describe >>)				m²	Please enter a description for any windows or doors that do not fit a predefined classification	07_WW or 08_ED	03 or 04
Curtain wall	Single skin façade	Glazed panel	Single glazed		m²	Please declare all single-skin façade area in this section. All double-skin façade area should be entered in the next section. Include all single glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Curtain wall	Single skin façade	Glazed panel	Double glazed		m²	Include all double glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Curtain wall	Single skin façade	Glazed panel	Triple glazed		m²	Include all triple glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Curtain wall	Single skin façade	Opaque panel	Aluminium cladding		m²		06_EW	03 or 04
Curtain wall	Single skin façade	Opaque panel	GRC cladding		m²	GRC = Glass-fibre Reinforced Concrete	06_EW	03 or 04
Curtain wall	Single skin façade	Opaque panel	Insulated shadow box		m²		06_EW	03 or 04
Curtain wall	Single skin façade	Opaque panel	Brick cladding		m²		06_EW	03 or 04
Curtain wall	Single skin façade	Opaque panel	Stone cladding		m²		06_EW	03 or 04
Curtain wall	Double skin façade	Glazed panel	Single glazed		m²	Please declare all double-skin façade area in this section. Please declare as the area of the curtain wall and do not enter the inner and outer skins twice. Include all single glazing, including standard, toughened, laminated and low-E.	06_EW	03 or 04
Curtain wall	Double skin façade	Glazed panel	Double glazed		m²	The type of glazing refers to the building's envelope wall, not including the outer skin	06_EW	03 or 04
Curtain wall	Double skin façade	Glazed panel	Triple glazed		m²	The type of glazing refers to the building's envelope wall, not including the outer skin	06_EW	03 or 04
Curtain wall	Double skin façade	Opaque panel	Aluminium cladding		m²		06_EW	03 or 04
Curtain wall	Double skin façade	Opaque panel	GRC cladding		m²	GRC = Glass-fibre Reinforced Concrete	06_EW	03 or 04

Curtain wall	Double skin façade	Opaque panel	Insulated shadow box		l2		06 EW	03 or 04
Curtain wall	Double skin façade Double skin facade	Opaque panel	Brick cladding		m²		06 EW	03 or 04
Curtain wall	Double skin façade	Opaque panel	Stone cladding		m²		06_EW	03 or 04
Curtain wall	Other (Please describe >>)	Opaque parier	Storie clauding		m²	Please enter a description for any curtain wall that does not fit a predefined classification	06_EW	03 or 04
Stick-framed wall system	Aluminium frame	Glazed section	Single glazed		m²	Include all single glazing, including standard, toughened, laminated and low-E	06 EW	03 or 04
Stick-framed wall system	Aluminium frame	Glazed section	Double glazed		m²	Include all double glazing, including standard, toughened, laminated and low-E Include all double glazing, including standard, toughened, laminated and low-E	06 EW	03 or 04
Stick-framed wall system	Aluminium frame	Glazed section	Triple glazed		m²	Include all double glazing, including standard, toughered, laminated and low-E	06_EW	03 or 04
Stick-framed wall system	Aluminium frame	Opaque section	Aluminium cladding		m²	include all triple glazing, including standard, tougheried, lanilitated and low-E	06_EW	03 or 04
Stick-framed wall system	Aluminium frame	Opaque section	GRC cladding		m²	GRC = Glass-fibre Reinforced Concrete	06 EW	03 or 04
Stick-framed wall system	Aluminium frame	Opaque section	Insulated shadow box		m²	ONO - Glass-fibre Newflorded Controlle	06 EW	03 or 04
Stick-framed wall system	Aluminium frame	Opaque section	Brick cladding		m²		06 EW	03 or 04
Stick-framed wall system	Aluminium frame	Opaque section	Stone cladding		m²		06_EW	03 or 04
Stick-framed wall system	Steel frame	Glazed section	Single glazed		m²	Include all single glazing, including standard, toughened, laminated and low-E	06 EW	03 or 04
Stick-framed wall system	Steel frame	Glazed section	Double glazed		m²	Include all double glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Stick-framed wall system	Steel frame	Glazed section	Triple glazed		m²	Include all triple glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Stick-framed wall system	Steel frame	Opaque section	Aluminium cladding		m²	monado di upo giazing, monading otanadia, toagnoroa, ianimatoa ana low z	06 EW	03 or 04
Stick-framed wall system	Steel frame	Opaque section	GRC cladding		m²	GRC = Glass-fibre Reinforced Concrete	06 EW	03 or 04
Stick-framed wall system	Steel frame	Opaque section	Insulated shadow box		m²	Site State in Cite in	06 EW	03 or 04
Stick-framed wall system	Steel frame	Opaque section	Brick cladding		m²		06_EW	03 or 04
Stick-framed wall system	Steel frame	Opaque section	Stone cladding		m²		06 EW	03 or 04
Stick-framed wall system	Other (Please describe >>)				m²	Please enter a description for any wall system that does not fit a predefined classification	06 EW	03 or 04
Wall louvre system	Aluminium	-			m²	I base onto a accomption of any war obtain that accomption and production	06 EW	03 or 04
External shading system	Aluminium frame	Aluminium cladding		1,158		Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
,		ŭ				Please enter as m² of shaded area = linear metres * (width in mm / 1000).	_	
External shading system	Aluminium frame	GRC cladding	-		m²	GRC = Glass-fibre Reinforced Concrete.	06_EW	03 or 04
External shading system	Aluminium frame	Terracotta cladding	-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Aluminium frame	Stone cladding	-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Aluminium frame	Pre-cast concrete	-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Aluminium frame	Timber	-		m²	Please enter as m ² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Aluminium frame	Glass (opague)	-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Aluminium frame	Steel			m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Other (Please describe >>)		-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
Roller doors	Steel profile				m²	Please note unit is square metres, not quantity	08_ED	03 or 04
Roller doors	Hardwood over steel				m²	Please note unit is square metres, not quantity	08_ED	03 or 04
Roller doors	Softwood over steel				m²	Please note unit is square metres, not quantity	08_ED	03 or 04
Revolving doors	Glass/aluminium/steel				no.		08_ED	03 or 04
Fire-rated doors	Engineered timber			14	no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	08_ED	03 or 04
Fire-rated doors	Steel				no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	08_ED	03 or 04
Fire-rated doors	Aluminium/glass	-	•		no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	08_ED	03 or 04
Insulation	Glass wool / fibreglass			4,526.0	m²	Please include both wall and ceiling insulation	05_RF or 06_EW	03 or 04
Insulation	Stone wool	-	•		m²	Please include both wall and ceiling insulation	05_RF or 06_EW	03 or 04
Insulation	Polyester				m²	Please include both wall and ceiling insulation	05_RF or 06_EW	03 or 04
Insulation	Expanded polystyrene	-			m²	Please include both wall and ceiling insulation	05_RF or 06_EW	03 or 04
Insulation	Other (Please describe >>)		-		m²	Please include both wall and ceiling insulation	05_RF or 06_EW	03 or 04
Other (Please describe and add unit >>)		-	•			Please enter a description for any envelope material that does not fit a predefined classification		
Other (Please describe and add unit >>)		-	•			Please enter a description for any envelope material that does not fit a predefined classification		
Other (Please describe and add unit >>)		-	-			Please enter a description for any envelope material that does not fit a predefined classification		

Permanent internal walls and doors

Walls and doors within the building that are either structural or designed to be permanent.

Coverage of material spend on perma	nent internal walls and doors			81 %	Enter the % coverage of <u>spend</u> for the items you have entered below. There is no minimum requirement: enter what you know. This should include all structural walls. Exclude head contractor preliminaries and margins.		
Interior wall (permanent)	Steel (light framing)		-	t		09_NW	03 or 04
Interior wall (permanent)	Timber framing	-	-	m³		09_NW	03 or 04
Interior wall (permanent)	AAC panel (reinforced)		-	m²	Panels of autoclaved aerated concrete (AAC) with reinforcing steel. E.g., Hebel.	09_NW or 12_WF	03 or 04
Interior wall (permanent)	Concrete-filled steel panel	-	-	m²	Panels made from a steel sheet outer with an aerated concrete core. E.g., Speedpanel.	09_NW or 12_WF	03 or 04
Interior wall (permanent)	Plasterboard		-	11,842 m²	Enter as single-layer equivalent. If using 2 layers, multiply the area by 2.	09_NW or 12_WF	03 or 04
Interior wall (permanent)	Plywood	-	-	m²	Enter as single-layer equivalent. If using 2 layers, multiply the area by 2.	09_NW or 12_WF	03 or 04
Interior wall (permanent)	Fibre cement sheet	-	-	m²	Enter as single-layer equivalent. If using 2 layers, multiply the area by 2.	09_NW or 12_WF	03 or 04
Interior wall (permanent)	Insulation		-	8,500.0 m ²		09_NW or 12_WF	03 or 04
Interior wall (permanent)	Glass	-	-	m²		09_NW or 12_WF	03 or 04
Interior wall (permanent)	Other (Please describe >>)		-	m²	Please enter a description for any internal wall that does not fit a predefined classification	09_NW or 12_WF	03 or 04
Internal door (permanent)	Aluminium/glass	-	-	no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	11_ND	03 or 04

ternal door (permanent)	Timber/glass	-	-	no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	11_ND	03 or 04
ernal door (permanent)	Timber solid lightweight	•	•	143 no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	11_ND	03 or 04
ernal door (permanent)	Fire resistant		-	no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	11_ND	03 or 04
ernal door (permanent)	Steel	-	-	no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	11_ND	03 or 04
rnal door (permanent)	Other (Please describe >>)		-	no.	Please enter a description for any internal door that does not fit a predefined classification	11_ND	03 or 04
her (Please describe and add unit >>)		-	-		Please enter a description for any material that does not fit a predefined classification		
her (Please describe and add unit >>)		-	-		Please enter a description for any material that does not fit a predefined classification		
ner (Please describe and add unit >>)			-		Please enter a description for any material that does not fit a predefined classification		
ervices uilding services included within the ma	sin building contract. If the building co	omponents that are the subje	act of the developmen	Unit of measure	e		
	nly enter these items. If you cannot sp			Other services" category at the bottom.			
chanical services	-		-	1,061,493 AUD excl. GST	Where possible, enter material costs excluding labour, plant, equipment, margins and taxes	28_SS	05
rtical transportation	-		-	603,750 AUD excl. GST	Where possible, enter material costs excluding labour, plant, equipment, margins and taxes	28_SS	05
					Electrical services including the main power supply, backup generators, security and		
ctrical services	-	-	-	948,353 AUD excl. GST	communications. Excluding solar installations. Where possible, enter material costs excluding labour, plant, equipment, margins and taxes.	26_LP	05
ar photovoltaic installations	-		-	AUD excl. GST	Where possible, enter material costs excluding labour, plant, equipment, margins and taxes	26_LP_LPGP	05
mbing/hydraulic services	-			1,807,415 AUD excl. GST	Where possible, enter material costs excluding labour, plant, equipment, margins and taxes	18_PD and 19_WS	05 or 06
services				790,373 AUD excl. GST	Where possible, enter material costs excluding labour, plant, equipment, margins and taxes	25_FPSS04 or 39 XWAW_03 or 41_XF	05
					Please group all other services here, meaning that coverage will always be 100% for services.		
her services (Please describe)		-		AUD excl. GST	Please group all other services here, meaning that coverage will always be 100% for services. Enter only the material costs (excluding labour, plant, equipment, margins and taxes).	29_SS or multiple	
xternal works							
materials associated with hard land	scaping and outbuildings on the site b						
	eways, covered walkways, decks, pat	tios, awnings, fences, gates,	etc. Soft landscaping		Described Coverage of around for external years (
				83 %	Required. Coverage of spend for external works (excluding soft landscaping) entered below.		
erage of spend on external works	-	-		03 76	Minimum requirement = 80%. Exclude head contractor preliminaries and margins.		
•		-		65 76 t	Minimum requirement = 80%. Exclude head contractor preliminaries and margins.	33 XR	07
nalt	- - ≤10 MPa	-		t m ³		**=***	
halt crete in-situ	- - ≤10 MPa >10 MPa to <20 MPa	•	-	t m ³	Please enter reinforcing steel as part of "Reinforcing steel" below	33_XR or 34_XN or 35_XB or 36_XL	07
halt crete in-situ crete in-situ	>10 MPa to ≤20 MPa	- - -	- - -	t m ³	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below	33_XR or 34_XN or 35_XB or 36_XL 33_XR or 34_XN or 35_XB or 36_XL	07 07
halt ncrete in-situ ncrete in-situ ncrete in-situ	>10 MPa to ≤20 MPa >20 MPa to ≤32 MPa	- - - -	- - - -	t m³ m³ m³	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below	33_XR or 34_XN or 35_XB or 36_XL 33_XR or 34_XN or 35_XB or 36_XL 33_XR or 34_XN or 35_XB or 36_XL	07 07 07
ohalt norete in-situ norete in-situ norete in-situ norete in-situ	>10 MPa to ≤20 MPa >20 MPa to ≤32 MPa >32 MPa to ≤40 MPa		- - - -	t m³ m³ m³ 477.0 m³	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below	33_XR or 34_XN or 35_XB or 36_XL 33_XR or 34_XN or 35_XB or 36_XL 33_XR or 34_XN or 35_XB or 36_XL 33_XR or 34_XN or 35_XB or 36_XL	07 07 07 07
ohalt norete in-situ norete in-situ norete in-situ norete in-situ norete in-situ	>10 MPa to ≤20 MPa >20 MPa to ≤32 MPa >32 MPa to ≤40 MPa >40 MPa to ≤50 MPa	- - - - - -	- - - - -	t m³ m³ m³	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below	33_XR or 34_XN or 35_XB or 36_XL 33_XR or 34_XN or 35_XB or 36_XL	07 07 07 07
ohalt norete in-situ	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >40 MPa to <50 MPa >50 MPa		- - - - - -	t m³ m³ m³	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below	33 ./R or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL	07 07 07 07 07 07
chalt corete in-situ	>10 MPa to \$20 MPa >20 MPa to \$32 MPa >32 MPa to \$40 MPa >40 MPa to \$50 MPa >50 MPa Concrete		-	t m³ m³ m³	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below	33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR	07 07 07 07 07 07
shalt ncrete in-situ	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >40 MPa to <50 MPa >50 MPa		-	t m³ m³ m³	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below	33 ./R or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL	07 07 07 07 07 07
ohalt norete in-situ vers, bricks and blocks vers, bricks and blocks	>10 MPa to \$20 MPa >20 MPa to \$32 MPa >32 MPa to \$40 MPa >40 MPa to \$50 MPa >50 MPa Concrete		-	t m³ m³ m³	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre	33 JRR or 34 JNN or 35 JNB or 36 JNL 33 JRR or 34 JNN or 35 JNB or 36 JNL 33 JRR or 34 JNN or 35 JNB or 36 JNL 33 JRR or 34 JNN or 35 JNB or 36 JNL 33 JRR or 34 JNN or 35 JNB or 36 JNL 33 JRR or 34 JNN or 35 JNB or 36 JNL 33 JNR or 34 JNN or 35 JNB or 36 JNL 33 JNR or 34 JNN or 35 JNB or 36 JNL 33 JNR 33 JNR	07 07 07 07 07 07
chalt ncrete in-situ	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >40 MPa to <50 MPa >50 MPa Concrete Clay		-	t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please	33 //R or 34 //N or 35 //B or 36 //L 33 //R or 34 //N or 35 //B or 36 //L 33 //R or 34 //N or 35 //B or 36 //L 33 //R or 34 //N or 35 //B or 36 //L 33 //R or 34 //N or 35 //B or 36 //L 33 //R or 34 //N or 35 //B or 36 //L 33 //R or 34 //N or 35 //B or 36 //L 33 //R 33 //R 33 //R 33 //R or 34 //N or 35 //B or 36 //L	07 07 07 07 07 07 07
chalt corete in-situ	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >40 MPa to <50 MPa >50 MPa Concrete Clay		-	t m³ m³ m³ 477.0 m³ m³ m³ m² m² m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre	33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR 33 JRR 33 JRR 33 JRR 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR 33 JRR or 34 JRN or 35 JRB or 36 JRL	07 07 07 07 07 07 07 07
halt corete in-situ c	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >40 MPa to <50 MPa >50 MPa Concrete Clay			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concrete @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1.750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row.	33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR 33 JRR 33 JRR 33 JRR 33 JRR 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 33 JRR or 34 JRN or 35 JRB or 36 JRL 32 JRR or 34 JRN or 35 JRB or 36 JRL	07 07 07 07 07 07 07 07 07
halt corete in-situ c	>10 MPa to s20 MPa >20 MPa to s32 MPa >32 MPa to s40 MPa >40 MPa to s40 MPa >40 MPa to s50 MPa Concrete Clay Bar & mesh Fibre & strand			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m³ of 40 MPa concre @ 100 kg/m² + 5 m³ of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc.	33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR 33 XR 33 XR 33 XR 23 XR 23 XR or 34 XN or 35 XB or 36 XL 30 XR 20 XR or 34 XN or 35 XB or 36 XL 21 XR 22 XR or 34 XN or 35 XB or 36 XL 23 XR or 34 XN or 35 XB or 36 XL 22 XB	07 07 07 07 07 07 07 07 07
halt corete in-situ c	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <340 MPa >340 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand Polycarbonate			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concrete @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1.750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row.	33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 35 XB 35 XB	07 07 07 07 07 07 07 07 07 07
halt norete in-situ n	>10 MPa to s20 MPa >20 MPa to s32 MPa >32 MPa to s40 MPa >40 MPa to s40 MPa >40 MPa to s50 MPa Concrete Clay Bar & mesh Fibre & strand			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m³ of 40 MPa concre @ 100 kg/m² + 5 m³ of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc.	33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR 33 XR 33 XR 33 XR 23 XR 23 XR or 34 XN or 35 XB or 36 XL 30 XR 20 XR or 34 XN or 35 XB or 36 XL 21 XR 22 XR or 34 XN or 35 XB or 36 XL 23 XR or 34 XN or 35 XB or 36 XL 22 XB	07 07 07 07 07 07 07 07 07 07
halt corete in-situ c	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <340 MPa >340 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand Polycarbonate			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled polycarbonate sheet that would ordered, including allowance for overlap	33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 35 XB 35 XB	07 07 07 07 07 07 07 07 07 07
halt crete in-situ ers, bricks and blocks ers, bricks and blocks florcing steel cfurcing steel ctural steel ctural steel ctural steel ctural ofof/wall cladding ernal roof/wall cladding ernal roof/wall cladding	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >340 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand - Polycarbonate PVC			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m" per concrete element and then summed. Example: 10 m" of 40 MPa concrete @ 100 kg/m" 1.750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled PVC sheet that would ordered, including allowance for overlap	33 JRR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR 33 _XR 33 _XR 33 _XR 33 _XR 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 35 _XB or 34 _XN or 35 _XB or 36 _XL 35 _XB or 34 _XN or 35 _XB or 36 _XL 35 _XB or 34 _XN or 35 _XB or 36 _XL 35 _XB or 34 _XN or 35 _XB or 36 _XL 35 _XB or 35 _XB or 35 _XB or 35 _XB 35 _XB	07 07 07 07 07 07 07 07 07 07
halt corete in-situ c	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >32 MPa to <40 MPa >40 MPa to <50 MPa Concrete Clay Bar & mesh Fibre & strand Polycarbonate PVC Bitumen sheet			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concrete (0.100 kg/m² + 5 m² of 50 MPa concrete (0.150 kg/m² = 1.750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled PVC sheet that would ordered, including allowance for overlap Enter as profiled PVC sheet that would ordered, including allowance for overlap Enter as bituminous sheet that would ordered, including allowance for overlap	33 JRR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR or 34 _XN or 35 _XB or 36 _XL 33 _XR 33 _XR 33 _XR 34 _XR or 34 _XN or 35 _XB or 36 _XL 35 _XR or 34 _XN or 35 _XB or 36 _XL 35 _XR or 34 _XN or 35 _XB or 36 _XL 35 _XB 35 _XB 35 _XB 35 _XB 35 _XB	07 07 07 07 07 07 07 07 07 07 07 07
halt crete in-situ sers, bricks and blocks ars, bricks and blocks forcing steel cforcing steel ctural steel ctural aluminium mal roof/wall cladding	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >32 MPa to <40 MPa >40 MPa to <50 MPa Concrete Clay Bar & mesh Fibre & strand Polycarbonate PVC Bitumen sheet			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled PVC sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap	33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR 33 , XR star 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 35 , XR or 34 , XN or 35 , XB or 36 , XL 35 , XB	07 07 07 07 07 07 07 07 07 07 07 07
halt crete in-situ crete in-si	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >32 MPa to <40 MPa >40 MPa to <50 MPa Concrete Clay Bar & mesh Fibre & strand Polycarbonate PVC Bitumen sheet			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled Polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap	33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR or 34 XN or 35 XB or 36 XL 33 XR 33 XR 33 XR 32 XR 33 XR 33 XR 35 XB	07 07 07 07 07 07 07 07 07 07 07 07 07
halt crete in-situ crete in-si	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >32 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand - Polycarbonate PVC Bitumen sheet Steel profile -			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled Polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap	33	07 07 07 07 07 07 07 07 07 07 07 07 07 0
halt crete in-situ crete in-si	>10 MPa to <20 MPa >20 MPa to <32 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >40 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled Polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap	33 JR or 34 JN or 35 JR or 36 JL 33 JR or 34 JN or 35 JR or 36 JL 33 JR or 34 JN or 35 JR or 36 JL 33 JR or 34 JN or 35 JR or 36 JL 33 JR or 34 JN or 35 JR or 36 JL 33 JR or 34 JN or 35 JR or 36 JL 33 JR or 34 JN or 35 JR or 36 JL 33 JR or 34 JN or 35 JR or 36 JL 33 JR or 34 JN or 35 JR or 36 JL 33 JR or 34 JN or 35 JR or 36 JL 33 JR or 34 JN or 35 JR or 36 JL 34 JR or 34 JN or 35 JR or 36 JL 35 JR 35 JR 35 JR 35 JR 35 JR 35 JR 36 JR or 34 JN or 35 JR or 36 JL 31 JR or 34 JN or 35 JR or 36 JL 31 JR or 34 JN or 35 JR or 36 JL 31 JR or 34 JN or 35 JR or 36 JL 31 JR or 34 JN or 35 JR or 36 JL 31 JR or 34 JN or 35 JR or 36 JL 31 JR or 34 JN or 35 JR or 36 JL 31 JR or 34 JN or 35 JR or 36 JL	07 07 07 07 07 07 07 07 07 07 07 07 07 0
halt crete in-situ sers, bricks and blocks sers, bricks and bricks sers, bricks and br	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >32 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled Polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap	33 // R or 34 // X N or 35 // X B or 36 // X L 33 // X R or 34 // X N or 35 // X B or 36 // X L 33 // X R or 34 // X N or 35 // X B or 36 // X L 33 // X R or 34 // X N or 35 // X B or 36 // X L 33 // X R or 34 // X N or 35 // X B or 36 // X L 33 // X R or 34 // X N or 35 // X B or 36 // X L 33 // X R or 34 // X N or 35 // X B or 36 // X L 33 // X R or 34 // X N or 35 // X B or 36 // X L 33 // X R or 34 // X N or 35 // X B or 36 // X L 35 // X B 35 // X	07 07 07 07 07 07 07 07 07 07 07 07 07 0
halt norete in-situ n	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >340 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled Polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap	33	07 07 07 07 07 07 07 07 07 07 07 07 07 0
halt corete in-situ corete coret, bricks and blocks ers, bricks and blocks ersal coretivation co	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >340 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand - Polycarbonate PVC Bitumen sheet Steel profile - Sawn softwood Sawn hardwood CLT Glulam LVL			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled Polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap	33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR 35 , XB 36 , XB 37 , XR 38 , XB 39 , XB 39 , XB 30 , XB 31 , XB 32 , XB 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL	07 07 07 07 07 07 07 07 07 07 07 07 07 0
halt halt horete in-situ horete in-s	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >340 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled Polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap	33	07 07 07 07 07 07 07 07 07 07 07 07 07 0
halt crete in-situ ers, bricks and blocks ers, bricks and blocks efforcing steel ctoral steel ctural steel ctural steel ctural steel ctural duminium umal roof/wall cladding emal roof	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >340 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand - Polycarbonate PVC Bitumen sheet Steel profile - Sawn softwood Sawn hardwood CLT Glulam LVL			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled PVC sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as bituminous sheet that would ordered, including allowance for overlap Enter as bituminous sheet that would ordered, including allowance for overlap Enter as bituminous sheet that w	33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR 35 , XB 36 , XB 37 , XR 38 , XB 39 , XB 39 , XB 30 , XB 31 , XB 32 , XB 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL 33 , XR or 34 , XN or 35 , XB or 36 , XL	07 07 07 07 07 07 07 07 07 07 07 07 07 0
halt norete in-situ n	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >340 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand - Polycarbonate PVC Bitumen sheet Steel profile - Sawn softwood Sawn hardwood CLT Glulam LVL			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concrete @ 150 kg/m² = 1.750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Include structures, louvre systems, etc. Enter as profiled polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled PVC sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Include purchased material only. Exclude site-won material Include purchased material only. Exclude site-won material and sand/gravel in concrete.	33	07 07 07 07 07 07 07 07 07 07 07 07 07 0
verage of spend on external works phalt ncrete in-situ vers, bricks and blocks vers, bricks and blocks inforcing steel uctural stee	>10 MPa to <20 MPa >20 MPa to <32 MPa >32 MPa to <40 MPa >340 MPa to <50 MPa >50 MPa Concrete Clay Bar & mesh Fibre & strand - Polycarbonate PVC Bitumen sheet Steel profile - Sawn softwood Sawn hardwood CLT Glulam LVL			t m²	Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Please enter reinforcing steel as part of "Reinforcing steel" below Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m² per concrete element and then summed. Example: 10 m² of 40 MPa concre @ 100 kg/m² + 5 m² of 50 MPa concrete @ 150 kg/m² = 1,750 kg reinforcing steel. Include all steel fibre reinforcing and steel strand in the external works in this row. Includes structures, louvre systems, etc. Enter as profiled polycarbonate sheet that would ordered, including allowance for overlap Enter as profiled PVC sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as profiled steel sheet that would ordered, including allowance for overlap Enter as bituminous sheet that would ordered, including allowance for overlap Enter as bituminous sheet that would ordered, including allowance for overlap Enter as bituminous sheet that w	33	07 07 07 07 07 07 07 07 07 07 07 07 07 0

ı			

Step 3: Certifier details

Fill out blue cells

The material quantities must be determined through an itemised list of building materials (such as a bill of quantities) and certified by a quantity surveyor, designer, engineer or NABERS Assessor.

Person that completed this form	Value	Note
Name	Kelvin Perrie	Required
Company	MBMpl	Required
ABN	74 099 962 231	
Profession	Quantity Surveyor	Required
Qualification or registration	Встр	Required

Person that certified the details in this form	Value	Note
Name	Stephanie Tecli	Required
Company	MBMpl	Required
ABN	74 099 962 231	
Profession	Quantity Surveyor	Required
Qualification or registration	Встр	Required

Confirmation of certification	Value	Note
Are 80% of material costs captured for the building's structure, envelope and external works?	Yes	Required
If no - why not?		

Additional comments from data provider

Quantities in this report are indicative only pending detailed design.

Additional comments of certifier

Attach this Excel spreadsheet to your development application or construction certificate application.