



Douglas Partners

Geotechnics • Environment • Groundwater

Integrated Practical Solutions

REPORT

on

**PRELIMINARY GEOTECHNICAL AND
CONTAMINATION ASSESSMENT**

**KAMIRA COURT, VILLAWOOD
URBAN RENEWAL PROJECTS**

Prepared for

**MAJOR PROJECTS DIRECTORATE
OF HOUSING NSW**

Project 45789

November 2008



Douglas Partners
Geotechnics • Environment • Groundwater

**PRELIMINARY GEOTECHNICAL AND
CONTAMINATION ASSESSMENT**

**KAMIRA COURT, VILLAWOOD
URBAN RENEWAL PROJECTS**

**Prepared for
MAJOR PROJECTS DIRECTORATE
OF HOUSING NSW**

**Project 45789
November 2008**

*Douglas Partners Pty Ltd
ABN 75 053 980 117*

*96 Hermitage Road
West Ryde NSW 2114
Australia*

*PO Box 472
West Ryde NSW 1685*

*Phone (02) 9809 0666
Fax (02) 9809 4095
sydney@douglaspartners.com.au*



Glossary of Terms

As	arsenic
ASS	Acid Sulphate Soils
B(a)P	benzo(a)pyrene (a polycyclic aromatic hydrocarbon compound)
BTEX	benzene, toluene, ethyl benzene, total xylenes (monocyclic aromatic hydrocarbons)
Cd	cadmium
Cr	chromium (total)
Cr(III)	chromium with oxidation state III (stable in normal environments)
Cr(VI)	chromium with oxidation state VI (typically not stable in normal environments)
Cu	copper
C ₆ –C ₉	light hydrocarbon chain groups
C ₁₀ –C ₁₄	medium hydrocarbon chain groups
C ₁₅ –C ₂₈	heavy hydrocarbon chain groups
C ₂₉ –C ₃₆	heavy hydrocarbon chain groups
DECC	Department of Environment and Climate Change
DNR	Department of Natural Resources
DP	Douglas Partners Pty Ltd
DWE	Department of Water and Energy
EPA	Environmental Protection Authority
GW	groundwater
ha	hectares
HIL	NSW EPA Contaminated Sites: <i>Guidelines for the NSW Site Auditors Scheme, 1998</i> . Health-based investigation levels (Columns 1 to 4)
Hg	mercury
m	metres
mg/kg	milligrams per kilogram (or parts per million)
NATA	National Association of Testing Authorities
Ni	nickel
NSW	New South Wales
OCP	organochlorine pesticides
PAH	polycyclic aromatic hydrocarbon
PASS	Potential Acid Sulphate Soils

Pb	lead
PCB	polychlorinated biphenyls
PID	photoionisation detector
TPH	total petroleum hydrocarbons
TOPIC	total photoionisable compounds
VOC	Volatile Chlorinated Hydrocarbons
Zn	zinc

EXECUTIVE SUMMARY

This report details the methodology, scope of work and results of a combined preliminary geotechnical investigation and Phase 1 contamination assessment with limited soil sampling, undertaken by Douglas Partners Pty Ltd (DP) at a site described as Lot 37, Lot 38 and Lot 39 in Deposited Plan 202006 and Lot 136 in Deposited Plan 16186 in Fairfield local government, located south of Villawood Railway Station and east of Kamira Avenue, Villawood. The geotechnical and environmental investigations were commissioned by the Major Projects Directorate of Housing NSW.

The Kamira Court precinct is currently a vacant block of ground of approximately 1.5 ha. Previously, Kamira Court comprised 111 residential units which have all been demolished and the ground cleared. The land is to be redeveloped for public and private housing.

The objectives of the current investigation were

- Review of available site history information;
- Provide an assessment of the general potential for contamination of the site resulting from past and present site uses based on limited soil sampling;
- Based on the investigation results, comment on the likely suitability of the site for the proposed development and identify any development constraints associated with site contamination issues;
- Considering the site contamination issues, discussion on remedial and additional works required; Provision of a range of unit rates for suitable remediation options;
- Based on *in situ* geotechnical and laboratory testing, provide general and preliminary geotechnical comments on site preparation, earthworks, slope, groundwater, foundations and pavement.

A review of historical information indicated that the site covers four Lots which were historically vacant or used for residential purposes. Industrial or commercial activities on the site were not identified. The current registered proprietor is Housing Commission New South Wales.

According to Fairfield Council Section 149 Certificates, the site is within the floodplain and may be affected by local overland flooding in terms of local runoff.

The relevant Acid Sulphate Soil (ASS) and soil salinity risk maps indicate that the site is unlikely to be affected by either problem.

Eight test pits were excavated to profile the local lithology for both geotechnical and environmental purposes. The test pits were logged and surveyed in position and relative to Australian Height Datum (AHD). Soil samples were collected directly from the test pits for both geotechnical and contamination assessment.

Based on the limited programme of fieldwork carried out, it appears that the subsurface profile at this site may be roughly divided into two areas. The eastern half of the site appears to be deeply filled with 4 - 5 m of filling directly overlying shale, whereas the depth of the filling encountered over the western half was generally less than 0.8 m. In this area the filling was underlain by silty clay and shale. The deep filling also contained metal fragments, tiles, timber and fibre-cement fragments.

Soil samples were assessed for a suite of potential contaminants of concern including heavy metals (As, Cd, Cr, Cu, Pb, Hg, Ni, Zn), TPH, BTEX, PAH, PCB, OCP, total phenols and asbestos.

The contamination assessment did not identify contamination by heavy metals, PAH, TPH, BTEX, Phenols, OCP, PCB and asbestos in regards of the proposed redevelopment with respect to health risk based criteria for residential with minimal access to soil and for open space use. Minor exceedances of the provisional phytotoxicity based investigation levels (PPIL) were detected for arsenic (TP4) and zinc (TP2). However, the results of the contamination assessment show that the site is compatible with the proposed residential use with the appropriate testing and management of soil in excess of the PPIL. This would require further testing of soil for use in landscaped areas.

Groundwater quality has not been assessed. Given the low contamination levels in the soil, leaching of contaminants into a deeper groundwater system is unlikely. Groundwater should be assessed, however, the risk is considered to be low.

A waste classification may be required for the off-site disposal of excavated soil. DP recommends future waste classification with reference to the *Waste Classification Guidelines*, April 2008, issued by the Department of Environment and Climate Change (DECC).

Considering the limited site investigation and the restricted programme of subsurface sampling, screening and chemical testing which was set out in the proposal and although asbestos has not been detected in this study, DP recommends further soil assessment during earthworks specifically to assess for the presence of asbestos contaminants. If basement excavations are planned and asbestos-based waste is detected in the soil and will be retained on site, a Remedial Action Plan (RAP) and an Asbestos Management Plan (AMP) should be prepared for the site. Estimated costs of remedial and additional contamination works that may be necessary for the site are provided in Table 12 in Section 14.

General and preliminary geotechnical comments on site preparation, excavation and earthworks, slope, groundwater, foundations and pavements are provided in Section 13.

TABLE OF CONTENTS

	Page
1. INTRODUCTION.....	1
2. SCOPE OF WORKS	2
3. SITE DESCRIPTION.....	4
3.1 Site Identification	4
3.2 Site Description	4
4. GEOLOGY AND HYDROGEOLOGY	5
5. ACID SULPHATE SOILS AND SALINITY RISK	5
6. SITE HISTORY	6
6.1 Site History	6
6.2 Title Deeds	6
6.3 Aerial Photographs.....	9
6.4 Fairfield Council Section 149 Certificates and Council Records	10
6.5 NSW Department of Environment and Climate Change (DECC) Notices.....	11
6.6 WorkCover Search	12
7. POTENTIAL CONTAMINANTS.....	12
8. FIELD WORK	13
8.1 Sampling Rationale	13
8.2 Environmental Sampling Procedures	13
8.3 Geotechnical Fieldwork.....	15
9. LABORATORY TESTING	16
9.1 Analytical Rationale for Contamination Testing.....	16
9.2 Geotechnical Testing.....	16
10. CONTAMINATION SITE ASSESSMENT CRITERIA.....	18
11. RESULTS OF SOIL INVESTIGATION.....	20
11.1 Fieldwork Results	20
11.2 Total Photoionisable Compounds (TOPIC)	22
11.3 Laboratory Results	23
11.4 Asbestos Testing.....	26
12. ASSESSMENT OF LABORATORY RESULTS.....	26
12.1 Chemical Contaminants in Soil	26
12.2 Asbestos.....	27
13. PRELIMINARY GEOTECHNICAL COMMENTS.....	27
13.1 General.....	27
13.2 Site Classification	28
13.3 Site Preparation and Earthworks.....	28

TABLE OF CONTENTS

	Page
13.4 Batter Slopes and Excavation Support.....	29
13.5 Groundwater.....	29
13.6 Foundations.....	30
13.7 Pavements	30
14. CONCLUSIONS AND RECOMMENDATIONS	31
15. LIMITATIONS OF THIS REPORT.....	33

APPENDICES

- APPENDIX A - Site Drawings
- APPENDIX B - Site Photographs
- APPENDIX C - Site History Information
- APPENDIX D - Test Pit Logs and Notes Relating to this Report
- APPENDIX E - Laboratory Reports and Chain of Custody Documentation
- APPENDIX F - Geotechnical Laboratory Test Results
- APPENDIX G - Data Quality Objectives, Quality Assurance/Quality Control Procedures and Results

UK:jlb

Project 45789

5 November 2008

REPORT ON
PRELIMINARY GEOTECHNICAL AND CONTAMINATION ASSESSMENT
KAMIRA COURT, VILLAWOOD

1. INTRODUCTION

This report details the methodology, scope of work and results of a combined preliminary geotechnical investigation and Phase 1 contamination assessment with limited soil sampling, undertaken by Douglas Partners Pty Ltd (DP) at Kamira Court precinct, located south of Villawood Railway Station and east of Kamira Avenue, Villawood. The geotechnical and environmental investigations were commissioned by the Major Projects Directorate of Housing NSW.

The Kamira Court precinct is currently a vacant block of ground of approximately 1.5 ha. Previously, Kamira Court comprised 111 residential units which have all been demolished and the ground cleared. The land is to be redeveloped for public and private housing with plans to build up to units, of which approximately will revert to Housing NSW and the remainder will be sold privately.

The investigation included a review of available site history information, a site inspection, excavation of eight test pits with geotechnical logging, *in situ* testing, sampling, and laboratory testing, together with a limited soil sampling and analytical programme targeting a range of common contaminants. Details of the fieldwork and laboratory testing are given in the report together with comments relating to the geotechnical assessment and to the likely degree and extent of soil contamination and the suitability of the site for the proposed residential development.

Reference should be made to both Section 14 of this report (Limitations of this Report) and the general Notes Relating to this Report included within Appendix D. These describe the methods and procedures used in undertaking the work, limitations of this document and how it may be used.

2. SCOPE OF WORKS

The scope of the Preliminary Geotechnical and Contamination Assessment was as follows:-

- Undertake a site history search including a title deeds search, a review of historical aerial photographs, a search of the Contaminated Land Register for Notices issued under the *Contaminated Land Management Act 1997*, a search of the Register for Notices issued under the *Protection of the Environment Operations Act*, a search of the WorkCover dangerous goods licence database, and Council records (including Section 149 (2) Certificates);
- Review available site information with reference to local geology;
- Conduct a walkover inspection of the site to make an assessment of signs of potential contamination and relevant geotechnical aspects including slope stability;
- Excavate eight test pits to depths of 3 m, or prior refusal, to sample and log the soils. However, test pitting showed the presence of deep fill and four test pits (TP 4 – TP 7) were extended to depths of three to five meters to intercept the base of the fill (refer to Section 8.3);
- Survey all test pit locations to position relative to Australian Height Datum (AHD);
- Collect 12 soil/filling samples from eight test pits, nominally 1-2 samples from each sample location, plus a duplicate QA sample. Samples taken at changes in the strata or upon signs of contamination;
- Conduct laboratory analysis on selected soil samples (including 10% QA/QC) at a NATA accredited analytical laboratory for a combination of the following potential contaminants:
 - Heavy metals (As, Cd, Cr, Cu, Pb, Hg, Ni, Zn);
 - Total Petroleum Hydrocarbons (TPH);
 - Monocyclic aromatic hydrocarbons (Benzene, Toluene, Ethylbenzene and Xylene – BTEX);

- Polycyclic Aromatic Hydrocarbons (PAH);
- Phenols
- Polychlorinated Biphenyls (PCB);
- Organochlorine Pesticides (OCP);
- Asbestos;
- QA/QC sample analysed for BTEX, heavy metals and PAHs;
- Collect two undisturbed (U50) tube samples of the upper natural clay;
- *In situ* geotechnical testing and bulk sampling for laboratory testing, soil classification, strength and index;
- Conduct laboratory testing on selected soil samples for the preliminary geotechnical investigation:
 - Two Atterberg Limits and Linear Shrinkage tests;
 - Three Field Moisture Content tests;
 - Two Shrink-Swell Index tests;
 - Two California Bearing Ratio (CBR) tests with associated standard compaction tests
- Provision of a Preliminary Geotechnical and Contamination Assessment Report, providing general comments on the recorded level of contamination in the subsoils, a discussion of possible remediation options, including a range of unit rates for the alternative remedial methods and the likely suitability of the site for the proposed development. This report also includes a brief description of the topography, the local geology, soil types, geotechnical commentary including site classification in accordance with AS 2870-1996. The scope did not include an assessment of groundwater quality.

3. SITE DESCRIPTION

3.1 Site Identification

The Kamira Court precinct (hereafter referred to as 'the site') covers an area of approximately 1.5 ha and is located south of Villawood Road and east of Kamira Avenue, Villawood. The site comprises Lot 37, Lot 38 and Lot 39 in Deposited Plan 202006 and Lot 136 in Deposited Plan 16186 in Fairfield local government area. A locality map is shown in Drawing 1, Appendix A.

3.2 Site Description

The site is bounded by Kamira Avenue to the west, Villawood Road to the north, vacant land to the south and by the car park of the local shopping centre to the east. The site is subdivided in two parts by Kamira Court. Lot 37 in D.P. 202006 forms the northern part of the site and Lots 38 and 39 in D.P. 202006 and Lot 136 form the southern part in D.P. 16186. Plate 9, Appendix C shows the extent of the three lots forming the site in question.

The site is relatively flat with ground surface levels at the test pit locations (TP1 – TP8) ranging between RL 21.7 m at TP 6 and RL 24.7 m at TP 2, relative to Australian Height Datum (AHD). According to the surveyed test pit surface levels there is a slope upwards from the south-west of the site (TP 2) to the north-east (TP 6).

At the time of the investigation the site was mostly covered with grass and remnant stands of trees, as shown in Photos 1-7 (Plates 1-4, Appendix B). Where previous structures have been located on Lot 37 in D.P. 202006 (north of Kamira Court), the surface was partly bare with filling visible. In the north-east of Lot 37 there is a small pond with reeds, as shown in Photo 6, Plate 4 in Appendix B. The drainage channels of surface water runoff can also be seen in Photo 6.

Based on the test pit logging data and topography it appears that the site surface has been formed by previous earthworks at the site.

A small stockpile was identified on Lot 37 in D.P. 202006. Photo 4 in Plate 3 in Appendix B and Drawing 4 in Appendix A, show the location of the stockpile. The volume is estimated to be 4 - 5 m³.

4. GEOLOGY AND HYDROGEOLOGY

Reference to the *Soil Landscapes from the Penrith 1:100 000 Sheet*, (Soil Conservation Service of NSW, 1989) indicates that the site is underlain by alluvial soils of the Richmond Soil Landscape, as shown in Drawing 2, Appendix A.

Reference to the *Penrith 1:100 000 Geological Sheet*, 1991 indicates the site is underlain by Bringelly Shale that typically comprises shale, carbonaceous claystone and laminite (interbedded shale, siltstone and fine grained sandstone). Test pitting confirmed the presence of filling on site overlying silty clays and shale interpreted to be the Bringelly Shale formation (see Drawing 3 in Appendix A).

Minor groundwater seepage was intercepted at test pit TP 7 at a depth of approximately 4.6 m. Regional groundwater would be anticipated to be contained within the shale. At the north-east of Lot 37 there is a small a surface water pond. As discussed in Section 6.4, the site is situated within a low-lying floodplain and may be affected by local overland flooding in terms of local runoff and it can be presumed that the surface water body is caused by local runoff. This area is, according to the survey of test pit TP 6, likely to be the lowest location of the site.

5. ACID SULPHATE SOILS AND SALINITY RISK

A review of the Prospect/Parramatta River *Acid Sulphate Soils Risk Map* (Edition 2, DLWC, 1997) indicated that the site is mapped as being located in an area of 'no known acid sulphate soil'. It is also noted that acid sulphate soils typically occur in areas with surface level less than about 5 m AHD whereas the site has a nominal level of 20 m AHD.

The potential for Acid Sulphate Soils (ASS) to be present on the site is, therefore, considered to be low.

A review of the *Salinity Potential West Sydney Map* showed that the property is not likely to be affected by a salinity risk.

6. SITE HISTORY

6.1 Site History

A site historical information review was conducted, comprising a title deeds search, a review of historical aerial photographs, a search of the Contaminated Land Register for Notices issued under the *Contaminated Land Management Act*, 1997, a search of the Register for Notices issued under the *Protection of the Environment Operations Act*, a search of the WorkCover dangerous goods licence database, and Fairfield Council records including Section 149 Certificates. The site history search records are presented in Appendix C.

It is understood that the most recent development on the site, comprising residential units built by the Housing Commission of NSW between 1950 and 1970, was demolished in recent years.

6.2 Title Deeds

A historical title deeds search is used to obtain ownership or occupancy information on the property, including company names and the occupations of individuals. The title information can assist in the identification of previous land uses and can therefore assist in establishing whether there were potentially contaminating activities occurring at the site. A summary of the records with the owner/occupier details and the possible site uses are presented in Table 1 and 2. The full title deed records are included in Appendix C.

The Kamira Court site covers four Lots. These are currently Lots 37, 38 and 39 in Deposited Plan 202006 and Lot 136 in Deposited Plan 16186 as marked on the attached cadastre (Appendix C). In establishing the possible use of the site, information has also been drawn from other sources such as aerial photographs.

Table 1 – Lot 136 D.P. 16186 - Summary of Title Deeds Search

Date	Owner/Occupier	Possible Site Use
19.08.1915	William Charles Wadley Lippman (Bank Manager)	Residential
13.05.1918	John Symonds (Engineer)	Residential
21.06.1928	John Symonds (Engineer) Thomas Kennedy (Engineer) Thomas Peters (Contractor)	Residential
19.06.1928	John Symonds (Engineer) Thomas Kennedy (Engineer) Leonard James Hopper (Investor) Edward Thomas Hopper (Investor)	Residential
28.06.1929	John Symonds (Engineer) Thomas Kennedy (Engineer) Leonard James Hopper (Investor) Edward Thomas Hopper (Investor) Antoine William Mary D'Apice (Solicitor)	Residential
06.01.1930	Ernest Morris (Carpenter)	Residential
22.11.1944	Ernest Morris (Carpenter) Laura Morris (Married Woman)	Residential
12.12.1961	Ernest Morris (Carpenter)	Residential
03.10.1962	Ralph Edward Morris (Supervisor)	Residential
06.09.1971	Sime Muskie (Fitter and Tuner)	Residential
23.11.1973	Housing Commission of New South Wales Current registered proprietor	Residential

Lot 136 in D.P. 16186 was purchased in 1915 by William Charles Wadley Lippman (Bank Manager) for probably residential purposes. From 1918 to 1929 the property was owned by an engineer, John Symonds *et al.*

Reference to the aerial photograph of 1928 (Plate 5, Appendix C) shows that the land was probably used for residential purposes. It appears likely to have maintained a residential use through to 1973 when the Housing Commission became the owner.

Since 23 November 1973 the Housing Commission of New South Wales has been the registered proprietor of Lot 136 in D.P. 16186.

Table 2 – Lots 37, 38 and 39 D.P. 202006 - Summary of Title Deeds Search

Date	Owner/Occupier	Possible Site Use
15.10.1947	Housing Commission of New South Wales	Residential
1952	Housing Commission of New South Wales Current registered proprietor	Residential

According to the results of the title search Lots 37-39 in D.P. 202006 were previously subdivided into 40 lots (Lot 45-Lot 54, Lot 68-Lot 71, Lot 112-Lot 139) in Deposited Plan 16186 in 1929, as shown in Plate 10, Appendix C.

The aerial photographs of 1928, 1943 and 1950 (Plates 1-3, Appendix C) didn't show any development or structures on Lot 37, Lot 38 and Lot 39. The land was apparently bushland and not used for any commercial/industrial or residential purposes. On this basis it was assessed that a title deeds search for these 40 lots would not provide any relevant data in regards to the contamination assessment.

The Housing Commission of New South Wales undertook the first development of Lot 37-39 in D.P. 202006 after the Second World War. In 1947 Housing Commission of New South Wales purchased the property and is still the current registered proprietor.

The title deed search results and cadastral map extracts are included in Appendix C

6.3 Aerial Photographs

Aerial photographs from 1928, 1943, 1950, 1961, 1970, 1978 and 1991 were obtained from the NSW Department of Lands. The 1943 and 2007 images were obtained from the NSW Department of Lands website (www.lands.nsw.gov.au). The aerial photographs are presented in Appendix C. These aerial photos were reviewed to assess the likely past uses of the site. The findings are summarised below.

1928 – Plate 1 shows two structures on Lot 136 in D.P. 16186. The building in the west of Lot 136 had the size typical of a residential house. The building in the east is smaller. The photograph shows the development of the first residential houses in Kamira Avenue, Villawood.

Lot 37, 38 and 39 in D.P. 202006 appeared to be bushland with a few tracks. The area showed no sign of special usage.

1943 – Plate 2 shows an aerial photograph of 1943. Lot 37, 38 and 39 in D.P. 202006 were still bushland without any identifiable structures or special usage.

The two buildings on Lot 136 were still present but the use cannot be interpreted. Markings can be seen that may represent the land boundary of Lot 136.

1950 – On the aerial photograph of 1950 (Plate 3) two buildings are still identifiable. There are no significant differences to the 1943 photograph.

1961 – Plate 4 shows a significant amount of new structures on Lot 37 – Lot 39. Considering that the Housing Commission of New South Wales owned Lot 37 – Lot 39 since 1947 it appears likely that the buildings were for residential purposes

The boundary of Lot 136 D.P. 16186 and two buildings can be still seen.

1970 – Construction of the buildings had been completed on Lot 37 – Lot 39 in D.P. 202006.

The marking of the land boundary of Lot 136 D.P. 16186 and the two buildings appear to be still present (Plate 5, Appendix C).

1978 – Plate 6 shows that a total of 14 buildings had been constructed on Lot 37 – Lot 39. The site also comprised remnant stands of trees, car parks and a landscaped area between the two main buildings in the north and south of Lot 37. The two buildings previously identified on Lot 136 in D.P. 18186 have been demolished and removed and Lot 136 appears to be undeveloped.

At this time the site was already divided by Kamira Court into Lot 37 in the north and Lot 38, Lot 39 in D.P. 202006 and Lot 136 in D.P. 18186 in the south of the site.

1991 – Plate 7 shows that there were no significant changes to the number, location and size of buildings on Lot 37 – Lot 39.

2007 – The buildings and structures have been demolished and removed. Plate 8 shows a vacant block of land.

6.4 Fairfield Council Section 149 Certificates and Council Records

The Section 149 Planning Certificates of Lot 37 in Deposited Plan 202006 as the main Lot of the site, issued by the Fairfield City Council were reviewed as part of this assessment.

The land is subject to a Draft Local Environmental Plan (Draft L.E.P.) The draft L.E.P. is attached in the Section 149 Planning Certificate. The land is also subject to a number of State Environmental Planning Policies including, *inter alia*, State Environmental Planning Policy No. 55 – Remediation of Land.

The site is identified as a Residential B zone. The land doesn't include or comprise critical habitats or include environmental heritage items.

According to the Section 149(2) Planning Certificate – Clause 7, the site *‘is not affected by a policy adopted by Council or any other public authority and notified to Council that restricts development of the land because of the likelihood of land slip, subsidence, bushfire, tidal inundation and acid sulphate soils or any other risks’*.

Part of all of this land is within the floodplain and may be affected by local overland flooding. The term local overland flooding means inundation by local runoff rather than overbank discharge from a stream, river, estuary, lake or dam.

According to the Planning Certificate under Section 149 (2), the site has not been declared to be an “investigation area” or “remediation site” under Part 3 of the *Contaminated Land Management Act 1997* and *‘is not subject to an investigation or remediation order’* or to a *voluntary investigation/remediation proposal*. *The land is not subject of a site audit statement within the meaning of the Contaminated Land Act 1997.*

The Section 149(2) Planning Certificates are included in Appendix C.

A search of the Fairfield Council’s history archives has not located any records pertaining directly to the subject site.

6.5 NSW Department of Environment and Climate Change (DECC) Notices

A search of Notices on the DECC website on 25 June 2008 indicated that there are currently no Notices and/or Licences under the *Protection of the Environment Operations Act (1997)* that pertain directly to the subject site. No Notices or Orders to investigate or remediate the site are reported to have been issued for the site under the *Contaminated Land Management Act, 1997*.

6.6 WorkCover Search

A search by WorkCover New South Wales of the Stored Chemical Information Database (SCID) and the microfiche records held by WorkCover has not located any records relating to the current or historic storage of dangerous goods pertaining to Lot 37 – 39 in D.P. 202006 and Lot 136 in D.P. 16186.

7. POTENTIAL CONTAMINANTS

The desktop investigation showed no indication of industrial or commercial activities at the site which may be considered to be potentially contaminating. The potential soil contaminants on the subject site are likely to be associated with building, road construction and demolition wastes and the deep fill encountered during test pitting (refer to Section 11.1).

A broad range of commonly found organic and inorganic compounds were included in the analytical suite for soil, as follows:

- Heavy metals (As, Cd, Cr, Cu, Pb, Hg, Ni, Zn);
- Total Petroleum Hydrocarbons (TPH);
- Monocyclic Aromatic Hydrocarbons (Benzene, Toluene, Ethylbenzene and Xylene – BTEX);
- Polycyclic Aromatic Hydrocarbons (PAH);
- Phenols;
- Polychlorinated Biphenyls (PCB);
- Organochlorine Pesticides (OCP);
- Asbestos.

8. FIELD WORK

8.1 Sampling Rationale

The number of sample locations was based on the EPA publication *Sampling Design Guidelines* which recommends a minimum of 25 sampling locations for a site of 1.5 ha. DP recommended that eight sample locations be established. Based on the lower rate of the minimum sampling density recommended (30-50%), DP considers the adopted sampling density to be appropriate for a limited sampling programme. A total of 12 samples from eight test pit locations were analysed, nominally 1-2 samples per test location.

The test pit locations were placed over the site based on site observations, the site history review and with a view to providing appropriate site coverage. At least one sample location was placed on each of the Lots.

Soil samples were collected on changes in strata and signs of contamination. Sampling locations are indicated on Drawing 4 in Appendix A.

8.2 Environmental Sampling Procedures

All test pit locations were cleared for detectable services and pipes using Dial-Before-You-Dig information and electro-magnetic scanning by an accredited service locator.

Test pits TP1 and TP2 were placed one each in Lot 39 in D.P. 202006 and Lot 136 in D.P. 18186 (see Photo 1, Plate 1 in Appendix B). TP3 and TP4 were located in Lot 38 in D.P. 202006 (see Photo 2 and 3, Plate 1 and 2 in Appendix B). The largest lot (Lot 37 in D.P. 202006) was investigated by excavating four test pits (TP5 – TP8).

Test pits TP1 – TP 8 were generally located within the building footprint of previous structures. During the site inspection a significant unevenness of the ground level was noted around test pit TP4 as shown in Photo 3, Plate 2 in Appendix B. Similar conditions were noted at test pit TP7.

Test pits were logged and surveyed in position, using a differential GPS, and were surveyed using an optical level relative to Australian Height Datum (AHD). The surface levels of TP 1 – TP 8 are recorded in the Test Pit Records in Appendix D.

All strata and sampling data were recorded on DP Test Pit Log reports. The general sampling procedure is summarised below:-

- collect soil samples directly from test pits using disposable sampling equipment;
- transfer samples into laboratory-prepared glass jars, capping immediately and ensuring that the headspace within the sample jar is minimised;
- collect a split replicate at each location into a zip lock plastic bag;
- collect replicate samples for QA/QC purposes;
- label sample containers with individual and unique identification, including project number, sample location and sample depth; and
- place the glass jars, with Teflon lined lid, into a cooled, insulated and sealed container for transport to the laboratory.

The stockpiled soil was sampled, following the sampling procedures, as described above. A description of the soil is given in the Test Pit Log reports in Appendix D.

A photoionisation detector (PID) was used to screen the headspace gases of the replicate samples placed in the sealed zip-lock bag. The PID provides an indication of the presence of volatile organic compounds in the soil. The PID had a 10.6eV lamp and was calibrated with isobutylene gas at 100 ppm prior to commencement of each day's field work.

EnviroLab Services, a laboratory accredited by the National Association Testing Authorities (NATA), was employed to conduct the sample analysis. The laboratory is required to carry out routine in-house QC procedures.

8.3 Geotechnical Fieldwork

The fieldwork for the preliminary geotechnical assessment was carried out in conjunction with the environmental sampling described in Section 8.2. The following additional work was carried out for geotechnical purposes.

- Geotechnical walkover inspection for the purpose of assessing of slope stability, site filling and other geotechnical issues affecting the development;
- Collection of three (and analysis of two) 'undisturbed' (U50) tube samples collected within the upper horizon of natural clay;
- Collection of bulk samples of natural soils and filling material at four locations; and
- Site supervision by a geotechnical engineer to assist with sampling and logging for geotechnical purposes

The eight test pits were excavated to depths of between 2.3 m and 5.0 m using a rubber-tyred backhoe. Pocket penetrometer testing was carried out in the sidewalls of the test pits and on disturbed samples from the excavator bucket to indicate the strength and consistency of the subsurface materials.

Groundwater levels and seepage into the test pits were observed during the short period of time over which the pits remained open. It is noted that variations in groundwater levels occur over time due to climatic and other factors.

As described previously, the test pits were set-out using a differential GPS and the ground surface levels were determined using an optical survey level, relative to AHD. The test pit locations are shown on Drawing 4.

9. LABORATORY TESTING

9.1 Analytical Rationale for Contamination Testing

The analytical scheme (Table 3) was designed to assess the potential for contamination which may have arisen from current and past use of the site. A total of 13 selected soil samples (including QA/QC replicate) were analysed for various combinations of the contaminants of concern.

Table 3 – Analytical Scheme for soil samples

Sample ID (Location – Depth)	Heavy Metals	TPH	BTEX	PAH	PCB	OCP	Phenols	Asbestos
TP1/0.15-0.4m	✓	✓	✓	✓	✓	✓	✓	✓
TP2/0.1-0.4m	✓	✓	✓	✓	✓	✓	✓	✓
TP3/0.1-0.25m	✓	✓	✓	✓	✓	✓	✓	✓
TP4/0.7-1.4m	✓	✓	✓	✓	✓	✓	✓	
TP5/0.0-0.5m	✓	✓	✓	✓	✓	✓	✓	
BD1/170908	✓			✓	✓	✓		
TP5/0.5-1.4m	✓	✓	✓	✓	✓	✓		✓
TP6/0.5-1.6m	✓	✓	✓	✓	✓	✓	✓	
TP6/2.7-3.2m	✓	✓	✓	✓	✓	✓		✓
TP7/0.3-1.0m	✓	✓	✓	✓	✓	✓		
TP7/3.2-3.9m	✓	✓	✓	✓	✓	✓	✓	✓
TP8/0.1-0.8m	✓	✓	✓	✓	✓	✓	✓	✓
Stockpile	✓	✓	✓	✓	✓	✓		✓
TS-170908			✓					

Note: BD1: field replicate of sample TP5/0.0-0.5m
 TS: Spike

9.2 Geotechnical Testing

Selected samples of the materials intersected in the test pits were tested in the laboratory to determine soil classification and engineering properties. The following suite of geotechnical laboratory tests were undertaken:

- 2 No. Atterberg Limits and Linear Shrinkage tests;
- 3 No. Field Moisture Content Tests;
- 2 No. Shrink-Swell Index (I_{ss}) Tests; and

- 2 No. California Bearing Ratio (CBR) tests, with the associated standard compaction tests required for sample preparation.

The detailed laboratory test results are included in Appendix F

The results of the Atterberg limits and Linear Shrinkage tests are summarised in Table 4.

Table 4 – Summary of Soil Classification Test Results

Test Location	Depth (m)	Material	Field Moisture Content (%)	Atterberg Limits			Linear Shrinkage (%)
				LL (%)	PL (%)	PI (%)	
TP1	1.0	Silty clay	18.9	51	22	29	12.5
TP6	1.0	Filling (silty clay)	24.1	49	22	27	11.5
TP8	1.0	Silty clay	20.3	-	-	-	-

The results of the Shrink-Swell Index (I_{ss}) tests are presented in Table 5.

Table 5 – Summary of Shrink-Swell Index Tests

Test Location	Depth (m)	Material	Shrink-Swell Index (I_{ss}) (%)
TP3	0.5 – 0.8	Silty clay	3.4
TP8	0.8 – 1.0	Silty clay	1.6

The two CBR samples were soaked for four days under a standard surcharge load of 4.5 kg. The CBR and compaction test results are summarised in Table 6 below.

Table 6 – Summary of CBR Tests

Test Location	Depth (m)	Material	Field Moisture Content (%)	Optimum Moisture Content (%)	Max. Dry Density (t/m^3)	Swell (%)	CBR (%)
TP1	0.5	Silty clay	25.3	25.0	1.58	2.2	2.5
TP8	1.2	Silty clay	20.9	16.5	1.77	4.0	1.0

10. CONTAMINATION SITE ASSESSMENT CRITERIA

In determining the appropriate criteria against which to assess the results of the chemical analysis, DP has made the following assumptions with regard to the planned development;

- There will be no individual houses or townhouses with private gardens;
- Housing will consist of low rise apartments;
- The areas in between buildings will include roads, paved areas, landscaping and lawns and will not include allotments for growing vegetables.

The DECC's standard, health risk based settings (health-based investigation levels – HIL) are defined in the *Guidelines for the NSW Site Auditor Scheme*, 2nd edition, 2006, Appendix I and it includes the following land uses;

- Residential with accessible soil and use of home grown produce. Includes child-care centres, primary schools, pre-schools, town houses and villas;
- Residential with minimal access to soil such as high rise apartments and flats;
- Parks, recreational open space or playing fields and including secondary schools;
- Commercial or industrial use.

In addition, the DECC also sets provisional phytotoxicity-based investigation levels (PPIL) for the protection of plants in the appropriate setting (residential with gardens, areas outside of the building footprint of apartments and flats and open space).

With regard to the planned development and the standard, health risk settings we have assessed that the most appropriate settings are considered to be;

- Residential with minimal access to soil such as high rise apartments and flats where this soil will be under building slabs, roads or other pavements (HIL Column2, Appendix II);
- Recreational open space for the landscaped areas (HIL Column 3, Appendix II);
- PPIL for the protection of plants in landscaped areas and lawns (Column 5, Appendix II).

Appendix II of the *Guidelines for the NSW Site Auditor Scheme* and the NSW EPA publication *Guidelines for Assessing Service Station Sites* 1994 provides the health-based investigation levels for these settings and, together with the PPIL, these form the site acceptance criteria (SAC) for the assessment of the site. The adopted site assessment criteria are shown in Table 7, below.

In addition to the HIL concentrations, the following criteria are also considered:

A contaminant concentration in soil/filling material is considered to be significant if:

- i) The concentration of the contaminant is more than 2.5 times the site assessment criteria. Any location more than 2.5 times the SAC is classified as a 'hotspot', requiring further assessment/ management.
- ii) For a data of like material, with respect to the health-based criteria, the calculated 95% Upper Confidence Limit of average concentrations (excluding any 'hotspot' concentrations) exceeds the SAC.
- iii) The standard deviation of the results is greater than 50% of the health-based investigation levels.

Note that for plant health, the PPIL are single number criteria as shown in Table 7 and, therefore, the statistical analysis would only apply to HILs.

Table 7 – Site Assessment Criteria for Contamination

Contaminant	Adopted Criteria (SAC)			Source
TPH C ₆ – C ₉ C ₁₀ – C ₃₆	65 mg/kg 1000 mg/kg			NSW EPA ¹ Contaminated Sites <i>Guidelines for Assessing Service Station Sites</i> (1994) threshold concentrations for sensitive land use - soils. Currently there are no other comprehensive, EPA endorsed investigation levels for petroleum hydrocarbons.
BTEX Benzene Toluene Ethylbenzene Xylene	1 mg/kg 1.4 mg/kg 3.1 mg/kg 14 mg/kg			
Metals Arsenic (total) Cadmium Chromium Copper Lead Mercury Nickel Zinc	HIL-Column 2 400 mg/kg 80 mg/kg 48,000 mg/kg 4,000 mg/kg 1,200 mg/kg 60 mg/kg 2,400 mg/kg 28,000 mg/kg	HIL-Column 3 200 mg/kg 40 mg/kg 24,000 mg/kg 2,000 mg/kg 600 mg/kg 30 mg/kg 600 mg/kg 14,000 mg/kg	PPIL-Column 5 20 mg/kg 3 mg/kg 400 mg/kg 100 mg/kg 600 mg/kg 1 mg/kg 60 mg/kg 200 mg/kg	
Total Phenols	34,000 mg/kg	17,000 mg/kg		NSW EPA Contaminated Sites <i>Guidelines for the NSW Site Auditor Scheme</i> (2 nd Edition) (2006) Soil Investigation Levels for Urban Redevelopment Sites in NSW Heath-based Investigation Levels outlined in Column 2 and 3, and Provisional Phytotoxicity Investigation Levels outlined in Column 5.
PAH Total Benzo(a)Pyrene	80 mg/kg 4 mg/kg	40 mg/kg 2 mg/kg		
PCB	40 mg/kg	20 mg/kg		
OCP Aldrin + Dieldrin Chlordane DDT+DDD+ DDE Heptachlor	40 mg/kg 200 mg/kg 800 mg/kg 40 mg/kg	20 mg/kg 100 mg/kg 400 mg/kg 20 mg/kg		
Asbestos	No asbestos present in soil at the surface			

11. RESULTS OF SOIL INVESTIGATION

11.1 Fieldwork Results

Details of the sub-surface conditions encountered during the course of the investigation are included in the Test Pit Log Report Sheets (Appendix D), together with notes describing classification methods and descriptive terms. The test pit locations are shown on Drawing 4, Appendix A. Based on the limited programme of fieldwork carried out, it appears that the subsurface profile at this site may be roughly divided into two areas.

¹ NSW EPA is now part of the NSW Department of Environment and Climate Change (DECC).

The eastern half of the site appears to be deeply filled with 4 – 5 m of filling directly overlying shale, whereas the depth of filling encountered over the western half (TP1 – TP3 and TP8) was generally less than 0.8 m.

The general sequence of materials encountered in the test pits is summarised as follows:

Topsoil

Surficial topsoil overlies filling to depths of approximately 0.1 m, except in parts of Lot 37 where the main residential buildings were located (at test pit locations TP 5 – TP 7). At these locations the fill is not covered by topsoil.

Filling

Filling generally comprised brown and grey or grey and red silty clay with some gravel, crushed shale, brick, timber, concrete, glass, ceramics and metal fragments. The filling encountered in TP2 (0.0-0.4m), TP6 (2.7-3.2m), TP7 (3.2-3.9m) and TP8 (0.1-0.8m) contained fragments of fibre-cement products. Styrofoam was found in TP 7. Traces of ash were detected in the filling at TP 3.

Filling encountered in TP4 – TP7 was between 4 m and 5 m deep. The deepest filling was intersected in TP7 (4.9 m). The deep filling also contained metal fragments, tiles, timber, and fibre-cement fragments in test pits TP6 and TP7. The fibre-cement fragments were sent for asbestos analysis. The results are given in Section 11.4. Over the eastern half of the site (TP4 – TP7) the filling was directly underlain by shale bedrock.

Natural Soils

The natural soil profile comprised red and grey silty clay with a trace of ironstone gravel typically of a stiff to hard consistency and at, or drier than, the Plastic Limit. The natural clay soil profile was only encountered over the western half of the site (TP1 – TP3 and TP8).

Bedrock

The silty clay is underlain by Bringelly Shale. The shale is typically grey and has some ironstaining. Bringelly shale was intersected in depths between 1.2 m and 1.9 m where shallow filling was encountered (TP 1 – TP 3 and TP 8). In test pits TP 4 and TP 5 Bringelly shale was encountered in depths to 3.8 / 3.9 m. In test pit TP6 the natural shale was intersected at a depth of 4.3 m. Over the eastern half of the site the underlying shale was interpreted to be generally low (and possibly medium) strength with shallow depth.

Perched water was intersected as minor seepage inflow at a depth of 4.6 m in test pit TP 7.

Table 8 summarises the subsurface profile encountered during the current investigation.

Table 8 – Subsurface Profile

Sampling Location	Topsoil	Filling (minimum depth in metres)	Silty Clay (minimum depth in metres)	Shale (minimum depth in metres)	Completion Depth
					in metres
TP1	0-0.1	0.1-0.4	0.4-1.9	1.9-2.4	2.4
TP2	0-0.1	0.1-0.4	0.4-1.2	1.2-2.3	2.3
TP3	0-0.1	0.1-0.25	0.25-1.6	1.6-3.0	3.0
TP4	0-0.1	0.1-3.9	-	3.9-4.2	4.2
TP5	-	0-3.8	-	3.8-4.0	4.0
TP6	-	0-4.3	-	4.3-4.5	4.5
TP7	-	0-4.9	-	4.9-5.0	5.0
TP8	0-0.1	0.1-0.8	0.8-1.2	1.2-1.9	1.9

11.2 Total Photoionisable Compounds (TOPIC)

The replicate soil samples, collected in sealed zip-lock bags, were allowed to equilibrate under ambient temperatures before screening for Total Photoionisable Compounds (TOPIC) using a calibrated Photoionisation Detector (PID). The PID provides an indication of the presence of volatile organic compounds in the soil. The PID had a 10.6eV lamp and was calibrated with isobutylene gas at 100 ppm prior to commencement of fieldwork.

Results of sample screening are shown in the Test Bore Reports in Appendix D. The PID readings were 0 ppm in all screened samples and, therefore, do not indicate the presence of contamination by volatile organic compounds.

11.3 Laboratory Results

The collected soil samples (including QA/QC samples) were sent for analysis at a NATA accredited laboratory. The results of laboratory analysis of the soil are summarised in Tables 9 and Table 10. NATA Reports are also provided in Appendix E.

Table 9 - Laboratory Results - Soil

Sample ID	Heavy Metals								PAH		TPH		BTEX				Total Phenols	OCP			Total PCB ²	Asbestos								
	As	Cd	Cr ¹	Cu	Pb	Hg	Ni	Zn	Total ²	Benzo(a)pyrene	C ₆ -C ₉	C ¹⁰ -C ³⁶	Benzene	Toluene	Ethyl-Benzene	Total Xylene		Total OCP ²	DDT+DDD+DD E ²	Aldrin + Dieldrin ²										
Filling Material																														
TP1/0.15-0.4m	9.0	<0.5	21.0	19.0	24.0	<0.1	8.0	99.0	<PQL	<0.05	<25	<250	<0.5	<0.5	<1.0	<3.0	<5.0	<0.1	<0.1	<0.1	<0.1	NIL								
TP2/0.1-0.4m	9.0	0.6	17.0	52.0	140.0	<0.1	13.0	270.0	<PQL	<0.05	<25	<250	<0.5	<0.5	<1.0	<3.0	<5.0	<0.1	<0.1	<0.1	<0.1	NIL								
TP3/0.1-0.25m	9.0	0.5	31.0	13.0	22.0	<0.1	9.0	18.0	0.06	0.06	<25	<250	<0.5	<0.5	<1.0	<3.0	<5.0	<0.1	<0.1	<0.1	<0.1	NIL								
TP4/0.7-1.4m	26.0	<0.5	12.0	34.0	19.0	<0.1	26.0	86.0	<PQL	<0.05	<25	<250	<0.5	<0.5	<1.0	<3.0	<5.0	<0.1	<0.1	<0.1	<0.1	-								
TP5/0.0-0.5m	9.0	<0.5	10.0	34.0	18.0	<0.1	20.0	71.0	<PQL	<0.05	<25	<250	<0.5	<0.5	<1.0	<3.0	<5.0	<0.1	<0.1	<0.1	<0.1	-								
BD1/170908	9.0	<0.5	9.0	31.0	16.0	<0.1	25.0	70.0	<PQL	<0.05	-	-	-	-	-	-	-	-	-	-	-	-								
TP5/0.5-1.4m	6.0	<0.5	9.0	29.0	17.0	<0.1	17.0	94.0	<PQL	<0.05	<25	<250	<0.5	<0.5	<1.0	<3.0	-	<0.1	<0.1	<0.1	<0.1	NIL								
PQL																														
	<4.0	<1.0	<1.0	<1.0	<1.0	<0.1	<1.0	<1.0	<0.1/0.2	<0.05	<25	<250	< 0.5	< 0.5	<1.0	<3.0	<5.0	<0.1	<0.1	<0.1	<0.1									
Site Assessment Criteria ⁴																														
HIL-Column 2 ⁴	400	80	48000	4000	1200	60	2400	28000	80	4	65 ⁶	1,000 ⁶	1 ⁶	1.4 ⁶	3.1 ⁶	14 ⁶	34000	-	800	40	40									
HIL-Column 3 ⁵	200	40	24000	2000	600	30	600	14000	40	2	65 ⁶	1,000 ⁶	1 ⁶	1.4 ⁶	3.1 ⁶	14 ⁶	17000	-	400	20	20									
PPIL	20	3	400	100	600	1	60	200																						

Notes:

- 1 All Chromium are assumed to exist in the stable Cr(III) oxidation state, as Cr(VI) will be too reactive and unstable in normal environmental conditions
- 2 Where results are above practical quantitation limit (PQL) sum of all results given, when below PQL results quoted as <PQL of majority of individual analytes
- 3 Field replicate of sample listed directly above
- 4 NSW EPA Contaminated Sites *Guidelines for the NSW Site Auditor Scheme* (2nd Edition) (2006) Soil Investigation Levels for Urban Redevelopment Sites in NSW Heath-based investigation levels residential with minimal access to soil (HIL Column 2)
- 5 NSW EPA Contaminated Sites *Guidelines for the NSW Site Auditor Scheme* (2nd Edition) (2006) Soil Investigation Levels for Urban Redevelopment Sites in NSW Heath-based investigation levels Parks, recreational open space, playing fields including secondary schools (HIL Column 3)
- 6 NSW EPA Contaminated Sites *Guidelines for Assessing Service Station Sites* (1994) threshold concentrations for sensitive land use-soils
- not analysed
- NIL No asbestos found at reporting limit of 0.1g/kg, respirables fibres not detected

BOLD Indicates exceedance of HIL

Table 10 - Laboratory Results - Soil

Sample ID	Heavy Metals								PAH		TPH		BTEX				Total Phenols	OCP			Total PCB ²	Asbestos							
	As	Cd	Cr ¹	Cu	Pb	Hg	Ni	Zn	Total ²	Benzo(a)pyrene	C ⁶ -C ⁹	C ¹⁰ -C ³⁶	Benzene	Toluene	Ethyl-Benzene	Total Xylene		Total OCP ²	DDT+DDD+DDE ²	Aldrin + Dieldrin ²									
Filling Material																													
TP6/0.5-1.6m	6.0	<0.5	11.0	50.0	22.0	<0.1	21.0	72.0	<PQL	<0.05	<25	<250	<0.5	<0.5	<1.0	<3.0	<5.0	<0.1	<0.1	<0.1	<0.1	-							
TP6/2.7-3.2m	9.0	<0.5	11.0	34.0	19.0	<0.1	24.0	110.0	<PQL	<0.05	<25	<250	<0.5	<0.5	<1.0	<3.0	-	<0.1	<0.1	<0.1	<0.1	NIL							
TP7/0.3-1.0m	6.0	<0.5	10.0	37.0	15.0	<0.1	25.0	110.0	<PQL	<0.05	<25	<250	<0.5	<0.5	<1.0	<3.0	-	<0.1	<0.1	<0.1	<0.1	-							
TP7/3.2-3.9m	4.0	<0.5	10.0	35.0	19.0	<0.1	17.0	78.0	<PQL	<0.05	<25	<250	<0.5	<0.5	<1.0	<3.0	<5.0	<0.1	<0.1	<0.1	<0.1	NIL							
TP8/0.1-0.8m	<4.0	<0.5	9.0	9.0	11.0	<0.1	3.0	27.0	<PQL	<0.05	<25	<250	<0.5	<0.5	<1.0	<3.0	<5.0	<0.1	<0.1	<0.1	<0.1	NIL							
Stockpile	5.0	<0.5	16.0	19.0	30.0	<0.1	15.0	73.0	<PQL	<0.05	<25	<250	<0.5	<0.5	<1.0	<3.0	-	<0.1	<0.1	<0.1	<0.1	NIL							
PQL	<4.0	<1.0	<1.0	<1.0	<1.0	<0.1	<1.0	<1.0	<0.1/0.2	<0.05	<25	<250	< 0.5	< 0.5	<1.0	<3.0	<5.0	<0.1	<0.1	<0.1	<0.1								
Site Assessment Criteria ⁴																													
HIL-Column 2 ⁴	400	80	48000	4000	1200	60	2400	28000	80	4	65 ⁶	1,000 ⁶	1 ⁶	1.4 ⁶	3.1 ⁶	14 ⁶	34000	-	800	40	40								
HIL-Column 3 ⁵	200	40	24000	2000	600	30	600	14000	40	2	65 ⁶	1,000 ⁶	1 ⁶	1.4 ⁶	3.1 ⁶	14 ⁶	17000	-	400	20	20								
PPIL	20	3	400	100	600	1	60	200																					

Notes:

- 1 All Chromium are assumed to exist in the stable Cr(III) oxidation state, as Cr(VI) will be too reactive and unstable in normal environmental conditions
- 2 Where results are above practical quantitation limit (PQL) sum of all results given, when below PQL results quoted as <PQL of majority of individual analytes
- 3 Field replicate of sample listed directly above
- 4 NSW EPA Contaminated Sites *Guidelines for the NSW Site Auditor Scheme* (2nd Edition) (2006) Soil Investigation Levels for Urban Redevelopment Sites in NSW Heath-based investigation levels residential with minimal access to soil (HIL Column 2)
- 5 NSW EPA Contaminated Sites *Guidelines for the NSW Site Auditor Scheme* (2nd Edition) (2006) Soil Investigation Levels for Urban Redevelopment Sites in NSW Heath-based investigation levels Parks, recreational open space, playing fields including secondary schools (HIL Column 3)
- 6 NSW EPA Contaminated Sites *Guidelines for Assessing Service Station Sites* (1994) threshold concentrations for sensitive land use-soils
- not analysed
- NIL No asbestos found at reporting limit of 0.1g/kg, respirables fibres not detected

BOLD Indicates exceedance of HIL

11.4 Asbestos Testing

Four fibre-cement fragments were sent for asbestos analysis. The results are summarised in Table 11.

Table 11 – Asbestos Testing of Bulk Material

Sampling Location	Depth	Asbestos fibres detected
TP2	0.1-0.4	No asbestos detected
TP6	2.7-3.2	No asbestos detected
TP7	3.2-3.9	No asbestos detected
TP8	0.1-0.8	No asbestos detected

12. ASSESSMENT OF LABORATORY RESULTS

12.1 Chemical Contaminants in Soil

Soil samples were assessed for a suite of potential contaminants of concern including heavy metals (As, Cd, Cr, Cu, Pb, Hg, Ni, Zn), TPH, BTEX, PAH, PCB, OCP, Total Phenols and asbestos.

The laboratory results (Table 9 and Table 10) indicated that contaminant concentrations of heavy metals in the soil samples analysed were within the health-based SAC for residential with minimum opportunities for soil access and for recreational open space and mostly within the Provisional Phytotoxicity-based Investigation Levels (PPIL), which are relevant for landscaped areas. Arsenic and zinc concentrations in soil sample TP4/0.7-1.4 m and respectively in soil sample TP2/0.1-0.4m exceed the PPIL levels.

PAH were detected only in one soil sample (TP3/0.1-0.25m). The PAH concentration of 0.06 mg/kg, consisting of Benzo(a)pyrene, was within the more sensitive health-based SAC for recreational open space.

The chemical analysis didn't detect any total petroleum hydrocarbons, BTEX, Phenols, polychlorinated biphenyls in the tested soil samples. The detection limits are listed in Tables 9 and Table 10.

12.2 Asbestos

Eight samples of filling and four fibre-cement fragments were analysed for asbestos. Asbestos minerals were not detected in any of these samples.

13. PRELIMINARY GEOTECHNICAL COMMENTS

13.1 General

The present site surface is relatively flat with a gentle slope down towards the north-eastern corner of the site. It is therefore considered that there is currently no significant risk of slope instability affecting the existing site.

Topographically, the site is understood to be within a defined floodplain and as such, due consideration should be given to the risks associated with flooding and inundation of the present site.

The relevant Acid Sulphate Soil (ASS) and soil salinity risk maps indicate that the site is unlikely to be affected by either problem.

Probably the most important aspect, at least from a geotechnical viewpoint, is the deep filling encountered over the eastern half of the site. This is likely to have a major impact on the type of foundation systems and earthworks required for the development of this site.

13.2 Site Classification

The significant depth of filling encountered over most of the site, of up to 5 m, would necessitate a 'Class P' site classification in accordance with AS 2870-1996 (Residential Slabs and Footings). In the absence of filling records and, in particular, density and compaction test results, the existing fill should be regarded as 'uncontrolled'.

Based on the relatively minor depth of filling encountered over the south-western part of the site (TP1 – TP3), a 'Class M' (moderately reactive) or 'Class H' (highly reactive) site classification may be possible. Further field investigation and laboratory soil testing would, however, be necessary to confirm the site classification appropriate for the final design of footings.

Based on the I_{ss} test results, the natural site soils are indicated to be moderately to highly reactive, such that significant volume changes could be expected for the clays in response to variations in the soil moisture content.

13.3 Site Preparation and Earthworks

The extent of earthworks will be controlled by design surface levels for flood mitigation, the extent of below-ground basements for the development and the need to remove any contaminated soil for environmental reasons. Material to be removed from site will generally require waste classification assessment prior to disposal at a licensed landfill.

Based on the observed conditions in the test pits, the excavation of a single basement for example (i.e. to about 3 m depth), would primarily involve the excavation of filling, natural clays and relatively weak, weathered shale. These materials should be readily excavated using conventional earthmoving equipment (e.g. bulldozers). Along the western side of the site, the lowest 0.5 – 1.0 m of excavation for a one-level basement would entail the removal of some medium strength shale. This may require the use of medium-sized ripping tynes and hydraulic rock hammering for excavation purposes.

Depending on the nature of the proposed residential developments and other factors, it may be possible to leave the existing filling *in situ* and fully support the superstructure of the buildings on piled foundations, socketed into the underlying shale. Alternatively, it may be possible to compact the existing filling *in situ* using heavy impact-rolling compaction plant. Further geotechnical information will generally be required to provide further assessment of these options.

13.4 Batter Slopes and Excavation Support

Within the filling and natural soils temporary batters of 1.5 Horizontal (H) : 1 Vertical (V), and permanent batters of 2H : 1V are suggested for excavations of up to 3 m depth. Permanent batters should be provided with erosion protection using vegetation cover or similar.

It is assumed that retaining/shoring walls for basements (single level assumed) will be limited to a maximum height of 3 m. The preliminary design of retaining walls that are capable of some outward rotation (e.g. cantilever walls or walls with a single row of 'tie-back' anchors) may be designed on the basis of a bulk density of 18 kN/m^3 for the retained material, and an active earth pressure coefficient (K_a) of 0.4 assuming a triangular earth pressure distribution on the rear of the wall. Additional allowance should be made for lateral pressures from surcharge loads above the wall and also for hydrostatic pressures.

13.5 Groundwater

Based on the minor amount of seepage noted in the test pits, it is considered that the construction of below-ground basements should not be adversely impacted by groundwater. Inflows should be readily handled by conventional 'sump-and-pump' methods.

Due to the topographic setting of the site and consequent risk of periodic flooding, it will be important to incorporate a comprehensive subfloor drainage system.

The system of subfloor drains should direct groundwater and the water collected from catch-drains in the basement, towards permanent sumps serviced by an activated pump system. Sizing of the pumps is usually carried out when bulk excavation of complete.

13.6 Foundations

Foundations for new buildings should be uniformly supported on the underlying shale bedrock, to avoid the potential for the settlement of footings supported in the existing uncontrolled filling and differential movement between footings supported on materials with a substantially different stiffness.

The use of piled foundations will generally be required over much of the site, where existing filling depths are in excess of one metre. Suitable pile types could include bored piers or continuous flight auger (CFA), concrete or grout-injected piles. Temporary liners or casing may be required to support the filling in some areas, with pumps likely to be required to remove seepage into open pier holes, prior to concrete placement.

The preliminary design of piles founded within low strength shale may be based on a maximum allowable end bearing pressure of 1500 kPa, and a maximum allowable shaft adhesion of 100 kPa (within low strength shale).

Piles proportioned on the basis of the above parameters would experience total settlements of less than 1% of the diameter, with differential settlements between adjacent columns of less than half of this value.

13.7 Pavements

The CBR results obtained for the two samples of the natural clay soils from this site are indicative of a material that exhibits a considerable loss in strength when it becomes saturated. A design CBR value of 2% is considered suitable for the preliminary design of pavements supported on either the natural clay subgrade, or a subgrade comprising reworked site soils derived either from the natural clay or existing filling material.

The low CBR value indicated for the site clays is such that some form of lime stabilisation may be required to improve these materials.

Further, it will be critically important to incorporate adequate surface and subsoil drainage for all pavement areas, to reduce the potential for saturation of the subgrade materials.

14. CONCLUSIONS AND RECOMMENDATIONS

The scope of work for the current assessment comprised a site walkover inspection, review of site history and a limited soil sampling programme for contamination and geotechnical purposes.

A review of historical information indicated that the site covers four Lots which were historically vacant or used for residential purposes. Industrial or commercial activities on the site were not identified. The current registered proprietor is Housing Commission New South Wales.

The contamination assessment did not identify contamination by heavy metals, PAH, TPH, BTEX, Phenols, OCP and PCB in regards of the proposed redevelopment with respect to health risk based criteria for residential with minimal access to soil and for open space use.

The provisional phytotoxicity based investigation levels were exceeded for arsenic (TP4) and zinc (TP2). These minor exceedances of the PPIL may occur at other locations within the fill. It should be noted that the exceedance of the arsenic PPIL was at a depth below 0.5 m (0.7 – 1.4 m) which is usually considered to be below the root zone.

However, the results of the contamination assessment show that the site is compatible with the proposed residential use with the appropriate testing and management of soil in excess of the PPIL. This would require further testing of soil for use in landscaped areas.

A waste classification may be required for the off-site disposal of excavated soil. DP recommends future waste classification with reference to the *Waste Classification Guidelines*, April 2008, issued by the Department of Environment and Climate Change (DECC).

If filling is to be excavated in areas where basements are planned, depending on the final proposed design for the site, the excavated soil should be stockpiled to allow waste classification assessment to be conducted prior to removal.

Considering the limited site investigation and the restricted programme of subsurface sampling, screening and chemical testing which was set out in the proposal and although asbestos has not been detected in this study, DP recommends further soil assessment during earthworks specifically to assess for the presence of asbestos contaminants.

Stockpiled soil and excavation pits should be assessed and if asbestos-containing products are detected via observation or sampling and analysis, the affected soil has to be classified as Special Waste. Before removal a competent occupational hygienist has to assess whether the asbestos waste is bonded or friable. Removal and disposal of bonded asbestos must be undertaken by a contractor holding a bonded asbestos removal licence (AS2 licence). If the asbestos waste is considered friable a friable asbestos removal licence (AS1 licence) is required (WorkCover Guide, *Working with Asbestos* (2008)). Any asbestos removal works would also have to be conducted in a manner that is in compliance with the relevant requirements of WorkCover Guide, *Working with asbestos* (2008) and *Code of Practice for the Safe Removal of Asbestos*, National Occupational Health and Safety Commission, Canberra (2005). Footprints of asbestos-contaminated stockpiles should be validated by an Occupational Health & Safety Specialist.

If basement excavations are planned and asbestos-based waste is detected in the soil and is to be retained on site, a Remedial Action Plan (RAP) and an Asbestos Management Plan (AMP) should be prepared for the site.

Estimated costs of remedial and additional contamination works that may be necessary for the site are provided in Table 12, below.

Table 12 - Estimated Remediation and Additional Works Costs

Item	Estimated Cost
Waste Classification#	\$15,000 - \$25,000
Disposal of excavated soils (if required)*	\$50 - \$250/tonne
Asbestos Management Plan (if asbestos contaminated Soils retained on site)^	\$4,000 - \$6,000
Remedial Action Plan (if basements of deep excavations planned)	\$5,000 - \$8,000
Disposal of Asbestos Contaminated Soils as Special Waste (if required)*	\$200 - \$500/tonne

^ May include additional costs if material required to be imported to site for capping layer

* includes estimate of excavation, trucking and tipping costs only. For a more detailed assessment of the costs associated with disposal of asbestos contaminated soils should seek advice from a contractor with appropriate asbestos handling licenses. The actual cost would be dependant on contractor. Note if basements planned actual costs associated with remediation would only include that which would not normally be associated with excavation works

Dependent on volume of filling removed

Please note that the above estimates are “ball park” figures only and may not reflect the costs associated with remedial and management works and are dependent on the final proposed design for the site.

Groundwater quality has not been assessed. Given the low contamination levels in the soil, leaching of contaminants into a deeper groundwater system is unlikely. Groundwater should be assessed, however, the risk is considered to be low.

15. LIMITATIONS OF THIS REPORT

The scope of the site assessment activities and consulting services undertaken by DP were limited to those detailed in the proposal dated 13 August 2008 and accepted by Major Projects Directorate Department of Housing NSW, Sydney NSW 2000.

DP's assessment is necessarily based upon the result of a limited site investigation and the restricted programme of subsurface sampling, screening and chemical testing which was set out in the proposal.

DP cannot provide unqualified warranties with regards to site contamination nor does DP assume any liability for site conditions not observed or accessible during the time of the investigations.

Despite all reasonable care and diligence, the ground conditions encountered and concentrations of contaminants measured may not be representative of conditions between the locations sampled and investigated.

In addition, site characteristics may change over time due to activities such as spillages of contaminating substances. These changes may occur subsequent to DP's investigations and assessment.

This report, its associated documentation and the information herein have been prepared solely for the use of Major Projects Directorate Department of Housing NSW. Any reliance assumed by third parties on this report shall be at such parties' own risk.

DOUGLAS PARTNERS PTY LTD



Ulrike Krause
Senior Environmental Scientist


Reviewed by



Lindsay Rockett
Senior Associate




Mathew Mikhail
Geotechnical Engineer



Bruce McPherson
Principal

APPENDIX A

Site Drawings



Site Locality
Preliminary Geotechnical and Contamination Assessment
Kamira Court, Villawood NSW 2163

Project
45789

October
2008


Drawing
1

LEGEND

- Coordinate Grid (GDA94/MGA Zone 56)
- Approximate Site Boundary
- Rail Line

SOILS LEGEND

- ALLUVIAL RICHMOND SOILS LANDSCAPE
- ALLUVIAL SOUTH CREEK SOILS LANDSCAPE
- ALLUVIAL BERKSHIRE PARK SOILS LANDSCAPE
- RESIDUAL BLACKTOWN SOILS LANDSCAPE



Douglas Partners
Geotechnics . Environment . Groundwater

Sydney, Newcastle, Brisbane,
Melbourne, Perth, Darwin,
Wyang, Campbelltown, Canberra
Townsville, Cairns, Wollongong

TITLE: **SOILS MAP**
URBAN RENEWAL PROJECT
KAMIRA COURT
VILLAWOOD, NSW


CLIENT: HOUSING NSW	
DRAWN BY: ALT	PROJECT No: 45789.0
SCALE: 1:10,000	
OFFICE: SYDNEY	
APPROVED BY:	DATE: 1 OCTOBER 2008
DRAWING No: 2	

LEGEND

- Coordinate Grid (GDA94/MGA Zone 56)
- Approximate Site Boundary
- Rail Line

GEOLOGY LEGEND

- Quaternary Fluvial Sediment
Medium-grained sand, clay and silt
- Minchinbury Sandstone
Fine to medium-grained quartz-lithic sandstone
- Ashfield Shale
Dark-grey to black claystone-siltstone and fine sandstone -siltstone laminate
- Bringelly Shale
Shale, carbonaceous claystone, claystone, laminate, fine to medium-grained lithic sandstone, rare coal and tuff



NOTE: Geological mapping is extracted from 'Penrith 1:100,000 Geological Sheet', 1991, Geological Survey of NSW .




Sydney, Newcastle, Brisbane,
Melbourne, Perth, Darwin,
Wyong, Campbelltown, Canberra
Townsville, Cairns, Wollongong

Douglas Partners
Geotechnics . Environment . Groundwater

TITLE: **GEOLOGY MAP**
URBAN RENEWAL PROJECT
KAMIRA COURT
VILLAWOOD, NSW

CLIENT: HOUSING NSW		
DRAWN BY: ALT	SCALE: 1:10,000	PROJECT No: 45789.0
APPROVED BY:		DATE: 1 OCTOBER 2008
		DRAWING No: 3





Douglas Partners

Geotechnics . Environment . Groundwater

Sydney, Newcastle, Brisbane,
Melbourne, Perth, Darwin,
Wyang, Campbelltown, Canberra
Townsville, Cairns, Wollongong

TITLE:

SITE PLAN AND TEST PIT LOCATIONS

URBAN RENEWAL PROJECT

KAMIRA COURT

VILLAWOOD, NSW

CLIENT: HOUSING NSW

DRAWN BY: ALT

APPROVED BY:

PROJECT No: 45789.0


SCALE: 1:1000


DATE: 1 OCTOBER 2008


OFFICE: SYDNEY


DRAWING No: 4

LEGEND

Coordinate Grid (GDA94/MGA Zone 56)

Approximate Site Boundary

Test Pit Locations

Stockpile Location

APPENDIX B
Site Photographs



PHOTO 1: View on Lot 136 D.P. 16186 and Lot 39 D.P. 202006 in NW direction



PHOTO 2: View on Lot 38 D.P. 202006 in WNW direction



PHOTO 3: Eastern boundary of Lot 38 D.P. 202006, location of test pit TP 4



PHOTO 4: View on Lot 37 D.P. 202006 in W direction; Stockpile location



PHOTO 5: View on Lot 37 D.P. 202006 in NW direction

<p>Preliminary Geotechnical and Contamination Assessment Kamira Court, Villawood NSW 2163</p>	<p>Project 45789</p>	<p>October 2008</p>	<p>Plate 3</p>
---	--------------------------	-------------------------	--------------------



PHOTO 6: View on Lot 37 D.P. 202006 in NE direction, location of test pit TP 6



PHOTO 7: View on Lot 37 D.P. 202006 in N direction, location of test pit TP 7

APPENDIX C
Site History Information
Results of DNR Search

APPENDIX C
Site History Information



Aerial Photograph 1928
Preliminary Geotechnical and Contamination Assessment
Kamira Court, Villawood NSW 2163

Project
45789

October
2008

Plate
1




Aerial Photograph 1943
Preliminary Geotechnical and Contamination Assessment
Kamira Court, Villawood NSW 2163

Project
45789

October
2008

Plate
2



Aerial Photograph 1950
Preliminary Geotechnical and Contamination Assessment
Kamira Court, Villawood NSW 2163

Project
45789

October
2008

Plate
3



Aerial Photograph 1961
Preliminary Geotechnical and Contamination Assessment
Kamira Court, Villawood NSW 2163

Project
45789

October
2008

Plate
4



Aerial Photograph 1970
Preliminary Geotechnical and Contamination Assessment
Kamira Court, Villawood NSW 2163

Project
45789

October
2008

Plate
5



Aerial Photograph 1978
Preliminary Geotechnical and Contamination Assessment
Kamira Court, Villawood NSW 2163

Project
45789

October
2008

Plate
6



Aerial Photograph 1991
Preliminary Geotechnical and Contamination Assessment
Kamira Court, Villawood NSW 2163

Project
45789

October
2008

Plate
7



Douglas Partners
Geotechnics • Environment • Groundwater



Aerial Photograph 2007
Preliminary Geotechnical and Contamination Assessment
Kamira Court, Villawood NSW 2163

Project
45789

October
2008

Plate
8

Cadastral Records Enquiry Report

Ref : surv:scim-grollm

Locality : VILLAWOOD


Requested Parcel : Lot 37 DP 202006

Identified Parcel : Lot 37 DP 202006

LGA : FAIRFIELD

Parish : ST JOHN

County : CUMBERLAND



Cadastral Records, Subdivision of D.P. 16186 in 1929
Geotechnical and Contamination Report
Kamira Court, Villawood NSW 2163

Project
45789

October
2008

Plate
10

ACN: 093 398 611
ABN: 61 093 412 474

Peter S. Hopley Pty Limited
Legal Searchers

1 Boronia Avenue
Mount Annan , NSW , 2567
Mobile: 0412 199 304
Fax 9233 4590 (Attn Box 29)

SUMMARY AS TO OWNERS.

Property: - Kamira Avenue, Villawood

Description: Lot 136 D.P. 16186 and Lots 37, 38 & 39 D.P. 202006

As regards Lot 136 D.P. 16186

19.08.1915	William Charles Wadley Lippmann (<i>Bank Manager</i>)	Vol 2598 Fol 181
13.05.1918	John Symonds (<i>Engineer</i>)	Vol 2598 Fol 181
21.06.1928	John Symonds (<i>Engineer</i>) Thomas Kennedy (<i>Engineer</i>) Thomas Peters (<i>Contractor</i>)	Vol 3907 Fol's 190 to 192
19.06.1928	John Symonds (<i>Engineer</i>) Thomas Kennedy (<i>Engineer</i>) Leonard James Hooper (<i>Investor</i>) Edward Thomas Hooper (<i>Investor</i>)	Vol 3907 Fol 190, Vol 3907 Fol 191, Vol 4343 Fol 58 & Vol 4343 Fol 59
28.06.1929	John Symonds (<i>Engineer</i>) Thomas Kennedy (<i>Engineer</i>) Leonard James Hooper (<i>Investor</i>) Edward Thomas Hooper (<i>Investor</i>) Antoine William Mary D'Apice (<i>Solicitor</i>)	Vol 3907 Fol 190, Vol 3907 Fol 191, Vol 4343 Fol 58 & Vol 4343 Fol 59
06.01.1930	Ernest Morris (<i>Carpenter</i>)	Vol 4388 Fol 244
22.11.1944	Ernest Morris (<i>Carpenter</i>) Laura Morris (<i>Married Woman</i>)	Vol 4388 Fol 244
12.12.1961	Ernest Morris (<i>Carpenter</i>)	Vol 4388 Fol 244
03.10.1962	Ralph Edward Morris (<i>Supervisor</i>) (<i>We have not investigated the Section 94 Application</i>)	Vol 4388 Fol 244
06.09.1971	Sime Muskie (<i>Fitter and Turner</i>)	Vol 4388 Fol 244

ACN: 093 398 611
ABN: 61 093 412 474

Peter S. Hopley Pty Limited
Legal Searchers

1 Boronia Avenue
Mount Annan , NSW , 2567
Mobile: 0412 199 304
Fax 9233 4590 (Attn Box 29)

23.11.1973 # Housing Commission of New South Wales

136/16186

Current Registered Proprietor

As regards Lots 37, 38 & 39 D.P. 202006

15.10.1947 # Housing Commission of New South Wales

37/202006,
38/202006 &
39/202006

As regards the parcels marked as Lot numbers on the attached cadastre.

1952 # Housing Commission of New South Wales

37/202006,
38/202006 &
39/202006

As regards the parts marked as roads and lanes on the attached cadastre

Current Registered Proprietor

Cadastral Records Enquiry Report

Ref : surv.scim-grollm

Requested Parcel : Lot 37 DP 202006


Identified Parcel : Lot 37 DP 202006

Locality : VILLAWOOD

LGA : FAIRFIELD

Parish : ST JOHN

County : CUMBERLAND



Cadastral Records Enquiry Report

Requested Parcel : Lot 37 DP 202006

Identified Parcel : Lot 37 DP 202006

LGA : FAIRFIELD

Parish : ST JOHN

County : CUMBERLAND

Locality : VILLAWOOD

RIVER AVE

DP 1016382

AIRWAY

PT1
DP 200817

WOOD RD

KIRANG AVE

DP 13355

WATTLE AVE

KAMIRA AVE

DP 16186

(c) Copyright 2003 NSW Department of Lands. Map Projection: MGA Zone 56

Report Generated 8:18:49 PM, 10 September, 2008

This information is provided as a searching aid only. While every endeavour is made to ensure the current cadastral pattern is accurately reflected, the Registrar General cannot guarantee the information provided. For all ACTIVITY PRIOR to SEPT 2002 you must refer to the RGs Charting and Reference Maps.

SHEET 12

SOUTHERN RAILWAY

MAIN

VILLAWOOD

WATTLE AVE

KIRRRANG

AVENUE

AVENUE

ROAD

KOORINGAL

ROAD

DP
16186(E)
1999.

186	187	188	189	190	191	192	193	194	195	196	197	198	199	200
186	187	188	189	190	191	192	193	194	195	196	197	198	199	200
186	187	188	189	190	191	192	193	194	195	196	197	198	199	200
186	187	188	189	190	191	192	193	194	195	196	197	198	199	200
186	187	188	189	190	191	192	193	194	195	196	197	198	199	200

201	202	203	204	205	206	207	208	209	210	211	212	213	214	215	216	217	218	219	220
201	202	203	204	205	206	207	208	209	210	211	212	213	214	215	216	217	218	219	220
201	202	203	204	205	206	207	208	209	210	211	212	213	214	215	216	217	218	219	220
201	202	203	204	205	206	207	208	209	210	211	212	213	214	215	216	217	218	219	220
201	202	203	204	205	206	207	208	209	210	211	212	213	214	215	216	217	218	219	220

221	222	223	224	225	226	227	228	229	230	231	232	233	234	235	236	237	238	239	240
221	222	223	224	225	226	227	228	229	230	231	232	233	234	235	236	237	238	239	240
221	222	223	224	225	226	227	228	229	230	231	232	233	234	235	236	237	238	239	240
221	222	223	224	225	226	227	228	229	230	231	232	233	234	235	236	237	238	239	240
221	222	223	224	225	226	227	228	229	230	231	232	233	234	235	236	237	238	239	240

121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140
121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140
121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140
121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140
121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140

141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160
141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160
141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160
141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160
141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160

161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180
161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180
161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180
161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180
161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180

58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84
58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84
58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84
58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84
58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84

See Diagram N Sheet 2

SH 2/2 (E)

SHEET 2/2

Diagram

SOUTHERN


Width

DEP PLAN 16186(E)
29th July 1929

[Signature]

A

RAILWAY



PL 185 141 (2 ok 6) 22 2 29

SH 1/2

Municipality of Fairfield.

B 78514 (25 hrs) 22.2.29

PLAN

OF

VILLAWOOD ESTATE No 2

being a subdivision of part of the land comprised in Certs of Title Vol 3907 Fols 190 191 & 192

Parish of St John County of Cumberland


Scale 100ft to an Inch




DEP PLAN 16186(E)
29th July 1929.

WAT

D.V. 14169 1st 1/2





All Permanent Marks (P.M.) are concrete blocks.
 Restrictions and Covenants if any will be embodied
 in the Transfers of the Lots shown hereon.
 Any new Streets or Lanes shown on this plan
 are intended to be dedicated to the Public.
 It is intended to grant Right of Drainage along
 Drainage Easements to the Fairfield Council
 Corner splay and widenings of Streets shown
 hereon are intended to be dedicated to the Public

Date of Survey May 1928
 Datum line of Azimuth A.B. (See Sheet 2)


Two Sheets

DP 16186 SH 1/2 (E)

I John Alexander Harrison of 350 George St. Sydney Licensed Surveyor, specially licensed under the Real Property Act 1900, do hereby solemnly and sincerely declare (a) that all boundaries and measurements shown on this plan are correct, (b) that all survey marks found and relevant physical objects on or adjacent to the boundaries are correctly represented (c) that all physical objects indicated actually exist in the positions shown (d) that the whole of the material facts in relation to the survey are correctly represented (e) that the survey has been made under my immediate supervision and make this solemn declaration conscientiously believing the same to be true, and by virtue of the provisions of the Real Property Act 1900.

John Alexander Harrison
 Licensed Surveyor

Subscribed and declared before me at Sydney
 this 16th day of May A.D. 1928 *Edw. Houghton*




DP 16186 SH 1/2


This plan of subdivision has been approved by the Fairfield Council and is covered by Council Clerk's Certificate No. 179 of 29 January 1994. In witness whereof the Common Seal of the Council of Fairfield was affixed the 29 day of January in pursuance of a resolution of the Council passed on the 29 day of January 1994.

J. Kennedy
Mayor

Sydney Licensed Surveyor specially licensed under and sincerely declares that all boundaries and (b) that all survey marks found and relevant are correctly represented (c) that all physical shown (d) that the whole of the material facts in relation to the survey has been made under my immediate supervision and delivering the same to be true and by virtue of

J. Kennedy
Licensed Surveyor





Scale of Diagrams 50ft to an Inch


This plan of Subdivision has been approved by the Fairfield Council and is covered by Council Clerk's Certificate No 150 of 29 January 1929. In witness whereof the Common Seal of the Council was affixed the 29 day of January 1929 in pursuance of a Resolution of the Council passed on the 29th day of January 1929.

A. Bailey
Mayor

John Bailey
Town Clerk

DP 16186 SH 212 (E)

Sheet 2 of plan referred to in my Declaration dated 19/5/28
J. H. H. H.
Licensed Surveyor




FEET INCHES	METRES
2 0 1/2	0.51
2 1 5/8	0.62
2 1 1/4	0.65
2 9 1/4	0.845
2 9 1/2	0.85
2 3 3/4	0.96
2 1 3/2	1.025
2 1 1/2	1.063
2 5 3/4	1.423
2 7 5/4	1.72
2 9 5/4	1.755
2 1 1/4	1.835
2 6 3/4	1.93
2 6 3/4	2
2 6 3/4	2.005
2 9 1/2	2.07
2 1 5/4	2.16
2 1 5/4	2.18
2 2 3/4	2.235
2 6 1/4	2.29
2 6 1/2	2.3
2 7 7/8	2.355
2 8 3/4	2.415
2 8 3/4	2.45
2 8 3/4	2.47
2 1 1/2	2.505
2 10 6	3.05
2 7 3/4	3.2
2 3 5/8	3.25
2 3 7/8	3.76
2 5 1/8	4.575
2 5 1/4	4.705
2 5 3/4	4.82
2 1 1/2	4.985
2 1 1/2	5.15
2 1 1/2	5.185
2 1 1/4	5.25
2 1 1/4	5.285
2 1 1/2	5.35
2 5 3/8	5.935
2 0 1/8	6.095
2 0 3/8	6.105
2 0 3/4	6.115
2 0 2	6.145
2 0 1/4	6.185
2 0 3	6.17
2 0 5 1/4	6.23
2 0 9 3/4	6.345
2 1 4 1/4	6.355
2 1 10 3/4	6.425
2 1 11	6.705
2 5 1/2	6.865
2 2 1/4	7.065
2 2 1/2	7.075
2 3 5 1/2	7.15
2 3 7 1/4	7.195
2 4 1 1/4	7.315
2 4 5 1/2	7.455
2 4 5 5/8	7.46
2 5 3/4	7.62
2 5 2 3/4	7.69
2 5 10 1/2	7.855
2 6 1 1/4	7.825
2 6 8 3/4	8.39
2 7 9 1/4	8.465
2 7 11 1/4	8.51
2 8 0 3/4	8.555

FEET INCHES	METRES
32 6 1/4	9.91
33 3 1/2	10.06
33 10 1/4	10.145
34 10	10.615
34 3 3/4	10.79
36 4 3/4	11.095
39 11 1/4	12.175
40 3 3/4	12.585
41 4 3/4	12.615
44 11 1/4	13.595
50 5 3/4	13.985
52 5 1/4	15.245
55 2	16.765
56 2	17.12
57 5 1/4	17.505
57 10 1/4	17.635
64 1 3/4	18.85
65 -	19.81
66 -	20.115
66 2 1/2	20.39
66 10	20.57
67 10 1/4	20.595
71 5 3/4	21.65
72 4 3/4	22.58
73 4 3/4	23.375
76 7 1/2	23.355
77 4 1/2	23.485
85 4 3/4	24.03
88 11 1/4	27.11
89 -	27.125
94 0 1/4	28.655
94 0 1/2	28.665
96 9 3/4	29.51
99 0 1/4	30.15
105 0 1/2	32.025
106 9 3/4	32.355
108 3 3/4	33.025
108 7 3/4	33.355
109 1 1/2	33.55
112 4	34.24
115 5	35.05
115 9 3/4	35.3
116 1	35.38
116 2 1/2	35.42
117 -	35.66
118 9 3/4	36.215
122 1 3/4	37.23
123 4 1/2	37.505
124 5 1/4	37.93
125 -	38.1
125 3 3/4	38.235
125 5 1/4	38.355
125 7 1/4	38.525
126 1 1/2	38.645
126 8 1/2	38.775
126 9 3/4	38.85
126 11 1/2	38.955
127 2 3/4	39.78
127 4 1/2	39.835

FEET INCHES	METRES
127 6	38.86
127 7	38.865
127 7 1/2	38.9
127 8 3/4	38.93
127 9 1/4	38.945
127 11 3/4	39.015
128 9 3/4	39.25
128 10 1/4	39.275
130 0 1/4	39.63
131 3	40.005
132 1 3/4	40.2
132 5 3/4	40.3
133 8 1/4	40.73
134 -	40.845
134 11	41.25
135 3	41.255
136 1 3/4	41.455
137 4 1/2	41.67
138 7 1/4	42.215
139 5	42.57
142 3 3/4	43.7
147 4 1/2	45.11
157 4 1/2	47.06
220 0 1/4	67.06
220 5 1/4	67.19
220 9 3/4	67.3
221 5 1/4	67.49
222 5 1/2	67.81
223 5 1/2	68.11
223 10	68.22
223 9 3/4	68.297
1131 3	344.8


AC RD P 50 P
- 9 227.6
- 9 1/4 234
- 9 1/2 240.3
- 9 3/4 246.6
- 10 1/4 252.9
- 10 1/2 259.3
- 11 265.6
- 11 1/4 272.2
- 15 1/4 308.7
- 16 1/4 311
- 17 320
- 21 3/4 425.3
- 23 1/2 445

ST (66' wide)



KOONOONA (66' wide) AVE

Diagram C



DP 16186 SH 2/2 (E)

MAIN

VILLAWOOD

PRATTEN (66' wide) Rd

LANE

KAMIRA (66' wide) AVE

uneven Width

SOL

Dia

SH 2/2

B78514125649 22.2.29


B78514125649 22.2.29

FEET INCHES	METRES
0 1/4	0.1
0 1/2	0.25
0 3/4	0.375
1 0	1.0
1 1/4	1.25
1 1/2	1.5
1 3/4	1.75
2 0	2.0
2 1/4	2.25
2 1/2	2.5
2 3/4	2.75
3 0	3.0
3 1/4	3.25
3 1/2	3.5
3 3/4	3.75
4 0	4.0
4 1/4	4.25
4 1/2	4.5
4 3/4	4.75
5 0	5.0
5 1/4	5.25
5 1/2	5.5
5 3/4	5.75
6 0	6.0
6 1/4	6.25
6 1/2	6.5
6 3/4	6.75
7 0	7.0
7 1/4	7.25
7 1/2	7.5
7 3/4	7.75
8 0	8.0
8 1/4	8.25
8 1/2	8.5
8 3/4	8.75
9 0	9.0
9 1/4	9.25
9 1/2	9.5
9 3/4	9.75
10 0	10.0
10 1/4	10.25
10 1/2	10.5
10 3/4	10.75
11 0	11.0
11 1/4	11.25
11 1/2	11.5
11 3/4	11.75
12 0	12.0
12 1/4	12.25
12 1/2	12.5
12 3/4	12.75
13 0	13.0
13 1/4	13.25
13 1/2	13.5
13 3/4	13.75
14 0	14.0
14 1/4	14.25
14 1/2	14.5
14 3/4	14.75
15 0	15.0
15 1/4	15.25
15 1/2	15.5
15 3/4	15.75
16 0	16.0
16 1/4	16.25
16 1/2	16.5
16 3/4	16.75
17 0	17.0
17 1/4	17.25
17 1/2	17.5
17 3/4	17.75
18 0	18.0
18 1/4	18.25
18 1/2	18.5
18 3/4	18.75
19 0	19.0
19 1/4	19.25
19 1/2	19.5
19 3/4	19.75
20 0	20.0
20 1/4	20.25
20 1/2	20.5
20 3/4	20.75
21 0	21.0
21 1/4	21.25
21 1/2	21.5
21 3/4	21.75
22 0	22.0
22 1/4	22.25
22 1/2	22.5
22 3/4	22.75
23 0	23.0
23 1/4	23.25
23 1/2	23.5
23 3/4	23.75
24 0	24.0
24 1/4	24.25
24 1/2	24.5
24 3/4	24.75
25 0	25.0
25 1/4	25.25
25 1/2	25.5
25 3/4	25.75
26 0	26.0
26 1/4	26.25
26 1/2	26.5
26 3/4	26.75
27 0	27.0
27 1/4	27.25
27 1/2	27.5
27 3/4	27.75
28 0	28.0
28 1/4	28.25
28 1/2	28.5
28 3/4	28.75
29 0	29.0
29 1/4	29.25
29 1/2	29.5
29 3/4	29.75
30 0	30.0
30 1/4	30.25
30 1/2	30.5
30 3/4	30.75
31 0	31.0
31 1/4	31.25
31 1/2	31.5
31 3/4	31.75
32 0	32.0
32 1/4	32.25
32 1/2	32.5
32 3/4	32.75
33 0	33.0
33 1/4	33.25
33 1/2	33.5
33 3/4	33.75
34 0	34.0
34 1/4	34.25
34 1/2	34.5
34 3/4	34.75
35 0	35.0
35 1/4	35.25
35 1/2	35.5
35 3/4	35.75
36 0	36.0
36 1/4	36.25
36 1/2	36.5
36 3/4	36.75
37 0	37.0
37 1/4	37.25
37 1/2	37.5
37 3/4	37.75
38 0	38.0
38 1/4	38.25
38 1/2	38.5
38 3/4	38.75
39 0	39.0
39 1/4	39.25
39 1/2	39.5
39 3/4	39.75
40 0	40.0
40 1/4	40.25
40 1/2	40.5
40 3/4	40.75
41 0	41.0
41 1/4	41.25
41 1/2	41.5
41 3/4	41.75
42 0	42.0
42 1/4	42.25
42 1/2	42.5
42 3/4	42.75
43 0	43.0
43 1/4	43.25
43 1/2	43.5
43 3/4	43.75
44 0	44.0
44 1/4	44.25
44 1/2	44.5
44 3/4	44.75
45 0	45.0
45 1/4	45.25
45 1/2	45.5
45 3/4	45.75
46 0	46.0
46 1/4	46.25
46 1/2	46.5
46 3/4	46.75
47 0	47.0
47 1/4	47.25
47 1/2	47.5
47 3/4	47.75
48 0	48.0
48 1/4	48.25
48 1/2	48.5
48 3/4	48.75
49 0	49.0
49 1/4	49.25
49 1/2	49.5
49 3/4	49.75
50 0	50.0
50 1/4	50.25
50 1/2	50.5
50 3/4	50.75
51 0	51.0
51 1/4	51.25
51 1/2	51.5
51 3/4	51.75
52 0	52.0
52 1/4	52.25
52 1/2	52.5
52 3/4	52.75
53 0	53.0
53 1/4	53.25
53 1/2	53.5
53 3/4	53.75
54 0	54.0
54 1/4	54.25
54 1/2	54.5
54 3/4	54.75
55 0	55.0
55 1/4	55.25
55 1/2	55.5
55 3/4	55.75
56 0	56.0
56 1/4	56.25
56 1/2	56.5
56 3/4	56.75
57 0	57.0
57 1/4	57.25
57 1/2	57.5
57 3/4	57.75
58 0	58.0
58 1/4	58.25
58 1/2	58.5
58 3/4	58.75
59 0	59.0
59 1/4	59.25
59 1/2	59.5
59 3/4	59.75
60 0	60.0
60 1/4	60.25
60 1/2	60.5
60 3/4	60.75
61 0	61.0
61 1/4	61.25
61 1/2	61.5
61 3/4	61.75
62 0	62.0
62 1/4	62.25
62 1/2	62.5
62 3/4	62.75
63 0	63.0
63 1/4	63.25
63 1/2	63.5
63 3/4	63.75
64 0	64.0
64 1/4	64.25
64 1/2	64.5
64 3/4	64.75
65 0	65.0
65 1/4	65.25
65 1/2	65.5
65 3/4	65.75
66 0	66.0
66 1/4	66.25
66 1/2	66.5
66 3/4	66.75
67 0	67.0
67 1/4	67.25
67 1/2	67.5
67 3/4	67.75
68 0	68.0
68 1/4	68.25
68 1/2	68.5
68 3/4	68.75
69 0	69.0
69 1/4	69.25
69 1/2	69.5
69 3/4	69.75
70 0	70.0
70 1/4	70.25
70 1/2	70.5
70 3/4	70.75
71 0	71.0
71 1/4	71.25
71 1/2	71.5
71 3/4	71.75
72 0	72.0
72 1/4	72.25
72 1/2	72.5
72 3/4	72.75
73 0	73.0
73 1/4	73.25
73 1/2	73.5
73 3/4	73.75
74 0	74.0
74 1/4	74.25
74 1/2	74.5
74 3/4	74.75
75 0	75.0
75 1/4	75.25
75 1/2	75.5
75 3/4	75.75
76 0	76.0
76 1/4	76.25
76 1/2	76.5
76 3/4	76.75
77 0	77.0
77 1/4	77.25
77 1/2	77.5
77 3/4	77.75
78 0	78.0
78 1/4	78.25
78 1/2	78.5
78 3/4	78.75
79 0	79.0
79 1/4	79.25
79 1/2	79.5
79 3/4	79.75
80 0	80.0
80 1/4	80.25
80 1/2	80.5
80 3/4	80.75
81 0	81.0
81 1/4	81.25
81 1/2	81.5
81 3/4	81.75
82 0	82.0
82 1/4	82.25
82 1/2	82.5
82 3/4	82.75
83 0	83.0
83 1/4	83.25
83 1/2	83.5
83 3/4	83.75
84 0	84.0
84 1/4	84.25
84 1/2	84.5
84 3/4	84.75
85 0	85.0
85 1/4	85.25
85 1/2	85.5
85 3/4	85.75
86 0	86.0
86 1/4	86.25
86 1/2	86.5
86 3/4	86.75
87 0	87.0
87 1/4	87.25
87 1/2	87.5
87 3/4	87.75
88 0	88.0
88 1/4	88.25
88 1/2	88.5
88 3/4	88.75
89 0	89.0
89 1/4	89.25
89 1/2	89.5
89 3/4	89.75
90 0	90.0
90 1/4	90.25
90 1/2	90.5
90 3/4	90.75
91 0	91.0
91 1/4	91.25
91 1/2	91.5
91 3/4	91.75
92 0	92.0
92 1/4	92.25
92 1/2	92.5
92 3/4	92.75
93 0	93.0
93 1/4	93.25
93 1/2	93.5
93 3/4	93.75
94 0	94.0
94 1/4	94.25
94 1/2	94.5
94 3/4	94.75
95 0	95.0
95 1/4	95.25
95 1/2	95.5
95 3/4	95.75
96 0	96.0
96 1/4	96.25
96 1/2	96.5
96 3/4	96.75
97 0	97.0
97 1/4	97.25
97 1/2	97.5
97 3/4	97.75
98 0	98.0
98 1/4	98.25
98 1/2	98.5
98 3/4	98.75
99 0	99.0
99 1/4	99.25
99 1/2	99.5
99 3/4	99.75
100 0	100.0
100 1/4	100.25
100 1/2	100.5
100 3/4	100.75

FEET INCHES	METRES
11 3/4	11.875
12 0	12.0
12 1/4	12.25
12 1/2	12.5
12 3/4	12.75
13 0	13.0
13 1/4	13.25
13 1/2	13.5
13 3/4	13.75
14 0	14.0
14 1/4	14.25
14 1/2	14.5
14 3/4	14.75
15 0	15.0
15 1/4	15.25
15 1/2	15.5
15 3/4	15.75
16 0	16.0
16 1/4	16.25
16 1/2	16.5
16 3/4	16.75
17 0	17.0
17 1/4	17.25
17 1/2	17.5
17 3/4	17.75
18 0	18.0
18 1/4	18.25
18 1/2	18.5
18 3/4	18.75
19 0	19.0
19 1/4	19.25
19 1/2	19.5
19 3/4	19.75
20 0	20.0
20 1/4	20.25
20 1/2	20.5
20 3/4	20.75
21 0	21.0
21 1/4	21.25
21 1/2	21.5
21 3/4	21.75
22 0	22.0
22 1/4	22.25
22 1/2	22.5
22 3/4	22.75
23 0	23.0
23 1/4	23.25
23 1/2	23.5
23 3/4	23.75
24 0	24.0
24 1/4	24.25
24 1/2	24.5
24 3/4	24.75
25 0	25.0
25 1/4	25.25
25 1/2	25.5
25 3/4	25.75
26 0	26.0
26 1/4	26.25
26 1/2	26.5
26 3/4	26.75
27 0	27.0
27 1/4	27.25
27 1/2	27.5
27 3/4	27.75
28 0	28.0
28 1/4	28.25
28 1/2	28.5
28 3/4	28.75
29 0	29.0
29 1/4	29.25
29 1/2	29.5
29 3/4	29.75
30 0	30.0
30 1/4	30.25
30 1/2	30.5
30 3/4	30.75
31 0	31.0
31 1/4	31.25
31 1/2	31.5
31 3/4	31.75
32 0	32.0

FEET INCHES	METRES
0 1/2	0.013
0 3/4	0.019
1 0	0.025
1 1/4	0.032
1 1/2	0.038
1 3/4	0.044
2 0	0.051
2 1/4	0.057
2 1/2	0.064
2 3/4	0.070
3 0	0.076
3 1/4	0.083
3 1/2	0.089
3 3/4	0.095
4 0	0.102
4 1/4	0.108
4 1/2	0.114
4 3/4	0.121
5 0	0.127
5 1/4	0.134
5 1/2	0.140
5 3/4	0.146
6 0	0.152
6 1/4	0.159
6 1/2	0.165
6 3/4	0.171
7 0	0.178
7 1/4	0.184
7 1/2	0.190
7 3/4	0.197
8 0	0.203
8 1/4	0.210
8 1/2	0.216
8 3/4	0.222
9 0	0.228
9 1/4	0.235
9 1/2	0.241
9 3/4	0.247
10 0	0.254
10 1/4	0.260
10 1/2	0.266
10 3/4	0.272
11 0	0.279
11 1/4	0.285
11 1/2	0.291
11 3/4	0.298
12 0	0.305
12 1/4	0.311
12 1/2	0.317
12 3/4	0.323
13 0	0.330
13 1/4	0.336
13 1/2	0.342
13 3/4	0.348
14 0	0.354
14 1/4	0.360
14 1/2	0.366
14 3/4	0.372
15 0	0.378
15 1/4	0.385
15 1/2	0.391
15 3/4	0.397
16 0	0.403
16 1/4	0.409
16 1/2	0.415
16 3/4	0.421
17 0	0.427
17 1/4	0.433
17 1/2	0.439
17 3/4	0.445
18 0	0.451
18 1/4	0.457
18 1/2	0.463
18 3/4	0.469
19 0	0.475
19 1/4	0.481
19 1/2	0.487
19 3/4	0.493
20 0	0.500
20 1/4	0.506
20 1/2	0.512
20 3/4	0.518
21 0	0.524
21 1/4	0.530
21 1/2	0.536
21 3/4	0.542
22 0	0.548
22 1/4	0.554
22 1/2	0.560
22 3/4	0.566
23 0	0.572
23 1/4	0.578
23 1/2	0.584
23 3/4	0.590
24 0	0.596
24 1/4	0.602
24 1/2	0.608
24 3/4	0.614
25 0	0.620
25 1/4	0.626
25 1/2	0.632
25 3/4	0.638
26 0	0.644
26 1/4	0.650
26 1/2	0.656
26 3/4	0.662
27 0	0.668
27 1/4	0.674
27 1/2	0.680
27 3/4	0.686
28 0	0.692
28 1/4	0.698
28 1/2	0.704
28 3/4	0.710
29 0	0.716
29 1/4	0.722
29 1/2	0.728
29 3/4	0.734
30 0	0.740
30 1/4	0.746
30 1/2	0.752
30 3/4	0.758
31 0	0.764
31 1/4	0.770
31 1/2	0.776
31 3/4	0.782
32 0	0.788
32 1/4	0.794
32 1/2	0.800
32 3/4	0.806
33 0	0.812
33 1/4	0.818
33 1/2	0.824
33 3/4	0.830
34 0	0.836
34 1/4	0.842
34 1/2	0.848
34 3/4	0.854
35 0	0.860
35 1/4	0.866
35 1/2	0.872
35 3/4	0.878
36 0	0.884
36 1/4	0.890
36 1/2	0.896
36 3/4	0.902
37 0	0.908
37 1/4	0.914
37 1/2	0.920
37 3/4	0.926
38 0	0.932
38 1/4	0.938
38 1/2	0.944
38 3/4	0.950
39 0	0.956
39 1/4	0.962
39 1/2	0.968
39 3/4	0.974
40 0	0.980
40 1/4	0.986
40 1/2	0.992
40 3/4	0.998
41 0	1.004
41 1/4	1.010
41 1/2	1.016
41 3/4	1.022
42 0	1.028
42 1/4	1.034
42 1/2	1.040
42 3/4	1.046
43 0	1.052
43 1/4	1.058
43 1/2	1.064
43 3/4	1.070
44 0	1.076
44 1/4	1.082
44 1/2	1.088
44 3/4	1.094
45 0	1.100
45 1/4	1.106
45 1/2	1.112
45 3/4	1.118
46 0	1.124
46 1/4	1.130
46 1/2	1.136
46 3/4	1.142
47 0	1.148
47 1/4	1.154
47 1/2	1.160
47 3/4	1.166
48 0	1.172
48 1/4	1.178
48 1/2	1.184
48 3/4	1.190
49 0	1.196
49 1/4	1.202
49 1/2	1.208
49 3/4	1.214
50 0	1.220
50 1/4	1.226
50 1/2	1.232
50 3/4	1.238
51 0	1.244
51 1/4	1.250
51 1/2	1.256
51 3/4	1.262
52 0	1.268
52 1/4	1.274
52 1/2	1.280
52 3/4	1.286
53 0	1.292
53 1/4	1.298
53 1/2	1.304
53 3/4	1.310
54 0	1.316
54 1/4	1.322
54 1/2	1.328
54 3/4	1.334
55 0	1.340
55 1/4	1.346
55 1/2	1.352
55 3/4	1.358
56 0	1.364
56 1/4	1.370
56 1/2	1.376
56 3/4	1.382
57 0	1.388
57 1/4	1.394
57 1/2	1.400
57 3/4	1.406
58 0	1.412
58 1/4	1.418
58 1/2	1.424
58 3/4	1.430
59 0	1.436
59 1/4	1.442
59 1/2	1.448
59 3/4	1.454
60 0	1.460

AC RD PA	50 M
- 30 1/2	771.4
- 2 32 1/4	2859
AC RD PA	HA
- 2 27 1/4	1.1



Ref 2199

1. Bruce Richard Davies, Registrar General for New South Wales, certify that this regulation is in accordance with the provisions of the Land Management Act, 1977.

IN REGISTER GENERAL'S OFFICE.

LegalStream Australia Pty Ltd

ABN: 80 002 801 498
Level 15, 115 Pitt Street, SYDNEY NSW 2000, AUSTRALIA * DX654, SYDNEY
Tel: (02) 9231 0122 Fax: (02) 9233 6411 www.legalstream.com.au

An Approved
LPI NSW
Information Broker

LAND AND PROPERTY INFORMATION NEW SOUTH WALES - TITLE SEARCH

FOLIO: 136/16186

SEARCH DATE	TIME	EDITION NO	DATE
21/9/2008	11:42 AM	-	-

VOL 4388 FOL 244 IS THE CURRENT CERTIFICATE OF TITLE

LAND

LOT 136 IN DEPOSITED PLAN 16186
LOCAL GOVERNMENT AREA FAIRFIELD
PARISH OF ST JOHN COUNTY OF CUMBERLAND
TITLE DIAGRAM DP16186

FIRST SCHEDULE

THE HOUSING COMMISSION OF NEW SOUTH WALES (T N603245)

SECOND SCHEDULE (2 NOTIFICATIONS)

- 1 RESERVATIONS AND CONDITIONS IN THE CROWN GRANT(S)
- 2 B930826 COVENANT

NOTATIONS

UNREGISTERED DEALINGS: NIL

*** END OF SEARCH ***

krause

PRINTED ON 21/9/2008

LegalStream Australia Pty Ltd

ABN: 80 002 801 498
Level 15, 115 Pitt Street, SYDNEY NSW 2000, AUSTRALIA * DX654, SYDNEY
Tel: (02) 9231 0122 Fax: (02) 9233 6411 www.legalstream.com.au

An Approved
LPI NSW
Information Broker

LAND AND PROPERTY INFORMATION NEW SOUTH WALES - TITLE SEARCH

FOLIO: 37/202006

SEARCH DATE	TIME	EDITION NO	DATE
21/9/2008	11:42 AM	-	-

VOL 9186 FOL 85 IS THE CURRENT CERTIFICATE OF TITLE

LAND

LOT 37 IN DEPOSITED PLAN 202006
AT VILLAWOOD
LOCAL GOVERNMENT AREA FAIRFIELD
PARISH OF ST JOHN COUNTY OF CUMBERLAND
TITLE DIAGRAM DP202006

FIRST SCHEDULE

THE HOUSING COMMISSION OF NEW SOUTH WALES

SECOND SCHEDULE (1 NOTIFICATION)

1 J662786 EASEMENT FOR DRAINAGE AFFECTING THE SITE OF PROPOSED
DRAINAGE EASEMENT 6 FEET WIDE IN DP202006

NOTATIONS

UNREGISTERED DEALINGS: NIL

*** END OF SEARCH ***

krause

PRINTED ON 21/9/2008

LegalStream Australia Pty Ltd

ABN: 80 002 801 498
Level 15, 115 Pitt Street, SYDNEY NSW 2000, AUSTRALIA * DX654, SYDNEY
Tel: (02) 9231 0122 Fax: (02) 9233 6411 www.legalstream.com.au

An Approved
LPI NSW
Information Broker

LAND AND PROPERTY INFORMATION NEW SOUTH WALES - TITLE SEARCH

FOLIO: 38/202006

SEARCH DATE	TIME	EDITION NO	DATE
21/9/2008	11:42 AM	-	-

VOL 9186 FOL 86 IS THE CURRENT CERTIFICATE OF TITLE

LAND

LOT 38 IN DEPOSITED PLAN 202006
AT VILLAWOOD
LOCAL GOVERNMENT AREA FAIRFIELD
PARISH OF ST JOHN COUNTY OF CUMBERLAND
TITLE DIAGRAM DP202006

FIRST SCHEDULE

THE HOUSING COMMISSION OF NEW SOUTH WALES

SECOND SCHEDULE (0 NOTIFICATIONS)

NIL

NOTATIONS

UNREGISTERED DEALINGS: NIL

*** END OF SEARCH ***

krause

PRINTED ON 21/9/2008

LegalStream Australia Pty Ltd

ABN: 80 002 801 498
Level 15, 115 Pitt Street, SYDNEY NSW 2000, AUSTRALIA * DX654, SYDNEY
Tel: (02) 9231 0122 Fax: (02) 9233 6411 www.legalstream.com.au

An Approved
LPI NSW
Information Broker

LAND AND PROPERTY INFORMATION NEW SOUTH WALES - TITLE SEARCH

FOLIO: 39/202006

SEARCH DATE	TIME	EDITION NO	DATE
21/9/2008	11:42 AM	-	-

VOL 9186 FOL 87 IS THE CURRENT CERTIFICATE OF TITLE

LAND

LOT 39 IN DEPOSITED PLAN 202006
AT VILLAWOOD
LOCAL GOVERNMENT AREA FAIRFIELD
PARISH OF ST JOHN COUNTY OF CUMBERLAND
TITLE DIAGRAM DP202006

FIRST SCHEDULE

THE HOUSING COMMISSION OF NEW SOUTH WALES

SECOND SCHEDULE (0 NOTIFICATIONS)

NIL


NOTATIONS

UNREGISTERED DEALINGS: NIL

*** END OF SEARCH ***

krause

PRINTED ON 21/9/2008



Our Ref: D08/092963
Your Ref: Ulrike Krause

17 September 2008

Attention: Mr Krause
Douglas Partners
PO Box 472
West Ryde DC NSW 1685

Dear Mr Krause

RE SITE: Lot 37-39 DP202006, Lot 136 DP16186 Villawood NSW 2163.

I refer to your search request of 15th September 2008 requesting information on licences to Keep Dangerous Goods for the above site.

A search of the Stored Chemical Information Database (SCID) and the microfiche records held by WorkCover has not located any records pertaining to the above-mentioned premises.

If you have any further queries, please contact Dangerous Goods Licensing staff on (02) 4321 5500.

Brent Jones
Senior LICencing Officer
Dangerous Goods

WorkCover. Watching out for you.

WorkCover NSW ABN 77 682 742 966 92-100 Donnison Street Gosford NSW 2250 Locked Bag 2906 Lisarow NSW 2252
Telephone 02 4321 5000 Facsimile 02 4325 4145 WorkCover Assistance Service **13 10 50**
DX 731 Sydney Website www.workcover.nsw.gov.au

18 September 2008

Douglas Partners
PO Box 472
WEST RYDE NSW 2114

Dear Sir/ Madam

Following is your planning certificate as requested. Should you have any further queries please contact Council's Environmental Standards Department on (02) 9725 0848.


PLANNING CERTIFICATE

(under section 149 of the Environmental Planning and Assessment Act 1979 as amended)

Applicant:	Douglas Partners
Certificate No.:	2880
Applicant's Reference:	ULRIKE KRAUSE
Issue Date:	18 September 2008
Receipt No.:	109921

PROPERTY ADDRESS:	2 Kamira Avenue VILLAWOOD
LEGAL DESCRIPTION:	Lot: 37 DP: 202006

for
Alan Young
City Manager
Fairfield City Council



PLEASE NOTE: This is page 1 of 10. Should this certificate or any subsequent copy not contain this many pages, please confirm with council prior to acting on the basis of information contained in this certificate.

**Information provided under
Section 149(2) of the Environmental Planning and Assessment Act 1979**

Notes:

- (1) The following prescribed matters may apply to the land to which this certificate relates.
 - (2) Where this certificate refers to a specific allotment (or allotments) within a strata plan, the certificate is issued for the whole of the land within the strata plan, not just the specific allotment(s) referred to, and any information contained in the certificate may relate to the whole, or any part, of the strata plan.
 - (3) The following information is provided pursuant to Section 149(2) of the Environmental Planning and Assessment Act 1979 as prescribed by Schedule 4 of the Environmental Planning and Assessment Regulation 2000 and is applicable as at the date of this certificate.
 - (4) Information provided in this certificate should be interpreted in conjunction with the relevant plans, policies and documents held at Council. In order to obtain copies of these documents you may purchase them by either contacting Council's Environmental Standards Department on (02) 9725 0848 or attending Council's Administration Centre at 86 Avoca Road, Wakeley.
-

1. Names of relevant State Environmental Planning Policies (SEPPs), Regional Environmental Plans (REPs), Local Environmental Plans (LEPs) and Development Control Plans (DCPs)

- (a) Names of the relevant Local Environmental Plans (LEPs) and amendments that apply to the land.

**Fairfield Local Environmental Plan 1994.
Government Gazette No.104.
12th August 1994.
As Amended.**

- (b) Whether a Draft Local Environmental Plan as exhibited under Section 66(1)(b) of the Act applies to the land.

Council has resolved to prepare a draft Local Environmental Plan (DLEP) affecting the land, pursuant to Section 66 1(b) of the Environmental Planning & Assessment Act (E.P. & A.), 1979. (See attached Draft L.E.P. list.)

- (c) Each development control plan applying to the land that has been made by the relevant planning authority under Division 6 of Part 3 of the Act (including any made by the council under section 72, or the Director-General under section 51A, before the repeal of those sections).

**The land is subject to Draft & adopted Development Control Plans.
(See attached schedule).**

- (d) Names of Regional Environmental Plans and Draft REPs applying to the land.

The following Regional Environmental Plans apply:

Sydney Regional Environmental Plan No.9 - Extractive Industries

The Greater Metropolitan Regional Environmental Plan No. 2 - Georges River Catchment (GMREP 2)

The following Draft Regional Environmental Plans apply:

No Draft Regional Environmental Plans apply

- (e) Names of State Environmental Planning Policies and Draft SEPPs applying to the land.

The following State Environmental Planning Policies apply:

State Environmental Planning Policy (Housing for Seniors or People with a Disability) 2004

State Environmental Planning Policy No. 33 - Hazardous and Offensive Development

State Environmental Planning Policy - Major Projects - 2005.

State Environmental Planning Policy No. 37 - Continued Mines and Extractive Industries

State Environmental Planning Policy No. 45 - Permissibility of Mining

State Environmental Planning Policy No. 50 - Canal Estates

State Environmental Planning Policy No. 10 - Retention of Low-Cost Rental Accommodation

State Environmental Planning Policy No. 55 - Remediation of Land

State Environmental Planning Policy No. 64 - Advertising and Signage

State Environmental Planning Policy No. 4 - Development Without Consent and Miscellaneous Exempt and Complying Development

State Environmental Planning Policy No. 65 - Design Quality of Residential Flat Development

State Environmental Planning Policy No. 19 - Bushland In Urban Areas

State Environmental Planning Policy No. 32 - Urban Consolidation (Redevelopment of Urban Land).

State Environmental Planning Policy (Infrastructure) 2007

The following Draft State Environmental Planning Policies apply:
Draft State Environmental Planning Policy - Subdivision

2. Zoning and land use under relevant LEPs

For each local environmental plan, deemed environmental planning instrument and draft local environmental planning instrument applying to the land that includes the land in any zone (however described):

(a) What is the identity of the zone?

Residential B

(b) What is permitted without development consent?

Nil.

(c) What is permitted only with development consent?

Any purpose other than a purpose included in item (b) or (d).

(d) What is prohibited?

Abattoirs, advertisements, agriculture, amusement centres, amusement parks, animal establishments, brothels, bulky goods salesrooms or showrooms, business premises, camping grounds and caravan parks, carparks other than those provided by the Council, communication facilities, entertainment facilities, extractive industry, forestry, gaming taverns, generating works, hazardous industry, hazardous storage establishments, helicopter landing sites, heliports, hotels, industry, institutions, intensive agriculture, junkyards, light industry, medical centres, mines, motels, motor showrooms, offensive industry, offensive storage establishments, plant hire, plant nurseries, recreation facilities, refreshment rooms, roadside stalls, rural industry, sawmills, service stations, shops, stock and sales yards, transport depots, transport terminals, vehicle body repair workshops, vehicle repair stations, veterinary hospitals, warehouses.

(e) Whether any development standards applying to the land fix minimum land dimensions for the erection of a dwelling house on the land and, if so, the minimum land dimensions so fixed.

Under Fairfield LEP 1994, there are no minimum or maximum land dimension requirements relating to the permissibility of dwelling houses in the zone. However, Council will have regard to the merits of land dimensions and Guidelines for Residential Development (DCP 1/97) when considering development proposals for a dwelling house on the land.

- (f) Whether the land includes or comprises critical habitat.

No

- (g) Whether the land is in a conservation area (however described).

No

- (h) Whether an item of environmental heritage (however described) is situated on the land.

No

Attention is drawn however to Clause 31 of Fairfield LEP 1994: "When determining an application for consent to carry out development on land in the vicinity of a heritage item, the Council must take into consideration the likely effect of the proposed development on the heritage significance of that heritage item and on its setting."

3. (Repealed)

(This section is deliberately left blank)

4. Coastal Protection

Whether or not the land is affected by the operation of section 38 or 39 of the *Coastal Protection Act 1979*, but only to the extent that the council has been notified by the Department of Public Works.

No, this land is not affected.

5. Mine Subsidence

Whether or not the land is proclaimed to be a mine subsidence district within the meaning of section 15 of the *Mine Subsidence Compensation Act 1961*.

No, this land is not affected.

6. Road widening and road realignment

Whether or not the land is affected by any road widening or road realignment under Division 2 or Part 3 of the *Roads Act* 1993, any environmental planning instrument, or any resolution of the council.

The land is not affected by any road widening proposal under Division 2 of Part 3 of the Roads Act, any Environmental Planning Instrument or any resolution of the Council.

7. Council and other public authority policies on hazard risk restrictions

Whether or not the land is affected by a policy:

- (a) adopted by the council, or
- (b) adopted by any other public authority and notified to the council for the express purpose of its adoption by that authority being referred to in planning certificates issued by the council,

that restricts the development of the land because of the likelihood of land slip, bushfire, tidal inundation, subsidence, acid sulphate soils or any other risk.

Council's policies on hazard risk restrictions are as follows:

(i) Landslip

The land is not affected by a policy adopted by Council or adopted by any other public authority and notified to Council (for the express purpose of its adoption by that authority being referred to in Planning Certificates issued by Council) that restricts development on the land because of the likelihood of land slip or subsidence.

(ii) Bushfire

Council has been supplied by the NSW Rural Fire Service with a hazard map for the purposes of a bush fire risk management plan applying to land within the Fairfield local government area. Based on that map, it appears the land referred to in this certificate is not bush fire prone as defined in section 4 of the Environmental Planning and Assessment Act, 1979.

(iii) Tidal Inundation

The land is not affected by a policy adopted by Council or adopted by any other public authority and notified to Council (for the express purpose of

its adoption by that authority being referred to in Planning Certificates issued by Council) that restricts development on the land because of the likelihood of tidal inundation.

(iv) Subsidence

No, the land is not so affected

(v) Acid Sulphate Soils

The land is not affected by a policy adopted by Council or adopted by any other public authority and notified to Council (for the express purpose of its adoption by that authority being referred to in Planning Certificates issued by Council) that restricts development on the land because of the likelihood of acid sulfate soils or any other risk.

(vi) Any other risks

No, the land is not so affected

7A. Flood related development controls information

Whether or not development on that land or part of the land for the purposes of dwelling houses, dual occupancies, multi dwelling housing or residential flat buildings (not including development for the purposes of group homes or seniors housing) is subject to flood related development controls.

Part or all of this land is within the floodplain and may be affected by local overland flooding. This parcel is not in an area in which Council's current programme of overland flood risk mapping has been completed. . The term local overland flooding means inundation by local runoff rather than overbank discharge from a stream, river, estuary, lake or dam.

Whether or not development on that land or part of the land for any other purpose is subject to flood related development controls.

Part or all of this land is within the floodplain and may be affected by local overland flooding. This parcel is not in an area in which Council's current programme of overland flood risk mapping has been completed. . The term local overland flooding means inundation by local runoff rather than overbank discharge from a stream, river, estuary, lake or dam.

Note:

- (1) Words and expressions in this clause have the same meanings as in the instrument set out in the Schedule to the Standard Instrument (Local Environmental Plans) Order 2006.

8. Land reserved for acquisition

Whether or not any environmental planning instrument, deemed environmental planning instrument or draft environmental planning instrument applying to the land provides for the acquisition of the land by a public authority, as referred to in section 27 of the Act.

The land is not reserved for acquisition.

9. Contributions plans

The name of each contributions plan applying to the land.

Fairfield City Council Section 94 Developer Contributions Plan No. 1999 applies to all land within the City of Fairfield.

Fairfield City Council Section 94A Levy Development Contributions Plan 2007 applies to all land within the City of Fairfield.

10. Matters arising under the Contaminated Land Management Act 1997

Section 59(2) of the *Contaminated Land Management Act 1997* prescribes the following additional matters that are to be specified in a planning certificate:

- (a) that the land to which the certificate relates is within land declared to be an "investigation area" or "remediation site" under Part 3 of that Act (if it is within such an area or site at the date when the certificate is issued),
- (b) that the land to which the certificate relates is subject to an "investigation order" or a "remediation order" within the meaning of that Act (if it is subject to such an order at the date when the certificate is issued),
- (c) that the land to which the certificate relates is the subject of a voluntary investigation proposal (or voluntary remediation proposal) the subject of the Environment Protection Authority's agreement under section 19 or 26 of that Act (if it is the subject of such a proposal, and the proposal has been not been fully carried out, at the date when the certificate is issued).
- (d) that the land to which the certificate relates is the subject of a site audit statement within the meaning of Part 4 of that Act (if copy of such a statement has been provided at any time to the local authority issuing the certificate).

Council has adopted by resolution a policy (commencing 1 August 2000), on contaminated land which may restrict the development of land. This policy is implemented when zoning or land use changes are proposed on lands which have previously been used for certain purposes. Consideration of Council's adopted policy and the application of provisions under the State Legislation is warranted.

The land is not within an investigation area or remediation site under Part 3 of the Contaminated Land Management Act 1997.

The land is not subject to an investigation order or a remediation order within the meaning of the Contaminated Land Management Act 1997.

The land is not subject to a voluntary investigation proposal (or voluntary remediation proposal) that is the subject of the Environment Protection Authority's agreement under Section 19 or 26 of the Contaminated Land Management Act 1997.

The land is not subject of a site audit statement within the meaning of the Contaminated Land Management Act 1997.

11. Bush fire prone land

Whether all, or part, of the land is bush fire prone land (as defined in the Environmental Planning and Assessment Act 1979).

Council has been supplied by the NSW Rural Fire Service with a hazard map for the purposes of a bush fire risk management plan applying to land within the Fairfield local government area. Based on that map, it appears the land referred to in this certificate is not bush fire prone as defined in section 4 of the Environmental Planning and Assessment Act , 1979.

12. Property vegetation plans

Whether or not the land is land to which a property vegetation plan under the Native Vegetation Act 2003 applies (but only if the council has been notified of the existence of the plan by the person or body that approved the plan under the Act).

Council has not been informed of any such plan that affects this land.

13. Order under Trees (Disputes between Neighbours) Act 2006

Whether an order has been made under the Trees (Disputes between Neighbours) Act 2006 to carry out work in relation to a tree on the land (but only if the council has been notified of the order).

No

14. Directions under Part 3A

If there is a direction by the Minister in force under section 75P (2) (c1) of the Act that a provision of an environmental planning instrument prohibiting or restricting the carrying out of a project or a stage of a project on the land under Part 4 of the Act does not have effect, a statement to that effect identifying the provision that does not have effect.

No such direction applies to the land.

15. Site compatibility certificates and conditions for seniors housing

If the land is land to which State Environmental Planning Policy (Housing for Seniors or People with a Disability) 2004 applies:

- (a) a statement of whether there is a current site compatibility certificate (of which the council is aware), issued under clause 25 of that Policy in respect of proposed development on the land and, if there is a certificate, the statement is to include:
 - (i) the period for which the certificate is current, and
 - (ii) that a copy may be obtained from the head office of the Department of Planning, and

No such certificate applies to the land.

- (b) a statement setting out any terms of a kind referred to in clause 18 (2) of that Policy that have been imposed as a condition of consent to a development application granted after 11 October 2007 in respect of the land.

No such terms apply to the land.

16. Site compatibility certificates for infrastructure

A statement of whether there is a valid site compatibility certificate (of which the council is aware), issued under clause 19 of State Environmental Planning Policy (Infrastructure) 2007 in respect of proposed development on the land and, if there is a certificate, the statement is to include:

- (a) the period for which the certificate is valid, and
- (b) that a copy may be obtained from the head office of the Department of Planning.

No such certificate applies to the land.

Fairfield City Council

Draft LEP Register

(Exhibited Draft Plans or Draft Plans on Exhibition)
as at 18 June 2008

DRAFT LEP NO.	PURPOSE	LOCATION
47	Rezone part of site from 6(a) Existing & Proposed Recreation to 4(a) General Industrial	10-16 Robert Street, Smithfield (lots 1-4, DP499648)
82	Clarify certain requirements in relation to heritage items and include an additional property as a heritage item	All heritage listed items in Fairfield City. Property at 112 Cumberland St (lot 1, DP771455) – include as a heritage item
84	Permit the additional use of mixed use development comprising professional office suites on the ground floor level of Residential flat buildings.	Street block bounded by Hughes and Hill Streets, Park and Mcburney Roads, Cabramatta
96	Permit business premises, car parking and shops (provided subject site is amalgamated with adjoining parcel at 154 The Boulevard, Fairfield Heights.	181 Station Street, Fairfield Heights (Lot P, DP 383407)
102	To: * rezone properties bounded by Nelson Street Lane as Business 3(a1) – Sub-Regional Business Centre – Retail/Commercial which will not permit residential development * amend the existing Business 3(a) – Sub Regional Business Centre – Mixed Use and amending the objectives of this zone so they reflect the objectives in the Strategic Plan for the Fairfield Town Centre * prohibit Strata subdivision of new building stock or future redevelopments	Applies to the Fairfield Town Centre which is the area currently zoned Business 3(a) – Sub Regional Business Centre.
106	To establish site-specific development standards and principles that promote the orderly development of the Sunnybrook Hotel site, and to rezone part of the land to which this plan applies to 2(b)	Sunnybrook Hotel, cnr of Hume Highway and Liverpool Street, Cabramatta, being lot 1, DP 583848, lot 2, DP 617315 and lot 10, DP 748219
112	Adjust references within the Local Environmental Plan that refer to Development Control Plans that will become obsolete, or required updated referencing, for when the new City-Wide Development Control Plan comes into effect. This LEP is prepared in accordance with Section 73A of the Environmental Planning and Assessment Act 1979.	Applies to all land in the City of Fairfield.
122	To: * Reclassify part of Adams Reserve from 'Community' to 'Operational' land to	* Reclassification applies to Part of No. 243 Sackville Street, Canley Vale (Adams Reserve) being part of Lot D, DP 35362

	<p>permit construction of the Canley Vale Link Road and sale of part of the reserve (No. 65-67 Canley Vale Road, Canley Vale being Lots A and B, DP 35362)</p> <p>* Rezone part of Adams Reserve from Recreation 6(a) to Business 3(c) to permit a multi-storey commercial/residential development with Council consent under the Canley Corridor Development Control Plan No. 37</p>	<p>* Rezoning applies to No. 65-67 Canley Vale Road, Canley Vale being Lots A and B, DP 35362)</p>
--	---	--






















DEVELOPMENT CONTROL PLANS - As at 9 April 2008 (*Note: Some "In Force" Development Control Plans may be under review, check with Council for date of last amendment)

TITLE	STATUS*	DATE APPLIES FROM
GENERAL		
Fairfield City-Wide Development Control Plan 2006	In Force	July 2006
Fairfield City-Wide Development Control Plan 2006 - Amendment 1 (Chapter 5 – Single Dwelling)	Adopted August 2006	Effective September 2006
Fairfield City-Wide Development Control Plan 2006 - Amendment 2 (Chapter 6 – Multi-Unit Housing)	Adopted November 2006	Effective December 2006
Fairfield City-Wide Development Control Plan 2006 - Amendment 3 (Subdivision and other anomalies)	Adopted November 2006	Effective December 2006
Fairfield City-Wide Development Control Plan 2006 - Amendment 4 (Anomalies found in Chapter 10 - Miscellaneous Development)	Adopted March 2007	Effective April 2007
Fairfield City-Wide Development Control Plan 2006 - Amendment 5 (Child Care Centres and Subdivision)	Adopted March 2007	Effective April 2007
Exempt and Complying Development (No.29)	In Force	Oct 1999
Development Standards Relating to Public Roads (No.32)	In Force	Dec 1999
SITE SPECIFIC		
Fairfield Town Centre (2006)	In Force	Dec 2006
Cabramatta Town Centre (5/2000)	In Force	Aug-2000
Canley Corridor DCP No. 37 – Canley Vale and Canley Heights Local Town Centres - Amendment No. 1: Development controls for Master Plan Site No. 2, Adams Reserve, Canley Vale Road, Canley Vale - Amendment No. 2: Development controls for Master Plan Site No. 4, 45-47 Peel St, Canley Heights	In Force Adopted September 2006 Adopted 11 March 2008	March 2006 Not Effective – Can only take effect following gazettal of an amendment to Fairfield LEP 1994, which will rezone the land to permit the development Effective 9 April 2008
Fairfield Heights Town Centre (10/94)	In Force	October 1994
Bonnyrigg Town Centre (28)	In Force	May 2004
PROPOSED AMENDMENTS TO DCPs		
Site Specific (Sunnybrook Hotel)	Not to commence until gazettal of LEP 106.	To be advised











APPENDIX D
Test Pit Report Results & Notes Relating to this Report

GRAPHIC SYMBOLS FOR SOIL & ROCK




SOIL

	BITUMINOUS CONCRETE
	CONCRETE
	TOPSOIL
	FILLING
	PEAT
	CLAY
	SILTY CLAY
	SANDY CLAY
	GRAVELLY CLAY
	SHALY CLAY
	SILT
	CLAYEY SILT
	SANDY SILT
	SAND
	CLAYEY SAND
	SILTY SAND
	GRAVEL
	SANDY GRAVEL
	CLAYEY GRAVEL
	COBBLES/BOULDERS
	TALUS





SEDIMENTARY ROCK

	BOULDER CONGLOMERATE
	CONGLOMERATE
	CONGLOMERATIC SANDSTONE
	SANDSTONE FINE GRAINED
	SANDSTONE COARSE GRAINED
	SILTSTONE
	LAMINITE
	MUDSTONE, CLAYSTONE, SHALE
	COAL
	LIMESTONE

METAMORPHIC ROCK

	SLATE, PHYLITTE, SCHIST
	GNEISS
	QUARTZITE

IGNEOUS ROCK

	GRANITE
	DOLERITE, BASALT
	TUFF
	PORPHYRY



TEST PIT LOG

CLIENT: Housing NSW
PROJECT: Urban Renewal Project
LOCATION: Kamira Court, Villawood

SURFACE LEVEL: 24.4 AHD
EASTING: 312639.5
NORTHING: 6249038.1
DIP/AZIMUTH: 90°/--

PIT No: 1
PROJECT No: 45789
DATE: 17 Sep 08
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing			Water	Dynamic Penetrometer Test (blows per mm)			
				Type	Depth	Sample		5	10	15	20
	0.1	TOPSOIL - brown silty clay topsoil, with a trace of gravel and rootlets. M<Wp			0.15						
		FILLING - brown mottled red brown, silty clay filling with some building rubble, brick, glass fragments, M~Wp		E	0.4						
	0.4	SILTY CLAY - stiff to very stiff, light grey and red brown, silty clay with a trace of ironstone gravel. M~Wp		B	0.5						
				E	0.7						
	1			D	1.0						
		- grading to light grey, mottled red brown at 1.3m			1.5						
					1.8						
	1.9	SHALE - very low to low strength, grey shale with some ironstaining									
	2.4	Pit discontinued at 2.4m - refusal									

RIG: Backhoe - 600mm bucket

LOGGED: Mikhail

WATER OBSERVATIONS: No free groundwater observed

☐ Sand Penetrometer AS1289.6.3.3

REMARKS: E = Environmental sample. M = Moisture content; Wp = Plastic limit

☐ Cone Penetrometer AS1289.6.3.2

SAMPLING & IN SITU TESTING LEGEND			
A	Auger sample	pp	Pocket penetrometer (kPa)
D	Disturbed sample	PID	Photo ionisation detector
B	Bulk sample	S	Standard penetration test
U	Tube sample (x mm dia.)	PL	Point load strength Is(50) MPa
W	Water sample	V	Shear Vane (kPa)
C	Core drilling	Δ	Water seep
		≡	Water level

CHECKED
Initials: <i>BTM</i>
Date: <i>15/10/08</i>



Douglas Partners
Geotechnics · Environment · Groundwater

TEST PIT LOG

CLIENT: Housing NSW
PROJECT: Urban Renewal Project
LOCATION: Kamira Court, Villawood

SURFACE LEVEL: 24.7 AHD
EASTING: 312646
NORTHING: 6249022.3
DIP/AZIMUTH: 90°/-

PIT No: 2
PROJECT No: 45789
DATE: 17 Sep 08
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing				Water	Dynamic Penetrometer Test (blows per mm)			
				Type	Depth	Sample	Results & Comments		5	10	15	20
	0.1	TOPSOIL - brown silty sand topsoil, with a trace of rootlets, humid, fibre-cement fragments			0.1		PID<1ppm					
	0.4	FILLING - brown sandy filling, with some clay and gravel and building rubble (bricks, glass, ceramic fragments), humid		E	0.4		PID<1ppm					
		SILTY CLAY - hard, light grey and red brown, silty clay with a trace of ironstone gravel. M<Wp - some 20mm diameter tree roots at 0.5m		E	0.5		pp>400kPa					
					0.8		pp>400kPa					
				U ₅₀	0.9							
					1.15							
	1.2	SHALE - very low strength, grey shale with some ironstaining										
		- grading to low strength at 2.0m										
	2.3	Pit discontinued at 2.3m - refusal										

RIG: Backhoe - 600mm bucket

LOGGED: Mikhail

WATER OBSERVATIONS: No free groundwater observed

REMARKS: E = Environmental sample. M = Moisture content; Wp = Plastic limit

☐ Sand Penetrometer AS1289.6.3.3
☐ Cone Penetrometer AS1289.6.3.2

SAMPLING & IN SITU TESTING LEGEND			
A	Auger sample	pp	Pocket penetrometer (kPa)
D	Disturbed sample	PID	Photo ionisation detector
B	Bulk sample	S	Standard penetration test
U	Tube sample (x mm dia.)	PL	Point load strength Is(50) MPa
W	Water sample	V	Shear Vane (kPa)
C	Core drilling	D	Water seep
			Water level

CHECKED	
Initials:	BJM
Date:	16/10/08






Douglas Partners
Geotechnics • Environment • Groundwater

TEST PIT LOG

CLIENT: Housing NSW
PROJECT: Urban Renewal Project
LOCATION: Kamira Court, Villawood

SURFACE LEVEL: 24.1 AHD
EASTING: 312672.9
NORTHING: 6249004.9
DIP/AZIMUTH: 90°/-

PIT No: 3
PROJECT No: 45789
DATE: 17 Sep 08
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing				Water	Dynamic Penetrometer Test (blows per mm)			
				Type	Depth	Sample	Results & Comments		5	10	15	20
24.1	0.1	TOPSOIL - brown silty sand topsoil, with a trace of rootlets, humid		E	0.1		PID<1ppm pp=250kPa PID<1ppm					
	0.25	FILLING - brown silty clay filling with some gravel, M<Wp, brick, timber, ash			0.2							
		SILTY CLAY - very stiff to hard, light grey and red brown, silty clay with a trace of ironstone gravel, M~Wp		B	0.5		pp>400kPa					
				U ₅₀ E								
	0.8	SILTY CLAY - hard, light grey mottled red brown, silty clay with a trace of ironstone gravel, M<Wp			0.85							
				D	1.0		pp>400kPa	1				
					1.5		pp>400kPa					
	1.6	SHALE - very low strength, grey shale with some ironstaining										
		- grading to very low to low strength at 2.8m										
24.1	3.0	Pit discontinued at 3.0m - target depth reached										

RIG: Backhoe - 600mm bucket

LOGGED: Mikhail

WATER OBSERVATIONS: No free groundwater observed

☐ Sand Penetrometer AS1289.6.3.3

REMARKS: E = Environmental sample. M = Moisture content; Wp = Plastic limit

☐ Cone Penetrometer AS1289.6.3.2

SAMPLING & IN SITU TESTING LEGEND			
A	Auger sample	pp	Pocket penetrometer (kPa)
D	Disturbed sample	PID	Photo ionisation detector
B	Bulk sample	S	Standard penetration test
U	Tube sample (x mm dia.)	PL	Point load strength Is(50) MPa
W	Water sample	V	Shear Vane (kPa)
C	Core drilling	▷	Water seep
		≡	Water level

CHECKED	
Initials:	BJM
Date:	16/10/08



Douglas Partners
Geotechnics • Environment • Groundwater

TEST PIT LOG

CLIENT: Housing NSW
PROJECT: Urban Renewal Project
LOCATION: Kamira Court, Villawood

SURFACE LEVEL: 23.8 AHD
EASTING: 312707.6
NORTHING: 6248986.6
DIP/AZIMUTH: 90°/-

PIT No: 4
PROJECT No: 45789
DATE: 17 Sep 08
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing				Water	Dynamic Penetrometer Test (blows per mm)			
				Type	Depth	Sample	Results & Comments		5	10	15	20
23	0.1	TOPSOIL - brown silty clay filling, with some sand and a trace of rootlets, M<Wp										
		FILLING - brown and grey, silty clay filling with some gravel and crushed shale, M<Wp										
		- some brick fragments at 0.7m			0.7		PID<1ppm					
	1.0	FILLING - light grey and red brown, silty clay filling with a trace of ironstone gravel and building rubble, M~Wpm, appears moderately compacted		D	1.0		pp=200kPa	1				
22		- metal pipe at 1.4m		E	1.4		PID<1ppm					
21		- tiles, brick, sandstone and shale fragments at 2.0m		E	2.0		pp=250kPa	2				
20												
19												
	3.0				3.0		pp=150kPa	3				
	3.5				3.5		pp=200kPa					
	3.9	SHALE - very low to low strength, grey shale with some ironstaining		D	4.0			4				
	4.2	Pit discontinued at 4.2m - refusal										

RIG: Backhoe - 600mm bucket

LOGGED: Mikhail

WATER OBSERVATIONS: No free groundwater observed

REMARKS: E = Environmental sample. M = Moisture content; Wp = Plastic limit

☐ Sand Penetrometer AS1289.6.3.3

☐ Cone Penetrometer AS1289.6.3.2

SAMPLING & IN SITU TESTING LEGEND			
A	Auger sample	pp	Pocket penetrometer (kPa)
D	Disturbed sample	PID	Photo ionisation detector
B	Bulk sample	S	Standard penetration test
U	Tube sample (x mm dia.)	PL	Point load strength Is(50) MPa
W	Water sample	V	Shear Vane (kPa)
C	Core drilling	D	Water seep
		W	Water level

CHECKED	
Initials:	BJM
Date:	16/10/08




Douglas Partners
Geotechnics • Environment • Groundwater

TEST PIT LOG

CLIENT: Housing NSW
PROJECT: Urban Renewal Project
LOCATION: Kamira Court, Villawood

SURFACE LEVEL: 23.1 AHD
EASTING: 312703.8
NORTHING: 6249044.5
DIP/AZIMUTH: 90°/--

PIT No: 5
PROJECT No: 45789
DATE: 17 Sep 08
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing				Water	Dynamic Penetrometer Test (blows per mm)				
				Type	Depth	Sample	Results & Comments		5	10	15	20	
23	0.2	FILLING - brown silty clay filling, with some gravel and crushed shale and building rubble, M<Wp			0.0		PID<1ppm						
				E									
						0.5		PID<1ppm					
1													
22													

RIG: Backhoe - 600mm bucket

LOGGED: Mikhail

WATER OBSERVATIONS: No free groundwater observed

☐ Sand Penetrometer AS1289.6.3.3

REMARKS: E = Environmental sample. M = Moisture content; Wp = Plastic limit

☐ Cone Penetrometer AS1289.6.3.2

SAMPLING & IN SITU TESTING LEGEND			
A	Auger sample	pp	Pocket penetrometer (kPa)
D	Disturbed sample	PID	Photo ionisation detector
B	Bulk sample	S	Standard penetration test
U _i	Tube sample (x mm dia.)	PL	Point load strength is (50) MPa
W	Water sample	V	Shear Vane (kPa)
C	Core drilling	▷	Water seep
		≡	Water level

CHECKED
Initials: BTM
Date: 16/10/08



Douglas Partners
Geotechnics • Environment • Groundwater

TEST PIT LOG

CLIENT: Housing NSW
PROJECT: Urban Renewal Project
LOCATION: Kamira Court, Villawood

SURFACE LEVEL: 21.7 AHD
EASTING: 312715.09
NORTHING: 6249095.44
DIP/AZIMUTH: 90°/-

PIT No: 6
PROJECT No: 45789
DATE: 17 Sep 08
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing				Water	Dynamic Penetrometer Test (blows per mm)			
				Type	Depth	Sample	Results & Comments		5	10	15	20
		FILLING - brown and grey, silty clay filling with some gravel and crushed shale, M<Wp			0.0		PID<1ppm					
		- timber		E								
				D	0.5		PID<1ppm pp=150kPa					
				E								
				D	1.0		PP=100kPa					
					2.0		pp=150-200kPa					
		- tiles, fibre-cement fragments between 2.3-3.2m			2.7		PID<1ppm					
		- some metal fragments at 3.0m		E	3.0		pp=100kPa					
					3.2							
		- timber and metal fragments at 3.8m			4.0		pp=100-150kPa					
	4.3	SHALE - very low to low strength, grey shale with some ironstaining										
	4.5	Pit discontinued at 4.5m - refusal										

RIG: Backhoe - 600mm bucket

LOGGED: Mikhail

WATER OBSERVATIONS: No free groundwater observed

☐ Sand Penetrometer AS1289.6.3.3

REMARKS: E = Environmental sample. M = Moisture content; Wp = Plastic limit

☐ Cone Penetrometer AS1289.6.3.2

SAMPLING & IN SITU TESTING LEGEND			
A	Auger sample	pp	Pocket penetrometer (kPa)
D	Disturbed sample	PID	Photo ionisation detector
B	Bulk sample	S	Standard penetration test
U	Tube sample (x mm dia.)	PL	Point load strength Is(50) MPa
W	Water sample	V	Shear Vane (kPa)
C	Core drilling	▷	Water seep
		≡	Water level

CHECKED
Initials: <i>BTM</i>
Date: <i>16/10/08</i>



Douglas Partners
Geotechnics • Environment • Groundwater

TEST PIT LOG

CLIENT: Housing NSW
PROJECT: Urban Renewal Project
LOCATION: Kamira Court, Villawood

SURFACE LEVEL: 22.8 AHD
EASTING: 312681.6
NORTHING: 6249095.4
DIP/AZIMUTH: 90°/---

PIT No: 7
PROJECT No: 45789
DATE: 17 Sep 08
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing				Water	Dynamic Penetrometer Test (blows per mm)			
				Type	Depth	Sample	Results & Comments		5	10	15	20
		FILLING - brown and grey, silty clay filling with some gravel and crushed shale fragments, M<Wp			0.05		PID<1ppm					
				E	0.3		PID<1ppm					
				D	0.5		pp=200kPa					
		- some metal fragments in filling at 0.8m										
				D	1.0		pp=150-200kPa	1				
		- styrofoam at 1.4m										
				D	1.5		pp=150-200kPa					
		- grading to slightly shaly at 1.89m										
				D	2.0		pp=200kPa	2				
		- metal fragments, concrete, tiles at 2.0m										
				D	2.5		pp=100kPa					
				D	3.0		pp=100kPa	3				
		- fibre-cement fragments and tiles at 3.2-3.3m										
					3.2		PID<1ppm					
		- some wood fragments at 3.4m										
				E								
					3.9							
		- perched groundwater observed at 4.2m										
		- grading to M>Wp at 4.6m										
					4.8		PID<1ppm					
				E								
					5.0							
	4.9	SHALE - very low to low strength, grey shale with some ironstaining										
	5.0											

Pit discontinued at 5.0m - refusal

RIG: Backhoe - 600mm bucket

LOGGED: Mikhail

WATER OBSERVATIONS: Groundwater seepage observed at 4.6m (very minor)

☐ Sand Penetrometer AS1289.6.3.3

REMARKS: E = Environmental sample. M = Moisture content; Wp = Plastic limit

☐ Cone Penetrometer AS1289.6.3.2

SAMPLING & IN SITU TESTING LEGEND			
A	Auger sample	pp	Pocket penetrometer (kPa)
D	Disturbed sample	PID	Photo ionisation detector
B	Bulk sample	S	Standard penetration test
U	Tube sample (x mm dia.)	PL	Point load strength Is(50) MPa
W	Water sample	V	Shear Vane (kPa)
C	Core drilling	Δ	Water seep
		□	Water level

CHECKED
Initials: BTM
Date: 16/10/08



Douglas Partners
Geotechnics • Environment • Groundwater

TEST PIT LOG

CLIENT: Housing NSW
PROJECT: Urban Renewal Project
LOCATION: Kamira Court, Villawood

SURFACE LEVEL: 24.0 AHD
EASTING: 312628.6
NORTHING: 6249105.4
DIP/AZIMUTH: 90°/-

PIT No: 8
PROJECT No: 45789
DATE: 17 Sep 08
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing				Water	Dynamic Penetrometer Test (blows per mm)			
				Type	Depth	Sample	Results & Comments		5	10	15	20
24	0.1	TOPSOIL - brown silty clay filling, with a trace of rootlets, M<Wp		E	0.1		PID<1ppm					
		FILLING - brown and grey, silty clay filling with some gravel and building rubble (brick and glass fragments, fibre-cement products), concrete, tiles, M<Wp		E								
	0.8	SILTY CLAY - very stiff, light grey and red brown, silty clay with a trace of ironstone gravel, M<Wp		E	0.8		(2 samples) pp=300kPa PID<1ppm					
				U ₅₀								
23	1.0			D	1.0		pp=300kPa	1				
				B								
	1.2	SHALE - very low strength, grey shale with some ironstaining			1.2							
		- grading to very low to low strength at 1.4m										
22	1.9	Pit discontinued at 1.9m - refusal						2				
21	3											
20	4											

RIG: Backhoe - 600mm bucket

LOGGED: Mikhail

WATER OBSERVATIONS: No free groundwater observed

☐ Sand Penetrometer AS1289.6.3.3

REMARKS: E = Environmental sample. M = Moisture content; Wp = Plastic limit

☐ Cone Penetrometer AS1289.6.3.2

SAMPLING & IN SITU TESTING LEGEND			
A	Auger sample	pp	Pocket penetrometer (kPa)
D	Disturbed sample	PID	Photo ionisation detector
B	Bulk sample	S	Standard penetration test
U	Tube sample (x mm dia.)	PL	Point load strength Is(50) MPa
W	Water sample	V	Shear Vane (kPa)
C	Core drilling	Δ	Water seep
		≡	Water level

CHECKED	
Initials:	BIM
Date:	16/10/08




Douglas Partners
Geotechnics • Environment • Groundwater

TEST PIT LOG

CLIENT: Housing NSW
PROJECT: Urban Renewal Project
LOCATION: Kamira Court, Villawood

SURFACE LEVEL: --
EASTING:
NORTHING:
DIP/AZIMUTH: 90°/--

PIT No: Stockpile
PROJECT No: 45789
DATE: 17 Sep 08
SHEET 1 OF 1

RL	Depth (m)	Description of Strata	Graphic Log	Sampling & In Situ Testing				Water	Dynamic Penetrometer Test (blows per mm)			
				Type	Depth	Sample	Results & Comments		5	10	15	20
	0.1	FILLING - brown and yellow brown, silty clay and sand filling with some building rubble (brick, concrete, metal fragments), humid Pit discontinued at 0.1m		E	0.0		Stockpile					
	-1											
	-2											
	-3											
	-4											

RIG: Backhoe - 600mm bucket

LOGGED: Mikhail

WATER OBSERVATIONS: No free groundwater observed

☐ Sand Penetrometer AS1289.6.3.3

REMARKS: E = Environmental sample
One stockpile is located on Lot 37 DP 202006

☐ Cone Penetrometer AS1289.6.3.2

SAMPLING & IN SITU TESTING LEGEND			
A	Auger sample	pp	Pocket penetrometer (kPa)
D	Disturbed sample	PID	Photo ionisation detector
B	Bulk sample	S	Standard penetration test
U	Tube sample (x mm dia.)	PL	Point load strength Is(50) MPa
W	Water sample	V	Shear Vane (kPa)
C	Core drilling	Δ	Water seep * Water level

CHECKED	
Initials:	BTM
Date:	16/10/08



Douglas Partners
Geotechnics • Environment • Groundwater

NOTES RELATING TO THIS REPORT

Introduction

These notes have been provided to amplify the geotechnical report in regard to classification methods, specialist field procedures and certain matters relating to the Discussion and Comments section. Not all, of course, are necessarily relevant to all reports.

Geotechnical reports are based on information gained from limited subsurface test boring and sampling, supplemented by knowledge of local geology and experience. For this reason, they must be regarded as interpretive rather than factual documents, limited to some extent by the scope of information on which they rely.

Description and Classification Methods

The methods of description and classification of soils and rocks used in this report are based on Australian Standard 1726, Geotechnical Site Investigations Code. In general, descriptions cover the following properties - strength or density, colour, structure, soil or rock type and inclusions.

Soil types are described according to the predominating particle size, qualified by the grading of other particles present (eg. sandy clay) on the following bases:

Soil Classification	Particle Size
Clay	less than 0.002 mm
Silt	0.002 to 0.06 mm
Sand	0.06 to 2.00 mm
Gravel	2.00 to 60.00 mm

Cohesive soils are classified on the basis of strength either by laboratory testing or engineering examination. The strength terms are defined as follows.

Classification	Undrained Shear Strength kPa
Very soft	less than 12
Soft	12—25
Firm	25—50
Stiff	50—100
Very stiff	100—200
Hard	Greater than 200

Non-cohesive soils are classified on the basis of relative density, generally from the results of standard penetration tests (SPT) or Dutch cone penetrometer tests (CPT) as below:

Relative Density	SPT "N" Value (blows/300 mm)	CPT Cone Value (q_c — MPa)
Very loose	less than 5	less than 2
Loose	5—10	2—5
Medium dense	10—30	5—15
Dense	30—50	15—25
Very dense	greater than 50	greater than 25

Rock types are classified by their geological names. Where relevant, further information regarding rock classification is given on the following sheet.

Sampling

Sampling is carried out during drilling to allow engineering examination (and laboratory testing where required) of the soil or rock.

Disturbed samples taken during drilling provide information on colour, type, inclusions and, depending upon the degree of disturbance, some information on strength and structure.

Undisturbed samples are taken by pushing a thin-walled sample tube into the soil and withdrawing with a sample of the soil in a relatively undisturbed state. Such samples yield information on structure and strength, and are necessary for laboratory determination of shear strength and compressibility. Undisturbed sampling is generally effective only in cohesive soils.

Details of the type and method of sampling are given in the report.

Drilling Methods.

The following is a brief summary of drilling methods currently adopted by the Company and some comments on their use and application.

Test Pits — these are excavated with a backhoe or a tracked excavator, allowing close examination of the in-situ soils if it is safe to descent into the pit. The depth of penetration is limited to about 3 m for a backhoe and up to 6 m for an excavator. A potential disadvantage is the disturbance caused by the excavation.

Large Diameter Auger (eg. Pengo) — the hole is advanced by a rotating plate or short spiral auger, generally 300 mm or larger in diameter. The cuttings are returned to the surface at intervals (generally of not more than 0.5 m) and are disturbed but usually unchanged in moisture content. Identification of soil strata is generally much more reliable than with continuous spiral flight augers, and is usually supplemented by occasional undisturbed tube sampling.

Continuous Sample Drilling — the hole is advanced by pushing a 100 mm diameter socket into the ground and withdrawing it at intervals to extrude the sample. This is the most reliable method of drilling in soils, since moisture content is unchanged and soil structure, strength, etc. is only marginally affected.

Continuous Spiral Flight Augers — the hole is advanced using 90—115 mm diameter continuous spiral flight augers which are withdrawn at intervals to allow sampling or in-situ testing. This is a relatively economical means of drilling in clays and in sands above the water

table. Samples are returned to the surface, or may be collected after withdrawal of the auger flights, but they are very disturbed and may be contaminated. Information from the drilling (as distinct from specific sampling by SPTs or undisturbed samples) is of relatively lower reliability, due to remoulding, contamination or softening of samples by ground water.

Non-core Rotary Drilling — the hole is advanced by a rotary bit, with water being pumped down the drill rods and returned up the annulus, carrying the drill cuttings. Only major changes in stratification can be determined from the cuttings, together with some information from 'feel' and rate of penetration.

Rotary Mud Drilling — similar to rotary drilling, but using drilling mud as a circulating fluid. The mud tends to mask the cuttings and reliable identification is again only possible from separate intact sampling (eg. from SPT).

Continuous Core Drilling — a continuous core sample is obtained using a diamond-tipped core barrel, usually 50 mm internal diameter. Provided full core recovery is achieved (which is not always possible in very weak rocks and granular soils), this technique provides a very reliable (but relatively expensive) method of investigation.

Standard Penetration Tests

Standard penetration tests (abbreviated as SPT) are used mainly in non-cohesive soils, but occasionally also in cohesive soils as a means of determining density or strength and also of obtaining a relatively undisturbed sample. The test procedure is described in Australian Standard 1289, "Methods of Testing Soils for Engineering Purposes" — Test 6.3.1.

The test is carried out in a borehole by driving a 50 mm diameter split sample tube under the impact of a 63 kg hammer with a free fall of 760 mm. It is normal for the tube to be driven in three successive 150 mm increments and the 'N' value is taken as the number of blows for the last 300 mm. In dense sands, very hard clays or weak rock, the full 450 mm penetration may not be practicable and the test is discontinued.

The test results are reported in the following form.

- In the case where full penetration is obtained with successive blow counts for each 150 mm of say 4, 6 and 7
as 4, 6, 7
 N = 13
- In the case where the test is discontinued short of full penetration, say after 15 blows for the first 150 mm and 30 blows for the next 40 mm
as 15, 30/40 mm.

The results of the tests can be related empirically to the engineering properties of the soil.

Occasionally, the test method is used to obtain samples in 50 mm diameter thin walled sample tubes in clays. In such circumstances, the test results are shown on the borelogs in brackets.

Cone Penetrometer Testing and Interpretation

Cone penetrometer testing (sometimes referred to as Dutch cone — abbreviated as CPT) described in this report has been carried out using an electrical friction cone penetrometer. The test is described in Australian Standard 1289, Test 6.4.1.

In the tests, a 35 mm diameter rod with a cone-tipped end is pushed continuously into the soil, the reaction being provided by a specially designed truck or rig which is fitted with an hydraulic ram system. Measurements are made of the end bearing resistance on the cone and the friction resistance on a separate 130 mm long sleeve, immediately behind the cone. Transducers in the tip of the assembly are connected by electrical wires passing through the centre of the push rods to an amplifier and recorder unit mounted on the control truck.

As penetration occurs (at a rate of approximately 20 mm per second) the information is plotted on a computer screen and at the end of the test is stored on the computer for later plotting of the results.

The information provided on the plotted results comprises: —

- Cone resistance — the actual end bearing force divided by the cross sectional area of the cone — expressed in MPa.
- Sleeve friction — the frictional force on the sleeve divided by the surface area — expressed in kPa.
- Friction ratio — the ratio of sleeve friction to cone resistance, expressed in percent.

There are two scales available for measurement of cone resistance. The lower scale (0—5 MPa) is used in very soft soils where increased sensitivity is required and is shown in the graphs as a dotted line. The main scale (0—50 MPa) is less sensitive and is shown as a full line.

The ratios of the sleeve friction to cone resistance will vary with the type of soil encountered, with higher relative friction in clays than in sands. Friction ratios of 1%—2% are commonly encountered in sands and very soft clays rising to 4%—10% in stiff clays.

In sands, the relationship between cone resistance and SPT value is commonly in the range:—

$$q_c \text{ (MPa)} = (0.4 \text{ to } 0.6) N \text{ (blows per 300 mm)}$$

In clays, the relationship between undrained shear strength and cone resistance is commonly in the range:—

$$q_c = (12 \text{ to } 18) c_u$$

Interpretation of CPT values can also be made to allow estimation of modulus or compressibility values to allow calculation of foundation settlements.

Inferred stratification as shown on the attached reports is assessed from the cone and friction traces and from experience and information from nearby boreholes, etc. This information is presented for general guidance, but must be regarded as being to some extent interpretive. The test method provides a continuous profile of engineering properties, and where precise information on soil classification is required, direct drilling and sampling may be preferable.

Hand Penetrometers

Hand penetrometer tests are carried out by driving a rod into the ground with a falling weight hammer and measuring the blows for successive 150 mm increments of penetration. Normally, there is a depth limitation of 1.2 m but this may be extended in certain conditions by the use of extension rods.

Two relatively similar tests are used.

- Perth sand penetrometer — a 16 mm diameter flat-ended rod is driven with a 9 kg hammer, dropping 600 mm (AS 1289, Test 6.3.3). This test was developed for testing the density of sands (originating in Perth) and is mainly used in granular soils and filling.
- Cone penetrometer (sometimes known as the Scala Penetrometer) — a 16 mm rod with a 20 mm diameter cone end is driven with a 9 kg hammer dropping 510 mm (AS 1289, Test 6.3.2). The test was developed initially for pavement subgrade investigations, and published correlations of the test results with California bearing ratio have been published by various Road Authorities.

Laboratory Testing

Laboratory testing is carried out in accordance with Australian Standard 1289 "Methods of Testing Soil for Engineering Purposes". Details of the test procedure used are given on the individual report forms.

Bore Logs

The bore logs presented herein are an engineering and/or geological interpretation of the subsurface conditions, and their reliability will depend to some extent on frequency of sampling and the method of drilling. Ideally, continuous undisturbed sampling or core drilling will provide the most reliable assessment, but this is not always practicable, or possible to justify on economic grounds. In any case, the boreholes represent only a very small sample of the total subsurface profile.

Interpretation of the information and its application to design and construction should therefore take into account the spacing of boreholes, the frequency of sampling and the possibility of other than 'straight line' variations between the boreholes.

Ground Water

Where ground water levels are measured in boreholes, there are several potential problems;

- In low permeability soils, ground water although present, may enter the hole slowly or perhaps not at all during the time it is left open.
- A localised perched water table may lead to an erroneous indication of the true water table.
- Water table levels will vary from time to time with seasons or recent weather changes. They may not be

the same at the time of construction as are indicated in the report.

- The use of water or mud as a drilling fluid will mask any ground water inflow. Water has to be blown out of the hole and drilling mud must first be washed out of the hole if water observations are to be made.

More reliable measurements can be made by installing standpipes which are read at intervals over several days, or perhaps weeks for low permeability soils. Piezometers, sealed in a particular stratum, may be advisable in low permeability soils or where there may be interference from a perched water table.

Engineering Reports

Engineering reports are prepared by qualified personnel and are based on the information obtained and on current engineering standards of interpretation and analysis. Where the report has been prepared for a specific design proposal (eg. a three storey building), the information and interpretation may not be relevant if the design proposal is changed (eg. to a twenty storey building). If this happens, the Company will be pleased to review the report and the sufficiency of the investigation work.

Every care is taken with the report as it relates to interpretation of subsurface condition, discussion of geotechnical aspects and recommendations or suggestions for design and construction. However, the Company cannot always anticipate or assume responsibility for:

- unexpected variations in ground conditions — the potential for this will depend partly on bore spacing and sampling frequency
- changes in policy or interpretation of policy by statutory authorities
- the actions of contractors responding to commercial pressures.

If these occur, the Company will be pleased to assist with investigation or advice to resolve the matter.

Site Anomalies

In the event that conditions encountered on site during construction appear to vary from those which were expected from the information contained in the report, the Company requests that it immediately be notified. Most problems are much more readily resolved when conditions are exposed than at some later stage, well after the event.

Reproduction of Information for Contractual Purposes

Attention is drawn to the document "Guidelines for the Provision of Geotechnical Information in Tender Documents", published by the Institution of Engineers, Australia. Where information obtained from this investigation is provided for tendering purposes, it is recommended that all information, including the written report and discussion, be made available. In circumstances where the discussion or comments section

is not relevant to the contractual situation, it may be appropriate to prepare a specially edited document. The Company would be pleased to assist in this regard and/or to make additional report copies available for contract purposes at a nominal charge.

Site Inspection

The Company will always be pleased to provide engineering inspection services for geotechnical aspects of work to which this report is related. This could range from a site visit to confirm that conditions exposed are as expected, to full time engineering presence on site.

Copyright © 1998 Douglas Partners Pty Ltd

AN ENGINEERING CLASSIFICATION OF SEDIMENTARY ROCKS IN THE SYDNEY AREA

This classification system provides a standardized terminology for the engineering description of the sandstone and shales in the Sydney area, but the terms and definitions may be used elsewhere when applicable.

Under this system rocks are classified by Rock Type, Degree of Weathering, Strength, Stratification Spacing, and Degree of Fracturing. These terms do not cover the full range of engineering properties. Descriptions of rock may also need to refer to other properties (e.g. durability, abrasiveness, etc.) where these are relevant.

ROCK TYPE DEFINITIONS

Rock Type	Definition
Conglomerate:	More than 50% of the rock consists of gravel sized (greater than 2mm) fragments
Sandstone:	More than 50% of the rock consists of sand sized (.06 to 2mm) fragments
Siltstone:	More than 50% of the rock consists of silt-sized (less than 0.06mm) granular particles and the rock is not laminated
Claystone:	More than 50% of the rock consists of clay or sericitic material and the rock is not laminated
Shale:	More than 50% of the rock consists of silt or clay sized particles and the rock is laminated

Rocks possessing characteristics of two groups are described by their predominant particle size with reference also to the minor constituents, e.g. clayey sandstone, sandy shale.

DEGREE OF WEATHERING

Term	Symbol	Definition
Extremely Weathered	EW	Rock substance affected by weathering to the extent that the rock exhibits soil properties - i.e. it can be remoulded and can be classified according to the Unified Classification System, but the texture of the original rock is still evident.
Highly Weathered	HW	Rock substance affected by weathering to the extent that limonite staining or bleaching affects the whole of the rock substance and other signs of chemical or physical decomposition are evident. Porosity and strength may be increased or decreased compared to the fresh rock usually as a result of iron leaching or deposition. The colour and strength of the original fresh rock substance is no longer recognisable.
Moderately Weathered	MW	Rock substance affected by weathering to the extent that staining or discolouration of the rock substance usually by limonite has taken place. The colour and texture of the fresh rock is no longer recognisable.
Slightly Weathered	SW	Rock substance affected by weathering to the extent that partial staining or discolouration of the rock substance usually by limonite has taken place. The colour and texture of the fresh rock is recognisable.
Fresh	Fs	Rock substance unaffected by weathering, limonite staining along joints.
Fresh	Fr	Rock substance unaffected by weathering.

STRATIFICATION SPACING

Term	Separation of Stratification Planes
Thinly laminated	<6 mm
Laminated	6 mm to 20 mm
Very thinly bedded	20 mm to 60 mm
Thinly bedded	60 mm to 0.2 m
Medium bedded	0.2 m to 0.6 m
Thickly bedded	0.6 m to 2 m
Very thickly bedded	>2 m

ROCK STRENGTH

Rock strength is defined by the Point Load Strength Index (Is 50) and refers to the strength of the rock substance in the direction normal to the bedding. The test procedure is described by the International Society of Rock Mechanics (Reference).

Strength Term	Is(50) MPa	Field Guide	Approx. qu MPa*
Extremely Low:	0.03	Easily remoulded by hand to a material with soil properties	0.7
Very Low:	0.1	May be crumbled in the hand. Sandstone is "sugary" and friable.	2.4
Low:	0.3	A piece of core 150 mm long x 50 mm dia. may be broken by hand and easily scored with a knife. Sharp edges of core may be friable and break during handling.	7
Medium:	1	A piece of core 150 mm long x 50 mm dia. can be broken by hand with considerable difficulty. Readily scored with knife.	24
High:	3	A piece of core 150 mm long x 50 mm dia. cannot be broken by unaided hands, can be slightly scratched or scored with knife.	70
Very High:	10	A piece of core 150 mm long x 50 mm dia. may be broken readily with hand held hammer. Cannot be scratched with pen knife.	240
Extremely High:		A piece of core 150 mm long x 50 mm dia. is difficult to break with hand held hammer. Rings when struck with a hammer.	

* The approximate unconfined compressive strength (qu) shown in the table is based on an assumed ratio to the point load index of 24:1. This ratio may vary widely.

DEGREE OF FRACTURING

This classification applies to diamond drill cores and refers to the spacing of all types of natural fractures along which the core is discontinuous. These include bedding plane partings, joints and other rock defects, but exclude known artificial fractures such as drilling breaks

Term	Description
Fragmented:	The core is comprised primarily of fragments of length less than 20 mm, and mostly of width less than the core diameter.
Highly Fractured:	Core lengths are generally less than 20 mm - 40 mm with occasional fragments.
Fractured:	Core lengths are mainly 30 mm - 100 mm with occasional shorter and longer sections.
Slightly Fractured:	Core lengths are generally 300 mm - 1000 mm with occasional longer sections and occasional sections of 100 mm - 300 mm.
Unbroken:	The core does not contain any fracture.

REFERENCE

International Society of Rock Mechanics, Commission on Standardisation of Laboratory and Field Tests, Suggested Methods for Determining the Uniaxial Compressive Strength of Rock Materials and the Point Load Strength Index, Committee on Laboratory Tests Document No. 1 Final Draft October 1972

APPENDIX E
Laboratory Reports and Chain of Custody Documentation

Project Name: Kamira Court.....
Project No: 45789..... Sampler: Ulrike Krause.....
Project Mgr: Lindsay Rockett..... Mob. Phone: 0418635390.....
Email: Ulrike.Krause@douglaspartners.com.au.....
Date Required: 23/09/08..... Lab Quote No.

To: Envirolab Services
12 Ashley Street, Chatswood NSW 2068
Attn: Tania Notaras
Phone: 02 9910 6200 Fax: 02 9910 6201
Email: tnotaras@envirolabservices.com.au

Sample ID	Sample Depth	Lab ID	Sampling Date	Sample Type S - soil W - water	Container type	Analytes										Notes	
						As	Cd	Cr	Cu	Pb	Hg	Ni	Zn	BTEX/TPH	OCP/PCB		PAH
TP 1	0.05-0.4m	1	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Asbestos sample in plastic bag
TP 2	0.1-0.4m	2	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Asbestos sample in plastic bag
TP 3	0.1-0.25m	3	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Asbestos sample in plastic bag
TP 4	0.7-1.4m	4	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
TP 5	0.0-0.5m	5	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
BD1-170908		6	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓		✓			
TP 5	0.5-1.4m	7	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Asbestos sample in plastic bag
TP 6	0.5-1.6m	8	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
TP 6	2.7-3.2m	9	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Asbestos sample in plastic bag

Lab Report No.
Send Results to: Douglas Partners Address: 96 Hermitage Road, West Ryde 2114
Relinquished by: Ulrike Krause Signed: *U. Krause* Date & Time: 18/09/08
Relinquished by: Ulrike Krause Signed: *U. Krause* Date & Time: 18/09/08
Received By: Simon *Simon* Date & Time: 18/09/08
Received By: *Simon* Date & Time: 18/09/08

Phone: (02) 9809 0666
Fax: (02) 9809 4095

Envirolab Services
12 Ashley St
Chatswood NSW 2067
Ph: 9910 6200

Job No: 22789
Date received: 18/09/08
Time received: 1:30
Received by: *SS*
Temp: *20* Ambient
Cooling: *Ice* Ice/Back
Security: *Intact* Broken/None



Project Name:	Kamira Court	To:	Envirolab Services
Project No:	45789..... Sampler:Ulrike Krause.....		12 Ashley Street, Chatswood NSW 2068
Project Mgr:	Lindsay Rockett.....Mob. Phone: 0418635390	Attn:	Tania Notaras
Email:	Ulrike.Krause@douglaspartners.com.au		Phone: 02 9910 6200 Fax: 02 9910 6201
Date Required:	23/09/08..... Lab Quote No. Email: tnotaras@envirolabservices.com.au

Sample ID	Sample Depth	Lab ID	Sampling Date	Sample Type S - soil W - water	Container type	Analytes										Notes	
						As	Cd	Cr	Cu	Pb	Hg	Ni	Zn	BTEX/TPH	OCP/PCB		PAH
TP 7	0.3-1.0m	10	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Asbestos sample in plastic bag
TP 7	3.2-3.9m	11	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Asbestos sample in plastic bag
TP 8	0.1-0.8m	12	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Asbestos sample in plastic bag
Stockpile		13	17/09/08	S	glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
TS-170908		14		S	glass								Only BTEX				

Lab Report No.


Send Results to: Douglas Partners


Relinquished by: Ulrike Krause

Relinquished by: Ulrike Krause

Address: 96 Hermitage Road, West Ryde 2114

Date & Time: 18/09/08

Signed: 

Signed: 

Phone: (02) 9809 0666

Fax: (02) 9809 4095

Received By: Simon Song

Date & Time: 18/09/08 1:32

Date & Time:

Date & Time:



Envirolab Services Pty Ltd
ABN 37 112 535 645
12 Ashley St Chatswood NSW 2067
ph 02 9910 6200 fax 02 9910 6201
enquiries@envirolabservices.com.au
www.envirolabservices.com.au

CERTIFICATE OF ANALYSIS 22789

Client:

Douglas Partners
96 Hermitage Rd
West Ryde
NSW 2114

Attention: Ulrike Krause

Sample log in details:

Your Reference:	<u>45789, Kamira Court</u>
No. of samples:	14 Soils
Date samples received:	18/09/08
Date completed instructions received:	18/09/08

Analysis Details:

Please refer to the following pages for results, methodology summary and quality control data.
Samples were analysed as received from the client. Results relate specifically to the samples as received.
Results are reported on a dry weight basis for solids and on an as received basis for other matrices.
Please refer to the last page of this report for any comments relating to the results.


Report Details:

Date results requested by:	23/09/08
Date of Preliminary Report:	Not Issued
Issue Date:	23/09/08

NATA accreditation number 2901. This document shall not be reproduced except in full.
This document is issued in accordance with NATA's accreditation requirements.
Accredited for compliance with ISO/IEC 17025.
Tests not covered by NATA are denoted with *.

Results Approved By:


Jacinta Hurst
Operations Manager


Joshua Lim
Chemist

Envirolab Reference: 22789
Revision No: R 00

Page 1 of 24



vTPH & BTEX in Soil	UNITS	22789-1	22789-2	22789-3	22789-4	22789-5
Our Reference:	-----	TP1/0.05-0.4	TP2/0.1-0.4	TP3/0.1-0.25	TP4/0.7-1.4	TP5/0.0-0.5
Your Reference	-----	17/09/2008	17/09/2008	17/09/2008	17/09/2008	17/09/2008
Date Sampled		Soil	Soil	Soil	Soil	Soil
Type of sample						
Date extracted	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	20/09/2008	20/09/2008	20/09/2008	20/09/2008	20/09/2008
vTPH C6 - C9	mg/kg	<25	<25	<25	<25	<25
Benzene	mg/kg	<0.5	<0.5	<0.5	<0.5	<0.5
Toluene	mg/kg	<0.5	<0.5	<0.5	<0.5	<0.5
Ethylbenzene	mg/kg	<1	<1	<1	<1	<1
m+p-xylene	mg/kg	<2	<2	<2	<2	<2
o-Xylene	mg/kg	<1	<1	<1	<1	<1
Surrogate aaa-Trifluorotoluene	%	122	129	127	129	117

vTPH & BTEX in Soil	UNITS	22789-7	22789-8	22789-9	22789-10	22789-11
Our Reference:	-----	TP5/0.5-1.4	TP6/0.5-1.6	TP6/2.7-3.2	TP7/0.3-1.0	TP7/3.2-3.9
Your Reference	-----	17/09/2008	17/09/2008	17/09/2008	17/09/2008	17/09/2008
Date Sampled		Soil	Soil	Soil	Soil	Soil
Type of sample						
Date extracted	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	20/09/2008	20/09/2008	20/09/2008	20/09/2008	20/09/2008
vTPH C6 - C9	mg/kg	<25	<25	<25	<25	<25
Benzene	mg/kg	<0.5	<0.5	<0.5	<0.5	<0.5
Toluene	mg/kg	<0.5	<0.5	<0.5	<0.5	<0.5
Ethylbenzene	mg/kg	<1	<1	<1	<1	<1
m+p-xylene	mg/kg	<2	<2	<2	<2	<2
o-Xylene	mg/kg	<1	<1	<1	<1	<1
Surrogate aaa-Trifluorotoluene	%	136	120	127	124	123

vTPH & BTEX in Soil	UNITS	22789-12	22789-13	22789-14
Our Reference:	-----	TP8/0.1-0.8	Stockpile	TS-170908
Your Reference	-----	17/09/2008	17/09/2008	17/09/2008
Date Sampled		Soil	Soil	Soil
Type of sample				
Date extracted	-	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	20/09/2008	20/09/2008	20/09/2008
vTPH C6 - C9	mg/kg	<25	<25	[NA]
Benzene	mg/kg	<0.5	<0.5	96%
Toluene	mg/kg	<0.5	<0.5	96%
Ethylbenzene	mg/kg	<1	<1	99%
m+p-xylene	mg/kg	<2	<2	99%
o-Xylene	mg/kg	<1	<1	99%
Surrogate aaa-Trifluorotoluene	%	125	128	99

sTPH in Soil (C10-C36)	UNITS	22789-1	22789-2	22789-3	22789-4	22789-5
Our Reference:	-----	TP1/0.05-0.4	TP2/0.1-0.4	TP3/0.1-0.25	TP4/0.7-1.4	TP5/0.0-0.5
Your Reference	-----	17/09/2008	17/09/2008	17/09/2008	17/09/2008	17/09/2008
Date Sampled		Soil	Soil	Soil	Soil	Soil
Type of sample						
Date extracted	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
TPH C10 - C14	mg/kg	<50	<50	<50	<50	<50
TPH C15 - C28	mg/kg	<100	<100	<100	<100	<100
TPH C29 - C36	mg/kg	<100	<100	<100	<100	<100
Surrogate o-Terphenyl	%	102	112	107	110	110

sTPH in Soil (C10-C36)	UNITS	22789-7	22789-8	22789-9	22789-10	22789-11
Our Reference:	-----	TP5/0.5-1.4	TP6/0.5-1.6	TP6/2.7-3.2	TP7/0.3-1.0	TP7/3.2-3.9
Your Reference	-----	17/09/2008	17/09/2008	17/09/2008	17/09/2008	17/09/2008
Date Sampled		Soil	Soil	Soil	Soil	Soil
Type of sample						
Date extracted	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
TPH C10 - C14	mg/kg	<50	<50	<50	<50	<50
TPH C15 - C28	mg/kg	<100	<100	<100	<100	<100
TPH C29 - C36	mg/kg	<100	<100	<100	<100	<100
Surrogate o-Terphenyl	%	109	104	106	106	105

sTPH in Soil (C10-C36)	UNITS	22789-12	22789-13
Our Reference:	-----	TP8/0.1-0.8	Stockpile
Your Reference	-----	17/09/2008	17/09/2008
Date Sampled		Soil	Soil
Type of sample			
Date extracted	-	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008
TPH C10 - C14	mg/kg	<50	<50
TPH C15 - C28	mg/kg	<100	<100
TPH C29 - C36	mg/kg	<100	<100
Surrogate o-Terphenyl	%	122	119

PAHs in Soil Our Reference: Your Reference Date Sampled Type of sample	UNITS ----- -----	22789-1 TP1/0.05-0.4 17/09/2008 Soil	22789-2 TP2/0.1-0.4 17/09/2008 Soil	22789-3 TP3/0.1-0.25 17/09/2008 Soil	22789-4 TP4/0.7-1.4 17/09/2008 Soil	22789-5 TP5/0.0-0.5 17/09/2008 Soil
Date extracted	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Naphthalene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Acenaphthylene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Acenaphthene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Fluorene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Phenanthrene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Anthracene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Fluoranthene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Pyrene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Benzo(a)anthracene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Chrysene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Benzo(b+k)fluoranthene	mg/kg	<0.2	<0.2	<0.2	<0.2	<0.2
Benzo(a)pyrene	mg/kg	<0.05	<0.05	0.06	<0.05	<0.05
Indeno(1,2,3-c,d)pyrene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Dibenzo(a,h)anthracene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Benzo(g,h,i)perylene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Surrogate p-Terphenyl-d14	%	97	100	101	101	101

PAHs in Soil Our Reference: Your Reference Date Sampled Type of sample	UNITS ----- -----	22789-6 BD1-170908 17/09/2008 Soil	22789-7 TP5/0.5-1.4 17/09/2008 Soil	22789-8 TP6/0.5-1.6 17/09/2008 Soil	22789-9 TP6/2.7-3.2 17/09/2008 Soil	22789-10 TP7/0.3-1.0 17/09/2008 Soil
Date extracted	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Naphthalene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Acenaphthylene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Acenaphthene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Fluorene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Phenanthrene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Anthracene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Fluoranthene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Pyrene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Benzo(a)anthracene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Chrysene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Benzo(b+k)fluoranthene	mg/kg	<0.2	<0.2	<0.2	<0.2	<0.2
Benzo(a)pyrene	mg/kg	<0.05	<0.05	<0.05	<0.05	<0.05
Indeno(1,2,3-c,d)pyrene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Dibenzo(a,h)anthracene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Benzo(g,h,i)perylene	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Surrogate p-Terphenyl-d14	%	107	101	102	100	105

PAHs in Soil Our Reference: Your Reference Date Sampled Type of sample	UNITS ----- -----	22789-11 TP7/3.2-3.9 17/09/2008 Soil	22789-12 TP8/0.1-0.8 17/09/2008 Soil	22789-13 Stockpile 17/09/2008 Soil
Date extracted	-	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008
Naphthalene	mg/kg	<0.1	<0.1	<0.1
Acenaphthylene	mg/kg	<0.1	<0.1	<0.1
Acenaphthene	mg/kg	<0.1	<0.1	<0.1
Fluorene	mg/kg	<0.1	<0.1	<0.1
Phenanthrene	mg/kg	<0.1	<0.1	<0.1
Anthracene	mg/kg	<0.1	<0.1	<0.1
Fluoranthene	mg/kg	<0.1	<0.1	<0.1
Pyrene	mg/kg	<0.1	<0.1	<0.1
Benzo(a)anthracene	mg/kg	<0.1	<0.1	<0.1
Chrysene	mg/kg	<0.1	<0.1	<0.1
Benzo(b+k)fluoranthene	mg/kg	<0.2	<0.2	<0.2
Benzo(a)pyrene	mg/kg	<0.05	<0.05	<0.05
Indeno(1,2,3-c,d)pyrene	mg/kg	<0.1	<0.1	<0.1
Dibenzo(a,h)anthracene	mg/kg	<0.1	<0.1	<0.1
Benzo(g,h,i)perylene	mg/kg	<0.1	<0.1	<0.1
Surrogate p-Terphenyl-d14	%	102	111	105

Organochlorine Pesticides in soil	UNITS	22789-1	22789-2	22789-3	22789-4	22789-5
Our Reference:	-----	TP1/0.05-0.4	TP2/0.1-0.4	TP3/0.1-0.25	TP4/0.7-1.4	TP5/0.0-0.5
Your Reference	-----	17/09/2008	17/09/2008	17/09/2008	17/09/2008	17/09/2008
Date Sampled		Soil	Soil	Soil	Soil	Soil
Type of sample						
Date extracted	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
HCB	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
alpha-BHC	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
gamma-BHC	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
beta-BHC	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Heptachlor	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
delta-BHC	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Aldrin	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Heptachlor Epoxide	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
gamma-Chlordane	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
alpha-chlordane	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Endosulfan I	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
pp-DDE	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Dieldrin	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Endrin	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
pp-DDD	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Endosulfan II	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
pp-DDT	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Endrin Aldehyde	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Endosulfan Sulphate	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Methoxychlor	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Surrogate TCLMX	%	84	85	81	87	88

Organochlorine Pesticides in soil						
Our Reference:	UNITS	22789-7	22789-8	22789-9	22789-10	22789-11
Your Reference	-----	TP5/0.5-1.4	TP6/0.5-1.6	TP6/2.7-3.2	TP7/0.3-1.0	TP7/3.2-3.9
Date Sampled	-----	17/09/2008	17/09/2008	17/09/2008	17/09/2008	17/09/2008
Type of sample		Soil	Soil	Soil	Soil	Soil
Date extracted	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
HCB	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
alpha-BHC	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
gamma-BHC	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
beta-BHC	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Heptachlor	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
delta-BHC	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Aldrin	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Heptachlor Epoxide	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
gamma-Chlordane	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
alpha-chlordane	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Endosulfan I	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
pp-DDE	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Dieldrin	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Endrin	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
pp-DDD	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Endosulfan II	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
pp-DDT	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Endrin Aldehyde	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Endosulfan Sulphate	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Methoxychlor	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Surrogate TCLMX	%	88	83	82	82	82

Organochlorine Pesticides in soil			
Our Reference:	UNITS	22789-12	22789-13
Your Reference	-----	TP8/0.1-0.8	Stockpile
Date Sampled	-----	17/09/2008	17/09/2008
Type of sample		Soil	Soil
Date extracted	-	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008
HCB	mg/kg	<0.1	<0.1
alpha-BHC	mg/kg	<0.1	<0.1
gamma-BHC	mg/kg	<0.1	<0.1
beta-BHC	mg/kg	<0.1	<0.1
Heptachlor	mg/kg	<0.1	<0.1
delta-BHC	mg/kg	<0.1	<0.1
Aldrin	mg/kg	<0.1	<0.1
Heptachlor Epoxide	mg/kg	<0.1	<0.1
gamma-Chlordane	mg/kg	<0.1	<0.1
alpha-chlordane	mg/kg	<0.1	<0.1
Endosulfan I	mg/kg	<0.1	<0.1
pp-DDE	mg/kg	<0.1	<0.1
Dieldrin	mg/kg	<0.1	<0.1
Endrin	mg/kg	<0.1	<0.1
pp-DDD	mg/kg	<0.1	<0.1
Endosulfan II	mg/kg	<0.1	<0.1
pp-DDT	mg/kg	<0.1	<0.1
Endrin Aldehyde	mg/kg	<0.1	<0.1
Endosulfan Sulphate	mg/kg	<0.1	<0.1
Methoxychlor	mg/kg	<0.1	<0.1
Surrogate TCLMX	%	93	94

PCBs in Soil Our Reference: Your Reference Date Sampled Type of sample	UNITS ----- -----	22789-1 TP1/0.05-0.4 17/09/2008 Soil	22789-2 TP2/0.1-0.4 17/09/2008 Soil	22789-3 TP3/0.1-0.25 17/09/2008 Soil	22789-4 TP4/0.7-1.4 17/09/2008 Soil	22789-5 TP5/0.0-0.5 17/09/2008 Soil
Date extracted	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Arochlor 1016	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Arochlor 1232	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Arochlor 1242	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Arochlor 1248	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Arochlor 1254	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Arochlor 1260	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Surrogate TCLMX	%	84	85	81	87	88

PCBs in Soil Our Reference: Your Reference Date Sampled Type of sample	UNITS ----- -----	22789-7 TP5/0.5-1.4 17/09/2008 Soil	22789-8 TP6/0.5-1.6 17/09/2008 Soil	22789-9 TP6/2.7-3.2 17/09/2008 Soil	22789-10 TP7/0.3-1.0 17/09/2008 Soil	22789-11 TP7/3.2-3.9 17/09/2008 Soil
Date extracted	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Arochlor 1016	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Arochlor 1232	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Arochlor 1242	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Arochlor 1248	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Arochlor 1254	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Arochlor 1260	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Surrogate TCLMX	%	88	83	87	82	82

PCBs in Soil Our Reference: Your Reference Date Sampled Type of sample	UNITS ----- -----	22789-12 TP8/0.1-0.8 17/09/2008 Soil	22789-13 Stockpile 17/09/2008 Soil
Date extracted	-	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008
Arochlor 1016	mg/kg	<0.1	<0.1
Arochlor 1232	mg/kg	<0.1	<0.1
Arochlor 1242	mg/kg	<0.1	<0.1
Arochlor 1248	mg/kg	<0.1	<0.1
Arochlor 1254	mg/kg	<0.1	<0.1
Arochlor 1260	mg/kg	<0.1	<0.1
Surrogate TCLMX	%	93	94

Total Phenolics in Soil						
Our Reference:	UNITS	22789-1	22789-2	22789-3	22789-4	22789-5
Your Reference	-----	TP1/0.05-0.4	TP2/0.1-0.4	TP3/0.1-0.25	TP4/0.7-1.4	TP5/0.0-0.5
Date Sampled	-----	17/09/2008	17/09/2008	17/09/2008	17/09/2008	17/09/2008
Type of sample		Soil	Soil	Soil	Soil	Soil
Date extracted	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	22/09/2008	22/09/2008	22/09/2008	22/09/2008	22/09/2008
Total Phenolics (as Phenol)	mg/kg	<5	<5	<5	<5	<5

Total Phenolics in Soil				
Our Reference:	UNITS	22789-8	22789-11	22789-12
Your Reference	-----	TP6/0.5-1.6	TP7/3.2-3.9	TP8/0.1-0.8
Date Sampled	-----	17/09/2008	17/09/2008	17/09/2008
Type of sample		Soil	Soil	Soil
Date extracted	-	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	22/09/2008	22/09/2008	22/09/2008
Total Phenolics (as Phenol)	mg/kg	<5	<5	<5

Acid Extractable metals in soil	UNITS	22789-1	22789-2	22789-3	22789-4	22789-5
Our Reference:	-----	TP1/0.05-0.4	TP2/0.1-0.4	TP3/0.1-0.25	TP4/0.7-1.4	TP5/0.0-0.5
Your Reference	-----	17/09/2008	17/09/2008	17/09/2008	17/09/2008	17/09/2008
Date Sampled		Soil	Soil	Soil	Soil	Soil
Type of sample						
Date digested	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Arsenic	mg/kg	9	9	9	26	9
Cadmium	mg/kg	<0.5	0.6	0.5	<0.5	<0.5
Chromium	mg/kg	21	17	31	12	10
Copper	mg/kg	19	52	13	34	34
Lead	mg/kg	24	140	22	19	18
Mercury	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Nickel	mg/kg	8	13	9	26	20
Zinc	mg/kg	99	270	18	86	71

Acid Extractable metals in soil	UNITS	22789-6	22789-7	22789-8	22789-9	22789-10
Our Reference:	-----	BD1-170908	TP5/0.5-1.4	TP6/0.5-1.6	TP6/2.7-3.2	TP7/0.3-1.0
Your Reference	-----	17/09/2008	17/09/2008	17/09/2008	17/09/2008	17/09/2008
Date Sampled		Soil	Soil	Soil	Soil	Soil
Type of sample						
Date digested	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Arsenic	mg/kg	9	6	6	9	6
Cadmium	mg/kg	<0.5	<0.5	<0.5	<0.5	<0.5
Chromium	mg/kg	9	9	11	11	10
Copper	mg/kg	31	29	50	34	37
Lead	mg/kg	16	17	22	19	15
Mercury	mg/kg	<0.1	<0.1	<0.1	<0.1	<0.1
Nickel	mg/kg	25	17	21	24	25
Zinc	mg/kg	70	94	72	110	110

Acid Extractable metals in soil				
Our Reference:	UNITS	22789-11	22789-12	22789-13
Your Reference	-----	TP7/3.2-3.9	TP8/0.1-0.8	Stockpile
Date Sampled	-----	17/09/2008	17/09/2008	17/09/2008
Type of sample		Soil	Soil	Soil
Date digested	-	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008
Arsenic	mg/kg	4	<4	5
Cadmium	mg/kg	<0.5	<0.5	<0.5
Chromium	mg/kg	10	9	16
Copper	mg/kg	35	9	19
Lead	mg/kg	19	11	30
Mercury	mg/kg	<0.1	<0.1	<0.1
Nickel	mg/kg	17	3	15
Zinc	mg/kg	78	27	73

Moisture Our Reference: Your Reference Date Sampled Type of sample	UNITS ----- -----	22789-1 TP1/0.05-0.4 17/09/2008 Soil	22789-2 TP2/0.1-0.4 17/09/2008 Soil	22789-3 TP3/0.1-0.25 17/09/2008 Soil	22789-4 TP4/0.7-1.4 17/09/2008 Soil	22789-5 TP5/0.0-0.5 17/09/2008 Soil
Date prepared	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Moisture	%	17	7.5	18	14	11

Moisture Our Reference: Your Reference Date Sampled Type of sample	UNITS ----- -----	22789-6 BD1-170908 17/09/2008 Soil	22789-7 TP5/0.5-1.4 17/09/2008 Soil	22789-8 TP6/0.5-1.6 17/09/2008 Soil	22789-9 TP6/2.7-3.2 17/09/2008 Soil	22789-10 TP7/0.3-1.0 17/09/2008 Soil
Date prepared	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008	19/09/2008	19/09/2008
Moisture	%	11	12	17	20	17

Moisture Our Reference: Your Reference Date Sampled Type of sample	UNITS ----- -----	22789-11 TP7/3.2-3.9 17/09/2008 Soil	22789-12 TP8/0.1-0.8 17/09/2008 Soil	22789-13 Stockpile 17/09/2008 Soil
Date prepared	-	19/09/2008	19/09/2008	19/09/2008
Date analysed	-	19/09/2008	19/09/2008	19/09/2008
Moisture	%	18	23	13

Asbestos ID - soils						
Our Reference:	UNITS	22789-1	22789-2	22789-3	22789-7	22789-9
Your Reference:	-----	TP1/0.05-0.4	TP2/0.1-0.4	TP3/0.1-0.25	TP5/0.5-1.4	TP6/2.7-3.2
Date Sampled	-----	17/09/2008	17/09/2008	17/09/2008	17/09/2008	17/09/2008
Type of sample		Soil	Soil	Soil	Soil	Soil
Date analysed	-	22/09/2008	22/09/2008	22/09/2008	22/09/2008	22/09/2008
Sample Description	-	30g clay	30g clay	30g clay	30g clay	30g clay
Asbestos ID in soil	-	No asbestos found at reporting limit of 0.1g/kg	No asbestos found at reporting limit of 0.1g/kg	No asbestos found at reporting limit of 0.1g/kg	No asbestos found at reporting limit of 0.1g/kg	No asbestos found at reporting limit of 0.1g/kg
Trace Analysis	-	Respirable fibres not detected	Respirable fibres not detected	Respirable fibres not detected	Respirable fibres not detected	Respirable fibres not detected

Asbestos ID - soils				
Our Reference:	UNITS	22789-11	22789-12	22789-13
Your Reference:	-----	TP7/3.2-3.9	TP8/0.1-0.8	Stockpile
Date Sampled	-----	17/09/2008	17/09/2008	17/09/2008
Type of sample		Soil	Soil	Soil
Date analysed	-	22/09/2008	22/09/2008	22/09/2008
Sample Description	-	30g clay	30g clay	30g clay
Asbestos ID in soil	-	No asbestos found at reporting limit of 0.1g/kg	No asbestos found at reporting limit of 0.1g/kg	No asbestos found at reporting limit of 0.1g/kg
Trace Analysis	-	Respirable fibres not detected	Respirable fibres not detected	Respirable fibres not detected

Method ID	Methodology Summary
GC.16	Soil samples are extracted with methanol and spiked into water prior to analysing by purge and trap GC-MS. Water samples are analysed directly by purge and trap GC-MS.
GC.3	Soil samples are extracted with Dichloromethane/Acetone and waters with Dichloromethane and analysed by GC-FID.
GC.12 subset	Soil samples are extracted with Dichloromethane/Acetone and waters with Dichloromethane and analysed by GC-MS.
GC-5	Soil samples are extracted with hexane/acetone and waters with dichloromethane and analysed by GC with dual ECD's.
GC-6	Soil samples are extracted with hexane/acetone and waters with dichloromethane and analysed by GC-ECD.
LAB.30	Total Phenolics - determined colorimetrically following distillation.
Metals.20 ICP-AES	Determination of various metals by ICP-AES.
Metals.21 CV-AAS	Determination of Mercury by Cold Vapour AAS.
LAB.8	Moisture content determined by heating at 105 deg C for a minimum of 4 hours.
ASB.1	Qualitative identification of asbestos type fibres in bulk using Polarised Light Microscopy and Dispersion Staining Techniques.

QUALITY CONTROL	UNITS	PQL	METHOD	Blank	Duplicate Sm#	Duplicate results	Spike Sm#	Spike % Recovery
vTPH & BTEX in Soil						Base II Duplicate II %RPD		
Date extracted	-			19/09/2008	22789-1	19/09/2008 19/09/2008	LCS-1	19/09/2008
Date analysed	-			20/9/08	22789-1	20/09/2008 20/09/2008	LCS-1	20/9/08
vTPH C6 - C9	mg/kg	25	GC.16	<25	22789-1	<25 <25	LCS-1	99%
Benzene	mg/kg	0.5	GC.16	<0.5	22789-1	<0.5 <0.5	LCS-1	86%
Toluene	mg/kg	0.5	GC.16	<0.5	22789-1	<0.5 <0.5	LCS-1	105%
Ethylbenzene	mg/kg	1	GC.16	<1	22789-1	<1 <1	LCS-1	101%
m+p-xylene	mg/kg	2	GC.16	<2	22789-1	<2 <2	LCS-1	102%
o-Xylene	mg/kg	1	GC.16	<1	22789-1	<1 <1	LCS-1	101%
Surrogate aaa-Trifluorotoluene	%		GC.16	132	22789-1	122 125 RPD: 2	LCS-1	132%
QUALITY CONTROL	UNITS	PQL	METHOD	Blank	Duplicate Sm#	Duplicate results	Spike Sm#	Spike % Recovery
sTPH in Soil (C10-C36)						Base II Duplicate II %RPD		
Date extracted	-			19/09/2008	22789-1	19/09/2008 19/09/2008	LCS-1	19/09/2008
Date analysed	-			19/09/2008	22789-1	19/09/2008 19/09/2008	LCS-1	19/09/2008
TPH C10 - C14	mg/kg	50	GC.3	<50	22789-1	<50 <50	LCS-1	118%
TPH C15 - C28	mg/kg	100	GC.3	<100	22789-1	<100 <100	LCS-1	115%
TPH C29 - C36	mg/kg	100	GC.3	<100	22789-1	<100 <100	LCS-1	132%
Surrogate o-Terphenyl	%		GC.3	120	22789-1	102 103 RPD: 1	LCS-1	113%
QUALITY CONTROL	UNITS	PQL	METHOD	Blank	Duplicate Sm#	Duplicate results	Spike Sm#	Spike % Recovery
PAHs in Soil						Base II Duplicate II %RPD		
Date extracted	-			19/9/08	22789-1	19/09/2008 19/09/2008	LCS-1	19/9/08
Date analysed	-			19/9/08	22789-1	19/09/2008 19/09/2008	LCS-1	19/9/08
Naphthalene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	LCS-1	92%
Acenaphthylene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Acenaphthene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Fluorene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	LCS-1	87%
Phenanthrene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	LCS-1	89%
Anthracene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Fluoranthene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	LCS-1	88%
Pyrene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	LCS-1	94%
Benzo(a)anthracene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]

QUALITY CONTROL	UNITS	PQL	METHOD	Blank	Duplicate Sm#	Duplicate results	Spike Sm#	Spike % Recovery
PAHs in Soil						Base II Duplicate II %RPD		
Chrysene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	LCS-1	108%
Benzo(b+k)fluoranthene	mg/kg	0.2	GC.12 subset	<0.2	22789-1	<0.2 <0.2	[NR]	[NR]
Benzo(a)pyrene	mg/kg	0.05	GC.12 subset	<0.05	22789-1	<0.05 <0.05	LCS-1	99%
Indeno(1,2,3-c,d)pyrene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Dibenzo(a,h)anthracene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Benzo(g,h,i)perylene	mg/kg	0.1	GC.12 subset	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Surrogate p-Terphenyl-d14	%		GC.12 subset	105	22789-1	97 95 RPD: 2	LCS-1	112%
QUALITY CONTROL	UNITS	PQL	METHOD	Blank	Duplicate Sm#	Duplicate results	Spike Sm#	Spike % Recovery
Organochlorine Pesticides in soil						Base II Duplicate II %RPD		
Date extracted	-			19/09/2008	22789-1	19/09/2008 19/09/2008	LCS-1	19/09/2008
Date analysed	-			19/09/2008	22789-1	19/09/2008 19/09/2008	LCS-1	19/09/2008
HCB	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
alpha-BHC	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	LCS-1	107%
gamma-BHC	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
beta-BHC	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	LCS-1	107%
Heptachlor	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	LCS-1	107%
delta-BHC	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Aldrin	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	LCS-1	103%
Heptachlor Epoxide	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	LCS-1	113%
gamma-Chlordane	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
alpha-chlordane	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Endosulfan I	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
pp-DDE	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	LCS-1	121%
Dieldrin	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	LCS-1	111%
Endrin	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	LCS-1	98%
pp-DDD	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	LCS-1	115%
Endosulfan II	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
pp-DDT	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Endrin Aldehyde	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Endosulfan Sulphate	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	LCS-1	103%
Methoxychlor	mg/kg	0.1	GC-5	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Surrogate TCLMX	%		GC-5	91	22789-1	84 86 RPD: 2	LCS-1	91%

QUALITY CONTROL	UNITS	PQL	METHOD	Blank	Duplicate Sm#	Duplicate results	Spike Sm#	Spike % Recovery
PCBs in Soil						Base II Duplicate II %RPD		
Date extracted	-			19/09/2008	22789-1	19/09/2008 19/09/2008	LCS-1	19/09/2008
Date analysed	-			19/09/2008	22789-1	19/09/2008 19/09/2008	LCS-1	19/09/2008
Arochlor 1016	mg/kg	0.1	GC-6	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Arochlor 1232	mg/kg	0.1	GC-6	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Arochlor 1242	mg/kg	0.1	GC-6	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Arochlor 1248	mg/kg	0.1	GC-6	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Arochlor 1254	mg/kg	0.1	GC-6	<0.1	22789-1	<0.1 <0.1	LCS-1	91%
Arochlor 1260	mg/kg	0.1	GC-6	<0.1	22789-1	<0.1 <0.1	[NR]	[NR]
Surrogate TCLMX	%		GC-6	91	22789-1	84 86 RPD: 2	LCS-1	106%
QUALITY CONTROL	UNITS	PQL	METHOD	Blank	Duplicate Sm#	Duplicate results	Spike Sm#	Spike % Recovery
Total Phenolics in Soil						Base II Duplicate II %RPD		
Date extracted	-			19/9/08	22789-1	19/09/2008 19/09/2008	LCS-1	19/9/08
Date analysed	-			22/9/08	22789-1	22/09/2008 22/09/2008	LCS-1	22/9/08
Total Phenolics (as Phenol)	mg/kg	5	LAB.30	<5	22789-1	<5 <5	LCS-1	97%
QUALITY CONTROL	UNITS	PQL	METHOD	Blank	Duplicate Sm#	Duplicate results	Spike Sm#	Spike % Recovery
Acid Extractable metals in soil						Base II Duplicate II %RPD		
Date digested	-			19/09/08	22789-1	19/09/2008 19/09/2008	LCS-3	19/09/08
Date analysed	-			19/09/08	22789-1	19/09/2008 19/09/2008	LCS-3	19/09/08
Arsenic	mg/kg	4	Metals.20 ICP-AES	<4	22789-1	9 8 RPD: 12	LCS-3	99%
Cadmium	mg/kg	0.5	Metals.20 ICP-AES	<0.5	22789-1	<0.5 <0.5	LCS-3	102%
Chromium	mg/kg	1	Metals.20 ICP-AES	<1	22789-1	21 17 RPD: 21	LCS-3	104%
Copper	mg/kg	1	Metals.20 ICP-AES	<1	22789-1	19 17 RPD: 11	LCS-3	105%
Lead	mg/kg	1	Metals.20 ICP-AES	<1	22789-1	24 26 RPD: 8	LCS-3	99%
Mercury	mg/kg	0.1	Metals.21 CV-AAS	<0.1	22789-1	<0.1 <0.1	LCS-3	114%
Nickel	mg/kg	1	Metals.20 ICP-AES	<1	22789-1	8 5 RPD: 46	LCS-3	104%
Zinc	mg/kg	1	Metals.20 ICP-AES	<1	22789-1	99 84 RPD: 16	LCS-3	102%

QUALITY CONTROL Moisture	UNITS	PQL	METHOD	Blank	
Date prepared	-			[NT]	
Date analysed	-			[NT]	
Moisture	%	0.1	LAB.8	<0.1	
QUALITY CONTROL Asbestos ID - soils	UNITS	PQL	METHOD	Blank	
Date analysed	-			[NT]	
QUALITY CONTROL vTPH & BTEX in Soil	UNITS	Dup. Sm#	Duplicate Base + Duplicate + %RPD	Spike Sm#	Spike % Recovery
Date extracted	-	22789-12	19/09/2008 19/09/2008	22789-2	19/09/2008
Date analysed	-	22789-12	20/09/2008 20/09/2008	22789-2	20/9/08
vTPH C6 - C9	mg/kg	22789-12	<25 <25	22789-2	88%
Benzene	mg/kg	22789-12	<0.5 <0.5	22789-2	79%
Toluene	mg/kg	22789-12	<0.5 <0.5	22789-2	92%
Ethylbenzene	mg/kg	22789-12	<1 <1	22789-2	90%
m+p-xylene	mg/kg	22789-12	<2 <2	22789-2	90%
o-Xylene	mg/kg	22789-12	<1 <1	22789-2	88%
Surrogate aaa-Trifluorotoluene	%	22789-12	125 133 RPD: 6	22789-2	130%
QUALITY CONTROL sTPH in Soil (C10-C36)	UNITS	Dup. Sm#	Duplicate Base + Duplicate + %RPD	Spike Sm#	Spike % Recovery
Date extracted	-	22789-12	19/09/2008 19/09/2008	22789-2	19/09/2008
Date analysed	-	22789-12	19/09/2008 19/09/2008	22789-2	19/09/2008
TPH C10 - C14	mg/kg	22789-12	<50 <50	22789-2	111%
TPH C15 - C28	mg/kg	22789-12	<100 <100	22789-2	106%
TPH C29 - C36	mg/kg	22789-12	<100 <100	22789-2	109%
Surrogate o-Terphenyl	%	22789-12	122 119 RPD: 2	22789-2	112%
QUALITY CONTROL PAHs in Soil	UNITS	Dup. Sm#	Duplicate Base + Duplicate + %RPD	Spike Sm#	Spike % Recovery
Date extracted	-	22789-12	19/09/2008 19/09/2008	22789-2	19/9/08
Date analysed	-	22789-12	19/09/2008 19/09/2008	22789-2	19/9/08
Naphthalene	mg/kg	22789-12	<0.1 <0.1	22789-2	88%
Acenaphthylene	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Acenaphthene	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Fluorene	mg/kg	22789-12	<0.1 <0.1	22789-2	84%
Phenanthrene	mg/kg	22789-12	<0.1 <0.1	22789-2	84%
Anthracene	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Fluoranthene	mg/kg	22789-12	<0.1 <0.1	22789-2	83%
Pyrene	mg/kg	22789-12	<0.1 <0.1	22789-2	88%
Benzo(a)anthracene	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]

QUALITY CONTROL PAHs in Soil	UNITS	Dup. Sm#	Duplicate Base + Duplicate + %RPD	Spike Sm#	Spike % Recovery
Chrysene	mg/kg	22789-12	<0.1 <0.1	22789-2	99%
Benzo(b+k)fluoranthene	mg/kg	22789-12	<0.2 <0.2	[NR]	[NR]
Benzo(a)pyrene	mg/kg	22789-12	<0.05 <0.05	22789-2	84%
Indeno(1,2,3-c,d)pyrene	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Dibenzo(a,h)anthracene	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Benzo(g,h,i)perylene	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Surrogate p-Terphenyl-d14	%	22789-12	111 111 RPD: 0	22789-2	103%
QUALITY CONTROL Organochlorine Pesticides in soil	UNITS	Dup. Sm#	Duplicate Base + Duplicate + %RPD	Spike Sm#	Spike % Recovery
Date extracted	-	22789-12	19/09/2008 19/09/2008	22789-2	19/09/2008
Date analysed	-	22789-12	19/09/2008 19/09/2008	22789-2	19/09/2008
HCB	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
alpha-BHC	mg/kg	22789-12	<0.1 <0.1	22789-2	99%
gamma-BHC	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
beta-BHC	mg/kg	22789-12	<0.1 <0.1	22789-2	96%
Heptachlor	mg/kg	22789-12	<0.1 <0.1	22789-2	103%
delta-BHC	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Aldrin	mg/kg	22789-12	<0.1 <0.1	22789-2	96%
Heptachlor Epoxide	mg/kg	22789-12	<0.1 <0.1	22789-2	102%
gamma-Chlordane	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
alpha-chlordane	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Endosulfan I	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
pp-DDE	mg/kg	22789-12	<0.1 <0.1	22789-2	111%
Dieldrin	mg/kg	22789-12	<0.1 <0.1	22789-2	101%
Endrin	mg/kg	22789-12	<0.1 <0.1	22789-2	77%
pp-DDD	mg/kg	22789-12	<0.1 <0.1	22789-2	96%
Endosulfan II	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
pp-DDT	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Endrin Aldehyde	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Endosulfan Sulphate	mg/kg	22789-12	<0.1 <0.1	22789-2	70%
Methoxychlor	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Surrogate TCLMX	%	22789-12	93 96 RPD: 3	22789-2	84%

QUALITY CONTROL PCBs in Soil	UNITS	Dup. Sm#	Duplicate Base + Duplicate + %RPD	Spike Sm#	Spike % Recovery
Date extracted	-	22789-12	19/09/2008 19/09/2008	22789-2	19/09/2008
Date analysed	-	22789-12	19/09/2008 19/09/2008	22789-2	19/09/2008
Arochlor 1016	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Arochlor 1232	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Arochlor 1242	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Arochlor 1248	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Arochlor 1254	mg/kg	22789-12	<0.1 <0.1	22789-2	87%
Arochlor 1260	mg/kg	22789-12	<0.1 <0.1	[NR]	[NR]
Surrogate TCLMX	%	22789-12	93 96 RPD: 3	22789-2	109%
QUALITY CONTROL Total Phenolics in Soil	UNITS	Dup. Sm#	Duplicate Base + Duplicate + %RPD	Spike Sm#	Spike % Recovery
Date extracted	-	[NT]	[NT]	22789-2	19/9/08
Date analysed	-	[NT]	[NT]	22789-2	22/9/08
Total Phenolics (as Phenol)	mg/kg	[NT]	[NT]	22789-2	96%
QUALITY CONTROL Acid Extractable metals in soil	UNITS	Dup. Sm#	Duplicate Base + Duplicate + %RPD	Spike Sm#	Spike % Recovery
Date digested	-	22789-12	19/09/2008 19/09/2008	22789-2	19/09/08
Date analysed	-	22789-12	19/09/2008 19/09/2008	22789-2	19/09/08
Arsenic	mg/kg	22789-12	<4 5	22789-2	100%
Cadmium	mg/kg	22789-12	<0.5 <0.5	22789-2	93%
Chromium	mg/kg	22789-12	9 13 RPD: 36	22789-2	100%
Copper	mg/kg	22789-12	9 12 RPD: 29	22789-2	77%
Lead	mg/kg	22789-12	11 16 RPD: 37	22789-2	79%
Mercury	mg/kg	22789-12	<0.1 <0.1	22789-2	109%
Nickel	mg/kg	22789-12	3 7 RPD: 80	22789-2	93%
Zinc	mg/kg	22789-12	27 41 RPD: 41	22789-2	84%

QUALITY CONTROL Moisture	UNITS	Dup. Sm#	Duplicate Base + Duplicate + %RPD
Date prepared	-	22789-1	19/09/2008 19/09/2008
Date analysed	-	22789-1	19/09/2008 19/09/2008
Moisture	%	22789-1	17 17 RPD: 0
QUALITY CONTROL Moisture	UNITS	Dup. Sm#	Duplicate Base + Duplicate + %RPD
Date prepared	-	22789-12	19/09/2008 19/09/2008
Date analysed	-	22789-12	19/09/2008 19/09/2008
Moisture	%	22789-12	23 23 RPD: 0

Report Comments:

Asbestos: A portion of the supplied sample was sub-sampled for asbestos according to Envirolab procedures. We cannot guarantee that this sub-sample is indicative of the entire sample.

Envirolab recommends supplying 30-40g of sample in it's own container.

Asbestos was analysed by Approved Identifier: Joshua Lim

INS: Insufficient sample for this test

NT: Not tested

PQL: Practical Quantitation Limit

RPD: Relative Percent Difference

NA: Test not required

LCS: Laboratory Control Sample

NR: Not requested

<: Less than

>: Greater than

Quality Control Definitions

Blank: This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.

Duplicate: This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.

Matrix Spike: A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.

LCS (Laboratory Control Sample): This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.

Surrogate Spike: Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.

Laboratory Acceptance Criteria:

Duplicates: <5xPQL - any RPD is acceptable; >5xPQL - 0-50% RPD is acceptable.

Matrix Spikes and LCS: Generally 70-130% for inorganics/metals; 60-140% for organics and 10-140% for

SVOC and speciated phenols is acceptable.

Surrogates: 60-140% is acceptable for general organics and 10-140% for

SVOC and speciated phenols.

8 OCT 2008

CHAIN OF CUSTODY

Project Name: Kamira Court To: Envirolab Services
 Project No: 45789 Sampler: Ulrike Krause 12 Ashley Street, Chatswood NSW 2068
 Project Mgr: Lindsay Rockett Mob. Phone: 0418635390 Attn: Tania Notaras
 Email: Lindsay.Rockett@douglaspartners.com.au Phone: 02 9910 6200 Fax: 02 9910 6201
 Date Required: 08/10/08 Lab Quote No. Email: tnotaras@envirolabservices.com.au


Sample ID	Sample Depth	Lab ID	Sampling Date	Sample Type S - soil W - water	Container type	Analytes											Notes		
						As	Cd	Cr	Cu	Pb	Hg	Ni	Zn	BTEX/ TPH	OCP/ PCB	PAH		Phenols	Other: Asbestos
TP 2	0.1-0.4m	1	17/09/08	Bulk mat.	plastic													✓	Asbestos sample in plastic bag
TP 6	2.7-3.2m	2	17/09/08	Bulk mat.	plastic													✓	Asbestos sample in plastic bag
TP 7	3.2-3.9m	3	17/09/08	Bulk mat.	plastic													✓	Asbestos sample in plastic bag
TP 8	0.1-0.8 m	4	17/09/08	Bulk mat.	plastic													✓	Asbestos sample in plastic bag

Lab Report No. Phone: (02) 9809 0666
 Send Results to: Douglas Partners Address: 96 Hermitage Road, West Ryde 2114 Fax: (02) 9809 4095
 Relinquished by: Ulrike Krause Signed: Date & Time: 03/10/08 Received By: Date & Time: 3/10/08 1230
 Relinquished by: Ulrike Krause Signed: Date & Time: Received By: Date & Time:

Please forward results to Lindsay Rockett.



Job No: 23205
 Date received: 3/10/08
 Time received: 1230hrs
 Received by: [Signature]
 Temp: Cool/Ambient
 Cooling: Icepack
 Security: Intact/Broken/None



EnviroLab Services Pty Ltd
ABN 37 112 535 645
12 Ashley St Chatswood NSW 2067
ph 02 9910 6200 fax 02 9910 6201
enquiries@envirolabservices.com.au
www.envirolabservices.com.au

CERTIFICATE OF ANALYSIS 23205

Client:

Douglas Partners
96 Hermitage Rd
West Ryde
NSW 2114

Attention: Lindsay Rockett

Sample log in details:

Your Reference:	<u>45789, Kamira Court</u>
No. of samples:	4 Materials
Date samples received:	03/10/08
Date completed instructions received:	03/10/08

Analysis Details:

Please refer to the following pages for results and methodology summary.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Note, even after disintegration it can be difficult to detect the presence of asbestos in some asbestos -containing bulk materials using PLM and dispersion staining. This is due to the low grade or small length or diameter of the asbestos fibres present in the material, or to the fact that very fine fibres have been distributed intimately throughout the materials. Vinyl/asbestos floor tiles, some asbestos containing epoxy resins and some ore samples are examples of these types of material, which are difficult to analyse.

Report Details:

Date results requested by:	8/10/08
Date of Preliminary Report:	Not issued
Issue Date:	7/10/08

NATA accreditation number 2901. This document shall not be reproduced except in full.


This document is issued in accordance with NATA's accreditation requirements.

Accredited for compliance with ISO/IEC 17025.

Tests not covered by NATA are denoted with *.

Results Approved By:

Asbestos was analysed by Approved Identifier: Joshua Lim


Joshua Lim
Chemist



Envirolab Ref:	Sample ID:	Date analysed	Sample Description	Asbestos ID in materials	Asbestos Fibres
--	--	-	-	-	-
23205-1	TP2/0.1-0.4	7/10/2008	40x10x10mm cement fragment	No asbestos detected	Not applicable
23205-2	TP6/2.7-3.2	7/10/2008	40x30x10mm cement fragment	No asbestos detected	Not applicable
23205-3	TP7/3.2-3.9	7/10/2008	40x30x10mm cement fragment	No asbestos detected	Not applicable
23205-4	TP8/0.1-0.8	7/10/2008	30x30x5mm cement fragment	No asbestos detected	Not applicable

Method ID	Methodology Summary
AS4964-2004	Qualitative identification of asbestos type fibres in bulk using Polarised Light Microscopy and Dispersion Staining Techniques.

APPENDIX F
Geotechnical Laboratory Test Results



RESULT OF SHRINK-SWELL INDEX DETERMINATION


Client :	HOUSING NSW	Project No. :	45789
Project :	URBAN RENEWAL PROJECT	Report No. :	S08-213 A
Location :	KAMIRA COURT, VILLAWOOD	Report Date :	14/10/08
Test Location :	TP 3	Date Sampled :	18/09/08
Depth / Layer :	0.5-0.8m	Date of Test:	22/09/08
		Page:	1 of 1

CORE SHRINKAGE TEST

Shrinkage - air dried	3.3 %
Shrinkage - oven dried	3.5 %
Significant inert inclusions	4.0 %
Extent of cracking	MC
Extent of soil crumbling	0.1 %
Moisture content of core	18.4 %

SWELL TEST

Pocket penetrometer reading at initial moisture content	500 kPa
Pocket penetrometer reading at final moisture content	90 kPa
Initial Moisture Content	16.3 %
Final Moisture Content	26.6 %
Swell under 25kPa	5.4 %



SHRINK-SWELL INDEX I_{ss} 3.4% per ΔpF

Description:	SILTY CLAY - Light grey and red brown silty clay with a trace of ironstone gravel
Test Method(s):	AS 1289.7.1.1 - 2003, AS 1289.2.1.1 - 2005
Sampling Method(s):	AS 1289.1.3.1-1999
Extent of Cracking:	UC - Uncracked SC - Slightly cracked MC - Moderately cracked HC - Highly cracked FR - Fractured
Remarks:	

Note that NATA accreditation does not cover the performance of pocket penetrometer readings



NATA Accredited Laboratory Number: 828
This Document is issued in accordance with NATA's accreditation requirements.
Accredited for compliance with ISO/IEC 17025

Approved Signatory:

Tested:	JLG
Checked:	NW

Norman Weimann
Norman Weimann
Laboratory Manager



RESULT OF SHRINK-SWELL INDEX DETERMINATION


Client :	HOUSING NSW	Project No. :	45789
Project :	URBAN RENEWAL PROJECT	Report No. :	S08-213 B
Location :	KAMIRA COURT, VILLAWOOD	Report Date :	29/09/08
Test Location :	TP 8	Date Sampled :	18/09/08
Depth / Layer :	0.8-1.0m	Date of Test:	22/09/08
		Page:	1 of 1

CORE SHRINKAGE TEST

Shrinkage - air dried	2.7 %
Shrinkage - oven dried	2.7 %
Significant inert inclusions	0.5 %
Extent of cracking	MC
Extent of soil crumbling	0.1 %
Moisture content of core	19.0 %

SWELL TEST

Pocket penetrometer reading at initial moisture content	280 kPa
Pocket penetrometer reading at final moisture content	220 kPa
Initial Moisture Content	14.5 %
Final Moisture Content	20.2 %
Swell under 25kPa	0.4 %



SHRINK-SWELL INDEX I_{ss} 1.6% per ΔpF

Description:	SILTY CLAY - Light grey and red brown silty clay with a trace of ironstone gravel
Test Method(s):	AS 1289.7.1.1 - 2003, AS 1289.2.1.1 - 2005
Sampling Method(s):	AS 1289.1.3.1-1999
Extent of Cracking:	UC - Uncracked SC - Slightly cracked MC - Moderately cracked HC - Highly cracked FR - Fractured
Remarks:	

Note that NATA accreditation does not cover the performance of pocket penetrometer readings



NATA Accredited Laboratory Number: 828
This Document is issued in accordance with NATA's accreditation requirements.
Accredited for compliance with ISO/IEC 17025

Approved Signatory:

Tested:	JLG
Checked:	NW

Norman Weimann

Norman Weimann
Laboratory Manager



RESULTS OF MOISTURE CONTENT, PLASTICITY AND LINEAR SHRINKAGE TESTS

Client: HOUSING NSW		Project No: 45789	
Project: URBAN RENEWAL PROJECT		Report No: S08-213	
Location: KAMIRA COURT, VILLAWOOD		Report Date: 29/09/08	
		Date Sampled: 17/09/08	
		Date of Test: 24/09/08	
		Page: 1 of 1	

TEST LOCATION	DEPTH (m)	DESCRIPTION	CODE	W _F %	W _L %	W _P %	PI %	*LS %
TP 1	1.0	SILTY CLAY - Stiff to very stiff, light grey and red brown silty clay with a trace of ironstone gravel	2,5	18.9	51	22	29	12.5 CU
TP 6	1.0	FILLING - Brown and grey silty clay filling with some gravel and crushed shale	2,5	24.1	49	22	27	11.5 CU

Legend:

W_F Field Moisture Content
W_L Liquid limit
W_P Plastic limit
PI Plasticity index
LS Linear shrinkage from liquid limit condition (Mould length 150mm)

NO No Result

NP Non Plas

Test Methods:

Moisture Content: AS 1289 2.1.1 - 2005
Liquid Limit: AS 1289 3.1.2 - 1995, 3.1.1 - 1995
Plastic Limit: AS 1289 3.2.1 - 1995
Plasticity Index: AS 1289 3.3.1 - 1995
Linear Shrinkage: AS 1289 3.4.1 - 1995
Cone Liquid Limit: AS 1289 3.9.1 - 2002
AS 1289.1.3.1 - 1999

Code

Sample history for plasticity tests

1. Air dried
2. Low temperature (<50°C) oven dried
3. Oven (105°C) dried
4. Unknown

Method of preparation for plasticity tests

5. Dry sieved
6. Wet sieved
7. Natural

*Specify if sample crumbled CR or curled CU

Sampling Method(s): AS 1289.1.2.1-1998, AS 1289.1.1-2001

Remarks:



NATA Accredited Laboratory Number: 828

This Document is issued in accordance with
NATA's accreditation requirements.
Accredited for compliance with ISO/IEC 17025

Approved Signatory:

Tested: LW
Checked: NW

Norman Weimann
Norman Weimann
Laboratory Manager



RESULTS OF MOISTURE CONTENT TEST

Client	HOUSING NSW	Project No:	45789
Project	URBAN RENEWAL PROJECT	Report No:	S08-213
Location	KAMIRA COURT, VILLAWOOD	Report Date:	24/09/08
		Date Sampled	17/09/08
		Date of Test:	19/09/08
		Page:	1 of 1
TEST LOCATION	DEPTH (m)	DESCRIPTION	MOISTURE CONTENT (%)
TP1	1.0	SILTY CLAY – Stiff to very stiff, light grey and red brown silty clay with a trace of ironstone gravel	18.9
TP6	1.0	FILLING – Brown and grey silty clay filling with some gravel and crushed shale	24.1
TP8	1.0	SILTY CLAY – Very stiff, light grey and red brown silty clay with a trace of ironstone gravel	20.3

Test Method(s): AS 1289.2.1.1-2005

Sampling Method(s): AS 1289.1.2.1-1998, AS 1289.1.1-2001

Remarks:

Approved Signatory:


Tested: LW
Checked: NW

Norman Weimann
Laboratory Manager



RESULT OF CALIFORNIA BEARING RATIO TEST

Client :	HOUSING NSW	Project No. :	45789
Project :	URBAN RENEWAL PROJECT	Report No. :	S08-213 C
Location :	KAMIRA COURT, VILLAWOOD	Report Date :	24/09/08
Test Location :	TP 1	Date Sampled :	18/09/08
Depth / Layer :	0.5-0.7m	Date of Test:	19/09/08
		Page:	1 of 1



Description: SILTY CLAY - Stiff to very stiff, light grey & red brown silty clay with a trace of ironstone gravel
Test Method(s): AS 1289.6.1.1-1998, AS 1289.2.1.1-2005
Sampling Method(s): AS 1289.1.2.1-1998, AS 1289.1.1-2001 **Percentage > 19mm:** 0.0%

LEVEL OF COMPACTION: 101% of STD MDD
MOISTURE RATIO: 99% of STD OMC

SURCHARGE: 4.5 kg
SOAKING PERIOD: 4 days

SWELL: 2.2%


CONDITION	MOISTURE CONTENT %	DRY DENSITY t/m ³
At compaction	24.7	1.60
After soaking	27.1	1.56
After test		
Top 30mm of sample	28.4	-
Remainder of sample	25.2	-
Field values	25.3	-
Standard Compaction	24.9	1.58

RESULTS		
TYPE	PENETRATION	CBR (%)
TOP	2.5 mm	2.5
	5.0 mm	2.5
BOTTOM	2.5 mm	5
	5.0 mm	4.5



RESULTS OF COMPACTION TEST

Client :	HOUSING NSW	Project No. :	45789
Project :	URBAN RENEWAL PROJECT	Report No. :	S08-213 C
Location :	KAMIRA COURT, VILLAWOOD	Report Date :	19/09/08
		Date of Test:	19/09/08
		Page:	1 of 1



Sample Details **Location:** TP1
 Depth: 0.5-0.7m

Particles > 19mm: 0%

Description: SILTY CLAY - Stiff to very stiff, light grey and red brown silty clay with a trace of ironstone gravel

Maximum Dry Density:	1.58 t/m³
Optimum Moisture Content:	25.0 %

Remarks:

Test Methods: AS 1289.5.1.1-2003 (STD), AS1289.2.1.1-2005

Sampling Methods: AS 1289.1.1-2001, AS 1289.1.2.1-1998



NATA Accredited Laboratory Number: 828
This Document is issued in accordance with NATA's
accreditation requirements.
Accredited for compliance with ISO/IEC 17025

Approved Signatory:


Tested:	RR
Checked:	NW

Norman Weimann
Laboratory Manager



RESULT OF CALIFORNIA BEARING RATIO TEST

Client :	HOUSING NSW	Project No. :	45789
Project :	URBAN RENEWAL PROJECT	Report No. :	S08-213 D
Location :	KAMIRA COURT, VILLAWOOD	Report Date :	24/09/08
Test Location :	TP 8	Date Sampled :	18/09/08
Depth / Layer :	1.0-1.2m	Date of Test:	19/09/08
		Page:	1 of 1



Description: SILTY CLAY - Very stiff, light grey and red brown silty clay with a trace of ironstone gravel

Test Method(s): AS 1289.6.1.1-1998, AS 1289.2.1.1-2005

Sampling Method(s): AS 1289.1.2.1-1998, AS 1289.1.1-2001

Percentage > 19mm: 0.0%

LEVEL OF COMPACTION: 99% of STD MDD

SURCHARGE: 4.5 kg

SWELL: 4.0%

MOISTURE RATIO: 99% of STD OMC

SOAKING PERIOD: 4 days

CONDITION	MOISTURE CONTENT %	DRY DENSITY t/m ³
At compaction	16.3	1.75
After soaking	20.8	1.68
After test	Top 30mm of sample	-
	Remainder of sample	-
Field values	20.9	-
Standard Compaction	16.4	1.77


RESULTS		
TYPE	PENETRATION	CBR (%)
TOP	2.5 mm	1.0
	5.0 mm	1.0
BOTTOM	2.5 mm	8
	5.0 mm	7



RESULTS OF COMPACTION TEST

Client : HOUSING NSW
Project : URBAN RENEWAL PROJECT
Location : KAMIRA COURT, VILLAWOOD

Project No. : 45789
Report No. : S08-213 D
Report Date : 19/09/08
Date of Test: 19/09/08
Page: 1 of 1



Sample Details **Location:** TP 8
Depth: 1.0-1.2m

Particles > 19mm: 0%

Description: SILTY CLAY - Very stiff, light grey and red brown silty clay with a trace of ironstone gravel

Maximum Dry Density:	1.77 t/m³
Optimum Moisture Content:	16.5 %

Remarks:

Test Methods: AS 1289.5.1.1-2003 (STD), AS1289.2.1.1-2005

Sampling Methods: AS 1289.1.1-2001, AS 1289.1.2.1-1998



NATA Accredited Laboratory Number: 828
This Document is issued in accordance with NATA's accreditation requirements.
Accredited for compliance with ISO/IEC 17025

Approved Signatory:

Tested:	RR
Checked:	NW

Norman Weimann
Laboratory Manager

APPENDIX G
***Data Quality Objectives/Quality Assurance/
Quality Control Procedures and Results***

DATA QUALITY OBJECTIVES

The data quality objectives (DQO) of the Contamination Assessment have been developed to define the type and quality of the data to achieve the project objectives and were based broadly in accordance with the seven step data quality objective process, as defined in Australian Standard (AS) *Guide to the Sampling and Investigation of Potentially Contaminated Soil Part 1: Non-volatile and Semi-volatile Compounds* (AS 4482.1 – 2005). The DQO process is outlined in the AS and defined by:

- Stating the Problem;
- Identifying the Decision;
- Identifying Inputs to the Decision;
- Defining the Boundary of the Assessment;
- Developing a Decision Rule;
- Specifying Acceptable Limits on Decision Errors;
- Optimising the Design for Obtaining Data.

Data quality objectives have been established for the project and are summarised in Table G1.

Table G1 – Data Quality Objectives

Data Quality Objective	Report section where addressed
State the Problem	S1 Introduction S3 Site Description
Identify the Decision	S10 Site Assessment Criteria S12 Assessment of Laboratory Results S13 Conclusions and Recommendations
Identify Inputs to the Decision	S3 Site Description S4 Geology and Hydrogeology S7 Potential Contaminants S10 Site Assessment Criteria S11 Results of the Soil Investigation S12 Assessment of Laboratory Results
Define the Boundary of the Assessment	S3 Site Description, Appendix A
Develop a Decision Rule	S10 Site Assessment Criteria
Specify Acceptable Limits on Decision Errors	Appendix F
Optimise the Design for Obtaining Data.	S8 Field Work

QA/QC PROCEDURES AND RESULTS

Quality assurance and control formed an integral part of this assessment. The results of the QA/QC assessments are detailed below.

The Data Quality Indicators (DQI's) have been addressed within the report as follows in Table G2.

Table G2 – DQIs and Evaluation Procedures

DQI	Evaluation Procedure
Documentation completeness	Completion of field and laboratory documentation including chain of custody, test bore reports.
Data completeness	Sampling density appropriate for preliminary assessment, analysis of appropriate contaminants, analysis of appropriate soil horizons, analysis of appropriate QA samples etc
Data comparability	Use of NATA accredited analytical methods, use of consistent sampling technique, commitment to equipment decontamination, field sample storage techniques etc.
Data representativeness	Sampling from targeted areas and a broad grid pattern across the site in order to obtain samples representative of contamination present.
Precision and accuracy for sampling and analysis	Use of NATA accredited analytical methods, achievement of 30-50% RPD for replicate analysis (as appropriate) and achievement of laboratory QC criteria.

As indicated above, the DQIs for sampling and analysis were achieved and the quality of the data satisfactorily meets the objectives of the current assessment.

FIELD QUALITY ASSURANCE AND QUALITY CONTROL

The field QC procedures for sampling as prescribed in Douglas Partners *Field Procedures Manual* were followed at all times during the validation assessment. Field sampling comprised one replicate sampling and one trip blank.

Relative Percentage Difference

Seven samples were selected for analytical analysis, including one duplicate sample. A measure of the consistency of results is derived by the calculation of relative percentage differences (RPDs) for the duplicate sample. A RPD of $\pm 30\%$ is generally considered acceptable by the EPA, although some exceptions apply. The comparative results of analysis are included in Table G3.

**Table G3 – Comparative Results of Duplicate Sample Analysis
for Heavy Metals and PAH's**

Sample ID	As	Cd	Cr	Cu	Pb	Hg	Ni	Zn	PAH	BaP
TP5/0.0-0.5	9	<0.5	10	34	18	<0.1	20	71	<PQL	<0.05
BD1	9	<0.5	9	31	16	<0.1	25	70	<PQL	<0.05
RPD %	0	0	11	9	12	0	22	1	0	0

Notes:

1 field replicate of sample above

Bold RPD greater than $\pm 30\%$

- All the RPD results for total PAH, BaP and heavy metals fall within the typical acceptable range ($\pm 30\%$).

It is therefore considered that the results indicate an acceptable consistency between the sample and its duplicate and suitable field sampling methodology.

Laboratory QA/QC Procedures

The analytical laboratory is accredited by the National Association of Testing Authorities (NATA) and is required to conduct in-house QA/QC procedures. These are normally incorporated into every analytical run and include the following:-

Reagent Blank

A reagent blank sample is prepared and analysed at the beginning of every analytical run, following calibration of the analytical apparatus. The laboratory results for reagent blanks for soil analysis indicated that concentrations of all analytes were below respective laboratory practical quantitation (detection) limits. These results are included in the laboratory report in Appendix E.

Spike Recovery

This is a sample replicate prepared by adding a known amount of analyte prior to analysis, and then treated exactly the same as all other samples. The recovery result indicates the proportion of the known concentration of the analyte that is detected during analysis. These results are included in the laboratory report in Appendix E.

The spike recovery rates are compared with limits as specified in Envirolab Services Quality Control System, and any exceedances are highlighted in the report.

As no exceedances and no comments were noted on the report, it is considered that the results indicate that the analytical results are not significantly affected by matrix interference.

Surrogate Recovery

This sample is prepared by adding a known amount of surrogate, which behaves similarly to the analyte, prior to analysis to each sample. The recovery result indicates the proportion of the known concentration of the surrogate that is detected during analysis.

As no exceedances and no comments were noted on the report, it is considered that the results indicate that the analytical results are not significantly affected by matrix interference.

Duplicates

These are additional portions of a sample which are analysed in exactly the same manner as all other samples. The duplicate sample results are included in the laboratory results in Appendix E.

In overall terms, therefore, the data quality objectives have been attained and the quality of the investigation data is considered acceptable.