

FITZPATRICK INVESTMENTS PTY LTD

ERSKINE PARK INDUSTRIAL ESTATE LOCKWOOD ROAD, ERSKINE PARK LOTS 2, 3, 4 AND 5

DEVELOPMENT APPLICATION

DRAWING SCHEDULE

190050-05-DA2-C23.01

DRAWING NUMBER DESCRIPTION

190050-05-DA2-C01.01 COVER SHEET AND DRAWING SCHEDULE **GENERAL NOTES** 190050-05-DA2-C01.21

190050-05-DA2-C01.41 GENERAL ARRANGEMENT PLAN 190050-05-DA2-C04.01

190050-05-DA2-C05.01 190050-05-DA2-C05.02 190050-05-DA2-C11.01 190050-05-DA2-C11.02

190050-05-DA2-C14.01

190050-05-DA2-C20.01 190050-05-DA2-C20.21 POST-DEVELOPMENT STORMWATER CATCHMENT PLAN


190050-05-DA2-C22.01 TURNING PATH PLAN - SHEET 01

SAFETY IN DESIGN

4	20/10/2022	ISSUED FOR DEVELOPMENT APPLICATION	СВ	MKH	MKH	MKI
3	30/06/2022	AMENDMENTS TO ADDRESS COUNCIL COMMENTS - DA ISSUE	FR	MKH	MKH	MKI
2	22/03/2022	AMENDMENTS TO ADDRESS COUNCIL COMMENTS - DA ISSUE	MDH	MKH	MKH	MKI
1	22/10/2021	ISSUED FOR DEVELOPMENT APPLICATION	MDH	DL	MKH	MKI
REV.	DATE	DESCRIPTION	DRN.	DES.	VERIF.	APP

Fitzpatrick Investments





		Scale 1
	enspire	Date 19/
	Enspire Solutions Pty Ltd Level 4, 153 Walker Street, North Sydney NSW 2060	Size
art	ABN: 71 624 801 690 Phone: 02 9922 6135	Datun MC

	Scale	Status
	1:5000	
	Date	
	19/04/2021	
	Size	Projec
NSW 2060	A1	۱ ا
	Datum	

FOR APPROVAL NOT TO BE USED FOR CONSTRUCTION

190050-05-DA2-C01.01

SURVEY

- THE EXISTING SITE CONDITIONS SHOWN ON THE FOLLOWING DRAWINGS HAVE BEEN SUPPLIED BY REGISTERED SURVEYORS TO PROVIDE A BASIS FOR DESIGN. REFER SURVEY DRAWINGS 10848 DETAIL SURVEY 10954 DET 1 A REV A PRODUCED BY ICD ASIA PACIFIC PTY LTD FOR DETAILS.
- SHOULD DISCREPANCIES BE ENCOUNTERED DURING CONSTRUCTION BETWEEN THE SURVEY DATA AND ACTUAL FIELD DATA, CONTACT THE DESIGN ENGINEER.
- THE RELATIONSHIP OF IMPROVEMENTS TO BOUNDARIES ARE DIAGRAMMATIC ONLY. WHERE DISTANCES TO BOUNDARIES ARE CRITICAL THEY SHOULD BE CONFIRMED ON SITE PRIOR TO CONSTRUCTION BY FURTHER SURVEY.

GENERAL

- ALL WORKS TO BE CONSTRUCTED IN ACCORDANCE WITH PENRITH CITY COUNCIL STANDARDS.
- 2. PENRITH CITY COUNCIL STANDARD DETAILS TO BE USED WHERE POSSIBLE.
- 3. UTILITY ADJUSTMENTS AT DEVELOPERS EXPENSE.
- 6. CONDUITS TO BE PLACED WHERE REQUIRED BY THE RELEVANT AUTHORITIES.
- SUBSOIL DRAINAGE LINES AND FLUSHING POINTS AT MAXIMUM 60m CENTRES SHALL BE INSTALLED BEHIND ALL KERBS.
- 6. A MINIMUM OF 3m OF SUBSOIL LINE SHALL BE LAID INTO UPSTREAM SIDE OF ALL DRAINAGE PITS.
- LOT NUMBERS AND STREET NAMES MUST BE STENCILED ON THE FACE OF KERB OR IN ALTERNATIVE LOCATIONS DIRECTED BY THE PCA. THE STENCIL MEDIUM MUST BE OF GOOD QUALITY UV STABILISED PAINT AND APPLIED TO
- THE KERB THUSLY: 7.1. LOT NUMBERS - WHITE NUMBER IN 'BRUNSWICK GREEN' BACKGROUND LOCATED ON THE PROLONGATION OF BOTH COMMON BOUNDARIES OF
- 7.2. STREET NAMES WHITE LETTERING ON 'BRUNSWICK GREEN' BACKGROUND AT KERB AND GUTTER TANGENT POINTS.
- PIT LINTELS MUST BE LABELED WITH PERMANENT STENCILED SIGNS IN ACCORDANCE WITH COUNCIL'S CURRENT ENGINEERING DESIGN SPECIFICATIONS.

GENERAL NOTES

- THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH OTHER CONSULTANTS' DRAWINGS AND SPECIFICATIONS AND WITH OTHER SUCH WRITTEN INSTRUCTIONS AS MAY BE ISSUED DURING THE COURSE OF THE CONTRACT. ANY DISCREPANCY SHALL BE REFERRED TO THE ENGINEER BEFORE PROCEEDING WITH THE WORK.
- DO NOT OBTAIN DIMENSIONS BY SCALING THE DRAWINGS. ALL DIMENSIONS ARE IN MILLIMETERS (mm) AND ALL LEVELS ARE IN METERS (m), UNO. ALL LEVELS ARE TO AUSTRALIAN HEIGHT DATUM (MGA2020).

EROSION AND SEDIMENT CONTROL

GENERAL INSTRUCTIONS

- . THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE CONTROL OF EROSION AND SEDIMENTATION TO THE SATISFACTION OF COUNCIL, NSW OFFICE OF WATER, OFFICE OF ENVIRONMENT AND HERITAGE, THE EROSION AND SEDIMENTATION CONTROLS SHOWN ON THE DRAWINGS SHALL ONLY BE USED AS A GUIDE BY THE CONTRACTOR, AND SHALL REPRESENT THE MINIMUM REQUIREMENT ONLY.
- 2. THE CONTRACTOR SHALL ENSURE THAT ALL SOIL AND WATER MANAGEMENT WORKS ARE LOCATED AS DOCUMENTED OR AS OTHERWISE DIRECTED BY THE SUPERINTENDENT. ALL WORK SHALL BE GENERALLY CARRIED OUT IN ACCORDANCE WITH
- a. LOCAL AUTHORITY REQUIREMENTS b. EPA REQUIREMENTS c. NSW DEPARTMENT OF HOUSING MANUAL "MANAGING URBAN
- STORMWATER, SOILS AND CONSTRUCTION", 4th EDITION, MARCH 2004.
- MAINTAIN THE EROSION CONTROL DEVICES TO THE SATISFACTION OF THE SUPERINTENDENT AND THE LOCAL AUTHORITY. WHEN STORMWATER PITS ARE CONSTRUCTED, PREVENT SITE RUNOFF

ENTERING UNLESS SEDIMENT FENCES ARE ERECTED AROUND PITS.

5. CONTRACTOR IS TO ENSURE ALL EROSION & SEDIMENT CONTROL DEVICES ARE MAINTAINED IN GOOD WORKING ORDER AND OPERATE EFFECTIVELY. REPAIRS AND OR MAINTENANCE SHALL BE UNDERTAKEN AS REQUIRED, PARTICULARLY FOLLOWING STORM EVENTS.

LAND DISTURBANCE

- WHERE PRACTICAL, THE SOIL EROSION HAZARD ON THE SITE WILL BE KEPT AS LOW AS POSSIBLE. TO THIS END, WORKS SHOULD BE UNDERTAKEN IN THE FOLLOWING SEQUENCE:
- a. INSTALL A SEDIMENT FENCE ALONG THE BOUNDARIES AS SHOWN ON PLAN. REFER DETAIL.
- b. CONSTRUCT STABILISED CONSTRUCTION ENTRANCE TO LOCATION AS
- DETERMINED BY SUPERINTENDENT/ENGINEER, REFER DETAIL.
- c. INSTALL SEDIMENT BASIN AS SHOWN ON PLAN d. INSTALL SEDIMENT TRAPS AS SHOWN ON PLAN.
- e. UNDERTAKE SITE DEVELOPMENT WORKS IN ACCORDANCE WITH THE ENGINEERING PLANS. WHERE POSSIBLE, PHASE DEVELOPMENT SO THAT LAND DISTURBANCE IS CONFINED TO AREAS OF WORKABLE SIZE.

EROSION CONTROL

- DURING WINDY WEATHER, LARGE, UNPROTECTED AREAS WILL BE KEPT MOIST (NOT WET) BY SPRINKLING WITH WATER TO KEEP DUST UNDER CONTROL.
- 8. FINAL SITE LANDSCAPING WILL BE UNDERTAKEN AS SOON AS POSSIBLE AND WITHIN 20 WORKING DAYS FROM COMPLETION OF CONSTRUCTION ACTIVITIES.

SEDIMENT CONTROL

- 9. STOCKPILES WILL NOT BE LOCATED WITHIN 2 METRES OF HAZARD AREAS, INCLUDING LIKELY AREAS OF CONCENTRATED OR HIGH VELOCITY FLOWS SUCH AS WATERWAYS. WHERE THEY ARE BETWEEN 2 AND 5 METRES FROM SUCH AREAS, SPECIAL SEDIMENT CONTROL MEASURES SHOULD BE TAKEN TO MINIMISE POSSIBLE POLLUTION TO DOWNSLOPE WATERS, E.G. THROUGH INSTALLATION OF SEDIMENT FENCING.
- 10. ANY SAND USED IN THE CONCRETE CURING PROCESS (SPREAD OVER THE SURFACE) WILL BE REMOVED AS SOON AS POSSIBLE AND WITHIN 10 WORKING DAYS FROM PLACEMENT.
- 11. WATER WILL BE PREVENTED FROM ENTERING THE PERMANENT DRAINAGE SYSTEM UNLESS IT IS RELATIVELY SEDIMENT FREE, I.E. THE CATCHMENT AREA HAS BEEN PERMANENTLY LANDSCAPED AND/OR ANY LIKELY SEDIMENT HAS BEEN FILTERED THROUGH AN APPROVED STRUCTURE.
- 12. TEMPORARY SOIL AND WATER MANAGEMENT STRUCTURES WILL BE REMOVED ONLY AFTER THE LANDS THEY ARE PROTECTING ARE REHABILITATED.
- 13. ACCEPTABLE RECEPTORS WILL BE PROVIDED FOR CONCRETE AND MORTAR SLURRIES, PAINTS, ACID WASHINGS, LIGHT-WEIGHT WASTE MATERIALS AND LITTER.
- 14. ANY EXISTING TREES WHICH FORM PART OF THE FINAL LANDSCAPING PLAN WILL BE PROTECTED FROM CONSTRUCTION ACTIVITIES BY:

OTHER MATTERS

- PROTECTING THEM WITH BARRIER FENCING OR SIMILAR MATERIALS
- INSTALLED OUTSIDE THE DRIP LINE
- ENSURING THAT NOTHING IS NAILED TO THEM PROHIBITING PAVING, GRADING, SEDIMENT WASH OR PLACING OF STOCKPILES WITHIN THE DRIP LINE EXCEPT UNDER THE FOLLOWING CONDITIONS.
-) ENCROACHMENT ONLY OCCURS ON ONE SIDE AND NO CLOSER TO THE TRUNK THAN EITHER 1.5 METRES OR HALF THE DISTANCE BETWEEN THE OUTER EDGE OF THE DRIP LINE AND THE TRUNK, WHICH EVER IS THE GREATER
- (II) A DRAINAGE SYSTEM THAT ALLOWS AIR AND WATER TO CIRCULATE THROUGH THE ROOT ZONE (E.G. A GRAVEL BED) IS PLACED UNDER ALL FILL LAYERS OF MORE THAN 300 MILLIMETRES DEPTH
- (III) CARE IS TAKEN NOT TO CUT ROOTS UNNECESSARILY NOR TO COMPACT THE SOIL AROUND THEM.

SITEWORKS

- . ALL WORKS TO BE IN ACCORDANCE WITH LOCAL AUTHORITY REQUIREMENTS, SPECIFICATIONS AND AUSTRALIAN STANDARDS. CONFLICTS SHALL BE REFERRED TO THE SUPERINTENDENT FOR
- 2. CONTRACTOR MUST VERIFY ALL DIMENSIONS AND EXISTING LEVELS ON SITE PRIOR TO COMMENCEMENT OF WORK, ANY DISCREPANCIES TO BE REPORTED TO THE DESIGN ENGINEER.
- B. THE CONTRACTOR IS TO DESIGN, OBTAIN APPROVALS AND CARRY OUT REQUIRED TEMPORARY TRAFFIC CONTROL PROCEDURES DURING CONSTRUCTION IN ACCORDANCE WITH RMS AND LOCAL AUTHORITY REGULATIONS AND REQUIREMENTS.
- 4. THE CONTRACTOR IS TO OBTAIN ALL AUTHORITY APPROVALS AS REQUIRED.
- RESTORE ALL PAVED, COVERED, GRASSED AND LANDSCAPED AREAS TO THEIR ORIGINAL CONDITION ON COMPLETION OF WORKS.
- 6. ON COMPLETION OF ANY TRENCHING WORKS, ALL DISTURBED AREAS SHALL BE RESTORED TO THEIR ORIGINAL CONDITION, INCLUDING KERBS, FOOTPATHS, CONCRETE AREAS, GRAVEL, GRASSED AREAS AND ROAD PAVEMENTS.
- 7. THE CONTRACTOR SHALL ARRANGE ALL SURVEY SETOUT TO BE CARRIED OUT BY A REGISTERED SURVEYOR.
- 8. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND EXISTING LEVELS ON SITE PRIOR TO LODGMENT OF TENDER AND ON SITE WORKS. THE PRICE AS TENDERED SHALL BE INCLUSIVE OF ALL WORKS SHOWN ON THE TENDER PROJECT DRAWINGS. ADDITIONAL PAYMENTS FOR WORKS SHOWN ON THE TENDER PROJECT DRAWINGS WILL NOT BE APPROVED.
-). THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH THE ENGINEERING PLANS AND SPECIFICATIONS, AND ANY OTHER WRITTEN INSTRUCTIONS THAT MAY BE ISSUED RELATING TO DEVELOPMENT OF THE SUBJECT SITE.
- 10. THESE PLANS SHALL BE READ IN CONJUNCTION WITH ALL APPROVED DRAWINGS AND SPECIFICATIONS PREPARED BY OTHER PROJECT CONSULTANTS.
- 11. DO NOT OBTAIN DIMENSIONS BY SCALING THE DRAWINGS. ALL DIMENSIONS ARE IN MILLIMETERS (mm) AND ALL LEVELS ARE IN METERS (m), UNO. ALL LEVELS ARE TO AUSTRALIAN HEIGHT DATUM (AHD).
- 12. IN CASE OF DOUBT OR DISCREPANCY REFER TO THE DESIGN ENGINEER AND SUPERINTENDENT FOR CLARIFICATION OR CONFIRMATION PRIOR TO THE COMMENCEMENT OF CONSTRUCTION. OTHERWISE THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE COST OF REMEDIATION WORKS.
- 13. WHERE NEW WORKS ABUT EXISTING THE CONTRACTOR SHALL ENSURE THAT A SMOOTH EVEN PROFILE, FREE FROM ABRUPT CHANGES IS OBTAINED.
- 14. THE CONTRACTOR SHALL COMPLY WITH ALL STATUTORY AND INDUSTRIAL REQUIREMENTS FOR PROVISION OF A SAFE WORKING ENVIRONMENT INCLUDING TRAFFIC CONTROL.
- 15. THE CONTRACTOR SHALL ENSURE THAT AT ALL TIMES ACCESS TO ALL BUILDINGS ADJACENT THE WORKS IS NOT DISRUPTED.
- 16. WHERE NECESSARY THE CONTRACTOR SHALL PROVIDE SAFE PASSAGE OF VEHICLES AND/OR PEDESTRIANS THROUGH OR BY THE SITE.
- 17. WHERE NOTED ON THE DRAWINGS THAT WORKS ARE TO BE CARRIED BY OTHERS, (eg. ADJUSTMENT OF SERVICES), THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CO-ORDINATION OF THESE WORKS.
- 18. ALL VARIATIONS TO SPECIFIED PRODUCTS OR DESIGNS SHALL BE REFERRED TO THE DESIGN ENGINEER IN WRITING FOR APPROVAL.
- 19. ANY EXISTING TREES WHICH FORM PART OF THE FINAL LANDSCAPING PLAN WILL BE PROTECTED FROM CONSTRUCTION ACTIVITIES BY:
- PROTECTING THEM WITH BARRIER FENCING OR SIMILAR MATERIALS INSTALLED OUTSIDE THE DRIP LINE
- ENSURING THAT NOTHING IS NAILED TO THEM PROHIBITING PAVING, GRADING, SEDIMENT WASH OR PLACING OF STOCKPILES WITHIN THE DRIP LINE EXCEPT
- UNDER THE FOLLOWING CONDITIONS: ENCROACHMENT ONLY OCCURS ON ONE SIDE AND NO CLOSER TO THE TRUNK THAN EITHER 1.5 METRES OR HALF THE DISTANCE BETWEEN THE OUTER EDGE OF THE DRIP LINE AND THE TRUNK, WHICH EVER IS THE
- GREATER A DRAINAGE SYSTEM THAT ALLOWS AIR AND WATER TO CIRCULATE THROUGH THE ROOT ZONE (E.G. A GRAVEL BED) IS PLACED UNDER ALL FILL LAYERS OF MORE
- THAN 300 MILLIMETRES DEPTH CARE IS TAKEN NOT TO CUT ROOTS UNNECESSARILY NOR TO COMPACT THE SOIL AROUND THEM.
- 20. EPA AND COUNCIL REQUIREMENTS MUST BE ADHERED TO REGARDING THE LEVEL OF NOISE AND WORKING HOURS, TO ENSURE THAT RESIDENTS AND OTHER APPLICABLE NEIGHBOURS TO THE SITE ARE NOT DISTURBED UNREASONABLY. THE GENERATION OF NOISE MUST BE MINIMISED.

without the permission of Enspire Solutions Pty Ltd.

EARTHWORKS

- AT THE COMMENCEMENT OF THE CUT AND FILLING OPERATIONS FOR BULK EARTHWORKS A GEOTECHNICAL ENGINEER IS TO VISIT THE SITE & CONFIRM THE SUITABILITY OF THE METHODOLOGY OF ACHIEVING THE REQUIRED BUILDING PLATFORMS AND COMPACTION REQUIREMENTS. SUBSEQUENTLY, THE HEAD CONTRACTOR IS TO CONFIRM, IN WRITING TO THE DESIGNING CIVIL & STRUCTURAL ENGINEERS. THAT THE METHODOLOGY APPROVED AT THE TIME OF THE GEOTECHNICAL ENGINEERS VISIT WAS MAINTAINED DURING ALL THE BULK EARTHWORKS PROCESS.
- STRIP TOPSOIL, ORGANIC MATTER AND RUBBLE FROM CONSTRUCTION AREA TO EXPOSE NATURALLY OCCURRING MATERIAL AND STOCKPILE ON SITE AS DIRECTED BY THE SUPERINTENDENT.
- WHERE FILLING, STRUCTURAL SLABS OR PAVEMENTS ARE REQUIRED, PROOF ROLL THE EXPOSED NATURAL SURFACE WITH A MINIMUM OF TEN PASSES OF A SMOOTH DRUM VIBRATING ROLLER (MINIMUM STATIC WEIGHT OF 10 TONNES) TO DETECT THEN REMOVE SOFT SPOTS (AREAS WITH MORE THAN 2mm MOVEMENT UNDER ROLLER) IN THE PRESENCE OF THE SUPERINTENDENT. THE CONTRACTOR IS TO ALLOW TO REMOVE AND REPLACE A PROVISIONAL QUANTITY OF UNSUITABLE SUBGRADE MATTER.
- 4. ALL SOFT, WET OR UNSUITABLE MATERIAL IS TO BE REMOVED AS DIRECTED BY THE SUPERINTENDENT AND REPLACED WITH APPROVED MATERIAL SATISFYING THE REQUIREMENTS LISTED BELOW.
- EXCAVATED MATERIAL IS NOT TO BE USED AS STRUCTURAL FILL UNLESS APPROVED BY THE GEOTECHNICAL ENGINEER.
- THE CONTRACTOR IS TO PROVIDE CERTIFICATES VERIFYING THE QUALITY OF IMPORTED MATERIAL FOR THE SUPERINTENDENTS APPROVAL.
- ALL FILL MATERIAL SHALL BE PLACED IN MAXIMUM 200mm THICK LAYERS AND COMPACTED AT OPTIMUM MOISTURE CONTENT (+ OR - 2%) TO ACHIEVE A DRY DENSITY DETERMINED IN ACCORDANCE WITH AS1289 E3.1 OF NOT LESS THAN THE FOLLOWING STANDARD MINIMUM DRY DENSITY IN ACCORDANCE WITH AS1289 E5.1.1.1:

LOCATION	COMPACTION REQUIREM
UNDER BUILDING SLABS	98% SMDD
LANDSCAPED AREAS	95% SMDD
ROADS & PAVED AREAS	100% SMDD

- FOR NON COHESIVE MATERIAL, COMPACT TO NOT LESS THAN UNDER ROAD 80% DENSITY OTHER AREA 75% DENSITY
- THE CONTRACTOR IS TO ALLOW FOR COMPACTION TESTING BY NATA REGISTERED LABORATORY FOR PLATFORMS AND FILL LAYERS IN ACCORDANCE WITH THE LATEST VERSION OF AS3798 - FOR TYPE 1 OPERATIONS (MINIMUM 3 TESTS PER LAYER).
- 9. FREQUENCY OF COMPACTION TESTING SHALL NOT BE LESS THAN: 1 TEST PER 200m³ OF FILL PLACED PER 300mm LAYER OF FILL
- 3 TESTS PER VISIT 1 TEST PER 1000m² OF EXPOSED SUBGRADE TESTING SHALL BE "LEVEL 1" UNDERTAKEN IN ACCORDANCE D.
- WITH AS1398. 10. WHERE TEST RESULTS ARE BELOW THE SPECIFIED COMPACTION, RECOMPACT AND RETEST UNTIL SPECIFIED COMPACTION STANDARD IS

ACHIEVED.

- 11. ALLOW FOR EXCAVATION IN ALL MATERIALS AS FOUND U.N.O. NO ADDITIONAL PAYMENTS WILL BE MADE FOR EXCAVATION IN WET OR HARD GROUND.
- 12. WHERE THERE IS INSUFFICIENT EXCAVATED MATERIAL SUITABLE FOR FILLING OR SUBGRADE REPLACEMENT. THE CONTRACTOR IS TO ALLOW TO
- IMPORT FILL. IMPORTED FILL SHALL COMPLY WITH THE FOLLOWING: MAXIMUM SIZE 50mm. PASSING 75 MICRON SIEVE (<25%). PLASTICITY INDEX BETWEEN 2-15% AND CBR>8.
- FREE FROM ORGANIC AND PERISHABLE MATTER. 13. REFER TO THE SITE SPECIFIC GEOTECHNICAL REPORT FOR GENERAL REQUIREMENTS ON SITE PREPARATION AND RE-USE OF EXISTING SITE

MATERIAL AS ENGINEERED FILL.

- 4. THE CONTRACTOR SHALL PROGRAM THE EARTHWORKS OPERATION SO THAT THE WORKING AREAS ARE ADEQUATELY DRAINED DURING THE PERIOD OF CONSTRUCTION. THE SURFACE SHALL BE GRADED AND SEALED OFF TO REMOVE DEPRESSIONS, ROLLER MARKS AND SIMILAR WHICH WOULD ALLOW WATER TO POND AND PENETRATE THE UNDERLYING MATERIAL. ANY DAMAGE RESULTING FROM THE CONTRACTOR NOT OBSERVING THESE REQUIREMENTS SHALL BE RECTIFIED AT THEIR COST.
- 15. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ENSURE AND MAINTAIN THE INTEGRITY OF ALL SERVICES, CONDUITS AND PIPES DURING CONSTRUCTION, SPECIFICALLY DURING THE BACKFILLING AND COMPACTION PROCEDURE. ANY AND ALL DAMAGE TO NEW OR EXISTING SERVICES AS A RESULT OF THESE WORKS SHALL BE REPAIRED BY THE CONTRACTOR AT NO EXTRA COST.
- 6. PROTECT FINAL SURFACE WITH EITHER A TEMPORARY LOOSE SOIL LAYER OR A GRANULAR SUB-BASE LAYER TO PREVENT DRYING OUT PRIOR TO ON-GROUND SLAB CONSTRUCTION.

STORMWATER DRAINAGE

- 1. ALL INTERNAL WORKS WITHIN PROPERTY BOUNDARIES ARE TO COMPLY WITH THE REQUIREMENTS OF AS 3500 3.1 AND AS/NZS 3500 3.2.
- 2. PIPES UP TO 300 DIA SHALL BE SEWER GRADE uPVC (CLASS SN4) WITH SOLVENT WELDED JOINTS.
- 3. PIPES 300 DIA. AND LARGER TO BE REINFORCED CONCRETE MIN CLASS '2'

APPROVED SPIGOT AND SOCKET WITH RUBBER RING JOINTS, U.N.O.

- 4. ALL PIPES ARE TO BE LAID AT (min) 0.5% GRADE (UNO)
- 5. EQUIVALENT STRENGTH FRC PIPES MAY BE USED TO DESIGN ENGINEER AND SUPERINTENDENTS APPROVAL.
- 6. ALL PIPES ARE TO BE UNIFORMLY SUPPORTED ALONG THE LENGTH OF THE BARREL BY SUITABLE FILL MATERIAL. REFER TO BEDDING SUPPORT TYPE.
- 7. PIPES WITH SOCKETS SHALL BE LAID IN BEDDING WHERE SUITABLE RECESSES HAVE BEEN PROVIDED TO ENSURE PIPES DO NOT BEAR ON THEIR SOCKETS.
- 8. ENLARGERS, CONNECTIONS AND JUNCTIONS TO BE PREFABRICATED FITTINGS WHERE PIPES ARE LESS THAN 300 DIA.
- 9. ALL STORMWATER DRAINAGE LINES UNDER PROPOSED BUILDING SLABS TO BE uPVC PRESSURE PIPE GRADE
- 10. ENSURE ALL VERTICALS AND DOWNPIPES ARE uPVC PRESSURE PIPE, GRADE 6 FOR A MIN OF 3.0m IN HEIGHT.
- 11. WHERE WORKING METHODS REQUIRE HIGHER CLASS PIPE. THE CONTRACTOR SHALL REFER TO AS 3725 TO DETERMINE THE APPROPRIATE PIPE CLASS. PROPOSED PIPE CLASS SHALL BE REVIEWED BY THE DESIGN ENGINEER PRIOR TO INSTALLATION.
- 12. CARE IS TO BE TAKEN WITH LEVELS OF STORMWATER LINES. GRADES SHOWN ARE NOT TO BE REDUCED WITHOUT APPROVAL.
- 13. PRECAST PITS MAY BE USED SUBJECT TO WRITTEN APPROVAL BY THE DESIGN ENGINEER.
- 14. ALL PIPE PENETRATIONS (EXISTING, IN-SITU AND PRECAST) ARE TO BE FINISHED FLUSH WITH THE INTERNAL PIT WALL AND PROPERLY SEALED WITH CEMENT RENDER. MASS CONCRETE BENCHING IS TO BE INSTALLED TO MATCH THE OUTLET PIPE INVERT LEVEL AND A LOCKABLE HINGED GRATE AND FRAME WITH CONCRETE SURROUND INSTALLED U.N.O.

15. COVERS

- USE HOT DIPPED GALVANISED GRATES AND CONCRETE FILLED COVERS WITH HINGES AND HOLD DOWN BOLTS COMPLYING WITH AS3996 AND OTHER
- AUSTRALIAN AND COUNCIL STANDARDS. ALL COVERS AND GRATES TO BE POSITIONED IN A FRAME AND MANUFACTURED AS A UNIT.
- ALL COVERS AND GRATES TO BE FITTED WITH POSITIVE COVER LIFTING KEYS. OBTAIN SUPERINTENDENT'S APPROVAL FOR THE USE OF CAST
- IRON SOLID COVERS AND GRATES. CAST IRON SOLID COVERS (IF APPROVED) TO CONSIST OF CROSS-WEBBED, CELLULAR CONSTRUCTION WITH THE RIBS UPPERMOST TO ALLOW INFILLING WITH CONCRETE. INSTALL POSITIVE COVER LIFTING KEYS AND PLASTIC PLUGS.
- UNLESS DETAILED OR SPECIFIED OTHERWISE COVERS AND GRATES TO BE CLASS "D" IN VEHICULAR PAVEMENTS AND CLASS "B" ELSEWHERE
- 16. NOTE THAT THE PIT COVER LEVEL NOMINATED IN GUTTERS ARE TO THE INVERT OF THE GUTTER WHICH ARE 40mm LOWER THAN THE PAVEMENT LEVEL AT LIP OF GUTTER.
- 17. Ø100mm SUB-SOIL DRAINAGE LINES SHALL BE CONNECTED TO A STORMWATER DRAINAGE PIT (AT min. 0.5% LONGITUDINAL GRADE) AND PROVIDED IN THE FOLLOWING LOCATIONS:
- A. ADJACENT ALL TRAFFICKED AND CARPARK PAVEMENT AREAS (BEHIND KERB);
- ALL PLANTER AND TREE BEDS PROPOSED ADJACENT TO PAVEMENT AREAS:
- BEHIND RETAINING WALLS (IN ACCORDANCE WITH DRAWINGS); BELOW ALL TRAFFICABLE DISH DRAINS;

ALL OTHER AREAS SHOWN ON THE DRAWINGS.

18. THE CONTRACTOR SHALL INSTALL FLUSHING POINTS TO ALL SUBSOIL DRAINAGE LINES AND DOWNPIPE LINES AS SPECIFIED ON DRAWINGS, AT

MAXIMUM 60m CENTRES AND AT ALL UPSTREAM ENDPOINTS.

- 19. PROVIDE 3.0m LENGTH OF Ø100 SUBSOIL DRAINAGE PIPE WRAPPED IN A NON-WOVEN GEOTEXTILE FABRIC, TO THE UPSTREAM SIDE OF STORMWATER PITS, LAID IN STORMWATER PIPE TRENCHES AND CONNECTED TO THE DRAINAGE PIT.
- 1) SUBSOIL TRENCHES SHALL BE BACKFILLED WITH SINGLE SIZED 10MM AGGREGATE WRAPED IN NON-WOVEN GEOTEXTILE FABRIC. SUBSOIL TRENCHES BELOW TRAFFICABLE PAVEMENTS SHALL BE BACKFILLED WITH NO FINES CONCRETE WRAPPED IN NON-WOVEN GEOTEXTILE FABRIC, U.N.O.
- 20. ALL RECTANGULAR HOLLOW SECTIONS (RHS) SPECIFIED AS STORMWATER CONDUITS TO BE HOT DIPPED GALVANISED AND HAVE (MINIMUM) 5mm WALL THICKNESS.
- 21. ALL BOX CULVERTS SHALL BE STRUCTURALLY DESIGNED BY THE MANUFACTURER AND DELIVERED TO SITE AS FIT FOR PURPOSE.
- 22. ELECTRICAL PITS ARE TO DRAIN TO THE NEAREST STORMWATER PIT WITH VERMIN PROOF NON-RETURN FLAP VALVES AS REQUIRED. THE CONTRACTOR IS TO CONFIRM WITH THE ELECTRICAL DESIGNER AS PART OF THE TENDER.

STORMWATER DRAINAGE (CONT.)


- 23. THE CONTRACTOR SHALL ENSURE AND PROTECT THE INTEGRITY OF ALL STORMWATER PIPES DURING CONSTRUCTION, ANY AND ALL DAMAGE TO THESE PIPES AS A RESULT OF THESE WORKS SHALL BE REPAIRED BY THE CONTRACTOR UNDER THE DIRECTION OF THE SUPERINTENDENT, AND AT NO EXTRA COST.
- 23. AT ALL TIMES DURING CONSTRUCTION OF STORMWATER PITS, ADEQUATE SAFETY PROCEDURES SHALL BE TAKEN TO ENSURE AGAINST THE POSSIBILITY OF PERSONNEL FALLING DOWN PITS.
- 24. ALL EXISTING STORMWATER DRAINAGE LINES AND PITS THAT ARE TO REMAIN ARE TO BE INSPECTED AND CLEANED. DURING THIS PROCESS ANY PART OF THE STORMWATER DRAINAGE SYSTEM THAT WARRANTS REPAIR SHALL BE REPORTED TO THE SUPERINTENDENT/ENGINEER FOR FURTHER DIRECTIONS.
- 25. ANY VARIATION TO SPECIFIED PRODUCTS OR DETAILS SHALL BE REFERRED TO THE DESIGN ENGINEER FOR APPROVAL. DOWN PITS.

20/10/2022 ISSUED FOR DEVELOPMENT APPLICATION CB | MKH | MKH | MKH FR | MKH | MKH | MKH B |30/06/2022| AMENDMENTS TO ADDRESS COUNCIL COMMENTS - DA ISSUE 2 | 22/03/2022 | AMENDMENTS TO ADDRESS COUNCIL COMMENTS - DA ISSUE MDH | MKH | MKH | MKH MDH DL MKH MKH 1 | 22/10/2021 | ISSUED FOR DEVELOPMENT APPLICATION DRN. DES. VERIF. APPI EV. DATE DESCRIPTION



Enspire Solutions Pty Ltd

Phone: 02 9922 6135



ERSKINE PARK INDUSTRIAL ESTATE OCKWOOD ROAD, ERSKINE PARK OTS 2, 3, 4 AND 5 GENERAL NOTES


19/04/2021


FOR APPROVAL NOT TO BE USED FOR CONSTRUCTION oject Number/Drawing Number


190050-05-DA2-C01.21


MGA2020


N.T.S



















- MIN CBR 3.0% (CONTRACTOR TO CONFIRM ONSITE).
- DESIGN LOADING = 1x10⁷ESA's
- PRIME AND TACK COAT BASECOURSE SURFACE PRIOR TO PLACEMENT OF AC WEARING COURSE.




CARPARK FLEXIBLE PAVEMENT

- SCALE 1:10 1. MIN CBR 3.0% (CONTRACTOR TO CONFIRM ONSITE).
- DESIGN LOADING = 5x10⁵ ESA's
- PRIME AND TACK COAT BASECOURSE SURFACE PRIOR TO PLACEMENT OF AC WEARING COURSE.




TYPICAL PIPE TRENCH - UNDER ROADS

- 1. TRENCH WIDTH MAY NEED TO BE INCREASED SUBJECT TO ACHIEVING COMPACTION. ENSURE MINIMUM 300mmCLEARANCE BETWEEN, WHEN USING MULTIPLE PIPES TO ACHIEVE ADEQUATE COMPACTION.
- 2. MINIMUM PIPE COVER UNDER ROADS TO BE 600mm U.N.O. FOR CLASS '2' PIPES.
- 3. THE CONTRACTOR SHALL ENSURE THAT SHORING OF TRENCHES IS INSTALLED AS REQUIRED BY STATUTORY REQUIREMENTS.
- 4. ENSURE BACKFILLING COMPACTION MEETS THE FOLLOWING STANDARDS;
- 4.1 TRENCHES UNDER PAVED AREAS / BUILDING 100% SMDD



CONCRETE FOOTPATH



1. COUNCIL'S STANDARDS SHOWN ON PENRITH CITY COUNCIL STANDARD DRAWINGS SD1001, SD1002, SD1003/1, SD1003/2, SD1004, SD2001/1, SD2001/2, SD2001/3, SD2003 AND SD2004 ARE TO BE USED UNLESS NOTED OTHERWISE.

GRATE AND FRAME CLASS 'D' PROVIDE MIN 1% FALL BOLT DOWN. TO OUTLET (U.N.O)	AND FRAME
PAVEMENT AS SPECIFIED NIM (1) OWN (1)	MORTAR BEDDING R10-450
2 75 L 450 L 200 NO	5N12
$\mathbb{E}_{\mathcal{E}} = \frac{75m}{MIN} = \frac{150m}{(TYP)} = \frac{200 \text{ NON}}{150m}$	M 150m 75m (TYP) MIN
GRATED TRENCH	DRAIN (GTD)
SCALE 1:10	0


\vdash			1	ı			
							Cli
4	20/10/2022	ISSUED FOR DEVELOPMENT APPLICATION	СВ	MKH	MKH	MKH	
3	30/06/2022	AMENDMENTS TO ADDRESS COUNCIL COMMENTS - DA ISSUE	FR	MKH	MKH	MKH	
2	22/03/2022	AMENDMENTS TO ADDRESS COUNCIL COMMENTS - DA ISSUE	MDH	MKH	MKH	MKH	
1	22/10/2021	ISSUED FOR DEVELOPMENT APPLICATION	MDH	DL	MKH	MKH	
REV.	DATE	DESCRIPTION	DRN.	DES.	VERIF.	APPD.	





S	cale	0	200	400	600	800	1000mm	North	
		SCALE 1:1	0				@A1		
		0	500	10	000	1500	2000mm		5
		SCALE 1:20	0				@A1		Enspire Solutions Pty Ltd Level 4, 153 Walker Stree
			his drawing re ssion of Ensp			Solutions Pty I	_td and must no	ot be copied wholly or in part	ABN: 71 624 801 690 Phone: 02 9922 6135


	enspire	PELLT
	Enspire Solutions Pty Ltd Level 4, 153 Walker Street, North Sydney NSW 2060	S
art	ADN: 71 604 901 600	

				4:45 PI
roject	Scale	Status		2022
RSKINE PARK INDUSTRIAL ESTATE	AS SHOWN	FOR APPROVAL		
OCKWOOD ROAD, ERSKINE PARK	Date			October
OTS 2, 3, 4 AND 5	19/04/2021	NOT TO BE USED FOR CONSTRUCTION		
itle	Size	Project Number/Drawing Number	Revision	Ë
SITEWORKS DETAILS	A1	100050 05 040 044 04	1	10.
	Datum	190050-05-DA2-C14.01	4	Ы
	MGA2020			DATE














							Client
4	20/10/2022	ISSUED FOR DEVELOPMENT APPLICATION	СВ	MKH	MKH	MKH	
3	30/06/2022	AMENDMENTS TO ADDRESS COUNCIL COMMENTS - DA ISSUE	FR	MKH	MKH	MKH	
2	22/03/2022	AMENDMENTS TO ADDRESS COUNCIL COMMENTS - DA ISSUE	MDH	MKH	MKH	MKH	
1	22/10/2021	ISSUED FOR DEVELOPMENT APPLICATION	MDH	DL	MKH	MKH	
REV.	DATE	DESCRIPTION	DRN.	DES.	VERIF.	APPD.	

Fitzpatrick Investments







pire	Project ERSKINE PAI LOCKWOOD LOTS 2, 3, 4 /
ey NSW 2060	Title TURNING PA
	SHEET 01

ect SKINE PARK INDUSTRIAL ESTATE	Scale 1:250	Status FOR A DDD OVAL		
CKWOOD ROAD, ERSKINE PARK TS 2, 3, 4 AND 5	Date 19/04/2021	FOR APPROVAL NOT TO BE USED FOR CONSTRUCTIO		
RNING PATH PLAN	Size A1	,	Revision	
EET 01	Datum MGA2020	190050-05-DA2-C22.01	 4 	

B-DOUBLE (26m)

OVERALL BODY HEIGHT

LOCK-TO-LOCK TIME

TRAVELLING SPEED

MIN BODY GROUND CLEARANCE

CURB TO CURB TURNING RADIUS

OVERALL LENGTH

OVERALL WIDTH

TRACK WIDTH

VEHICLE PROFILE

26.00m

2.500m

4.300m 0.540m

2.500m

6.00s

23.400m

15 km/h

SAFETY IN DESIGN REPORT

INTRODUCTION

ENSPIRE HAS BEEN APPOINTED BY FITZPATRICK INVESTMENTS PTY LTD TO PREPARE DESIGN DOCUMENTATION FOR ROADS, STORMWATER PIT AND PIPE INFRASTRUCTURE, SERVICES AND SEDIMENT BASIN FOR ERSKINE PARK INDUSTRIAL ESTATE. THIS SAFETY IN DESIGN REPORT HAS BEEN DEVELOPED IN PARALLEL WITH THE DESIGN TO IDENTIFY POTENTIAL HAZARDS TO WORK HEALTH AND SAFETY AND DEVELOP RISK ASSESSMENT METHODS TO POTENTIALLY REDUCE THE LIKELIHOOD AND SEVERITY OF HAZARDS.

THIS SAFETY IN DESIGN REPORT HAS BEEN PREPARED IN ACCORDANCE WITH THE REQUIREMENTS OF THE WORK HEALTH AND SAFETY ACT 2011 AND THE WORK HEALTH AND SAFETY REGULATION PART 6.2 CLAUSE 295. UNDER THE WORK HEALTH AND SAFETY ACT DESIGNERS HAVE THE RESPONSIBILITY TO ENSURE THEIR DESIGN ELIMINATES OR MINIMISES RISKS TO HEALTH AND SAFETY AND GIVE ADEQUATE INFORMATION TO PEOPLE COMMISSIONING THE DESIGN AND UNDERTAKING CONSTRUCTION, OPERATION AND MAINTENANCE ACTIVITIES BASED ON THE DESIGN.

THIS REPORT SPECIFIES POTENTIAL HEALTH AND SAFETY RISKS AND HAZARDS ASSOCIATED WITH THE DESIGN ELEMENTS DOCUMENTED IN THIS DRAWING PACKAGE TO RELEVANT PERSONNEL DURING THE DESIGN, CONSTRUCTION, OPERATION AND MAINTENANCE PROCESS AND ASSESSES THEIR LIKELIHOOD AND CONSEQUENCES. THIS REPORT PROPOSES ACTIONS AND STRATEGIES AGAINST RISKS IDENTIFIED TO ACHIEVE EFFECTIVE MITIGATION OF THE RISKS AND HAZARDS, AND ASSESSES RESIDUAL RISKS BASED ON CONTROL MEASURES BEING IMPLEMENTED. ANY SAFETY ISSUES UNRESOLVED THROUGH DESIGN ARE ALSO IDENTIFIED FOR THEIR APPROPRIATE MANAGEMENT.

THE INFORMATION CONTAINED IN THIS SAFETY IN DESIGN REPORT HAS BEEN PREPARED PRIOR TO THE COMMENCEMENT OF THE WORK ON SITE. IT DOES NOT TAKE ACCOUNT OF ANY MATTERS OR INFORMATION WHICH MAY COME TO LIGHT AFTER THAT TIME. WHEN A DESIGN IS ALTERED, AN ADDITIONAL REVIEW MUST BE CONDUCTED TO ENSURE NEW RISKS HAVE BEEN CAPTURED DUE TO MODIFICATION OF THE DESIGN. ADDITIONALLY, CLIENTS ARE REQUIRED TO INFORM ENSPIRE OF ANY EXISTING RISKS AND HAZARDS IN THE AREA WHERE CONSTRUCTION WILL TAKE PLACE.

THE RISKS IDENTIFIED IN THIS SAFETY IN DESIGN REPORT ARE PROJECT AND DESIGN SPECIFIC RISKS WHICH WOULD NOT BE EASILY RECOGNIZED BY A REASONABLY COMPETENT STAKEHOLDER. IT DOES NOT ADDRESS THE COMMON-PLACE HAZARDS OR HAZARDS WHERE KNOWN SOLUTIONS APPLY, AND WHICH ARE ASSOCIATED WITH CONSTRUCTION, OPERATION AND MAINTENANCE GENERALLY. THESE COMMON-PLACE HAZARDS MUST BE CONTROLLED BY THE APPLICATION OF NORMAL GOOD MANAGEMENT PRACTICES.

THIS DESIGN REPORT ASSUMES THAT DURING CONSTRUCTION, OPERATION AND MAINTENANCE OF THE DEVELOPMENT, THE PRINCIPAL WILL ENGAGE EXPERIENCED AND COMPETENT PERSONNEL AS PART OF THE RESPECTIVE TENDER EVALUATION PROCESS. IT IS THE HEAD CONTRACTOR'S OBLIGATION TO PREPARE AND IMPLEMENT SITE SPECIFIC WORK HEALTH AND SAFETY MANAGEMENT PLANS TO MITIGATE COMMON RISKS ASSOCIATED WITH GENERAL CONSTRUCTION AND OPERATION ACTIVITIES IN ACCORDANCE WITH THE WORK HEALTH AND SAFETY ACT 2011.

PROPOSED WORKS

THE SCOPE OF THE MAIN ACTIVITIES INVOLVED IN THESE WORKS ARE:

- DESIGN OF ROADS, STORMWATER INFRASTRUCTURE AND SERVICES;
- CONSTRUCTION OF ROADS, STORMWATER INFRASTRUCTURE AND SERVICES;
- SITE VISITS AND INSPECTIONS;
- POST CONSTRUCTION OPERATION AND MAINTENANCE.

INFORMATION TRANSFER

SAFETY IN DESIGN RELIES ON EFFECTIVE DOCUMENTATION AND COMMUNICATION BETWEEN EVERYONE INVOLVED IN THE LIFE CYCLE OF THE DESIGN ELEMENTS. IN ACCORDANCE WITH THE WORK HEALTH AND SAFETY REGULATION 2017, THE DESIGNER MUST PROVIDE A COPY OF THIS SAFETY IN DESIGN REPORT TO THE PRINCIPAL CONTRACTOR IN PARALLEL WITH THE COMPLETED DESIGN DOCUMENTATION AND ENSURE THAT THE FOLLOWING ACTIONS ARE UNDERTAKEN:

- ONSITE SAFETY INDUCTIONS, INCLUDING HAZARDS IDENTIFIED IN THIS REPORT, SHOULD BE CONDUCTED FOR ALL STAFF;
- SAFETY MANAGEMENT PLANS SHOULD BE PREPARED FOR THE HAZARDS IDENTIFIED IN THIS REPORT;
- THERE SHOULD BE NO VARIATION ON DESIGN REQUIREMENTS WITHOUT CONSULTATION WITH THE ORIGINAL DESIGNERS; ONSITE MANAGEMENT OF CONTRACTORS TO ENSURE THAT HAZARDS THAT ARISE THROUGH STARTING/COMPLETION OF JOBS DOES NOT OCCUR: AND
- THIS DESIGN MAY INTERFACE WITH OTHER PLANS AND ACCOUNT SHOULD BE TAKEN OF ANY INTERFACE ISSUES.

IT IS RECOMMENDED THAT THIS SAFETY IN DESIGN REPORT BE PASSED ONTO ANY PARTICIPANT IN THE PROJECT WHO MAY EXTEND THE DESIGN OR FURTHER DEVELOP THE DESIGN.

SAFE DESIGN PROCESS

A SAFE DESIGN PROCESS SHOULD BE ENGAGED EARLY IN THE DEVELOPMENT OF THE DESIGN TO IDENTIFY ALL CONCEIVABLE RISKS AND HAZARDS THAT MAY AFFECT THE FUNDAMENTALS OF THE DESIGN AND AVOID UNNECESSARY REWORK. IT SHOULD BE IMPLEMENTED THROUGH A STRUCTURED APPROACH ACROSS EACH PHASE OF THE DESIGN PROCESS.

DELIVERY OF SAFE DESIGN FOR EACH DESIGN PHASE OF THE PROJECT HAS BEEN CARRIED OUT FOLLOWING THE STEPS BELOW:

- STEP 1: PRELIMINARY RISK IDENTIFICATION

THE DESIGNER/DESIGN TEAM TO CONDUCT A PRELIMINARY ASSESSMENT AND IDENTIFY ANY POTENTIAL RISKS RELEVANT TO THE SCOPE OF DESIGN WORKS. WITH PROJECTS INVOLVING MULTIPLE DISCIPLINES, THE DESIGNER/DESIGN TEAM TO ATTEND SAFETY IN DESIGN WORKSHOP AND IDENTIFY RISKS IN CONSULTATION WITH OTHER KEY PROJECT STAKEHOLDERS.

STEP 2: RISK ASSESSMENT AND MITIGATION

THE DESIGNER/DESIGN TEAM TO ASSESS THE LIKELIHOOD AND SEVERITY OF EACH HAZARD AND DEVELOP CONTROLS AND MEASURES TO ELIMINATE OR MINIMISE THE CONSEQUENCES OF THE HAZARD. STEP 3: VERIFICATION

ENSPIRE TO PERFORM INTERNAL VERIFICATION ON THE SAFE DESIGN RISK REGISTER PRIOR TO ISSUING TO THE CONTRACTOR AND CLIENT. STEP 4: REVIEW DESIGN

THE DESIGNER/DESIGN TEAM TO IDENTIFY ANY ALTERATIONS IN DESIGN AND REVIEW AND UPDATE RISK REGISTER ACCORDINGLY.

PROJECT REPRESENTATIVES								
ORGANISATION	PROJECT ROLE	MAIN CONTACT	CONTACT DETAILS					
FITZPATRICK INVESTMENTS PTY LTD	DEVELOPMENT PROPONENT	PHILIP GRECH	TEL: (02) 8117 5284 EMAIL: philipg@fitzpatrickproperty.com.au ADD: 22-24 JUNCTION STREET FOREST LODGE NSW 2037					
ENSPIRE SOLUTIONS	CIVIL DESIGN CONSULTANT	MICHAEL HODGES	TEL: 9922 6135 EMAIL: michael.hodges@enspiresolutions.com.au ADD: LEVEL 4, 153 WALKER STREET NORTH SYDNEY NSW 2060					

	QUALITATIVE MEASURES OF LIKELIHOOD OR FREQUENCY									
LEVEL	MEASURE	CRITERIA								
1	RARE	WOULD ONLY OCCUR IN HIGHLY EXCEPTIONAL CIRCUMSTANCES THAT ARE UNLIKELY TO EXIST IN ANY PHASE OF THE DEVELOPMENT'S LIFECYCLE PERIOD. EXTREMELY REMOTE CHANCE OF OCCURRENCE IN DEVELOPMENT'S LIFECYCLE PERIOD. 'ONCE IN A LIFETIME' EVENT.								
2	UNLIKELY	NOT LIKELY TO OCCUR IN THE DEVELOPMENT'S LIFECYCLE PERIOD. A SMALL, BUT REMOTE CHANCE OF OCCURRENCE DUE TO CIRCUMSTANCES / SITUATIONS THAT COULD ARISE.								
3	POSSIBLE	LIKELY TO OCCUR AT LEAST ONCE BUT NOT EXPECTED TO OCCUR MUCH MORE THAT THIS IN THE DEVELOPMENT'S LIFECYCLE PERIOD.								
4	LIKELY	LIKELY TO OCCUR MORE THAN ONCE IN THE DEVELOPMENT'S LIFECYCLE PERIOD BUT NOT AN 'EVERYDAY' OCCURRENCE. PRECONDITIONS WILL ARISE AT TIMES THROUGHOUT THE PERIOD.								
5	ALMOST CERTAIN	WILL OCCUR. CIRCUMSTANCES OR SITUATIONS ARE LIKELY TO ARISE OFTEN THROUGHOUT THE DEVELOPMENT'S LIFECYCLE PERIOD WHICH PROVIDES THE OPPORTUNITY FOR CRYSTALLISATION OF RISK. EXPECT FREQUENT, REGULAR OCCURRENCES.								

C	QUALITATIVE MEASURES OF IMPACT - CONSEQUENCE SEVERITY							
LEVEL	MEASURE	CRITERIA						
1	INSIGNIFICANT	NO INJURIES; NO ENVIRONMENTAL IMPACT.						
2	MINOR	FIRST AID; ENVIRONMENTAL RELEASE IMMEDIATELY CONTAINED.						
3	MODERATE	MEDICAL TREATMENT; ENVIRONMENTAL RELEASE NOT IMMEDIATELY CONTAINED WITH NO DETRIMENTAL EFFECTS.						
4	MAJOR	LOST TIME AND/OR LONG-TERM INJURY/ILLNESS; ENVIRONMENTAL RELEASE NOT IMMEDIATELY CONTAINED WITH TOXIC EFFECTS.						
5	CATASTROPHIC	FATALITY; RELEASE TO THE ENVIRONMENT WITH LONG TERM OR PERMANENT TOXIC EFFECTS.						

	MATRIX FO	OR	DETER	MINATI	ON OF	RISK LE	VEL	
	CATASTROPHIC	(5)	HIGH	VERY HIGH	VERY HIGH	VERY HIGH	VERY HIGH	
.NCE	MAJOR	(4)	HIGH	HIGH	VERY HIGH	VERY HIGH	VERY HIGH	
CONSEQUENCE	MODERATE	(3)	MODERATE	MODERATE	HIGH	HIGH	VERY HIGH	
NOS	MINOR	(2)	LOW	LOW	MODERATE	HIGH	VERY HIGH	
	INSIGNIFICANT		LOW	LOW	LOW	MODERATE	HIGH	
			RARE (1)	UNLIKELY (2)	POSSIBLE (3)	LIKELY (4)	ALMOST CERTAIN (5)	
			LIKELIHOOD					

	INITIAL RISK			RESIDUAL RISK								
ITEM	ACTIVITY	HAZARD	STAGE	LIKELIHOOD	CONSEQUENCE	RISK LEVEL	DESIGN ACTION		CONSEQUENCE	RISK LEVEL	PERSON RESPONSIBLE FOR CONTROLS	STATUS
1	SEDIMENT BASIN OPERATION	FALLING INTO BASIN WHICH HOLDS WATER	CONSTRUCTION	2	5	VERY HIGH	- PROVIDE MAN-PROOF FENCE TO PERIMETER MAINTAIN WATER LEVELS IN BASIN MINIMISE PERMANENT WATER DEPTH.	2	3	MODERATE	CONTRACTOR	ACTION ASSIGNED
2	TREE REMOVAL	- FALL FROM HEIGHT - CRUSH INJURY FROM FALLING TREE	CONSTRUCTION	2	5	VERY HIGH	- CERTIFIED ARBORIST USING BEST PRACTICES RESPONSIBLE FOR TREE REMOVAL.	2	3	MODERATE	CONTRACTOR	ACTION ASSIGNED
3	PIPE TRENCHING	FALL INTO DEEP EXCAVATIONS	CONSTRUCTION	1	4	HIGH	- PROVIDE SAFETY BARRIERS - PROVIDE BENCHING	1	2	LOW	CONTRACTOR	ACTION ASSIGNED
4	RETAINING WALL CONSTRUCTION	CRUSHING INJURY	CONSTRUCTION	2	5	VERY HIGH	- APPROPRIATE RETAINING WALL SYSTEM SPECIFIED TO MINIMISE HANDLING RETAINED HEIGHT ASSUMES NO LATERAL RESTRAINT AT LOW SIDE OF WALL PRIOR TO FORMATION OF FINISHED SURFACE LEVEL.	1	3	MODERATE	CONTRACTOR	ACTION ASSIGNED
5	WORKING ADJACENT TO EXISTING LOCKWOOD ROAD AND COMPASS DRIVE	COLLISION WITH ONGOING TRAFFIC	CONSTRUCTION	3	5	VERY HIGH	- APPLY WORK BARRICADES/TRAFFIC MANAGEMENT CONTROLS AT LOCKWOOD ROAD INTERSECTION WITH DISTRIBUTION DRIVE WHEN AVAILABLE, WORK DURING LOW TRAFFIC TIMES CONTRACTOR TO OBTAIN AND CARRY OUT APPROVED TRAFFIC MANAGEMENT CONTROLS AS NOTED IN ENSPIRE'S GENERAL NOTES AND LEGENDS 190050-05-DA-C01.21 INSTALL TRAFFIC BARRIER TO COMPASS DRIVE (WEST SIDE).	1	4	HIGH	CONTRACTOR	ACTION ASSIGNED

4	20/10/2022	ISSUED FOR DEVELOPMENT APPLICATION	СВ	MKH	MKH	MKH
3	30/06/2022	AMENDMENTS TO ADDRESS COUNCIL COMMENTS - DA ISSUE	FR	MKH	MKH	MKH
2	22/03/2022	AMENDMENTS TO ADDRESS COUNCIL COMMENTS - DA ISSUE	MDH	MKH	MKH	MKH
1	22/10/2021	ISSUED FOR DEVELOPMENT APPLICATION	MDH	DL	MKH	MKH
REV.	DATE	DESCRIPTION	DRN.	DES.	VERIF.	APPI



ale	North	enspire Solutions Pty Ltd
ne copyright of this drawing remains with Enspire Solutions Pty Ltd and must not ithout the permission of Enspire Solutions Pty Ltd.	Level 4, 153 Walker Street, North Sydney NSW 2060 ABN: 71 624 801 690 Phone: 02 9922 6135	

				9,
Project	Scale	Status		8
ERSKINE PARK INDUSTRIAL ESTATE		FOR APPROVAL		1
LOCKWOOD ROAD, ERSKINE PARK	PARK NOT TO BE LIGED FOR CONS			
LOTS 2, 3, 4 AND 5	19/04/2021	NOT TO BE USED FOR CONSTRUCTION		,
Title	Size	Project Number/Drawing Number	Revision	1
SAFETY IN DESIGN	A1	1000E0 0E DA2 C22 01	l ,	ļ
	Datum	190050-05-DA2-C23.01	4	[
	MGA2020			j