BROKEN HILL POLICE STATION

STORMWATER DRAINAGE CONCEPT PLAN

AUTHORITY STORMWATER NOTES:

- 1. IT IS THE CONTRACTOR'S RESPONSIBILITY TO CHECK ALL SET OUT AND LEVEL PRIOR TO COMMENCEMENT OF WORKS AND TO REPORT ANY DISCREPANCIES FOUND TO THE SUPERINTENDENT.
- 2. ALL SET OUT DIMENSIONS ARE TO FACE OF KERB, CENTRELINE OF FENCE/BOLARD/PIPE.
- 3. SMOOTH ALL TRANSITION BETWEEN NEW AND EXISTING WORK IN BOTH LEVEL AND ALIGNMENT.
- 4. IT IS THE CONTRACTOR'S RESPONSIBILITY TO PROVIDE ALL SAFETY FENCES, WARNING SIGNS, TRAFFIC DIVERSIONS AND THE LIKE DURING CONSTRUCTION. ALL WORKS TO COMPLY WITH OCCUPATIONAL HEALTH AND SAFETY REQUIREMENTS AND OTHER RELEVANT AUTHORITY SAFETY REQUIREMENTS.
- 5. NO TREES SHALL BE REMOVED, CUTBACK OR RELOCATED WITHOUT THE WRITTEN INSTRUCTION FROM THE SUPERINTENDENT.
- 6. THE CONTRACTOR SHALL PROVIDE CERTIFICATION AND COMPACTIONS AND PAVEMENT THICKNESS FROM A NATA REGISTERED TESTING AUTHORITY MINIMUM THREE TESTS PER LAYER AS FOLLOWS

MINIMUM THREE TESTS PER LAYER AS FOLLOWS
PIPE BACKFILL
SELECT FILL
SELECT FILL (LESS THAN 300mm)

DENSITY INDEX 75
95% STANDARD

FOLLOW BASE COURSE) 98% MODIFIED BASE COURSE 100% MODIFIED

7. THE AUSPEC SPECIFICATION SHALL BE THE SPECIFICATION FOR THESE WORKS.

DRAINAGE NOTES:

ALL PIPES TO BE LAID ON 75mm SAND BED WITH THE BARRELS FULLY SUPPORTED.

100mm AND 150mm DIAMETER PIPES TO BE LAID ON MINIMUM 1% GRADE.

MINIMUM DEPTH OF COVER FOR PIPES NOT SUBJECT TO VEHICULAR LOADING TO BE 300mm

ALL DRAINAGE PIPES LAID UNDER PAVEMENT SHALL BE REINFORCED CONCRETE WITH RUBBER RING JOINTS.

BACKFILL TRENCHES WITH COMPACTED SAND OR APPROVED AGGREGATE MATERIAL.

ALL PITS TO HAVE 600 x 600mm INTERNAL DIMENSIONS (U.N.O).

SILT ARRESTORS TO HAVE 900 x 900mm INTERNAL DIMENSIONS.

HEAVY DUTY GRATES AND COVERS ARE TO BE PROVIDED IN TRAFFICABLE AREAS.

PIT GRATE TO BE TYPE WELDLOK OR APPROVED EQUIVALENT.

ALL PITS SHALL BE PROVIDED WITH A LOCKING LIP.

ALL PITS SHALL BE MAINTAINED REGULARLY.

TOP OF BENCHING SHALL BE TO THE HALF OF THE OUTLET PIPE DIAMETER.

MAXIMUM FRONT ENTRY PIPE:-STRAIGHT ENTRY - ϕ 750

SKEW ENTRY - Ø525

 ϕ 100 SUBSOIL DRAINAGE PIPE 3000mm LONG WRAPPED IN FABRIC SOCK TO BE PROVIDED ADJACENT TO INLET PIPES.

COMPRESSIVE STRENGTH f'c FOR CAST IN SITU CONCRETE TO BE A MINIMUM OF 32 MPa AT 28 DAYS.

PROVIDE CLEANING EYES TO ALL DOWNPIPES NOT DIRECTLY CONNECTED TO PITS.

ISOLATED JOINTS TO BE PROVIDED TO ISOLATE CONCRETE PAVEMENTS FROM PITS.

ALL TRENCH GRATES PROVIDED SHALL HAVE MINIMUM CLEAR WIDTH OF 200mm.

STORMWATER DRAINAGE CONNECTIONS TO THE MAIN SYSTEM SHALL BE TO THE

REQUIREMENTS AND THE SATISFACTION OF LOCAL COUNCIL.

THESE STORMWATER DRAWINGS SHALL BE IN ACCORDANCE WITH AS 3500.3 AND

LOCAL COUNCIL REQUIREMENTS.

PROVIDE HEEL GUARD TO ALL PIT LIDS AND GRATED TRENCH LIDS AT PEDESTRIAN

ALL REINFORCED CONCRETE PIPES ARE TO BE CLASS 2 STRENGTH U.N.O.



DRAWING REGISTER				
NO.	TITLE	REV.		
SW.01	COVER SHEET	А		
SW.02	GROUND FLOOR DRAINAGE CONCEPT PLAN	А		
SW.03	STORMWATER DRAINAGE DETAILS	А		
SE.01	SOIL EROSION AND SEDIMENT CONTROL PLAN	А		
SE.02	SOIL EROSION AND SEDIMENT CONTROL DETAILS	А		

ABBREVIATIONS

CALIFORNIA BEARING RATIO CHAINAGE CENTRE LINE CLEAR OUT DISH CROSSING DISH DRAIN OUTLET DOWELLED EXPANSION JOINT DENSE GRADED BASECOURSE DENSE GRADED SUB-BASE EXISTING FINISHED FLOOR LEVEL GRATED TRENCH DRAIN GRATED SURFACE INLET PIT HYDRANT ISOLATING JOINT INTEGRAL KERB INVERT LEVEL INTERSECTION POINT KERB INLET PIT KERB ONLY KERB & GUTTER KERB RETURN LONGITUDINAL SECTION NATURAL GROUND LEVEL OVERLAND FLOW PATH ON-SITE DETENTION REINFORCED CONCRETE PIPE ROLL KERB & GUTTER REDUCED LEVEL RETAINING WALL RAINWATER TANK SAWN CONTROL JOINT SEWER MAN HOLE STORMWATER STORMWATER PIT STORMWATER RISING MAIN STORMWATER SUMP SWS STOP VALVE SV TOK TOP OF KERB TOW TOP OF WALL ΤP TANGENT POINT

UNPLASTICISED POLYVINYL CHRLORIDE


UNLESS NOTED OTHERWISE

WEAKENED PLANE JOINT



PRELIMINARY ISSUE


NOT FOR CONSTRUCTION




GROUND DRAINAGE CONCEPT PLAN

SCALE 1:200

NOTE: PIT AND PIPE SIZES TO BE CONFIRMED.









BROKEN HILL POLICE STATION

GROUND FLOOR
DRAINAGE CONCEPT PLAN

scales as noted @ A1			DATE APR , 2020			
DRAWN C.KE	DESIGN C.A	VERIFIED _		APPROVED		
REPRODUCTION OF THIS DRAWING IS PROHIBITED WITHOUT THE CONSENT OF BIRZULIS ASSOCIATES PTY. LTI						

PROJECT No.


A


7800

DRAWING No.


SW.02












SOIL EROSION AND SEDIMENT CONTROL PLAN SCALE 1:200

SERVICES ON THIS DRAWING ARE SHOWN BELOW SLAB U.N.O.



GENERAL NOTES.

- THIS PLAN IS A CONCEPT PLAN ONLY FOR STORMWATER DISPOSAL & EROSION CONTROL. IT IS NOT SUITABLE FOR CONSTRUCTION. THIS PLAN SHOULD BE ADAPTED BY THE BUILDER DURING DEMOLITION, EXCAVATION & CONSTRUCTION PHASES TO ENSURE ADEQUATE PERFORMANCE
- ALL DRAINAGE LAYOUT & DETAILS ARE DIAGRAMMATIC & INDICATIVE ONLY. ACTUAL LOCATION, SIZES, LEVELS & GRADES MAY LATER WHEN DETAIL DESIGN WORKS ARE DOCUMENTED.

CLAY SOILS


A SYSTEM SHALL BE INSTALLED TO EITHER:

- TRANSPORT STORMWATER RUNOFF WITH SUSPENDED SOLIDS FROM SITE VIA PUMP TRUCKS.
- TREAT THE STORMWATER RUNOFF WITH SUSPENDED SOLIDS SO THE DISCHARGE WATER QUALITY TO COUNCIL STORMWATER DRAINAGE SYSTEM HAS A MAXIMUM CONCENTRATION OF SUSPENDED SOLIDS THAT DOES NOT EXCEED 50 MILLIGRAMS PER LITRE IN ACCORDANCE WITH THE PROTECTION OF THE ENVIRONMENT OPERATION ACT (POEO 1997) AND SHALL BE APPROVED BY THE LOCAL COUNCIL.

EROSION & SEDIMENTATION CONTROL NOTES

- CONTRACTOR SHALL PROVIDE SEDIMENT FENCING MATERIAL DURING CONSTRUCTION TO THE LOW SIDE OF THE WORKS. TIE SEDIMENT FENCING MATERIAL TO CYCLONE WIRE SECURITY FENCE. SEDIMENT CONTROL FABRIC SHALL BE AN APPROVED MATERIAL (EG. HUMES PROPEX SILT STOP) STANDING 300mm ABOVE GROUND & EXTENDING 150mm BELOW GROUND.
- EXISTING DRAINS LOCATED WITHIN THE SITE SHALL ALSO BE ISOLATED BY SEDIMENT FENCING MATERIAL
- NO PARKING OR STOCKPILING OF MATERIAL IS PERMITTED ON THE LOWER SIDE OF THE SEDIMENT
- GRASS VERGES SHALL BE MAINTAINED AS MUCH AS PRACTICAL TO PROVIDE A BUFFER ZONE TO THE CONSTRUCTION SITE.
- CONSTRUCTION ENTRY/EXIT SHALL BE VIA THE LOCATION NOTED ON THE DRAWING. CONTRACTOR SHALL ENSURE ALL DROPPABLE SOIL & SEDIMENT IS REMOVED PRIOR TO CONSTRUCTION TRAFFIC EXITING SITE. CONTRACTOR SHALL ENSURE ALL CONSTRUCTION TRAFFIC ENTERING & LEAVING THE SITE DO SO IN A FORWARD DIRECTION.

PRELIMINARY ISSUE NOT FOR CONSTRUCTION



GARDNER WETHERILL ASSOCIATES T (02) 9929 6777 F (02) 9929 3999 E design@gardnerwetherill.com.au LEVEL 2 Suite 2.01




CONSULTING STRUCTURAL & CIVIL ENGINEERS 583 DARLING STREET ROZELLE NSW 2039 tel: (02) 9555 7230 email : office@birzulisassociates.com www.birzulisassociates.com

> **BROKEN HILL** POLICE STATION


PROJECT


SOIL EROSION AND SEDIMENT **CONTROL PLAN**






REPRODUCTION OF THIS DRAWING IS PROHIBITED WITHOUT THE CONSENT OF BIRZULIS ASSOCIATES PTY. LTD. ISSUE DRAWING No. SE.01 7800 A








NOT TO SCALE

SEDIMENT FENCE ON PAVED SURFAC E


NOT TO SCALE



TEMPORARY CONSTRUCTION EXIT

NOT TO SCALE

NOT TO SCALE



MESH AND GRAVEL INLET FILTER

SCALE 1:20

NOTES:

- FABRICATE A SSLEEVE MADE FROM GEOTEXTILE OR WIRE MESH LONGER THAN THE LENGTH OF THE INLET PIT AND FILL IT WITH 25mm TO 50mm GRAVEL.
- 2. FORM AN ELLIPTICAL CROSS-SECTION ABOUT 150mm HIGH Ax 400mm WIDE.
- 3. PLACE THE FILTER AT THE OPENING LEAVING AT LEAST A 100mm SPACE BETWEEN IT AND THE KERB INLET. MAINTAIN THE OPENING WITH SPACER BLOCKS.
- FORM A SEAL WITH THE KERB TO PREVENT SEDIMENT BYPASSING THE FILTER.
- . SANDBAGS FILLED WITH GRAVEL CAN SUBSTITUTE FOR THE MESH OR GEOTEXTILE PROVIDING THEY ARE PLACED SO THAT THEY CAN FIRMLY ABUT EACH OTHER AND SEDIMENT/LADEN WATERS CANNOT PASS BETWEEN.

